EQUITY RESEARCH PLATFORM — COMPLETE ORACLE ERD

23 tables | 175 columns | 35 foreign keys | schema 1.0.0

companies

P- company_id	N(19)
-- company_key	V(40)
-- company_name	V(250)
-- tax_code?	V(30)
-- created_at	TIMESTAMP_TZ

data_sources

P- source_id	N(19)
-- source_code	V(40)
-- source_name	V(200)

financial_items

P- item_id	N(19)
-- item_code	V(60)
-- item_name	V(200)
-- statement_kind	V(2)
-- value_kind	V(12)

report_sets

P- report_set_id	N(19)
-F company_id	N(19)
-- fiscal_year	N(4)
-- scope_code	V(16)
-- selection_version	N(6)
-- dataset_version	V(60)
-- set_state	V(8)
-- acceptance_status	V(12)
-- temporal_mode	V(16)
-- created_at	TIMESTAMP_TZ

metric_definitions

P- metric_id	N(19)
-- metric_code	V(60)
-- formula_version	V(20)
-- metric_name	V(200)
-- formula_text	V(1000)
-- display_unit	V(10)
-- decimal_places	N(2)

etl_batches

P- batch_id	N(19)
-- batch_key	V(100)
-- contract_version	V(40)
-- mapping_version	V(40)
-- batch_status	V(16)
-- started_at	TIMESTAMP_TZ
-- finished_at?	TIMESTAMP_TZ
-- received_count	N(19)
-- imported_count	N(19)
-- rejected_count	N(19)
-- skipped_count	N(19)

securities

P- security_id	N(19)
-F company_id	N(19)
-- symbol	V(20)
-- exchange_code	V(20)
-- security_kind	V(20)

source_artifacts

P- artifact_id	N(19)
-F source_id	N(19)
-- artifact_kind	V(12)
-- sha256	V(64)
-- storage_path	V(1000)
-- source_url?	V(2000)
-- collected_at?	TIMESTAMP_TZ
-- hosting_note?	V(500)

financial_reports

P- report_id	N(19)
-F company_id	N(19)
-- fiscal_year	N(4)
-- period_kind	V(10)
-- statement_kind	V(2)
-- scope_code	V(16)
-- source_report_type	V(20)
-F artifact_id	N(19)
-- mapping_version	V(40)
-- report_version	N(6)
-- fiscal_start?	DATE
-- fiscal_end?	DATE
-- publication_at?	TIMESTAMP_TZ
-F publication_artifact_id?	N(19)
-- currency_code	V(7)
-- original_unit	V(20)
-- unit_multiplier?	N(10)
-- metadata_status	V(12)
-F batch_id	N(19)

report_set_members

PF report_set_id	N(19)
PF statement_kind	V(2)
-F report_id	N(19)

metric_dependencies

PF metric_id	N(19)
P- input_position	N(2)
-F item_id	N(19)
-- year_offset	N(2)

staging_facts

P- staging_id	N(19)
-F batch_id	N(19)
-- row_no	N(19)
-F artifact_id?	N(19)
-- source_symbol?	V(40)
-- fiscal_year_raw?	V(30)
-- item_code_raw?	V(100)
-- value_text?	V(200)
-- row_status	V(12)
-- payload?	CLOB

daily_prices

P- price_id	N(19)
-F security_id	N(19)
-- trading_date	DATE
-F artifact_id	N(19)
-- price_basis	V(12)
-- currency_code	V(7)
-- price_multiplier?	N(10)
-- open_price?	N(20,6)
-- high_price?	N(20,6)
-- low_price?	N(20,6)
-- close_price	N(20,6)
-- volume?	N(24,0)

quality_issues

P- issue_id	N(19)
-F report_id	N(19)
-F fact_id?	N(19)
-- rule_code	V(60)
-- severity	V(8)
-- issue_status	V(24)
-- details	V(2000)
-F evidence_artifact_id?	N(19)

financial_facts

P- fact_id	N(19)
-F report_id	N(19)
-F item_id	N(19)
-F statement_kind	V(2)
-- value_text?	V(200)
-- value_original?	N(38,6)
-- value_vnd?	N(28,0)
-- quality_status	V(12)
-- raw_locator	V(1000)
-- raw_code	V(80)
-- raw_name?	V(500)

report_set_facts

P- selection_fact_id	N(19)
-F report_set_id	N(19)
-F report_id	N(19)
-F item_id	N(19)
-F fact_id	N(19)
-F correction_id?	N(19)
-- selected_quality	V(12)

calculation_runs

P- run_id	N(19)
-- run_key	V(100)
-F report_set_id	N(19)
-F previous_set_id?	N(19)
-- engine_version	V(40)
-- run_status	V(12)
-- started_at	TIMESTAMP_TZ

etl_errors

P- error_id	N(19)
-F batch_id	N(19)
-F staging_id?	N(19)
-- error_code	V(60)
-- error_message	V(2000)
-- logged_at	TIMESTAMP_TZ

business_change_log

P- change_id	N(19)
-- entity_name	V(60)
-- entity_key	V(200)
-- action_code	V(10)
-- old_data?	CLOB
-- new_data?	CLOB
-- actor_name	V(128)
-- changed_at	TIMESTAMP_TZ

fact_corrections

P- correction_id	N(19)
-F fact_id	N(19)
-- correction_key	V(100)
-- new_value_original	N(38,6)
-- new_value_vnd?	N(28,0)
-F evidence_artifact_id	N(19)
-- evidence_page	N(6)
-- reason	V(1000)
-- review_status	V(16)
-- reviewed_by?	V(100)
-- reviewed_at?	TIMESTAMP_TZ
-F supersedes_id?	N(19)

report_heads

PF company_id	N(19)
PF fiscal_year	N(4)
PF scope_code	V(16)
-F report_set_id	N(19)
-- lock_version	N(10)

metric_results

P- result_id	N(19)
-F run_id	N(19)
-F metric_id	N(19)
-- metric_value?	N(28,12)
-- result_status	V(28)
-- reason_codes?	V(1000)

metric_input_facts

PF result_id	N(19)
P- input_position	N(2)
-F selection_fact_id	N(19)

P = primary key; F = foreign-key column; ? = nullable. Arrows: referenced parent → child. Exact cardinalities and composite FK mapping: erd_full.mmd / docs/05.