

COPYRIGHT NOTICE / THÔNG BÁO BẢN QUYỀN

© 2025 Duc A. Hoang (Hoàng Anh Đức)

COPYRIGHT (English):

This document is licensed under Creative Commons Attribution-ShareAlike 4.0 International (CC-BY-SA 4.0). You are free to share and adapt this material with appropriate attribution and under the same license.

This document is not up to date and may contain several errors or outdated information.

Last revision date: 2025-10-07

BẢN QUYỀN (Tiếng Việt):

Tài liệu này được cấp phép theo Giấy phép Quốc tế Creative Commons Attribution-ShareAlike 4.0 (CC-BY-SA 4.0). Bạn được tự do chia sẻ và chỉnh sửa tài liệu này với điều kiện ghi nguồn phù hợp và sử dụng cùng loại giấy phép.

Tài liệu này không được cập nhật và có thể chứa nhiều lỗi hoặc thông tin cũ.

Ngày sửa đổi cuối cùng: 2025-10-07



Creative Commons Attribution-ShareAlike 4.0 International

VNU-HUS MAT1206E/3508: Introduction to AI

Limitations of Logic

In-class Discussion

Hoàng Anh Đức

Bộ môn Tin học, Khoa Toán-Cơ-Tin học
Đại học KHTN, ĐHQG Hà Nội
hoanganhduc@hus.edu.vn



Contents



Limitations of Logic

Hoàng Anh Đức

The Search Space
Problem

Decidability and
Incompleteness

Example: The Flying
Penguin

Modelling Uncertainty

The Search Space Problem

Decidability and Incompleteness

Example: The Flying Penguin

Modelling Uncertainty

The Search Space Problem



Limitations of Logic

Hoàng Anh Đức

2

The Search Space Problem

Decidability and Incompleteness

Example: The Flying Penguin

Modelling Uncertainty

- In the search for a proof, depending on the calculus, potentially *there are (infinitely) many ways to apply inference rules at each step*
- This is the main reason for the *explosive growth of the search space*



Because of the search space problem, *automated provers* today can *only prove relatively simple theorems in special domains with few axioms*

The Search Space Problem



Human experts can prove theorems that are *out of reach* for *automated provers*

Limitations of Logic

Hoàng Anh Đức


3 The Search Space Problem

Decidability and Incompleteness

Example: The Flying Penguin

Modelling Uncertainty

Human experts vs.
Automated Provers.
Image generated by
Gemini AI



The Search Space Problem



Limitations of Logic

Hoàng Anh Đức

4

The Search Space Problem

Decidability and Incompleteness

Example: The Flying Penguin

Modelling Uncertainty

Problems?

- Humans' *intuitive meta-knowledge* is difficult to formalize and integrate into automated provers.
- Humans acquire *heuristics through experience*, and these heuristics are hard to transfer to automated provers.

Possible Solutions?

- *Machine learning* techniques can be used to learn heuristics from large datasets of proofs.
- *Hybrid approaches* that combine automated reasoning with human expertise can be explored.

Decidability and Incompleteness



Limitations of Logic

Hoàng Anh Đức

The Search Space
Problem

5 Decidability and
Incompleteness

Example: The Flying
Penguin

Modelling Uncertainty

- *Decidability* refers to whether there exists an algorithm that can determine the truth or falsity of any statement in a given logical system.
- *Incompleteness* refers to the fact that in any sufficiently powerful logical system, there are statements that are true but cannot be proven within the system.

Examples?

- The *Halting Problem* is a classic example of an undecidable problem.
- In first-order logic, if a given formula is valid, there is a proof of it (Gödel's Completeness Theorem). However, if the formula is not valid, it may happen that the prover never halts (undecidability). On the other hand, propositional logic is decidable. **[Why?]**
- Gödel's *Incompleteness Theorems* show that in any consistent formal system that is capable of expressing basic arithmetic, there are true statements that cannot be proven within the system.

Decidability and Incompleteness



Limitations of Logic

Hoàng Anh Đức

The Search Space
Problem

6 Decidability and
Incompleteness

Example: The Flying
Penguin

Modelling Uncertainty

Note

The deeper background of Gödel's Incompleteness Theorem is that mathematical theories (axiom systems) and, more generally, *languages become incomplete if the language becomes too powerful* (e.g., PL1).

Example 1 ("Too powerful language")

- *Set theory* is so powerful that one can formulate paradoxes (= statements that contradict themselves) with it.
- For example, a paradox in set theory: "The set of all the barbers who all shave those who do not shave themselves"

Example: The Flying Penguin



Knowledge Base (KB)

- (1) Tweety is a penguin
- (2) Penguins are birds
- (3) Birds can fly

- (1) $penguin(Tweety)$
- (2) $\forall x (penguin(x) \Rightarrow bird(x))$
- (3) $\forall x (bird(x) \Rightarrow fly(x))$



Query (Q)

Can *Tweety fly*? ($Q = fly(Tweety)$)

Note that $KB \vdash Q$, i.e., Q can be proven from KB **[How?]**

Limitations of Logic

Hoàng Anh Đức

The Search Space
Problem

Decidability and
Incompleteness

7 Example: The Flying
Penguin

Modelling Uncertainty

Example: The Flying Penguin



Limitations of Logic

Hoàng Anh Đức

The Search Space
Problem

Decidability and
Incompleteness

8

Example: The Flying
Penguin

Modelling Uncertainty

However, in reality, *penguins cannot fly*. That is, we should prevent the derivation of Q from KB

First Attempt

To mimics the reality, we try to add $\forall x (penguin(x) \Rightarrow \neg fly(x))$ to KB .

- After adding this new information, we have $KB \vdash \neg Q$, i.e., $\neg Q$ can be proven from KB **[How?]**
- But Q can still be derived from KB **[How?]**
- Both Q and $\neg Q$ can be derived from $KB \Rightarrow$ *contradiction*
 $\Rightarrow KB$ is *inconsistent* \Rightarrow *everything can be proven from*
KB (principle of explosion)
 - **Reason:** PL1 is *monotonic*, i.e., if $KB \vdash Q$, then
 $(KB \cup \{R\}) \vdash Q$ for any formula R .

\Rightarrow Does not work!

Example: The Flying Penguin



Limitations of Logic

Hoàng Anh Đức

The Search Space
Problem

Decidability and
Incompleteness

9 Example: The Flying
Penguin

Modelling Uncertainty

Second Attempt

- Add “Penguins cannot fly” to the original KB
- Replace the non-realistic rule “Birds can fly” by “Birds except penguins can fly”.

Knowledge Base (KB_2)

- | | |
|-----------------------------------|---|
| (1) Tweety is a penguin | (1) $penguin(Tweety)$ |
| (2) Penguins are birds | (2) $\forall x (penguin(x) \Rightarrow bird(x))$ |
| (3) Birds except penguins can fly | (3) $\forall x (bird(x) \wedge \neg penguin(x) \Rightarrow fly(x))$ |
| (4) Penguins cannot fly | (4) $\forall x (penguin(x) \Rightarrow \neg fly(x))$ |

\Rightarrow Problem solved! Now, $\neg Q$ can be derived from KB_2 , but Q cannot

Example: The Flying Penguin



Limitations of Logic

Hoàng Anh Đức

The Search Space
Problem

Decidability and
Incompleteness

10 Example: The Flying
Penguin

Modelling Uncertainty

But ...

- Whenever we want to add a new bird, we have to specify whether it can fly or not
- This means we have to explicitly specify a rule saying that the newly added bird is not a penguin (because of the rule “Birds except penguins can fly”); otherwise, we have no conclusion about whether the new bird can fly or not
- For the construction of a knowledge base with all 9800 or so types of birds worldwide, this becomes a significant challenge.

In general, for every object in the knowledge base, in addition to its attributes, all of the attributes it does not have must be listed.

Example: The Flying Penguin



Limitations of Logic

Hoàng Anh Đức

The Search Space
Problem

Decidability and
Incompleteness

11 Example: The Flying
Penguin

Modelling Uncertainty

Another problem caused by the monotony is the so-called *frame problem*. This happens in complex planning problems in which the world can change

Example 2 (An example of the frame problem)

- A blue house is painted red, then afterwards it is red
- However, with the knowledge base

color(house, blue)

paint(house, red)

paint(x, y) \Rightarrow color(x, y)

one can derive *color(house, red)*

- Additionally, *color(house, blue)* is already in the knowledge base, which leads to the conclusion that, after painting, the house is both blue and red

Example: The Flying Penguin



Limitations of Logic

Hoàng Anh Đức

The Search Space
Problem

Decidability and
Incompleteness

12 Example: The Flying
Penguin

Modelling Uncertainty

Some Resolving Ideas

- *Non-monotonic reasoning* allows us to withdraw conclusions in the light of new information (i.e., old knowledge can be removed).
- *Probability theory* can be used to handle uncertainty and make decisions based on incomplete information.

Modelling Uncertainty



Limitations of Logic

Hoàng Anh Đức

The Search Space Problem

Decidability and Incompleteness

Example: The Flying Penguin

13 Modelling Uncertainty

- *Two-valued logic* can and should only *model circumstances in which there is true, false, and no other truth values*.
- For many tasks in everyday reasoning, *two-valued logic is therefore not expressive enough*.
 - For example, the rule $\text{bird}(x) \Rightarrow \text{fly}(x)$ is *true for almost all birds, but for some it is false*.
- As we already mentioned, to formulate uncertainty, we can use *probability theory*.
 - For example, we give a probability for "*birds can fly*":
 $P(\text{bird}(x) \Rightarrow \text{fly}(x)) = 0.99$ (i.e., "99% of all birds can fly")
 - Later, we will see that here it is better to work with *conditional probabilities* such as $P(\text{fly}|\text{bird}) = 0.99$. With the help of *Bayesian networks*, complex applications with many variables can also be modelled.
 - *Fuzzy logic* is required for "*The weather is nice*". Here it makes no sense to speak in terms of true and false.
 - The variable *weather_is_nice* is *continuous with values in $[0, 1]$* . $\text{weather_is_nice} = 0.7$ then means "*The weather is fairly nice*".

Modelling Uncertainty



Limitations of Logic

Hoàng Anh Đức

The Search Space Problem

Decidability and Incompleteness


Example: The Flying Penguin

14 Modelling Uncertainty

- Probability theory also offers the possibility of *making statements about the probability of continuous variables*.

“There is a high probability that there will be some rain”

$$P(\text{rainfall} = X) = Y$$



Note

This very *general and even visualizable representation* of both types of uncertainty we have discussed, together with *inductive statistics* and the theory of *Bayesian networks*, makes it possible, in principle, *to answer arbitrary probabilistic queries*.

Modelling Uncertainty



Limitations of Logic

Hoàng Anh Đức

The Search Space
Problem

Decidability and
Incompleteness

Example: The Flying
Penguin

Comparison of different formalisms for the modelling of
uncertain knowledge

Formalism	Number of truth values	Probabilities expressible
Propositional logic	2	—
Fuzzy logic	∞	—
Discrete probabilistic logic	n	yes
<i>Continuous probabilistic logic</i>	∞	<i>yes</i>

15

Modelling Uncertainty

15