

COPYRIGHT NOTICE / THÔNG BÁO BẢN QUYỀN

© 2025 Duc A. Hoang (Hoàng Anh Đức)

COPYRIGHT (English):

This document is licensed under Creative Commons Attribution-ShareAlike 4.0 International (CC-BY-SA 4.0). You are free to share and adapt this material with appropriate attribution and under the same license.

This document is not up to date and may contain several errors or outdated information.

Last revision date: 2025-09-07

BẢN QUYỀN (Tiếng Việt):

Tài liệu này được cấp phép theo Giấy phép Quốc tế Creative Commons Attribution-ShareAlike 4.0 (CC-BY-SA 4.0). Bạn được tự do chia sẻ và chỉnh sửa tài liệu này với điều kiện ghi nguồn phù hợp và sử dụng cùng loại giấy phép.

Tài liệu này không được cập nhật và có thể chứa nhiều lỗi hoặc thông tin cũ.

Ngày sửa đổi cuối cùng: 2025-09-07



Creative Commons Attribution-ShareAlike 4.0 International

VNU-HUS MAT1206E/3508: Introduction to AI

Propositional Logic

In-class Discussion

Hoàng Anh Đức

Bộ môn Tin học, Khoa Toán-Cơ-Tin học
Đại học KHTN, ĐHQG Hà Nội
hoanganhduc@hus.edu.vn



Contents



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of Propositional Logic

A general picture
Syntax and Semantics
Inference Rules
Proof Systems
Horn Clauses

More Applications of Propositional Logic

References

Introduction

Basics of Propositional Logic

A general picture
Syntax and Semantics
Inference Rules
Proof Systems
Horn Clauses

More Applications of Propositional Logic

Introduction



Propositional Logic

Hoàng Anh Đức

2 Introduction

Basics of

Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

- Logic is one of the oldest fields in AI. It was the dominant AI method from the 1950s to the 1980s (remember we talked about symbolic AI).
- Machine learning has established itself and is now the dominant AI method in every field of application. By contrast, logic no longer plays a significant role in AI.
- Nevertheless, logic remains important for understanding AI's foundations and for domains that require explicit, interpretable, and verifiable reasoning.
 - Planning systems for service robots.
 - Autonomous driving.
 - The connection between symbolic representation of knowledge in predicate logic and the implicit sub-symbolic knowledge gathered from sensors remains interesting. This is a promising application for automatic feature extraction using Deep Learning.
- We discuss propositional logic, the simplest form of logic, and its use in knowledge representation and reasoning.

Basics of Propositional Logic

A general picture



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

3

A general picture

Syntax and Semantics


Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References



Propositional Logic Formulas (Syntax)

Propositional
Variables
 Σ

Logical
Operators
 Op

Logical Constants
 t, f

$\neg, \wedge, \vee, \Rightarrow, \Leftrightarrow, (,)$

Propositional Logic Formulas (Semantics)

Truth Assignment
 $I : \Sigma \rightarrow \{t, f\}$

Logical
Operators
 Op

Logical Constants
 $I(t) = t, I(f) = f$

Truth table
for each operator

Propositional Logic Formulas
(Premise)

Derivation
→
(Applying inference rules)

Propositional Logic Formula
(Conclusion)

Basics of Propositional Logic

Syntax and Semantics



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

Exercise 1

Are you familiar with the following concepts? Review them if needed.

- (1) Propositional formulas
- (2) Truth assignments
- (3) Semantically equivalent formulas
- (4) Satisfiable, (logically) valid, unsatisfiable formulas
- (5) A model of a formula
- (6) KB (knowledge base – a collection of formulas) entails Q (query – a formula) (or Q follows (semantically) from KB , or $KB \models Q$)
- (7) $KB \models Q$ and $\models KB \Rightarrow Q$
- (8) Proof by model checking
- (9) Conjunctive Normal Form (CNF) (conjunction, disjunction, literal, clause) and how to convert a formula to CNF

Basics of Propositional Logic

Inference Rules



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

5

Premise \vdash Conclusion (= “Conclusion follows from Premise syntactically”)

Inference Rule

Propositional Logic Formulas
(Premise)

Premise
Conclusion

Propositional Logic Formula
(Conclusion)

$\{A, A \Rightarrow B\} \vdash B$ or $A \wedge (A \Rightarrow B) \vdash B$

Modus Ponens (MP)

$A, A \Rightarrow B$

$A, A \Rightarrow B$
B

B

$\{A \vee B, \neg B \vee C\} \vdash A \vee C$ or $(A \vee B) \wedge (\neg B \vee C) \vdash (A \vee C)$

Resolution (Res)

$A \vee B, \neg B \vee C$

$A \vee B, \neg B \vee C$
 $A \vee C$

$A \vee C$

Premise \vdash Conclusion (= “Conclusion follows from Premise syntactically”)

Inference Rules

Propositional Logic Formulas
(Premise)



Propositional Logic Formula
(Conclusion)

Basics of Propositional Logic

Inference Rules



Aristotle's Famous Syllogism^a

All men are mortal
Socrates is a man

Socrates is mortal

^aThe term comes from the Greek word *syllogismos*, meaning “conclusion” or “inference.” In a valid syllogism, if the premises are true, the conclusion must also be true. In Vietnamese, it is called “Tam đoạn luận” (three-part reasoning).



Figure: Aristotle (384–322 BC). His work (the *Organon* book) is considered as the earliest systematic study of logic. Image taken from Wikipedia.

Propositional Logic

Hoàng Anh Đức

Introduction

Basics of Propositional Logic

A general picture

Syntax and Semantics

6

Inference Rules

Proof Systems

Horn Clauses

More Applications of Propositional Logic

References

Basics of Propositional Logic

Calculus



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

7

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

Inference Rules

(has every possible rules that can be defined)

Calculus

(Rules you are allowed to use)

A calculus is

- **sound** if for any two formulas KB and Q , if $KB \vdash Q$ then $KB \models Q$;
- **complete** if for any two formulas KB and Q , if $KB \models Q$ then $KB \vdash Q$.

Basics of Propositional Logic

Calculus



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

If a calculus is *both sound and complete*, then *syntactic derivation and semantic entailment are two equivalent relations*




Figure: Syntactic derivation vs. Semantic entailment

Recall: We talked about the idea of “the process of human thought can be *mechanized*”.

Basics of Propositional Logic

Proof Systems



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

9 Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

Goal

We want to show that a knowledge base KB entails a query Q , i.e., $KB \models Q$.

Note: KB must be *consistent*, meaning that it does not contain any pair of formulas $\{P, \neg P\}$. **[What if it is not?]**

Proof System 1: Model checking

To show that $KB \models Q$, we can use a model checking algorithm. This involves checking all assignments (interpretations) of the propositional variables in KB and Q . If in every model where KB is true, Q is also true, then $KB \models Q$.

- **Pros:** Simple and straightforward.
- **Cons:** Very large computation in the worst case — 2^n assignments for n propositional variables.

Basics of Propositional Logic

Proof Systems



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

9 Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

Goal

We want to show that a knowledge base KB entails a query Q , i.e., $KB \models Q$.

Note: KB must be *consistent*, meaning that it does not contain any pair of formulas $\{P, \neg P\}$. **[What if it is not?]**

Proof System 1: Model checking

To show that $KB \models Q$, we can use a model checking algorithm. This involves checking all assignments (interpretations) of the propositional variables in KB and Q . If in every model where KB is true, Q is also true, then $KB \models Q$.

Proof System 2: A sound and complete calculus \mathcal{C}

To show that $KB \models Q$, we show $KB \vdash Q$ using the calculus \mathcal{C} . The soundness and completeness of \mathcal{C} guarantee that $KB \vdash Q$ if and only if $KB \models Q$.

Basics of Propositional Logic

Proof Systems



Let's discuss how we construct Proof System 2.

Note

We can assume that KB is in Conjunctive Normal Form (CNF). **[Why?]**

Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

10 Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

Basics of Propositional Logic

Proof Systems



Let's discuss how we construct Proof System 2.

Note

We can assume that KB is in Conjunctive Normal Form (CNF). **[Why?]**

Can we use only Modus Ponens in \mathcal{C} ?

No. Modus Ponens is sound but not complete. **[Why?]**

Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

10 Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

Basics of Propositional Logic

Proof Systems



Let's discuss how we construct Proof System 2.

Note

We can assume that KB is in Conjunctive Normal Form (CNF). **[Why?]**

Can we use only Modus Ponens in \mathcal{C} ?

No. Modus Ponens is sound but not complete. **[Why?]**

Can we use only Resolution in \mathcal{C} ?

No. Resolution is sound but not complete. **[Why?]**

Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

10

18

Basics of Propositional Logic

Proof Systems



Let's discuss how we construct Proof System 2.

Note

We can assume that KB is in Conjunctive Normal Form (CNF). **[Why?]**

Can we use only Modus Ponens in \mathcal{C} ?

No. Modus Ponens is sound but not complete. **[Why?]**

Can we use only Resolution in \mathcal{C} ?

No. Resolution is sound but not complete. **[Why?]**

Can we use both Modus Ponens and Resolution in \mathcal{C} ?

No. Resolution is a generalization of Modus Ponens **[Why?]**, and using both does not provide any additional power.

Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

10 Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

Basics of Propositional Logic

Proof Systems



What now?

One approach is to *combine Resolution with one or more additional inference rules* — rules that are not subsumed by Resolution — to obtain a calculus that is both sound and complete.

Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

11

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

Basics of Propositional Logic

Proof Systems



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

What now?

One approach is to *combine Resolution with one or more additional inference rules* — rules that are not subsumed by Resolution — to obtain a calculus that is both sound and complete.

There are several cases that Resolution does not work

For example, $\{A, B\} \models A \vee B$, but how do you derive $A \vee B$ from the premises A and B using only Resolution? **[Try it!]**
Another example: what happens if the premise is empty?

11

18

Basics of Propositional Logic

Proof Systems



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

What now?

One approach is to *combine Resolution with one or more additional inference rules* — rules that are not subsumed by Resolution — to obtain a calculus that is both sound and complete.

There are several cases that Resolution does not work

For example, $\{A, B\} \models A \vee B$, but how do you derive $A \vee B$ from the premises A and B using only Resolution? **[Try it!]**
Another example: what happens if the premise is empty?

Luckily, we can “prove by contradiction”

$KB \models Q$ means $KB \wedge \neg Q$ is unsatisfiable. **[Why?]** Instead of showing $KB \vdash Q$, we can show that $(KB \wedge \neg Q) \vdash ()$.

11

18

Basics of Propositional Logic

Proof Systems



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

What now?

One approach is to *combine Resolution with one or more additional inference rules* — rules that are not subsumed by Resolution — to obtain a calculus that is both sound and complete.

There are several cases that Resolution does not work

For example, $\{A, B\} \models A \vee B$, but how do you derive $A \vee B$ from the premises A and B using only Resolution? **[Try it!]**
Another example: what happens if the premise is empty?

Luckily, we can “prove by contradiction”

$KB \models Q$ means $KB \wedge \neg Q$ is unsatisfiable. **[Why?]** Instead of showing $KB \vdash Q$, we can show that $(KB \wedge \neg Q) \vdash ()$.

New Goal

Find a calculus \mathcal{C} which allows us to derive the empty clause from any unsatisfiable set of clauses.

11

18

Basics of Propositional Logic

Proof Systems



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

But ...

Unfortunately, *Resolution alone is not sufficient to derive the empty clause from every unsatisfiable set of clauses.* [Why?]

(**Hint:** Consider the Premise with two clauses $A \vee A$ and $\neg A \vee \neg A$.)

We need to add more inference rules to our calculus to make it complete.

12

18

Basics of Propositional Logic

Proof Systems



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

But ...

Unfortunately, *Resolution alone is not sufficient to derive the empty clause from every unsatisfiable set of clauses.* [Why?]

(Hint: Consider the Premise with two clauses $A \vee A$ and $\neg A \vee \neg A$.)

We need to add more inference rules to our calculus to make it complete.

An inference rules we can use: *Factorization*

Literals that are identical in a clause can be *factored* out. For example:

$$\frac{(A \vee A \vee B)}{(A \vee B)}$$

$$\frac{(A \vee A)}{A}$$

Note: Factorization is both sound and complete.

12

18

Basics of Propositional Logic

Proof Systems



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

But ...

Unfortunately, *Resolution alone is not sufficient to derive the empty clause from every unsatisfiable set of clauses.* [Why?]

(Hint: Consider the Premise with two clauses $A \vee A$ and $\neg A \vee \neg A$.)

We need to add more inference rules to our calculus to make it complete.

An inference rules we can use: *Factorization*

Literals that are identical in a clause can be *factored* out. For example:

$$\frac{(A \vee A \vee B)}{(A \vee B)}$$

$$\frac{(A \vee A)}{A}$$

Note: Factorization is both sound and complete.

And finally, we have $\mathcal{C} = \{\text{Resolution, Factorization}\}$. We call \mathcal{C} the *resolution calculus*. Resolution calculus is both sound and refutation-complete.

12

18

Basics of Propositional Logic

Proof Systems



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

13 Proof Systems

Horn Clauses

More Applications of Propositional Logic

References

In summary, to decide if $KB \models Q$ using the resolution calculus, we can use the following algorithm:

- (1) Convert $KB \wedge \neg Q$ to CNF.
- (2) Repeatedly apply the resolution and factorization rules until there is no resolvable pair of clauses.
- (3) Every time the resolution rule is applied, add the resolvent to KB if it has not yet been included.
- (4) If the empty clause is derived, then $KB \models Q$. Otherwise, $KB \not\models Q$.

Exercise 2

Confirm your understanding of the resolution calculus by seeing how the logic puzzles (“A charming English family” and “The High Jump”) in the textbook [Ertel 2025] are solved.

Basics of Propositional Logic

Horn Clauses



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules


Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

- In practice, many knowledge bases consist of *Horn clauses*, which are clauses with at most one positive literal.



- The full power of the resolution calculus is not needed to handle Horn clauses. One may use the (generalized) Modus Ponens rule instead of the general Resolution rule.

$$\frac{A_1 \wedge \dots \wedge A_m, A_1 \wedge \dots \wedge A_m \Rightarrow B}{B}$$

14

18

Basics of Propositional Logic

Horn Clauses



Two deriving algorithms:

- **Forward chaining** (data-driven reasoning): repeatedly apply the generalized Modus Ponens rule to derive new facts until either Q is derived or no new facts can be derived.
 - **Note:** In the case of large knowledge bases, however, Modus Ponens may derive many unnecessary formulas if one *begins with the wrong clauses*.
- **Backward chaining** (goal-driven reasoning): start from the query Q and work backwards to see if it can be derived from KB . In this case, the SLD resolution (“Selection rule driven linear resolution for definite clauses”) is used.

$$\frac{A_1 \wedge \cdots \wedge A_m \Rightarrow B_1, B_1 \wedge B_2 \wedge \cdots \wedge B_n \Rightarrow \mathbf{f}}{A_1 \wedge \cdots \wedge A_m \wedge B_2 \wedge \cdots \wedge B_n \Rightarrow \mathbf{f}}$$

- **Note:** In backward chaining, we always start applying inference rule to the negated query $\neg Q$ and further processing is always done on the currently derived clause

Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

15

Horn Clauses

More Applications of
Propositional Logic

References

Basics of Propositional Logic

Horn Clauses



Exercise 3

- (a) Confirm your understanding of forward and backward chaining by seeing the example in the textbook [Ertel 2025] of deriving `skiing` from the knowledge base using both forward chaining and backward chaining (SLD resolution).
- (b) Summarize the proof systems (Model checking, Resolution calculus) and deriving algorithms (forward chaining, backward chaining) we have discussed so far. You can start by answering the following questions:
- (1) What kind of formulas can they handle? (i.e., what are the restrictions on KB ?)
 - (2) What is the goal of each system/algorithm?
 - (3) How do they work?
 - (4) What are the pros and cons?
 - (5) What are the running time complexities?
 - (6) Can proof in propositional logic go faster? Are there better algorithms? (**Hint:** What can we conclude from the Cook-Levin theorem?)

Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic

References

16

18

More Applications of Propositional Logic



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

17 More Applications of
Propositional Logic

References

- Theorem provers for propositional logic are part of the developer's everyday toolset in *digital technology*
 - *Verification of digital circuits*
 - *Generation of test patterns* for testing of microprocessors in fabrication
 - Special proof systems that work with binary decision diagrams (BDD) are also employed as a data structure for *processing propositional logic formulas*
- *Simple AI applications*: simple expert systems can work with discrete variables, few values, no cross-relations between variables
- *Probabilistic logic* uses propositional logic and probabilistic computation to model uncertainty

References



Propositional Logic

Hoàng Anh Đức

Introduction

Basics of
Propositional Logic

A general picture

Syntax and Semantics

Inference Rules

Proof Systems

Horn Clauses

More Applications of
Propositional Logic



Ertel, Wolfgang (2025). *Introduction to Artificial Intelligence*. 3rd. Springer. DOI:
10.1007/978-3-658-43102-0.

18 References