Open Problems

Duc A. Hoang
VNU University of Science, Hanoi, Vietnam
hoanganhduc@hus.edu.vn

March 4, 2023

Abstract

This document contains a list of open problems that Duc A. Hoang is interested in. It is also available in HTML format. Please get in touch if you have any idea/comment/question/update. You can find (probably more interesting) open problems from the following resources.

- Open Problem Garden: Graph Theory.
- Open Problems - Graph Theory and Combinatorics, by Douglas B. West.
- List of IWOCA's Open Problems.
- Graph Theory - Favorite Conjectures and Open Problems - 1 (edited by Ralucca Gera, Stephen Hedetniemi, Craig Larson) and Graph Theory - Favorite Conjectures and Open Problems - 2 (edited by Ralucca Gera, Teresa W. Haynes, Stephen T. Hedetniemi).
- Open Problems in Computational Geometry, maintained by Erik D. Demaine, Joseph S. B. Mitchell, Joseph O'Rourke.
- Open Problems in Paramaterized Complexity.
- List of unsolved problems/conjectures in graph theory from Wikipedia.

Contents

1 Preliminaries **1**

2 Reconfiguration of Independent Sets under Token Sliding **2**
2.1 Definitions . . . 2
2.2 Conjecture/Question . . . 2
2.3 Background/Motivation . . . 2

3 Reconfiguring k-Path Vertex Covers on Trees under Token Sliding **2**
3.1 Definitions . . . 2
3.2 Conjecture/Question . . . 3
3.3 Background/Motivation . . . 3

4 Recoloring under Token Swapping **3**
4.1 Definitions . . . 3
4.2 Conjecture/Question . . . 3
4.3 Background/Motivation . . . 3

1 Preliminaries

Unless otherwise noted, all graphs are simple, undirected. We often denote by $P_n, C_n, K_n, K_{m,n}$ the *path*, *cycle*, *complete graph*, *complete bipartite graph* on n vertices, respectively. For two graphs G, H, the *disjoint union* of G and H, denoted by $G + H$, is the graph with $V(G + H) = V(G) \cup V(H)$ and $E(G + H) = E(G) \cup E(H)$. For the terminology and notation not defined here, see the textbooks by Diestel [8] or West [15]. For more details on *Combinatorial Reconfiguration* (https://en.wikipedia.org/wiki/Reconfiguration), see the surveys [5, 12–14] and the wiki page https://reconf.wikidot.com/.

2 Reconfiguration of Independent Sets under Token Sliding

2.1 Definitions

The *double-broom graph* $D_{r,n,s}$ is the tree obtained from a path $P_n = v_1 v_2 \dots v_n$ by attaching r leaves to v_1 and s leaves to v_n, where r, n, s are positive integers. Two independent sets I, J are *adjacent under Token Sliding* (TS) if there exists $u, v \in V(G)$ such that $I \setminus J = \{u\}$, $J \setminus I = \{v\}$, and $uv \in E(G)$. The Token Sliding problem asks whether there is a TS-*sequence* between I and J in G, that is, a sequence of independent sets starting with I and ending with J where any two consecutive members are adjacent under TS. For a fixed positive integer k, the graph $\mathsf{TS}_k(G)$ contains all size-k independent sets as its vertices/nodes, and two nodes are joined by an edge if their corresponding independent sets are adjacent under TS. A graph G is called a TS_k*-graph* if there exists a graph H such that G and $\mathsf{TS}_k(H)$ are isomorphic.

2.2 Conjecture/Question

Open Problem 1. *What is the complexity of Token Sliding on outerplanar graphs? And more generally, on series-parallel graphs (≡ graphs of treewidth at most two)?*

Open Problem 2. *Let G be a graph. What are necessary and sufficient conditions for G such that $\mathsf{TS}_2(G)$ is acyclic?*

Conjecture 3. *Let G be a forest. Then $\mathsf{TS}_k(G)$ is a forest if and only if G is $\{2K_2 + (k-2)K_1, D_{2,2,2} + (k-2)K_1, D_{2,4,2} + (k-3)K_1\}$-free, for some integer $k \geq 4$.*

2.3 Background/Motivation

Independent Set Reconfiguration (ISR) is one of the most well-studied problems in the Combinatorial Reconfiguration [5, 13]. Among several variants of ISR, Token Sliding is of particular interest. One of the main reasons is that in Token Sliding one often needs to deal with the situation where a token must make "detours" by "moving away" (and then moving back later) to allow some other token to move [7]. Alternatively, this can be seen as a kind of "bottleneck effect" [3] where a token may not be able to "reach" some vertices which are "far apart" from all tokens because some tokens "block the way".

Our motivation for Open Problem 1 comes from the following two results that both appeared in 2014.

Theorem 4 ([16])**.** *There exists a constant c such that Token Sliding (and two other variants of ISR) is* PSPACE*-complete on graphs of bandwidth at most c.*

Indeed, since a graph of bandwidth at most c also has pathwidth and treewidth at most c, Theorem 4 holds for graphs of pathwidth/treewidth at most c. Moreover, for $c = 1$,

Theorem 5 ([7])**.** *Token Sliding is in* P *on trees.*

Naturally, on graphs of treewidth at most c, one may ask what the value of c that separates "hard" from "easy" is. Toward answering this question, a first step is probably to consider $c = 2$.

Our motivation for Open Problem 2 and Conjecture 3 comes from [1, 2]. In [1], the authors initiated the study of $\mathsf{TS}_k(G)$ from a purely graph-theoretic viewpoint. They continued their study in [2] focusing on those that are acyclic. Open Problem 2 involve characterizing general graphs, which seems to be quite challenging and a first step may be to consider well-known graph classes. Toward this direction, in [2], the authors proved a forbidden induced subgraph characterization of a tree G satisfying that $\mathsf{TS}_k(G)$ is acyclic where $k \in \{2, 3\}$ and Conjecture 3, if true, will provide a complete analysis of which trees having acyclic TS_k-graphs.

3 Reconfiguring k-Path Vertex Covers on Trees under Token Sliding

3.1 Definitions

For a fixed integer $k \geq 2$, a k*-path vertex cover* of a graph G is a vertex subset I such that any path on k vertices contains at least one member from I. Two k-path vertex covers are *adjacent under Token Sliding (*TS*)* if there exists $u, v \in V(G)$ such that $I \setminus J = \{u\}$, $J \setminus I = \{v\}$, and $uv \in E(G)$. The k-Path Vertex Cover Reconfiguration under Token Sliding (k-PVCR-TS) problem asks if there is a TS-*sequence* between two given k-path vertex covers I and J in G, that is, a sequence of k-path vertex covers starting with I and ending with J where any two consecutive members are adjacent under TS.

3.2 Conjecture/Question

Open Problem 6. *What is the complexity of k-PVCR-TS on bipartite graphs? Or more restrictedly, on trees?*

3.3 Background/Motivation

The k-PVCR-TS problem was first introduced in [11]. The complexities of k-PVCR-TS and some other variants have been characterized in [11] for some graph classes, including planar and bounded bandwidth graphs, trees, paths, and cycles. However, k-PVCR-TS on trees remains open. Our motivation comes from an attempt in [10] to solve this problem for a subclass of trees called *caterpillars* (i.e., trees obtained by attaching leaves to a central path). Unlike the cases for independent sets, a token may have to make "detours" by "moving closer" (and then moving back later) to allow some other tokens to move.

4 Recoloring under Token Swapping

4.1 Definitions

For a fixed integer $k \geq 1$, a *proper k-coloring* α of a graph G is a function $\alpha : V(G) \to \{1, 2, \ldots, k\}$ such that for any edge $uv \in E(G)$ we have $\alpha(u) \neq \alpha(v)$. If G has a proper k-coloring, we say that it is *k-colorable*. Two proper k-colorings α, β are *adjacent under Token Swapping* if there exist $u, v \in V(G)$ such that $\alpha(u) = \beta(v)$, $\alpha(v) = \beta(u)$, $\alpha(w) = \beta(w)$ for any $w \in V(G) - \{u, v\}$, and $uv \in E(G)$. The k-Recoloring under Token Swapping (k-RTS) problem asks if there is a sequence of adjacent proper k-colorings of G under Token Swapping between two given proper k-colorings α, β. The graph $C_k^{RTS}(G)$ takes all proper k-colorings of G as its nodes and their adjacency are defined under Token Swapping.

4.2 Conjecture/Question

Open Problem 7. *What is the complexity of k-RTS on trees for some fixed $k \geq 3$?*

Open Problem 8. *What is the smallest value of k such that $C_k^{RTS}(G)$ is connected for some given graph G?*

Open Problem 9. *What are necessary and sufficient conditions for a k-colorable graph G such that $C_k^{RTS}(G)$ is connected?*

4.3 Background/Motivation

The k-RTS problem lies between two of the most well-studied problems in Combinatorial Reconfiguration: Token Swapping [17] and Vertex Recoloring [4]. (See [12, 13] for more details.) RTS was first proposed in [9] where the authors claimed that RTS remains PSPACE-complete on planar graphs and can be solved in polynomial time on paths ($k = 3$) and cographs (any k). Up to present, their results have not yet been published.

References

[1] David Avis and Duc A. Hoang. On Reconfiguration Graph of Independent Sets under Token Sliding. *arXiv preprint*, 2022. arXiv:2203.16861.

[2] David Avis and Duc A. Hoang. A Note On Acyclic Token Sliding Reconfiguration Graphs of Independent Sets. *arXiv preprint*, 2023. arXiv:2301.00317.

[3] Valentin Bartier, Nicolas Bousquet, and Amer E. Mouawad. Galactic Token Sliding. In Shiri Chechik, Gonzalo Navarro, Eva Rotenberg, and Grzegorz Herman, editors, *Proceedings of ESA 2022*, volume 244 of *LIPIcs*, pages 15:1–15:14. Schloss Dagstuhl – Leibniz-Zentrum für Informatik, 2022. doi:10.4230/LIPIcs.ESA.2022.15.

[4] Paul S. Bonsma and Luis Cereceda. Finding Paths Between Graph Colourings: PSPACE-Completeness and Superpolynomial Distances. In *Proceedings of MFCS 2007*, volume 4708 of *LNCS*, pages 738–749. Springer, 2007. doi:10.1007/978-3-540-74456-6_65.

[5] Nicolas Bousquet, Amer E. Mouawad, Naomi Nishimura, and Sebastian Siebertz. A survey on the parameterized complexity of the independent set and (connected) dominating set reconfiguration problems. *arXiv preprint*, 2022. arXiv:2204.10526.

[6] Boštjan Brešar, František Kardoš, Ján Katrenič, and Gabriel Semanišin. Minimum k-path vertex cover. *Discrete Applied Mathematics*, 159(12):1189–1195, 2011. doi:10.1016/j.dam.2011.04.008.

[7] Erik D. Demaine, Martin L. Demaine, Eli Fox-Epstein, Duc A. Hoang, Takehiro Ito, Hirotaka Ono, Yota Otachi, Ryuhei Uehara, and Takeshi Yamada. Linear-Time Algorithm for Sliding Tokens on Trees. *Theoretical Computer Science*, 600:132–142, 2015. doi:10.1016/j.tcs.2015.07.037. arXiv:1406.6576.

[8] Reinhard Diestel. *Graph Theory*, volume 173 of *Graduate Texts in Mathematics*. Springer, 5th edition, 2017. doi:10.1007/978-3-662-53622-3.

[9] Dennis Fischer and Janosch Fuchs. Color reconfiguration with token swapping, 2019. URL https://people.inf.ethz.ch/dkomm/arda2019/abstracts/ARDA2019-Fischer_Fuchs.pdf.

[10] Duc A. Hoang. TS-Reconfiguration of k-Path Vertex Covers in Caterpillars for $k \geq 4$. *arXiv preprint*, 2022. arXiv:2203.11667.

[11] Duc A. Hoang, Akira Suzuki, and Tsuyoshi Yagita. Reconfiguring k-Path Vertex Covers. *IEICE Transactions on Information and Systems*, E105-D(7):1258–1272, 2022. doi:10.1587/transinf.2021EDP7177. arXiv:1911.03026.

[12] C.M. Mynhardt and S. Nasserasr. Reconfiguration of colourings and dominating sets in graphs. In Fan Chung, Ron Graham, Frederick Hoffman, Ronald C. Mullin, Leslie Hogben, and Douglas B. West, editors, *50 years of Combinatorics, Graph Theory, and Computing*, pages 171–191. CRC Press, 1st edition, 2019. doi:10.1201/9780429280092-10.

[13] Naomi Nishimura. Introduction to reconfiguration. *Algorithms*, 11(4):52, 2018. doi:10.3390/a11040052.

[14] Jan van den Heuvel. The complexity of change. In *Surveys in Combinatorics*, volume 409 of *London Mathematical Society Lecture Note Series*, pages 127–160. Cambridge University Press, 2013. doi:10.1017/cbo9781139506748.005.

[15] Douglas B. West. *Introduction to Graph Theory*. Prentice Hall, 2nd edition, 2001.

[16] Marcin Wrochna. Reconfiguration in Bounded Bandwidth and Treedepth. *Journal of Computer and System Sciences*, 93:1–10, 2018. doi:10.1016/j.jcss.2017.11.003. arXiv:1405.0847.

[17] Katsuhisa Yamanaka, Erik D. Demaine, Takehiro Ito, Jun Kawahara, Masashi Kiyomi, Yoshio Okamoto, Toshiki Saitoh, Akira Suzuki, Kei Uchizawa, and Takeaki Uno. Swapping Labeled Tokens on Graphs. *Theoretical Computer Science*, 586:81–94, 2015. doi:10.1016/j.tcs.2015.01.052.