

Datorteknik, HT18, DT509G

Lab 3: Memory Organization

Kinfai Chin & Karl Eriksson

2018-10-12



Task 1: Array Storage (15 points)

The task was to write various functions and structures in order to store and fetch from a 2D byte array. The task also stated that a 1D char* array was to be used to emulate an 2D array in C.

Step 1

The function `two_d_alloc` takes in number of rows, columns and the element size in order to allocate enough memory using `malloc` for each slot in the array. (Codeline 4).

Step 2

The function `two_d_dealloc` deallocates the the array by using `free()`. (Codeline 24)

Step 3

Check `main()` at codeline 139.

Step 4

The function `two_d_store` takes in the array, the row and column which the new value is to be stored, the matrix size and the size of each arrayslot. The position of the value in the matrix will be converted via $\text{ColumnMax} * \text{Row} + \text{Column}$ to get the right position in the 1D array. (Codeline 29)

Step 5

The function `two_d_fetch` takes in the array, column and row number, it also takes in the size of each element and the amount of columns and rows the matrix has in total in order to be able to calculate position. It then takes out the value that is stored in that position and returns it.

Step 6

The `init_loop` function runs the store and fetch on a 3x3 matrix. (Codeline 92)


```
QEMU - Press Ctrl+Alt+G to release grab
Machine View
[ Wrote 151 lines ]
pi@raspberrypi:~$ gcc -o arraytask1 arraytask1.c
pi@raspberrypi:~$ ./arraytask1
allocation success
1
2
3
4
5
6
7
8
9
1 2 3 4 5 6 7 8 9
pi@raspberrypi:~$
```

Step 7

In order to counteract problems the store and fetch functions has if-statements that checks if the user is trying to store elements outside of the matrix boundaries.

Step 8

Two more functions were written. `two_d_store_col` (Codeline 66) and `two_d_fetch_col` (Codeline 69). Another initialization loop (`init_loop_col` Codeline 115) was written to check that everything works as intended. As seen on the bottom row (elements printed in order of the array) we can see that the printout follows the column major format.



The screenshot shows a QEMU terminal window titled "QEMU - Press Ctrl+Alt+G to release grab". The terminal output is as follows:

```
Machine View
pi@raspberrypi:~$ ls
arraytask1  arraytask3  code  exec  Public
arraytask1.c arraytask3.c Desktop  glass  python_games
arraytask2  arraytaskpekare  Documents Music  Templates
arraytask2.c arraytaskpekare.c Downloads Pictures Videos
pi@raspberrypi:~$ ./arraytask1

allocation success

1
2
3
4
5
6
7
8
9

1 4 7 2 5 8 3 6 9
pi@raspberrypi:~$
```

Step 9

The function arguments and return values were adjusted to accommodate memory address instead of taking in and returning the actual value. The functions structure is the same except for that the memory address is used instead of returning actual values.

```
28 . void two_d_store(char *p, int n, int m, int *value, int N, int M, int size){ .
.
.
45 . char* two_d_fetch(char *p,int n,int m, int N, int M, int size){
.
.
95 .     two_d_store(array, 0, 0,((int*)&a), n, m,size);
96 .     two_d_store(array, 1, 0,((int*)&b), n, m,size);
```

Step 10

To make sure that other data types also work with inserting and fetching values from the array each step takes into consideration how big the datatype is. For example if you insert data type int which consists of 4 bytes it jumps 4 bytes instead of just jumping one byte like before.

```
28 . void two_d_store(char *p, int n, int m, int *value, int N, int M, int size){
29 .     if(n >= N){
30 .         printf("\ndimensions doesnt match\n");
31 .         return;
32 .     }
33 .     if(m >= M){
34 .         printf("\ndimensions doesnt match\n");
35 .         return;
36 .     }
37 .     //printf("Value: %d\n", *value);
38 .     int i;
39 .     for(i = 0; i < size; i++){
40 .         p[(N * m + n)*size + i] = *((char*)value+i);
41 .     }
42 .     return;
43 . }
44 .
45 . char* two_d_fetch(char *p, int n, int m, int N, int M, int size){
46 .     if(n >= N){
47 .         printf("\nElement does not exist\n");
48 .         return;
49 .     }
50 .     if(m >= M){
51 .         printf("\nElement does not exist\n");
52 .         return;
53 .     }
54 .     int position = (N * m + n)*size;
55 .     char *x = p+position;
56 .     //printf("%d ", (int)*x);
57 .     return x;
58 . }
```

```
1 . #include <stdlib.h>
2 . #include <stdio.h>
3 .
4 . char* two_d_alloc(int N, int M, int size){
5 .
6 .     //allocates an char array with size n*m
7 .     //is acutally an 1D array using buffer
8 .
9 .     char *c_array;
10 .
11 .     //calls malloc to allocate appropriate number of bytes for the array
12 .     c_array = (char *) malloc(size*N*M);
13 .
14 .     if(c_array != NULL){
15 .         printf("\nallocation success\n");
16 .     }
17 .     else{
18 .         printf("\nallocation fail\n");
19 .     }
20 .     return c_array;
21 .
22 . }
23 .
24 . void two_d_dealloc(char *p){
25 .     free(p);
```

```

26 .     return;
27 . }
28 .
29 . void two_d_store(char *p, int n, int m, int value, int N, int M, int size){
30 .     if(n >= N){
31 .         printf("\ndimensions doesnt match\n");
32 .         return;
33 .     }
34 .     if(m >= M){
35 .         printf("\ndimensions doesnt match\n");
36 .         return;
37 .     }
38 .     p[N * m + n] = value;
39 .     return;
40 . }
41 .
42 . int two_d_fetch(char *p,int n,int m, int N, int M, int size){
43 .     if(n >= N){
44 .         printf("\nelement does not exist\n");
45 .         return;
46 .     }
47 .     if(m >= M){
48 .         printf("\nelement does not exist\n");
49 .         return;
50 .     }
51 .     int x = p[N * (m) + n];
52 .     printf("\n %d \n",x);
53 .     return p[n*m];
54 . }
55 .
56 . void two_d_store_col(char *p, int n, int m, int value, int N, int M, int size){
57 .     if(n >= N){
58 .         printf("\ndimensions doesnt match\n");
59 .         return;
60 .     }
61 .     if(m >= M){
62 .         printf("\ndimensions doesnt match\n");
63 .         return;
64 .     }
65 .     p[M * n + m] = value;
66 .     return;
67 . }
68 .
69 . int two_d_fetch_col(char *p,int n,int m, int N, int M, int size){
70 .     if(n >= N){
71 .         printf("\nelement does not exist\n");
72 .         return;
73 .     }
74 .     if(m >= M){
75 .         printf("\nelement does not exist\n");
76 .         return;
77 .     }
78 .     int x = p[M * n + m];
79 .     printf("\n %d \n",x);
80 .     return p[n*m];
81 . }
82 . int loop(char* p){
83 .     int i = 0;
84 .     printf("\n");
85 .     while ( i < 9){
86 .         printf(" %d ",p[i]);
87 .         i++;
88 .     }
89 .     printf("\n");
90 . }
91 .
92 . int init_loop(char *array, int n , int m){
93 .     two_d_store(array, 0, 0, 1, n, m,sizeof(int));
94 .     two_d_store(array, 1, 0, 2, n, m,sizeof(int));
95 .     two_d_store(array, 2, 0, 3, n, m,sizeof(int));

```

```

96 .   two_d_store(array, 0, 1, 4, n, m, sizeof(int));
97 .   two_d_store(array, 1, 1, 5, n, m, sizeof(int));
98 .   two_d_store(array, 2, 1, 6, n, m, sizeof(int));
99 .   two_d_store(array, 0, 2, 7, n, m, sizeof(int));
100 .  two_d_store(array, 1, 2, 8, n, m, sizeof(int));
101 .  two_d_store(array, 2, 2, 9, n, m, sizeof(int));
102 .
103 .   two_d_fetch(array, 0, 0, n, m, sizeof(int));
104 .   two_d_fetch(array, 1, 0, n, m, sizeof(int));
105 .   two_d_fetch(array, 2, 0, n, m, sizeof(int));
106 .   two_d_fetch(array, 0, 1, n, m, sizeof(int));
107 .   two_d_fetch(array, 1, 1, n, m, sizeof(int));
108 .   two_d_fetch(array, 2, 1, n, m, sizeof(int));
109 .   two_d_fetch(array, 0, 2, n, m, sizeof(int));
110 .   two_d_fetch(array, 1, 2, n, m, sizeof(int));
111 .   two_d_fetch(array, 2, 2, n, m, sizeof(int));
112 .   return;
113 . }
114 .
115 . int init_loop_col(char *array, int n , int m){
116 .   two_d_store_col(array, 0, 0, 1, n, m, sizeof(int));
117 .   two_d_store_col(array, 1, 0, 2, n, m, sizeof(int));
118 .   two_d_store_col(array, 2, 0, 3, n, m, sizeof(int));
119 .   two_d_store_col(array, 0, 1, 4, n, m, sizeof(int));
120 .   two_d_store_col(array, 1, 1, 5, n, m, sizeof(int));
121 .   two_d_store_col(array, 2, 1, 6, n, m, sizeof(int));
122 .   two_d_store_col(array, 0, 2, 7, n, m, sizeof(int));
123 .   two_d_store_col(array, 1, 2, 8, n, m, sizeof(int));
124 .   two_d_store_col(array, 2, 2, 9, n, m, sizeof(int));
125 .
126 .   two_d_fetch_col(array, 0, 0, n, m, sizeof(int));
127 .   two_d_fetch_col(array, 1, 0, n, m, sizeof(int));
128 .   two_d_fetch_col(array, 2, 0, n, m, sizeof(int));
129 .   two_d_fetch_col(array, 0, 1, n, m, sizeof(int));
130 .   two_d_fetch_col(array, 1, 1, n, m, sizeof(int));
131 .   two_d_fetch_col(array, 2, 1, n, m, sizeof(int));
132 .   two_d_fetch_col(array, 0, 2, n, m, sizeof(int));
133 .   two_d_fetch_col(array, 1, 2, n, m, sizeof(int));
134 .   two_d_fetch_col(array, 2, 2, n, m, sizeof(int));
135 .   return;
136 . }
137 .
138 .
139 . int main(){
140 .   int n = 3;
141 .   int m = 3;
142 .   //n = kolumn
143 .   //m = rad
144 .   //index start n = 0, m = 0
145 .   char *array = two_d_alloc(n,m, sizeof(char));
146 .   //init_loop(array,n,m);
147 .   init_loop_col(array, n , m);
148 .   loop(array);
149 .   two_d_dealloc(array);
150 .   return 0;
151 . }
152 .

```

Task 2: Memory Dump (5 points)

The assignment was to read through the array and print out the address of the first word then print the value of each word with four words per line. The words should also be displayed in hexadecimal notation. (Codeline 85)

```
QEMU - Press Ctrl+Alt+G to release grab
Machine View
Save modified buffer (ANSWERING "No" WILL DESTROY CHANGES) ?
pi@raspberrypi:~$ ls
arraytask1  arraytask3  code  exec  Public
arraytask1.c  arraytask3.c  Desktop  glass  python_games
arraytask2  arraytaskpekare  Documents  Music  Templates
arraytask2.c  arraytaskpekare.c  Downloads  Pictures  Videos
pi@raspberrypi:~$ ./arraytask2.c
-bash: ./arraytask2.c: command not found
pi@raspberrypi:~$ ./arraytask2
Allocation success

4x4 Matrix :
3.370000  7.210000  3.230000  0.000000
2.010000  2.000000  6.000000  0.000000
7.000000  0.000000  9.000000  0.000000
0.000000  0.000000  0.000000  0.000000

Minidump
Address> 0x21008 :0x0f5c28f6 0x400af5c2 0x3d70a3d7 0x401cd70a
Address> 0x21018 :0x3d70a3d7 0x4009d70a 0000000000 0000000000
Address> 0x21028 :0xc147ac14 0x4000147a 0000000000 0x40000000
Address> 0x21038 :0000000000 0x40180000 0000000000 0000000000
Address> 0x21048 :0000000000 0x401c0000 0000000000 0x40200000
Address> 0x21058 :0000000000 0x40220000 0000000000 0000000000
Address> 0x21068 :0000000000 0000000000 0000000000 0000000000
Address> 0x21078 :0000000000 0000000000 0000000000 0000000000
pi@raspberrypi:~$
```

```
1 . #include <stdlib.h>
2 . #include <stdio.h>
3 .
4 . char* two_d_alloc(int N, int M, int size){
5 .
6 .     //allocates an char array with size n*m
7 .     //is acutally an 1D array using buffer
8 .
9 .     char *c_array;
10 .
11 .     //calls malloc to allocate appropriate number of bytes for the array
12 .     c_array = (char *) malloc(size*N*M);
13 .
14 .     if(c_array != NULL){
15 .         printf("\nAllocation success\n");
16 .     }
17 .     else{
18 .         printf("\nAllocation fail\n");
19 .     }
20 .     return c_array;
21 . }
22 . }
23 .
24 . void two_d_dealloc(char *p){
25 .     free(p);
26 .     return;
27 . }
28 . void two_d_store(char *p, int n, int m, int *value, int N, int M, int size){
29 .     if(n >= N){
30 .         printf("\ndimensions doesnt match\n");
31 .         return;
32 .     }
33 .     if(m >= M){
34 .         printf("\ndimensions doesnt match\n");
35 .         return;
36 .     }
37 .     //printf("Value: %d\n", *value);
38 .     int i;
39 .     for(i = 0; i < size; i++){
40 .         p[(N * m + n)*size + i] = *((char*)value+i);
41 .     }
42 .     return;
43 . }
44 .
```

```

45 . char* two_d_fetch(char *p,int n,int m, int N, int M, int size){
46 .     if(n >= N){
47 .         printf("\nElement does not exist\n");
48 .         return;
49 .     }
50 .     if(m >= M){
51 .         printf("\nElement does not exist\n");
52 .         return;
53 .     }
54 .     int position = (N * m + n)*size;
55 .     char *x = p+position;
56 .     //printf("%d ", (int)*x);
57 .     return x;
58 . }
59 . void print_matrix(char *p,int n, int m){
60 .     printf("\n%d x %d Matrix : \n", n , m);
61 .     int i = 0;
62 .     int j = 0;
63 .     while (j < n){
64 .         while(i < m){
65 .             char *x = two_d_fetch(p,i,j,n,m,sizeof(double));
66 .             printf(" %f ", *(double*)x);
67 .             i++;
68 .         }
69 .         printf("\n");
70 .         j++;
71 .         i = 0;
72 .     }
73 . }
74 .
75 . int loop(char* p){
76 .     int i = 0;
77 .     printf("Array printed in order of elements : \n");
78 .     while ( i < 9*4){
79 .         printf(" %d ",p[i]);
80 .         i++;
81 .     }
82 .     printf("\n");
83 . }
84 .
85 . void memory_dump(char* array, int numbytes){
86 .     printf("\nMinnesdump\n");
87 .     int k;
88 .     int siffra = 0;
89 .     for(k = 0; k < numbytes/4;k++){ //divides the total amount of bytes by 4 because were casting to int
90 .         siffra = *(((int*)array) + k);
91 .         int *adressen = (((int*) array) + k);
92 .         if(k % 4 == 0){
93 .             printf("\nAdress> %p :",adressen);
94 .         }
95 .         printf("%#010x ", siffra);
96 .     }
97 .     printf("\n");
98 . }
99 .
100. int init_loop(char *array, int n , int m, int size){
101.     double a = 3.37;
102.     double b = 7.21;
103.     double c = 3.23;
104.     double d = 2.01;
105.     double e = 2;
106.     double f = 6;
107.     double g = 7;
108.     double h = 8;
109.     double i = 9;
110.     two_d_store(array, 0, 0,((int*)&a), n, m,size);
111.     two_d_store(array, 1, 0,((int*)&b), n, m,size);
112.     two_d_store(array, 2, 0,((int*)&c), n, m,size);
113.     two_d_store(array, 0, 1,((int*)&d), n, m,size);
114.     two_d_store(array, 1, 1,((int*)&e), n, m,size);

```

```

115.    two_d_store(array, 2, 1, ((int*)&f), n, m, size);
116.    two_d_store(array, 0, 2, ((int*)&g), n, m, size);
117.    two_d_store(array, 1, 2, ((int*)&h), n, m, size);
118.    two_d_store(array, 2, 2, ((int*)&i), n, m, size);
119.    two_d_fetch(array, 0, 0, n, m, size);
120.    two_d_fetch(array, 1, 0, n, m, size);
121.    two_d_fetch(array, 2, 0, n, m, size);
122.    two_d_fetch(array, 0, 1, n, m, size);
123.    two_d_fetch(array, 1, 1, n, m, size);
124.    two_d_fetch(array, 2, 1, n, m, size);
125.    two_d_fetch(array, 0, 2, n, m, size);
126.    two_d_fetch(array, 1, 2, n, m, size);
127.    two_d_fetch(array, 2, 2, n, m, size);
128.    return;
129. }
130.
131. int main(){
132.     //n = kolumn
133.     //m = rad
134.     //index start n = 0, m = 0
135.     int n = 4;
136.     int m = 4;
137.     int size = sizeof(double);
138.     char *array = two_d_alloc(n,m,size);
139.     //two_d_dealloc(array);
140.
141.     init_loop(array,n,m,size);
142.     print_matrix(array,n,m);
143.     memory_dump(array, n*m*size);
144.     //loop(array);
145.     return 0;
146. }

```

Task 3: Linked Lists (5 points)

The following task was to implement a struct which holds an element value and a pointer to the next node in the list. The nodes of the struct were then placed in the array in corresponding order. The memory dump shows the address and value in hexadecimal form. As shown below the value and address of every element in the linked list is printed. The address of each element is incremented and judging by what our memory dump has printed out we can see that each node points at the next one and that the last one points at NULL (0000000000000000). (Codeline 24)

```

QEMU - Press Ctrl+Alt+G to release grab
Machine View
node * list = list_init(n, m, array);
//print_LL(list);

//char* node=two_d_fetch(array, 1, 2, n, m, sizeof(node));
//printf("\n%d\n", ((node*)(node))->value);
memory_dump(array, sizeof(node)*n*m);
two_d_dealloc(array);

return 0;

[ Wrote 164 lines ]

pi@raspberrypi:~$ gcc -o arraytask3 arraytask3.c
pi@raspberrypi:~$ ./arraytask3

Allocation success

Minnesdump
Address> 0x21008 :0000000000 0x00021010 0x00000001 0x00021018
Address> 0x21018 :0x00000002 0x00021020 0x00000003 0x00021028
Address> 0x21028 :0x00000004 0x00021030 0x00000005 0x00021038
Address> 0x21038 :0x00000006 0x00021040 0x00000007 0x00021048
Address> 0x21048 :0x00000008 0000000000
pi@raspberrypi:~$

```



```

1 . #include <stdlib.h>
2 . #include <stdio.h>
3 . typedef struct element{
4 .     int value;
5 .     struct element * next;
6 . }node;
7 . void two_d_store(char *p, int n, int m, int *value, int N, int M, int size){
8 .     if(n >= N){
9 .         printf("\ndimensions doesnt match\n");
10 .        return;
11 .    }
12 .    if(m >= M){
13 .        printf("\ndimensions doesnt match\n");
14 .        return;c
15 .    }
16 .    //printf("Value: %d\n", *value);
17 .    int i;
18 .    for(i = 0; i < size; i++){
19 .        p[(N * m + n)*size + i] = *((char*)value+i);
20 .    }
21 .    return;
22 . }
23 .
24 . node * list_init(int n, int m, char *array){
25 .     node * head;
26 .     int elements = n*m;
27 .     head = (node *) (array);
28 .     head->value = 0;
29 .     head->next = NULL;
30 .     two_d_store(array, 0, 0, (int*)head, n, m, sizeof(node));
31 .     int i;
32 .     add_after(head, 1, 1, 0, array);
33 .     add_after(head, 2, 2, 0, array);
34 .     add_after(head, 3, 0, 1, array);
35 .     add_after(head, 4, 1, 1, array);
36 .     add_after(head, 5, 2, 1, array);
37 .     add_after(head, 6, 0, 2, array);
38 .     add_after(head, 7, 1, 2, array);
39 .     add_after(head, 8, 2, 2, array);
40 .     return head;
41 . }
42 .
43 . int add_after(node *list, int data, int n, int m, char *array){
44 .     node * current = list;
45 .
46 .     while(current->next != NULL){
47 .         current = current->next;
48 .     }
49 .     current->next = (node *) (array+(3 * m + n) * sizeof(node));
50 .     //two_d_store(array, n, m, (int*)(current->next), 3, 3, sizeof(node));
51 .     current->next->value = data;
52 .     current->next->next = NULL;
53 .     return 0;
54 . }
55 .
56 .
57 .
58 . char* two_d_alloc(int N, int M, int size){
59 .
60 .     //allocates an char array with size n*m
61 .     //is acutally an 1D array using buffer
62 .
63 .     char *c_array;
64 .
65 .     //calls malloc to allocate appropriate number of bytes for the array
66 .     c_array = (char *) malloc(size*N*M);
67 .
68 .     if(c_array != NULL){
69 .         printf("\nAllocation success\n");
70 .     }

```

```

71 .     else{
72 .         printf("\nAllocation fail\n");
73 .     }
74 .     return c_array;
75 .
76 . }
77 .
78 . void two_d_dealloc(char *p){
79 .     free(p);
80 .     return;
81 . }
82 .
83 .
84 . char* two_d_fetch(char *p,int n,int m, int N, int M, int size){
85 .     if(n >= N){
86 .         printf("\nElement does not exist\n");
87 .         return;
88 .     }
89 .     if(m >= M){
90 .         printf("\nElement does not exist\n");
91 .         return;
92 .     }
93 .     int position = (N * m + n)*size;
94 .     char *x = p+position;
95 .     //printf("%d ", (int)*x);
96 .     return x;
97 . }
98 . void print_matrix(char *p,int n, int m){
99 .     printf("\n%d x %d Matrix : \n", n , m);
100 .     int i = 0;
101 .     int j = 0;
102 .     while (j < n){
103 .         while(i < m){
104 .             char *x = two_d_fetch(p,i,j,n,m,sizeof(double));
105 .             printf(" %f ", *(double*)x);
106 .             i++;
107 .         }
108 .         printf("\n");
109 .         j++;
110 .         i = 0;
111 .     }
112 . }
113 .
114 . int loop(char* p){
115 .     int i = 0;
116 .     printf("Array printed in order of elements : \n");
117 .     while ( i < 9*4){
118 .         printf(" %d ",p[i]);
119 .         i++;
120 .     }
121 .     printf("\n");
122 . }
123 .
124 . void memory_dump(char * array, int numbytes){
125 .     printf("\nMinnesdump\n");
126 .     int k;
127 .     int siffra = 0;
128 .     for(k = 0; k < numbytes/4;k++){
129 .         siffra = *((int*)array + k);
130 .         int *adressen = ((int*) array) + k);
131 .         if(k % 4 == 0){
132 .             printf("\nAdress> %p :",adressen);
133 .         }
134 .         printf("%#010x ", siffra);
135 .     }
136 .     printf("\n");
137 . }
138 .
139 . void print_LL(node * head){
140 .     while(head != NULL){

```

```
141.         printf("\n%d\n",head->value);
142.         head = head->next;
143.     }
144. }
145.
146. int main(){
147.     //n = kolumn
148.     //m = rad
149.     //index start n = 0, m = 0
150.     int n = 3;
151.     int m = 3;
152.
153.     char* array = two_d_alloc(n,m,sizeof(node));
154.     node * list = list_init(n, m, array);
155.     //print_LL(list);
156.
157.
158.     //char* noder=two_d_fetch(array, 1, 2, n, m, sizeof(node));
159.     //printf("\n%d\n",((node*)(noder))->value);
160.     memory_dump(array, sizeof(node)*n*m);
161.     two_d_dealloc(array);
162.
163.     return 0;
164. }
165.
```