



INTERCEPTOR

ThS. Nguyễn Nghiệm
0913.745.789 - NghiemN@fpt.edu.vn



OBJECTIVES

- Theo dõi hành động của người dùng




AGENDA

- Giới thiệu Interceptor
- Xây dựng Interceptor
- Cấu hình chặn các url





INTERCEPTOR





INTERCEPTOR CONSTRUCTURE

```
public class MyInterceptor extends HandlerInterceptorAdapter{


    @Override
    public boolean preHandle(HttpServletRequest request,
        HttpServletResponse response, Object handler) throws Exception {
        return true;
    }

    @Override
    public void postHandle(HttpServletRequest request,
        HttpServletResponse response, Object handler,
        ModelAndView modelAndView) throws Exception {
    }

    @Override
    public void afterCompletion(HttpServletRequest request,
        HttpServletResponse response, Object handler, Exception ex)
        throws Exception {
    }
}
```



INTERCEPTOR HANDLING FLOW





LOGINTERCEPTOR

```
public class LogInterceptor extends HandlerInterceptorAdapter {
    @Override
    public boolean preHandle(HttpServletRequest request, HttpServletResponse response,
        Object handler) throws Exception {
        System.out.println("LogInterceptor.preHandle() " + request.getRequestURI());
        return true;
    }
    @Override
    public void postHandle(HttpServletRequest request, HttpServletResponse response,
        Object handler, ModelAndView modelAndView) throws Exception {
        System.out.println("LogInterceptor.postHandle() " + request.getRequestURI());
    }
    @Override
    public void afterCompletion(HttpServletRequest request, HttpServletResponse response,
        Object handler, Exception ex) throws Exception {
        System.out.println("LogInterceptor.afterCompletion() " + request.getRequestURI());
    }
}
```



INTERCEPTOR CONFIGURATION

@Configuration

```
public class InterceptorConfig implements WebMvcConfigurer {
```

@Override

```
public void addInterceptors(InterceptorRegistry registry) {  
    registry.addInterceptor(new LogInterceptor())  
        .addPathPatterns("/home/**")  
        .excludePathPatterns("/home/faq");  
}  
}
```

- addPathPatterns() chặn các url thỏa pattern
- excludePathPatterns() không chặn các url thỏa pattern
- ** đại diện cho mọi cấp



AUTHENTICATION WITH INTERCEPTOR

@Component

```
public class AuthInterceptor extends HandlerInterceptorAdapter{
    @Override
    public boolean preHandle(HttpServletRequest request,
                            HttpServletResponse response, Object handler) throws Exception {
        String cpath = request.getContextPath();
        String acturl = request.getRequestURI().replaceAll(cpath, "");

        HttpSession session = request.getSession();

        if(session.getAttribute("user") == null) {
            session.setAttribute("acturl", acturl);
            response.sendRedirect(cpath + "/account/login");
            return false;
        }
        return true;
    }
}
```



AUTHENTICATION CONFIGURATION

```
public class InterceptorConfig implements WebMvcConfigurer{
    @Autowired
    AuthInterceptor auth;

    @Override
    public void addInterceptors(InterceptorRegistry registry) {
        registry.addInterceptor(auth)
            .addPathPatterns("/account/edit",
                           "/account/change", "/account/logoff", "/admin/**")
            .excludePathPatterns("/admin/index");
    }
}
```



SUMMARY

- Giới thiệu Interceptor
- Xây dựng Interceptor
- Cấu hình chặn các url

