Supplementary Material

Table 1. **Sessions.** Top: CIL-CORD (classes with the prefix of their group); pool: CORD training receipts that contain one of the session's entities (10% of each pool is held out for early stopping under the clean protocol). Bottom: Mixed; schema: the annotation scheme SBR's supervision rule reads (Appendix B).

CIL-CORD (30 classes, 61 BIO tags)

S.	Classes	Pool
1	menu: cnt, discountprice, itemsubtotal, nm, num, price	800
2	menu: unitprice, vatyn, sub.cnt, sub.nm, sub.price, sub.unitprice	382
3	sub_total: discount_price, etc, othersvc_price, service_price, subtotal_price, tax_price	549
4	total: cashprice, changeprice, creditcardprice, emoneyprice, menuqty_cnt, menutype_cnt	723
5	total.total_etc, total.total_price, void_menu.nm, void_menu.price, sub.nm, sub.cnt	780

Mixed (25 tags)

S.	Dataset: tags introduced	Schema	Pool
1	FUNSD: HEADER, QUESTION	funsd	149
2	FUNSD: ANSWER	funsd	147–148
3	SROIE: COMPANY, DATE, ADDRESS, TOTAL	sroie	625–626
4	CORD (super-classes): menu, sub_total	cord	799–800
5	CORD (super-classes): total, void_menu, sub	cord	797–798
6	FUNSD: none (all FUNSD labels)	funsd	149

A. Setup and protocol

Streams. We use the dataset-provided OCR and boxes of FUNSD, CORD and SROIE, page images at 224×224 and 512 text tokens, so a LayoutLMv3 document is a sequence of 709 positions. On CIL-CORD (Tab. 1) a session's training and test pools keep every receipt that contains at least one of its entities, every entity of another session is labelled "O", and the head grows by twelve BIO tags per session; joint training uses the full-label pool, each receipt once with all its labels. Mixed alternates between new classes within a dataset and a new dataset, and its last session returns to FUNSD with all its labels and adds no tag. DIL keeps one schema {HEADER, KEY, VALUE, OTHER} fixed over FUNSD→SROIE→CORD. Every head is one linear layer; when it grows, old rows are kept and new rows are drawn from $\mathcal{N}(0, 0.02^2)$.

Scoring. A session's test labels show only its own classes, so raw scoring charges a model for every correct entity of another session and penalises it for knowing more classes. Hence, session-restricted scoring maps every predicted tag outside session j's label set to "O" before `seqeval` span matching (for SBR after the block decision of Eq. (1)); a predicted entity can then be a false positive only in its owning session and a gold entity a miss only in its own, so each error is charged at most once. However, its gap is coverage: a session's split keeps only receipts that contain one of its entities, so false positives on other receipts go uncounted. In contrast, full-label F1 scores the final model on the unmasked CORD test set and has no such gap. On every seed the order no memory (naive training, blocked readout) $<$ CoLaR $<$ memory relabelled at the boundaries $<$ {CoLaR-SBR, SBR-Recall, memory relabelled before each session, joint training} holds under both metrics; the MiB-style loss and ICE-O lie between CoLaR and the top group under both, and only the MiB-style loss and the boundary-relabelled memory swap places between the metrics. For CoLaR-SBR, SBR-Recall and joint training the two metrics differ by at most 1.3 points on every seed; for weak models AA is the more lenient, by 4.8 to 12.3 points without a memory and 1.2 to 5.2 for CoLaR. AA weights the five sessions equally, whereas session 1 holds 57% of the 1,306 gold spans. It is noted that for the shared softmax we have span counts but no per-token outputs. Given the exact true positives and misses, full-label F1 fixes the number of false-positive spans, and (misses − false positives)/misses would bound the share of missed spans labelled entirely "O" if every wrong span overlapped at most one missed gold span. Long runs of wrong tags break that proviso (the quantity reads up to 81% for the blocked readout without memory, whose per-token outputs put no old entity token at "O"), so we call it an indicator. The same count does bound CoLaR's old-span precision from below, at 71.6% on every seed.

Protocol. Under the clean protocol, we train every session in fp32 at batch size 2 with gradient checkpointing, AdamW (learning rate 5×10^{-5}, weight decay 0.01, clipping 1.0), at most 10 epochs (100 for joint training), and early-stop (patience 2, 0.1 F1 points, best weights restored) on 10% held out from the session's training pool, scored with the same session restriction; the test split never selects a model. Legacy (†) cells early-stop on the test split, differ in epoch cap by method and partly ran in fp16 mixed precision (Appendix C). A cell switches to the clean protocol only when its three clean seeds (42, 7, 123) exist, so no cell mixes the protocols. The clean, gate and rescore runs ran one at a time on one 6 GB RTX 2060; some rows of the first DIL grid ran on a rented GPU.

B. Method details

CoLaR. After the first session, we freeze the embeddings and layers $1..k$, so a stored activation is produced by the same layers forever and cannot go stale. At the end of each session the layer-k output of 50 training documents is kept as the fp16 factors $(U_r\Sigma_r)$ and $V_r^\top$ of its truncated SVD, with the document's boxes, attention mask, labels and storing session; no raw pixels and no token ids are kept. At every step four stored documents are rebuilt, injected at layer $k{+}1$ by a forward pre-hook (their boxes and mask drive the layout biases and attention mask), and their cross-entropy is added with weight 1; gradient checkpointing is off for the replayed pass. We count a document as $2r(709{+}768)$ bytes of factors plus 24,576 bytes of boxes, mask and labels (and one byte for the session under SBR), which for the 250 documents

of CIL-CORD gives the 100.7 MB of Tab. 4 (1 MB $= 10^6$ bytes). The rank r is the one knob that sets this size: at rank 64 or 32 a document would take 213.6 or 119.1 KB (53.4 or 29.8 MB in all), computed from the same count; we make no accuracy claim for these ranks. The record the implementation holds in memory is about 1% larger (406,800 against 402,689 bytes per document), because it also holds the labels in the final label space; no method reads that field, only the relabelled-memory diagnostics of rung H1.

SBR. A session that introduces at least one tag not yet covered opens a block with those tags, a background logit (a linear map from the 768-dimensional head input to one logit) and its session's schema; a session that only re-annotates known tags opens none, so on DIL SBR has one block. For a document of session s the supervision rule gives each block b one of three modes: *full* when s annotates every tag of b (target y on b's tags, O_b elsewhere); *all-background* when b belongs to another schema (target O_b on every token, a training-time convention that, between related receipt schemas, can call a real entity background); and *skipped* otherwise. As a result, on CIL-CORD a document trains only its own block; on Mixed the all-background mode keeps a block from claiming another dataset's tokens. A stored document follows the rule of the session that stored it. At inference, with $e_b = 1 - p_b(\mathrm{O}_b \mid x)$ and τ=0.5 (ties to the lower block index),

$$\hat{y}(x) = \begin{cases} \arg\max_{t \in \mathcal{T}_{b^\star}} p_{b^\star}(t \mid x) & e_{b^\star} > \tau, \\ \mathrm{O} & \text{otherwise}, \end{cases} \qquad b^\star = \arg\max_b e_b. \tag{1}$$

SBR-Recall. Every linear layer named query, key, value or dense (the attention output and both feed-forward layers) in layers k+1..12 carries one low-rank pair per delta, rank 64 with α=128, A Kaiming-uniform and B=0, so a fresh delta is the identity. A rank-64 delta over the eight layers above k=4 has $8 \times [3 \cdot 64 \cdot 1536 + 64 \cdot 1536 + 2 \cdot 64 \cdot (768{+}3072)] = 7{,}077{,}888$ parameters; the four deltas of CIL-CORD, counted at two bytes per parameter, give the 56.6 MB of Tab. 4 (14.2 MB per session), and 113.2 MB (28.3 MB per session) in fp32. The two-byte count is a reporting choice: the deltas were trained and evaluated in fp32, and no run evaluated half-precision deltas. The first session trains the base; after that, the encoder is frozen and only the head, the background weights and the current delta train. The loss groups a document's blocks by the delta each is read under and runs one forward pass per distinct delta, so every term is computed under its block's own trunk state, as is inference (five passes on CIL-CORD; a cached implementation repeats only the $12 - k$ upper layers, about 3.7 layer-equivalents of one pass). Without a memory on one schema a later session's loss contains only its own block, so an old block's delta and background weights are outside the graph and its rows of the tag head get zero gradient; only AdamW's decoupled weight decay (under 1% over a run) and out-claiming by new blocks can move its tokens. In the clean runs no session falls more than 0.6 points below its diagonal at any later boundary.

Memory accounting (Tab. 2). We count a raw-replay document as our code holds it: $3 \cdot 224^2$ pixels at four bytes (one byte in the 8-bit row, which no run used) and $512 \cdot 7{+}1$ int64 values (per token its id, four box coordinates, mask and label; one for the session). The uncompressed latent is $709 \cdot 768$ fp16 values plus the 24,576 bytes of the CoLaR record. Raw replay with the blocked readout trains the whole network (a raw memory could freeze the same layers; ours does not); CoLaR and SBR-Recall train only what lies above layer 4 after session 1, and CoLaR replays a document through the upper eight layers only. Wall-clock is reported for completeness: only one CoLaR-SBR run ran uninterrupted, so we do not compare run times.

C. Baselines

Ports. We port every baseline onto the one growing token head that every other row uses (Tab. 3); none is checked against its published NER numbers. Hyper-parameters are the methods' defaults as recorded by each run: ER and DER++ keep a reservoir of 200 documents (DER++ α=β=0.5), LwF uses T=2, CL-LoRA a rank-8 adapter with an orthogonality penalty of 0.5. LCA keeps its published optimiser instead of our AdamW recipe: SGD with momentum 0.9, a cosine schedule, learning rate 0.01 and weight decay $5{\times}10^{-4}$, and SGD at $5{\times}10^{-3}$ for the realignment. Rows marked ^{p} in the comparison table of the main paper were made before we fixed the order of the adapter matrices in our ports' orthogonality penalty.

How the set was fixed. We fixed the set after a first grid on all three streams. There, EWC [16], L2P [41] and DualPrompt [40] left at least sessions 4 and 5 of CIL-CORD unlearned on every seed, and ER with SAM (our C-Flat++ port, run with its curvature weight at 0) stayed within 2.8 AA of ER on every seed, so these were dropped; O-LoRA [39] was dropped because its runs predate the penalty fix. Methods that fail on the scenario (CPFD, IS3) were kept. Four baselines end below naive training on every seed because they learn later sessions poorly: CPFD learns no session after the first (at most 0.0 F1 on a later diagonal), and IS3, CODA-Prompt and LCA each learn some later session to at most 32.3 F1, where naive training learns every session to at least 78.6.

Table 2. **Memory accounting** (CIL-CORD: 250 stored documents, or four deltas; 1 MB $= 10^6$ bytes). Computed: the size of an encoding no run used, from the counts in the text. Trainable: parameters trained at once after session 1 (SBR-Recall: one delta at a time, four over the run); peak GPU memory and hours per run from the clean runs ($^{n=k}$: only k uninterrupted runs timed). Generated.

Storage form	Per unit	Total MB	Pixels	Token ids	Trainable (M)	Peak GPU MB	h/run
Layer-4 latent, fp16, uncompressed (computed)	1113.6 KB/doc	278.4	no	no	–	–	–
Raw document as held (fp32 pixels)	630.8 KB/doc	157.7	yes	yes	125.4	2666	2.9
Raw document, 8-bit pixels (computed)	179.2 KB/doc	44.8	yes	yes	–	–	–
CoLaR rank 128	402.7 KB/doc	100.7	no	no	56.8	2436	$2.0^{n=1}$
SBR-Recall deltas, fp16 (computed)	14.2 MB/session	56.6	no	no	–	–	–
SBR-Recall deltas, fp32, as trained	28.3 MB/session	113.2	no	no	7.1	2436	1.7

Table 3. **Baseline card** (the methods of the main paper's comparison table). What our port changes against the published method, what it keeps across sessions, and the number of seeds behind each cell (†: legacy protocol). Legacy cells early-stop on the session's test split; their epoch cap is 100 for ER, DER++, LwF, CPFD and IS3, 30 for CODA-Prompt and CL-LoRA and 10 for LCA and the CoLaR family; most ran in fp16 mixed precision, but IS3 and LCA always in fp32, and seed 42 of several CIL-CORD baselines in fp32, so some cells mix precisions across seeds. LwF excludes one fp16 seed per scenario that collapsed to all-background. The first DIL grid saved no configuration; its settings are the grid script's defaults. Generated.

				Seeds		
Method	Family	What our port changes	Memory	CIL-CORD	Mixed	DIL
ER	Replay	–	200 raw documents	$3^{\dagger}$	$2^{\dagger}$	$3^{\dagger}$
DER++	Replay	–	200 raw documents + logits	$3^{\dagger}$	$2^{\dagger}$	$3^{\dagger}$
LwF	Regularisation	–	previous model	$2^{\dagger}$	$1^{\dagger}$	$3^{\dagger}$
CODA-Prompt	Prompt, LoRA	prompts prepended to the input sequence (an input-prepend variant)	none (prompt pool)	$2^{\dagger}$	$2^{\dagger}$	$3^{\dagger}$
CL-LoRA	Prompt, LoRA	one shared rank-8 adapter retrained each session (published: random-orthogonal shared and block-wise task-specific adapters, early-exit distillation); gradient reassignment at scale 1, i.e. off	previous model, past adapter matrices	$2^{\dagger}$	$2^{\dagger}$	$3^{\dagger}$
CPFD	Continual NER	one growing token head (published: per-task classifiers); sample weights set to 1	previous model	$2^{\dagger}$	$2^{\dagger}$	$3^{\dagger}$
IS3	Continual NER	one growing token head (published: per-task classifiers)	previous model, class prototypes	$2^{\dagger}$	$2^{\dagger}$	$1^{\dagger}$
LCA	Merging	one growing token head (published: per-task heads); Gaussians per token class, "O" excluded	base and per-session backbones, class Gaussians	$2^{\dagger}$	$2^{\dagger}$	$3^{\dagger}$

D. Extended results and ablations

Retention (Fig. 1). We read the diagonal (each session when it is learned) and the bottom row (the final model). Naive training learns every session and keeps none of the earlier ones. CoLaR keeps part of the old sessions; however, from session 3 on its diagonal is low: the session being trained is suppressed (rung H0). With the relabelled memory sessions 3 and 4 rise one boundary after they are learned, while the last session stays low (rung H1). The blocked readout without a memory learns every session and loses the old ones; in contrast, with the memory the columns hold. *Where the remaining gap lies:* under CoLaR-SBR a column loses 1.5 to 9.0 points from its diagonal to the final row of the mean matrix, session 2 the most, and under SBR-Recall every column of the mean matrix ends within 1.4 points of its diagonal, so what CoLaR-SBR still loses to joint training is retention of early sessions, which per-session deltas remove on this stream.

Rung details (Sec. 4 of the main paper). *H0.* The memory run keeps 18.7 to 22.6% of the old sessions' spans where naive training keeps none, at an old-span precision of at least 71.6% (a lower bound; Appendix A). *H1.* At the boundary, the refresh lifts AA from 33.5 to 63.6 (means, three seeds), 48 to 56% of the seed-matched AA gap to joint training (92.0 full-label F1, 91.3 AA). It cannot reach the session being trained: sessions 3 to 5 are learned only to 2 to 37 F1 on their own diagonal, sessions 3 and 4 rise to 74 to 88 one session later, and the last ends at 3.9 to 14.7, a fifth of AA but 8% of the test spans. Refreshed before each session, the memory reaches 91.3±1.3 AA. *H2.* The MiB-style loss reaches 72.1±1.9 AA, 64 to 70% of the seed-matched AA gap. It learns every session to at least 90.1 on its diagonal, but the first session ends at no more than 35.5 F1 on any seed. *H3.* CoLaR-SBR reaches 88.4±2.6 AA; its owning block claims 95.4 to 98.3% of the old entity tokens, and most remaining errors (56.6 to 71.6% of the wrong tokens) give the token another tag of its own session. Without the memory the same readout scores 21.6±2.2 AA; not one old entity token is predicted "O", 83.8 to 93.5% of the wrong ones receive another session's class, and each old block claims 17.0 to 24.3% of the tokens of its own split that are not its entities, against 0.6 to 1.7% with the memory. *H4.* Under SBR-Recall the owning block claims 97.0 to 98.3% of the old entity tokens.




Figure 1. **Retention matrices** (CIL-CORD, LayoutLMv3, clean protocol, session-restricted F1, mean over the three seeds). Row i: after training session i; column j: session j. Joint training is one pooled run, so only its final row exists.




Figure 2. **Per-class full-label F1** of four prediction-dump re-runs (CIL-CORD, final model, unmasked test set; seed 42 only, each reproducing the full-label F1 of its clean run, given in the legend). Classes grouped by the session that introduces them; grey: the class does not occur in the test set.

Per class (Fig. 2). It is noted that the dump re-runs are not table cells, and every statement here is about seed 42 only. Of the 23 classes that occur in the test set, the joint-training re-run finds 21 (F1 above 0), the CoLaR-SBR re-run 20, the CoLaR re-run 15 and the naive re-run 1; 2 of the classes the CoLaR-SBR re-run misses are missed by joint training too. In the CoLaR re-run the session-5 classes are almost never found (the suppressed newest session) and the session-1 classes, which hold most test entities, are found only in part, while several session-2 and session-3 classes are kept.

Design choices (Fig. 3 and Tab. 5). Figure 3 draws the component grid with its seeds; Tab. 5 gathers the design-choice runs, all legacy gate runs and mostly single seeds, so each is compared only within its own protocol. *Delta capacity.* At rank 8 on query, key and value, SBR-Recall learns its weakest session (the sub-total and total fields, mostly prices) only to the value in the min $R[j, j]$ column, and adding the memory does not help; at rank 64 with the attention output and feed-forward layers every session is learned on all three seeds. Hence, isolation was sound at rank 8, and the capacity of the delta was the limit. Rank 64 is the one setting we chose on CIL-CORD, from these legacy runs, before the clean re-runs. *Across schemas.* Without a memory on Mixed, an old block is trained towards its background on every token of another schema's documents and nothing trains it towards its own tags, so its blocks fall silent until their domain returns and at least one session ends at zero; the trunk

Table 4. **Component ablations on CIL-CORD**, the runs of the ladder table of the main paper (clean protocol, LayoutLMv3, mean ± s.d. over three seeds). Ticks: memory (Mem.; latent unless marked raw), blocked readout (Blk.), per-session deltas (Δ), true labels (True). All rows but naive, joint and the raw memory freeze at least the embeddings and layers 1..4 after session 1. MB: bytes kept across sessions (the main paper's memory-cost section); SBR-Recall's deltas at two bytes per parameter, a reporting choice (113.2 as trained in fp32). ^{r}Stored documents given their true labels (H1): the older ones at each boundary, or all of them before each session (pre-session).

Configuration	Mem.	Blk.	Δ	True	Full-label F1	AA	MB
Naive					13.0±0.2	18.3±0.5	0
+ memory (CoLaR)	✓				30.7±1.5	33.5±1.0	100.7
+ blocked readout		✓			11.4±2.3	21.6±2.2	0
+ both (CoLaR-SBR)	✓	✓			89.1±2.0	88.4±2.6	100.7
+ both, raw memory	✓	✓			88.4±1.0	88.4±1.1	157.7
SBR-Recall		✓	✓		92.6±1.0	91.9±0.6	56.6
Relabel, boundary^{r}	✓			✓	76.5±2.3	63.6±1.9	100.9
Relabel, pre-session^{r}	✓			✓	92.1±1.3	91.3±1.3	100.9
Joint (reference)				✓	92.0±0.4	91.3±0.8	–




Figure 3. **The component grid of Tab. 4** (CIL-CORD, clean protocol; bar: mean of three seeds, dots: the seeds; full-label F1 dark, AA light).

is frozen, so this is a readout effect, not drift. In contrast, the 50-document memory supplies the positive counterweight: no session ends below the value in the last column, and isolation by deltas does not replace the memory across schemas (one seed). *Head slots.* LexSlot adds head slots that a session updates only when its OCR vocabulary selects them, and stores token ids, unlike CoLaR. Stacked on CoLaR-SBR it raises the gate mean and narrows the spread between seeds; we keep it as a row, not a method.

E. Drift evidence

Where drift sits. We observe that under naive fine-tuning on a fixed label space every encoder forgets its earlier domains (Tab. 6). On our pilot stream FUNSD→CORD→SROIE, where each dataset brings its own labels, the representation drift grows with depth on

Table 5. **Design-choice ablations** (fp32 gate runs†: 10-epoch cap, test-split early stopping, session-restricted scoring; AA per seed when fewer than three, else mean ± s.d.). The last two columns give the lowest diagonal entry (a session when learned) and the lowest final-row entry over every session and seed of the row. Generated.

Variant	AA	min $R[j,j]$	min $R[T,j]$
SBR-Recall delta capacity, CIL-CORD			
rank 8, Q/K/V, with memory	80.5†	61.5	63.2
rank 8, Q/K/V, no memory	82.5†	64.9	66.4
rank 64, Q/K/V + dense, no memory	92.8±0.5†	88.8	88.6
SBR-Recall across schemas, Mixed (rank 64)			
no memory	44.7†	82.0	0.0
50-document memory	85.9†	81.2	75.0
Head slots on CoLaR-SBR, CIL-CORD			
CoLaR-SBR	88.0±2.0†	85.9	72.8
+ LexSlot	89.7±0.5†	89.8	80.6

Table 6. **Drift and its remedy on four encoders** (DIL, AA, mean ± s.d. over three seeds; first grid, legacy protocol†). On average, replay comes within one point of joint training or exceeds it, and EWC and LwF stay within ten points of naive training. "–": did not fit the 6 GB GPU. Generated.

Backbone	Naive	EWC	LwF	ER	DER++	Joint
LayoutLMv3	41.3±1.5	41.2±1.1	43.7±1.1	87.9±1.4	88.0±0.9	88.7±1.1
LiLT	40.1±0.5	48.4±5.9	–	85.7±0.5	84.4±0.3	83.8±1.2
BROS	40.3±1.8	45.0±4.9	35.1±3.1	87.8±0.4	87.5±1.1	87.5±1.3
BERT	39.4±0.3	46.6±3.0	40.5±0.1	77.1±0.9	77.4±0.6	77.2±0.4




Figure 4. **Drift by depth**: linear CKA between checkpoints before and after the second task (FUNSD→CORD, each dataset with its own labels) under naive fine-tuning on four encoders (1.0: no drift; three seeds).

all four encoders, largest at the head and the last layer and smallest at the embeddings (Fig. 4). That forgetting concentrates in the output-facing computation is known for image classifiers [31]; here it holds, on that stream, for three multimodal document encoders and a text-only one. On images the readout can also be repaired from class statistics (Appendix F); on token-labelled documents, in our experiments, only old-task supervision of the readout repaired it.

Table 7. **Image class-incremental learning** (AA, mean ± s.d., seeds 42/7/123). CIFAR-100 and ImageNet-R in ten sessions (class order seed 1993, as in SLCA and RanPAC); ViT-B/16 pre-trained on ImageNet-21k with a linear head on the CLS token. House recipe, not the clean document protocol: AdamW at 5×10^{-5} (SLCA and LCA: SGD at 0.01), batch size 16, epoch cap 100 (SLCA: 20) with early stopping, fp32 with gradient checkpointing (the latent memory and CoLaR: mixed precision). ER and DER++ keep 2,000 raw images, SLCA class Gaussians, the latent memory and CoLaR 500 images per session as layer-4 latents (5,000 after ten sessions). SLCA and RanPAC take the slots CPFD and IS3 take on documents. [v]Diagnostic probe on seed-42 variant runs (on CIFAR-100 a second run of the latent memory, on ImageNet-R a CoLaR run with a 20-epoch cap): a ridge readout refit on all training data through the run's adapted trunk; not a method. Generated.

Method	CIFAR-100	ImageNet-R
Naive	11.7 ± 1.1	9.3 ± 0.3
LwF	15.7 ± 0.6	12.7 ± 1.4
ER (2,000 exemplars)	76.2 ± 1.2	54.8 ± 0.7
DER++ (2,000 exemplars)	76.5 ± 1.5	52.8 ± 1.1
CODA-Prompt	15.2 ± 1.8	8.4 ± 0.7
CL-LoRA (2025)	14.1 ± 1.2	11.4 ± 0.8
SLCA (2023)	87.5 ± 0.2	65.0 ± 0.3
RanPAC (2023)	85.3 ± 0.1	58.5 ± 0.3
LCA (2026)	77.2 ± 3.2	54.7 ± 3.6
Latent memory, 500/session (ours, uncompressed)	80.0 ± 0.7	55.1 ± 1.3
CoLaR r=128, 500/session (ours)	79.5 ± 1.0	55.3 ± 1.4
Ridge readout on a seed-42 variant run[v] (probe)	88.3	72.3
Joint training (reference)	89.5 ± 0.4	77.6 ± 0.5

Replay against the classical remedies. On every encoder of Tab. 6 replay (ER, DER++) comes close to joint training on average, whereas EWC and LwF stay near naive training; the benefit of EWC over naive training differs between encoders while the cause does not, which is why the table reports four. The buffer-free alternatives we built or ported for this drift each failed for a reason identified per boundary, in mostly single-seed diagnostics at their own operating points: head merging (TIES or Fisher) is close to a no-op; merging with Gaussian classifier realignment (LCA, three seeds) halves backward transfer but stops acquisition; subspace transfer (HGT, CUBER) trades stability for plasticity at the naive level; head slots without a buffer cannot re-ground the shared head; feature-Gaussian replay recovers only the densely labelled task, because a marginal summary breaks whole-document consistency; and refreshing stored labels with the model's own predictions is a no-op, because the model is confident on almost no stale "O" token.

F. Image classification

What transfers, and what does not. SLCA [44] and RanPAC [25] lead on both datasets, above the latent memory and CoLaR on every seed, and we make no state-of-the-art claim on images; our recipe is not SLCA's published one, and our SLCA and joint-training numbers are below the published ones. The latent memory is competitive with raw replay at 2.5× the items: on CIFAR-100 the latent memory and CoLaR are above ER and DER++ with 2,000 raw images on every seed, and on ImageNet-R they are within 2.7 and 1.6 points of ER on every seed. They store no pixel but more items (1,513 and 1,235 MB as recorded, against 1,204 MB for 2,000 raw images as our buffer stores them), and replay with 200 raw images falls to 42.3 / 21.6 (ER). Compressing each stored latent to rank 128 moves AA by at most 2.8 points on any seed. SLCA's margin comes from its classifier alignment: without it the same recipe falls to 38.0 / 25.8. On the one-seed variant runs of the probe row, the adapted trunk supports a readout above every seed of the latent memory and CoLaR rows, so the trunk holds more than the trained head reads out, the head-locus reading of documents; this rests on one seed. Since an image carries one label and has no background class, there is no background conflict to remove: SBR is not run on images, and a stored image's label never goes stale. With a plain softmax head CoLaR reaches 79.5 / 55.3 against 89.5 / 77.6 for joint training, whereas on CIL-CORD the same memory with a shared softmax reaches 33.5 AA against 91.3, a much larger gap, consistent with a cause that only token labelling has.

References

[1] Hongjoon Ahn, Jihwan Kwak, Subin Lim, Hyeonsu Bang, Hyojun Kim, and Taesup Moon. SS-IL: Separated softmax for incremental learning. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 844–853, 2021.

[2] Pietro Buzzega, Matteo Boschini, Angelo Porrello, Davide Abati, and Simone Calderara. Dark experience for general continual learning: A strong, simple baseline. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[3] Lucas Caccia, Rahaf Aljundi, Nader Asadi, Tinne Tuytelaars, Joelle Pineau, and Eugene Belilovsky. New insights on reducing abrupt representation change in online continual learning. In *International Conference on Learning Representations (ICLR)*, 2022.

[4] Fabio Cermelli, Massimiliano Mancini, Samuel Rota Bulò, Elisa Ricci, and Barbara Caputo. Modeling the background for incremental learning in semantic segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[5] Sungmin Cha and Kyunghyun Cho. Hyperparameters in continual learning: A reality check. *Transactions on Machine Learning Research (TMLR)*, 2025.

[6] Sungmin Cha, Beomyoung Kim, YoungJoon Yoo, and Taesup Moon. SSUL: Semantic segmentation with unknown label for exemplar-based class-incremental learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

[7] Arthur Douillard, Yifu Chen, Arnaud Dapogny, and Matthieu Cord. PLOP: Learning without forgetting for continual semantic segmentation. In *Proceedings of the IEEE/CVF Con-*

ference on Computer Vision and Pattern Recognition (CVPR), pages 4040–4050, 2021.

[8] Nathan Greenberg, Trapit Bansal, Patrick Verga, and Andrew McCallum. Marginal likelihood training of BiLSTM-CRF for biomedical named entity recognition from disjoint label sets. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 2824–2829, 2018.

[9] Tyler L. Hayes, Kushal Kafle, Robik Shrestha, Manoj Acharya, and Christopher Kanan. REMIND your neural network to prevent catastrophic forgetting. In *European Conference on Computer Vision (ECCV)*, 2020.

[10] Jiangpeng He, Zhihao Duan, and Fengqing Zhu. CL-LoRA: Continual low-rank adaptation for rehearsal-free class-incremental learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 30534–30544, 2025.

[11] Teakgyu Hong, Donghyun Kim, Mingi Ji, Wonseok Hwang, Daehyun Nam, and Sungrae Park. BROS: A pre-trained language model focusing on text and layout for better key information extraction from documents. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 10767–10775, 2022.

[12] Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*, 2022.

[13] Yupan Huang, Tengchao Lv, Lei Cui, Yutong Lu, and Furu Wei. LayoutLMv3: Pre-training for document AI with unified text and image masking. In *Proceedings of the 30th ACM International Conference on Multimedia (MM)*, pages 4083–4091, 2022.

[14] Gyuhak Kim, Bing Liu, and Zixuan Ke. A multi-head model for continual learning via out-of-distribution replay. In *Proceedings of the First Conference on Lifelong Learning Agents (CoLLAs)*, pages 548–563, 2022.

[15] Gyuhak Kim, Changnan Xiao, Tatsuya Konishi, Zixuan Ke, and Bing Liu. A theoretical study on solving continual learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2022.

[16] James Kirkpatrick, Razvan Pascanu, Neil Rabinowitz, Joel Veness, Guillaume Desjardins, Andrei A. Rusu, Kieran Milan, John Quan, Tiago Ramalho, Agnieszka Grabska-Barwinska, et al. Overcoming catastrophic forgetting in neural networks. *Proceedings of the National Academy of Sciences (PNAS)*, 114(13):3521–3526, 2017. 2

[17] Ritesh Kumar, Saurabh Goyal, Ashish Verma, and Vatche Isahagian. ProtoNER: Few shot incremental learning for named entity recognition using prototypical networks. In *Business Process Management Workshops (BPM 2023 International Workshops)*, pages 70–82. Springer, 2024.

[18] Siqi Li, Yufan Shen, Xiangnan Chen, Jiayi Chen, Hengwei Ju, Haodong Duan, Song Mao, Hongbin Zhou, Bo Zhang, Bin Fu, Pinlong Cai, Licheng Wen, Botian Shi, Yong Liu, Xinyu Cai, and Yu Qiao. GDI-Bench: A benchmark for general document intelligence with vision and reasoning decoupling. *arXiv preprint arXiv:2505.00063*, 2025.

[19] Zhizhong Li and Derek Hoiem. Learning without forgetting. In *European Conference on Computer Vision (ECCV)*, 2016.

[20] Minqian Liu and Lifu Huang. Teamwork is not always good: An empirical study of classifier drift in class-incremental information extraction. In *Findings of the Association for Computational Linguistics: ACL*, 2023.

[21] Yuyang Liu, Yang Cong, Dipam Goswami, Xialei Liu, and Joost van de Weijer. Augmented box replay: Overcoming foreground shift for incremental object detection. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, 2023.

[22] Ruotian Ma, Xuanting Chen, Lin Zhang, Xin Zhou, Junzhe Wang, Tao Gui, Qi Zhang, Xiang Gao, and Yunwen Chen. Learning "O" helps for learning more: Handling the unlabeled entity problem for class-incremental NER. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (ACL)*, pages 5959–5979, 2023.

[23] Marc Masana, Xialei Liu, Bartłomiej Twardowski, Mikel Menta, Andrew D. Bagdanov, and Joost van de Weijer. Class-incremental learning: Survey and performance evaluation on image classification. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 45(5):5513–5533, 2023.

[24] Michael McCloskey and Neal J. Cohen. Catastrophic interference in connectionist networks: The sequential learning problem. *Psychology of Learning and Motivation*, 24:109–165, 1989.

[25] Mark D. McDonnell, Dong Gong, Amin Parvaneh, Ehsan Abbasnejad, and Anton van den Hengel. RanPAC: Random projections and pre-trained models for continual learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2023. 6

[26] Mohammad Minouei, Khurram Azeem Hashmi, Mohammad Reza Soheili, Muhammad Zeshan Afzal, and Didier Stricker. Continual learning for table detection in document images. *Applied Sciences*, 12(18):8969, 2022.

[27] Qijie Mo, Yipeng Gao, Shenghao Fu, Junkai Yan, Ancong Wu, and Wei-Shi Zheng. Bridge past and future: Overcoming information asymmetry in incremental object detection. In *European Conference on Computer Vision (ECCV)*, pages 463–480. Springer, 2024.

[28] Natawut Monaikul, Giuseppe Castellucci, Simone Filice, and Oleg Rokhlenko. Continual learning for named entity recognition. In *Proceedings of the AAAI Conference on Artificial Intelligence*, pages 13570–13577, 2021.

[29] Lorenzo Pellegrini, Gabriele Graffieti, Vincenzo Lomonaco, and Davide Maltoni. Latent replay for real-time continual learning. In *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2020.

[30] Shengjie Qiu, Junhao Zheng, Zhen Liu, Yicheng Luo, and Qianli Ma. Incremental sequence labeling: A tale of two shifts. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 777–791, 2024. arXiv:2402.10447.

[31] Vinay V. Ramasesh, Ethan Dyer, and Maithra Raghu. Anatomy of catastrophic forgetting: Hidden representations and task semantics. In *International Conference on Learning Representations (ICLR)*, 2021. 5

[32] David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy P. Lillicrap, and Greg Wayne. Experience replay for continual learning. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2019.

[33] Abdellatif Sassioui, Yasser Elouargui, Mohamed El Kamili, Rachid Benouini, El Mehdi Benyoussef, Meriyem Chergui, and Mohammed Ouzzif. AMD-Proj: Adaptive memory-driven selective gradient projection for continual learning in document understanding. *Technologies*, 14(5):250, 2026.

[34] Abdellatif Sassioui, Yasser Elouargui, Mohamed El Kamili, Rachid Benouini, El Mehdi Benyoussef, Meriyem Chergui, and Mohamed Ouzzif. When documents evolve: Decomposing catastrophic forgetting in layout-aware document models. In *International Conference on Wireless Communications and Mobile Computing (IWCMC)*, pages 1124–1129, 2026.

[35] James Seale Smith, Leonid Karlinsky, Vyshnavi Gutta, Paola Cascante-Bonilla, Donghyun Kim, Assaf Arbelle, Rameswar Panda, Rogerio Feris, and Zsolt Kira. CODA-Prompt: Continual decomposed attention-based prompting for rehearsal-free continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2023.

[36] Tung Tran, Danilo Vasconcellos Vargas, and Khoat Than. LCA: Local classifier alignment for continual learning. In *International Conference on Learning Representations (ICLR)*, 2026.

[37] Jiapeng Wang, Lianwen Jin, and Kai Ding. LiLT: A simple yet effective language-independent layout transformer for structured document understanding. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2022.

[38] Liyuan Wang, Xingxing Zhang, Hang Su, and Jun Zhu. A comprehensive survey of continual learning: Theory, method and application. *IEEE Transactions on Pattern Analysis and Machine Intelligence (TPAMI)*, 46(8):5362–5383, 2024.

[39] Xiao Wang, Tianze Chen, Qiming Ge, Han Xia, Rong Bao, Rui Zheng, Qi Zhang, Tao Gui, and Xuanjing Huang. Orthogonal subspace learning for language model continual learning. In *Findings of the Association for Computational Linguistics: EMNLP*, 2023. 2

[40] Zifeng Wang, Zizhao Zhang, Sayna Ebrahimi, Ruoxi Sun, Han Zhang, Chen-Yu Lee, Xiaoqi Ren, Guolong Su, Vincent Perot, Jennifer Dy, and Tomas Pfister. DualPrompt: Complementary prompting for rehearsal-free continual learning. In *European Conference on Computer Vision (ECCV)*, 2022. 2

[41] Zifeng Wang, Zizhao Zhang, Chen-Yu Lee, Han Zhang, Ruoxi Sun, Xiaoqi Ren, Guolong Su, Vincent Perot, Jennifer Dy, and Tomas Pfister. Learning to prompt for continual learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2022. 2

[42] Yuexiang Zhai, Shengbang Tong, Xiao Li, Mu Cai, Qing Qu, Yong Jae Lee, and Yi Ma. Investigating the catastrophic forgetting in multimodal large language model fine-tuning. In *Proceedings of the Conference on Parsimony and Learning (CPAL)*, pages 202–227, 2024.

[43] Duzhen Zhang, Wei Cong, Jiahua Dong, Yahan Yu, Xiuyi Chen, Yonggang Zhang, and Zhen Fang. Continual named entity recognition without catastrophic forgetting. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2023.

[44] Gengwei Zhang, Liyuan Wang, Guoliang Kang, Ling Chen, and Yunchao Wei. SLCA: Slow learner with classifier alignment for continual learning on a pre-trained model. In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 19091–19101, 2023. 6