

Designing Databases

13

cuu duong than cong . com

Systems Analysis and Design, 7e Kendall & Kendall

© 2008 Pearson Prentice Hall

Learning Objectives

- Understand database concepts
- Use normalization to efficiently store data in a database
- Use databases for presenting data
- Understand the concept of data warehouses
- Comprehend the usefulness of publishing databases to the Web

Data Storage

- The data must be available when the user wants to use them
- The data must be accurate and consistent
- Efficient storage of data as well as efficient updating and retrieval
- It is necessary that information retrieval be purposeful

Data Storage (Continued)

- There are two approaches to the storage of data in a computer-based system:
 - Store the data in individual files, each unique to a particular application
 - Build a database
 - A database is a formally defined and centrally controlled store of data intended for use in many different applications

Major Topics

- Databases
- Normalization
- Key design
- Using the database
- Data warehouses
- Data mining


Databases

- Effectiveness objectives of the database:
 - Ensuring that data can be shared among users for a variety of applications
 - Maintaining data that are both accurate and consistent
 - Ensuring data required for current and future applications will be readily available
 - Allowing the database to evolve as the needs of the users grow
 - Allowing users to construct their personal view of the data without concern for the way the data are physically stored

Reality, Data, and Metadata

- Reality
 - The real world
- Data cuu duong than cong . com
 - Collected about people, places, or events in reality and eventually stored in a file or database
- Metadata cuu duong than cong . com
 - Information that describes data

Figure 13.1 Reality, data, and metadata



Entities

- Any object or event about which someone chooses to collect data
- May be a person, place or thing
- May be an event or unit of time

Entity Subtype

- An entity subtype is a special one-to-one relationship used to represent additional attributes, which may not be present on every record of the first entity
- This eliminates null fields stored on database tables
- For example, students who have internships. The STUDENT MASTER should not have to contain information about internships for each student

Relationships

- Relationships
 - One-to-one
 - One-to-many
 - Many-to-many
- A single vertical line represents one
- A crow's foot represents many

Figure 13.2 Entity-relationship (E-R) diagrams can show one-to-one, one-to-many, or many-to-many associations




Figure 13.3 The entity-relationship symbols and their meanings










Symbol	Official Explanation	What It Really Means
	Entity	A class of persons, places, or things
	Associative entity	Used to join two entities
	Attributive entity	Used for repeating groups
	To 1 relationship	Exactly one
	To many relationship	One or more
	To 0 or 1 relationship	Only zero or one
	To 0 or more relationship	Can be zero, one, or more
	To more than 1 relationship	Greater than one

Figure 13.4 The entity-relationship diagram for patient treatment. Attributes can be listed alongside the entities. In each case, the key is underlined



Attributes, Records, and Keys

- Attributes represent some characteristic of an entity
- Records are a collection of data items that have something in common with the entity described
- Keys are data items in a record used to identify the record

Key Types

- Key types are:
 - Primary key – unique attribute for the record
 - Candidate key – an attribute or collection of attributes, that can serve as a primary key
 - Secondary key, a key which may not be unique, used to select a group of records
 - Composite key, a combination of two or more attributes representing the key

Metadata

- Data about the data in the file or database
- Describe the name given and the length assigned each data item
- Also describe the length and composition of each of the records

Figure 13.7 Metadata includes a description of what the value of each data item looks like

Data Item	Value	
Salesperson Number	N	5
Salesperson Name	A	20
Company Name	A	26
Address	A	36
Sales	N	9.2
Width	N	2
Height	N	2
Length	N	2
Weight	N	2
Mailing Address	A	36
Return Address	A	36
Product(s)	A	4
Description(s)	A	30
Quantity Ordered	N	2
Last Name of Customer	A	24
First Initial	A	1
Street Address	A	28
City	A	12
State	A	2
Zip Code	N	9
Credit Card Number	N	10
Date Order Was Placed	D	8
Amount	\$	7.2
Status	A	22

Fields

- N Numeric
- A Alphanumeric or text
- D Date MM/DD/YYYY
- \$ Currency
- M Memo

7.2 means that the field takes up 7 digits, two of which are right of the decimal.

Special formats for fields may be specified.

Files

- A file contains groups of records used to provide information for operations, planning, management, and decision making
- Files can be used for storing data for an indefinite period of time, or they can be used to store data temporarily for a specific purpose

File Types

- Master file
- Table file
- Transaction file
- Report file

Master and Table Files

- Master files
 - Contain records for a group of entities
 - Contain all information about a data entity
- Table files
 - Contains data used to calculate more data or performance measures
 - Usually read-only by a program

Transaction and Report Files

- Transaction records
 - Used to enter changes that update the master file and produce reports
- Report files
 - Used when it is necessary to print a report when no printer is available
 - Useful because users can take files to other computer systems and output to specialty devices

File Organization

- Sequential organization
- Linked lists
- Hashed file organization

Relational Databases

- A database is intended to be shared by many users
- There are three structures for storing database files:
 - Relational database structures
 - Hierarchical database structures
 - Network database structures

Figure 13.10 Database design includes synthesizing user reports, user views and logical and physical designs




Figure 13.11 In a relational data structure, data are stored in many tables

ITEM PRICE		
ITEM-#	TITLE	PRICE
B235	Guys and Dolls	8.99
B521	My Fair Lady	6.99
B894	42nd Street	10.99
B992	A Chorus Line	10.99


ORDER						
ORDER-#	LAST NAME	I	STREET ADDRESS	CITY	ST	CHARGE ACCT
10784	MacRae	G	2314 Curly Circle	Lincoln	NE	45-4654-76
10796	Jones	S	34 Dream Lane	Oklahoma City	OK	44-9876-74
11821	Preston	R	1008 Madison Ave.	River City	IA	34-7642-64
11845	Channing	C	454 Harmonia St.	New York	NY	34-0876-87
11872	Kiley	R	765 Dulcinea Drive	La Mancha	CA	65-8798-87

ITEM STATUS		
ITEM-#	ORDER-#	STATUS
B235	10784	Shipped 5/12
B235	19796	Shipped 5/14
B235	11872	In Process
B521	11821	In Process
B894	11845	Backordered
B894	11872	Shipped 5/12
B992	10784	Shipped 5/12

Normalization

- Normalization is the transformation of complex user views and data stores to a set of smaller, stable, and easily maintainable data structures
- The main objective of the normalization process is to simplify all the complex data items that are often found in user views


Figure 13.12 Normalization of a relation is accomplished in three major steps



Data Model Diagrams

- Shows data associations of data elements
- Each entity is enclosed in an ellipse
- Arrows are used to show the relationships


Figure 13.15 Drawing data model diagrams for data associations sometimes helps analysts appreciate the complexity of data storage



First Normal Form (1NF)

- Remove repeating groups
- The primary key with repeating group attributes are moved into a new table
- When a relation contains no repeating groups, it is in first normal form


Figure 13.18 The Original unnormalized relation SALES-REPORT is separated into two relations, SALESPERSON (3NF) and SALESPERSON-CUSTOMER (1NF)



Second Normal Form (2NF)

- Remove any partially dependent attributes and place them in another relation
- A partial dependency is when the data are dependent on a part of a primary key
- A relation is created for the data that are only dependent on part of the key and another for data that are dependent on both parts


Figure 13.20 The relation SALESPERSON-CUSTOMER is separated into a relation called CUSTOMER-WAREHOUSE (2NF) and a relation called SALES (1NF)



Third Normal Form (3NF)

- Must be in 2NF
- Remove any transitive dependencies
- A transitive dependency is when nonkey attributes are dependent not only on the primary key, but also on a nonkey attribute

Figure 13.22 The relation CUSTOMER-WAREHOUSE is separated into two relations called CUSTOMER (1NF) and WAREHOUSE (1NF)



Using the Entity-relationship Diagram to Determine Record Keys

- When the relationship is one-to-many, the primary key of the file at the one end of the relationship should be contained as a foreign key on the file at the many end of the relationship
- A many-to-many relationship should be divided into two one-to-many relationships with an associative entity in the middle

Guidelines for Master File/Database Relation Design

- Each separate data entity should create a master database table
- A specific data field should exist on one master table
- Each master table or database relation should have programs to create, read, update, and delete the records

Integrity Constraints

- Entity integrity
- Referential integrity
- Domain integrity

Entity Integrity

- The primary key cannot have a null value
- If the primary key is a composite key, none of the fields in the key can contain a null value

Referential Integrity

- Referential integrity governs the nature of records in a one-to-many relationship
- Referential integrity means that all foreign keys in the many table (the child table) must have a matching record in the parent table

Referential Integrity (Continued)

Referential integrity implications:

- You cannot add a record in the child (many) table without a matching record in the parent table
- You cannot change a primary key that has matching child table records
- You cannot delete a record that has child records

Referential Integrity (Continued)

- Implemented in two ways:
 - A restricted database updates or deletes a key only if there are no matching child records
 - A cascaded database will delete or update all child records when a parent record is deleted or changed

Domain Integrity

- Domain integrity rules are used to validate the data
- Domain integrity has two forms:
 - Check constraints, which are defined at the table level
 - Rules, which are defined as separate objects and can be used within a number of fields

Anomalies

- Data redundancy
- Insert anomaly
- Deletion anomaly
- Update anomaly

Data Redundancy

- When the same data is stored in more than one place in the database
- Solved by creating tables that are in third normal form

Insert Anomaly

- Occurs when the entire primary key is not known and the database cannot insert a new record, which would violate entity integrity
- Can be avoided by using a sequence number for the primary key

Deletion Anomaly

- Happens when a record is deleted that results in the loss of other related data

cuu duong than cong . com

cuu duong than cong . com


Update Anomaly

- When a change to one attribute value causes the database to either contain inconsistent data or causes multiple records to need changing
- May be prevented by making sure tables are in third normal form

Retrieving and Presenting Database Data

- Choose a relation from the database
- Join two relations together
- Project columns from the relation
- Select rows from the relation
- Derive new attributes
- Index or sort rows
- Calculate totals and performance measures
- Present data

Figure 13.28 Data are retrieved and presented in eight distinct steps



Join Two Relations Together

- Takes many 3NF relations and combines them to make a more useful relation
- Join types: [duong than cong . com](http://duongthancong.com)
 - Inner join
 - Outer join
 - Left outer join
 - Right outer join
 - Full outer join
 - Self-join

Denormalization

- Denormalization is the process of taking the logical data model and transforming it into an efficient physical model

cuu duong than cong . com

Data Warehouses

- Used to organize information for quick and effective queries

cuu duong than cong . com

cuu duong than cong . com

Data Warehouses and Database Differences

- In the data warehouse, data are organized around major subjects
- Data in the warehouse are stored as summarized rather than detailed raw data
- Data in the data warehouse cover a much longer time frame than in a traditional transaction-oriented database
- Data warehouses are organized for fast queries

Data Warehouses and Database Differences (Continued)

- Data warehouses are usually optimized for answering complex queries, known as OLAP
- Data warehouses allow for easy access via data-mining software
- Data warehouses include multiple databases that have been processed so that data are uniformly defined
- Data warehouses usually include data from outside sources

Online Analytic Processing

- Online analytic processing (OLAP) is meant to answer decision makers' complex questions by defining a multidimensional database

cuu duong than cong . com

Data Mining

- Data mining, or knowledge data discovery (KDD), is the process of identifying patterns that a human is unable to detect

cuu duong than cong . com

Data-Mining Decision Aids


- Software

- Statistical analysis
- Decision trees
- Neural networks
- Intelligent agents
- Fuzzy logic
- Data visualization

Data-Mining Patterns

- Associations, patterns that occur together
- Sequences, patterns of actions that take place over a period of time
- Clustering, patterns that develop among groups of people
- Trends, the patterns that are noticed over a period of time

Figure 13.37 Data mining collects personal information about customers in an effort to be more specific in interpreting and anticipating their preferences



Data-Mining Problems

- Costs may be too high to justify
- Has to be coordinated
- Ethical aspects

Summary

- Storing data
 - Individual files
 - Database
- Reality, data, metadata
- Conventional files
 - Type
 - Organization
- Database
 - Relational
 - Hierarchical
 - Network

Summary (Continued)

- E-R diagrams
- Normalization
 - First normal form
 - Second normal form
 - Third normal form
- Denormalization
- Data warehouse
- Data mining