

第八次平時測驗

滿分: 100 分

及格分數: 60 分

試題數: 15 題

隨機出題題數: 15 題

配分方式: 平均配分，每題約 6.6 分

1 請根據下面程式執行後，將結果寫出。

```
1  #ifndef PERSON_H
2  #define PERSON_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class person
9  {
10     friend istream & operator >>(istream &in, person &a);
11     friend ostream & operator<<(ostream &out, person &a);
12     public:
13         person();
14         virtual ~person();
15
16     protected:
17
18     private:
19         string name;
20         string id;
21         string cell;
22 };
23
24 #endif // PERSON_H
```

6.66 分 (每格 6.66 分)

```
1  #include "person.h"
2
3  person::person()
4  {
5      //ctor
6  }
7
8
9  person::~~person()
10 {
11     //dtor
12 }
13
14 istream & operator >>(istream &in, person &a){
15     cout<<"name:";
16     in>>a.name;
17     cout<<"id:";
18     in>>a.id;
19     cout<<"cell:";
20     in>>a.cell;
21     return in;
22 }
23 ostream & operator<<(ostream &out, person &a)
24 {
25     out<<"name:"<<a.name<<" ";
26     out<<"id:"<<a.id<<" ";
27     out<<"cell:"<<a.cell<<endl;
28 }
29
```

```
#ifndef STUDENT_H
#define STUDENT_H

#include <person.h>

class student : public person
{
public:
    student();
    virtual ~student();

protected:

private:
    string school;
    string sid;
    string className;
};

#endif // STUDENT_H
```

```
1  #include <iostream>
2  #include "person.h"
3  #include "student.h"
4
5  using namespace std;
6
7  int main()
8  {
9      person a;
10     person *b;
11     student c;
12     student *d;
13     cout<<"1";
14
15     cout<<"2";|
16     return 0;
17 }
18
```

12

(忽略空白)

難易度: 未設定

2 請根據下面程式執行後，將結果寫出。

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

6.66 分 (每格 6.66 分)

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2
3  using namespace std;
4
5  int main()
6  {
7      cout << "1" << endl;
8
9      return 0;
10 }
11
```

1

(忽略空白)

難易度: 未設定

3 請根據下面程式執行後，將結果寫出。

6.66 分 (每格 6.66 分)

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      child a;
10     cout << "1";
11
12     return 0;
13 }
14
```

1a1b2

(忽略空白)

難易度: 未設定

4 請根據下面程式執行後，將結果寫出。

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

6.66 分 (每格 6.66 分)


```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      parent a;
10     cout << "x";
11
12     return 0;
13 }
14
```

1x2

(忽略空白)

難易度: 未設定

5 請根據下面程式執行後，將結果寫出。

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

6.66 分 (每格 6.66 分)

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      parent *a;
10     cout << "x";
11
12     return 0;
13 }
14
```

x

(忽略空白)

難易度: 未設定

6 請根據下面程式執行後，將結果寫出。

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

6.66 分 (每格 6.66 分)

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      parent *a;
10     cout << "x";
11     a=new parent();
12
13     return 0;
14 }
```

x1

(忽略空白)

難易度：困難

7 請根據下面程式執行後，將結果寫出。

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

6.66 分 (每格 6.66 分)

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      parent *a;
10     cout << "x";
11     a=new parent();
12
13     delete a;
14
15     return 0;
16 }
17
```

x12

(忽略空白)

難易度: 未設定

8 請根據下面程式執行後，將結果寫出。

6.66 分 (每格 6.66 分)


```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17     protected:
18
19     private:
20         int b;
21 };
22
23
24 #endif // CHILD_H
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      parent *a;
10     cout << "x";
11     a=new parent(10);
12
13     delete a;
14
15     return 0;
16 }
17
```

x52

(忽略空白)

難易度: 未設定

9 請根據下面程式執行後，將結果寫出。

6.66 分 (每格 6.66 分)

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17     protected:
18
19     private:
20         int b;
21 };
22
23
24 #endif // CHILD_H
```

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      child *a;
10     cout << "x";
11     a=new child(10);
12
13     delete a;
14
15     return 0;
16 }
17
```

x1cb2

(忽略空白)

難易度: 未設定

10 請根據下面程式執行後，將結果寫出。

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17     protected:
18
19     private:
20         int b;
21 };
22
23
24 #endif // CHILD_H
```

6.66 分 (每格 6.66 分)

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      child *a;
10     cout << "x";
11     a=new child();
12
13     delete a;
14
15     return 0;
16 }
17
```

(忽略空白)

難易度: 未設定

11 請根據下面程式執行後，將結果寫出。

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17     protected:
18
19     private:
20         int b;
21 };
22
23
24 #endif // CHILD_H
```

6.66 分 (每格 6.66 分)


```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      child *a;
10     cout << "x";
11     a=new child();
12
13     |
14
15     return 0;
16 }
17
```

x1a

(忽略空白)

難易度: 未設定

12 請根據下面程式執行後，將結果寫出。

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17     protected:
18
19     private:
20         int b;
21 };
22
23
24 #endif // CHILD_H
```

6.66 分 (每格 6.66 分)

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      child *a;
10     parent b;
11     cout << "x";
12     a=new child();
13
14
15
16     return 0;
17 }
18
```

1x1a2

(忽略空白)

難易度: 未設定

13 請根據下面程式執行後，將結果寫出。

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

6.66 分 (每格 6.66 分)

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      child *a;
10     parent b;
11
12     cout << "x";
13     a=new child();
14     delete a;
15
16
17
18     return 0;
19 }
20
```

1x1ab22

(忽略空白)

難易度: 未設定

14 請根據下面程式執行後，將結果寫出。

6.66 分 (每格 6.66 分)

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```



```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      child *a;
10     parent *b;
11     parent c;
12     child d;
13
14     cout << "x";
15     a=new child();
16     b=new parent(10);
17     cout << "y";
18     delete a;
19     delete b;
20
21     return 0;
22 }
23
```

11ax1a5yb22b22

(忽略空白)

難易度：困難**15** 請根據下面程式執行後，將結果寫出。

```
1  #ifndef PARENT_H
2  #define PARENT_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7
8  class parent
9  {
10     public:
11         parent();
12         parent(int a);
13         virtual ~parent();
14
15     protected:
16
17     private:
18         int a;;
19 };
20
21 #endif // PARENT_H
22
```

```
1  #ifndef CHILD_H
2  #define CHILD_H
3  #include <iostream>
4  #include <string>
5
6  using namespace std;
7  #include <parent.h>
8
9
10 class child : public parent
11 {
12     public:
13         child();
14         child(int a);
15         virtual ~child();
16
17
18     protected:
19
20     private:
21         int b;
22 };
23
24 #endif // CHILD_H
```

6.759999999999991 分 (每格 6.75 分)

```
1  #include "child.h"
2
3  child::child()
4  {
5      cout<<"a";
6  }
7  child::child(int a)
8  {
9      cout<<"c";
10 }
11
12 child::~~child()
13 {
14     cout <<"b";
15 }
16
```

```
1  #include "parent.h"
2
3  parent::parent()
4  {
5      cout<<"1";
6  }
7  parent::parent(int a)
8  {
9      cout<<"5";
10 }
11
12 parent::~~parent()
13 {
14     cout<<"2";
15 }
16
```

```
1  #include <iostream>
2  #include "child.h"
3  #include "parent.h"
4
5  using namespace std;
6
7  int main()
8  {
9      child *a;
10     parent *b;
11     parent c;
12     child d;
13
14     cout << "x";
15
16     return 0;
17 }
18
```

(忽略空白)

難易度： 困難

交卷

Copyright © Southern Taiwan University of Science and Technology. All rights reserved.

南臺科技大學圖書暨資訊處(STUST Library and Information Services Office) 建置

選課資料最後更新日期：2026年6月2日

[隱私權](#) [服務條款](#)