

BOM

Part No.	Part name	Qty.	Material/Stock	Specification	Files	Notes
P-01	Body	1	Printed		STEP/STL	
C-01	Light Seal Felt Strip	1	Felt	5 mm wide × 254 mm		Adhesive-backed felt recommended. Approx.1mm thick.
C-02	Light Seal Felt Sheet	1	Felt		SVG/PDF	Cut to match template. Adhesive-backed felt recommended. Approx.1mm thick.
M-01	Retaining Clip	1	Steel Round Bar	Ø1	PDF	Bend as shown
M-02	Film Claw	1	Steel Round Bar	Ø0.8	PDF	Bend as shown
P-02	Film Claw Arm	1	Printed		STEP/STL	0.2mm nozzle
M-03	Film Claw Arm Spring	1	Stainless Steel Spring Wire	Ø0.4	SVG	Bend as shown
P-03	Lever	1	Printed		STEP/STL	
M-04	Lever Pivot Pin	1	Steel Round Bar	Ø0.8 × 4 mm		Cut to length
P-04	Knob Gear	1	Printed		STEP/STL	0.2mm nozzle
P-05	Idler Gear	1	Printed		STEP/STL	0.2mm nozzle
P-06	Front Roller Gear	1	Printed		STEP/STL	0.2mm nozzle
P-07	Rear Roller Gear	1	Printed		STEP/STL	0.2mm nozzle
M-05	Roller Gear Pin	2	Steel Round Bar	Ø0.8 × 4.4 mm		Cut to length
M-06	Roller Shaft	2	Steel Round Bar	Ø3	PDF	Cut to length and drill holes
M-07	Roller	2	Aluminium Pipe	OD 7 mm × ID 3 mm	PDF	Cut to length and drill a hole
M-08	Roller Shaft Pin	2	Steel Round Bar	Ø0.8 × 5 mm		Cut to length
P-08	Left Roller Retainer	1	Printed		STEP/STL	
P-09	Right Roller Retainer	1	Printed		STEP/STL	
P-10	Shaft Spacer	1	Printed		STEP/STL	
M-09	Roller Pressure Spring	2	Stainless Steel Spring Wire	Ø0.8	SVG	A binder clip spring is a good substitute.
P-11	Roller Pressure Spring Seat	1	Printed		STEP/STL	
P-12	Roller Shaft Collar	2	Printed		STEP/STL	
M-10	Bearing Plate	2	Brass Plate	t0.5	PDF	This part can be made with a drill and files, but a milling machine makes the job much easier.
M-11	Back Panel	1	Metal Sheet	t0.3	STEP/DXF	Cut and bend as shown. Any sheet metal from approximately 0.2 mm to 0.8 mm thick should work.
C-03	Film Pack Spring	2	Steel	Ø9 × 15 mm Ø0.5		Maximum recommended size: Ø9 mm × 16 mm, wire Ø0.6 mm. A free length of 14-16 mm works well.
M-12	Latch Stud	1	Steel Round Bar	Ø2 × 2 mm		Cut to length and weld
C-04	Foam Tape	1	Foam Tape	3 mm thick		
C-05	Slotted Screw	2	Metal	M3 × 12 mm		Any M3 screw will work. Slotted screws are used only for appearance.
C-06	Back Panel Leather	1	Leather		SVG/PDF	Cut to match template

3Dプリント部品は、±0.1 mm 以内の寸法精度で印刷してください。

フィラメントは、十分な寸法精度と強度が得られるものであれば自由に選択できます。私は PLA+ を使用しましたが、PLA-CF、ABS、ナイロンなど、同等以上の性能を持つ材料であれば問題なく使用できるはずです。

この設計は厳密な仕様書ではありません。ご自身の設備や加工方法に合わせて、製作しやすい材料や工法を自由に選択してください。入手しやすく、扱いやすい材料を使用していただいて構いません。

摺動部品については、耐摩耗性を考慮した材料を選択することをおすすめします。

試作機を忠実に再現することよりも、確実に動作することを優先してください。動作性や製作性が向上するのであれば、寸法や材料を変更していただいても問題ありません。

改造改良大歓迎。作ったり改造したらぜひ見せてね。