OCOM5300M Artificial Intelligence Project Cross Attention LSTM Generate Predictions

In [1]:
```
# Custom Classes
from dataset_concept import ConceptVocabulary, ConceptLookup
from captions import Captions
from vocabulary import Vocabulary
from images import Images
from pipeline_concept import Encoder, BeamSearchDecoderModel
from evaluation import BLEU_Evaluation, Cosine_Similarity_Evaluation

# Deep learning Functionality
import torch  # PyTorch library
from torchvision import transforms # image transformation utilities

# Data Handling And Analysis
import pandas as pd  # data manipulation and analysis using DataFrame structures
import numpy as np  # numerical operations and array handling
from pathlib import Path  # object-oriented handling of filesystem paths

# Natural Language Processing And Evaluation
from nltk.translate.bleu_score import corpus_bleu, SmoothingFunction  # BLEU score evaluation

# Visualization
import matplotlib.pyplot as plt  # plotting and visualizing results
import seaborn as sns  # visualisation library for statistical graphics

# Utilities
import os  # file and directory operations
import textwrap  # formatting and wrapping long text
import random # random number generation
```

In [2]:
```
# suppress Intel specific Math Kernel Library (MKL) warnings
os.environ['KMP_DUPLICATE_LIB_OK'] = 'True'
```

In [3]:
```
#detect device (CPU/GPU)
device = torch.device('cpu')
```

In [4]:
```
# display the complete content of DataFrame columns without truncation
pd.set_option('display.max_colwidth', None);
```

In [5]:
```
# seed for reproducibility
seed = 42
```

In [6]:
```
# Python random seed
random.seed(seed)
```

In [7]:
```
# NumPy random seed
np.random.seed(seed)
```

In [8]:
```
# PyTorch random seed
torch.manual_seed(seed)
```

Out[8]:
```
<torch._C.Generator at 0x1626bf7d830>
```

Ground Truths

In [9]:
```
# test captions filename
test_captions_filename = "ROCOv2/test_captions.csv"
```

In [10]:
```
# instantiate test captions object
test_captions = Captions()
```

In [11]:
```
# load test captions from file
test_caption_data = test_captions.load_captions(test_captions_filename)
```

In [12]:
```
# clean captions
test_captions.clean_captions();
```

In [13]:
```
# confirm number of captions
len(test_caption_data)
```

Out[13]:
```
9927
```

In [14]:
```
test_caption_data.head()
```

Out[14]:

	ID	Caption	cleaned_caption
0	ROCOv2_2023_test_000001	CT chest axial view showing a huge ascending aortic aneurysm (*).	ct chest axial view showing a huge ascending aortic aneurysm
1	ROCOv2_2023_test_000002	Computed tomography (CT) shows floating thrombosis (white arrow)	computed tomography ct shows floating thrombosis white arrow
2	ROCOv2_2023_test_000003	Digitally subtracted angiogram demonstrates active extravasation of the superior rectal artery into the ileal-conduit (blue arrow)	digitally subtracted angiogram demonstrates active extravasation of the superior rectal artery into the ileal-conduit blue arrow
3	ROCOv2_2023_test_000004	Digitally subtracted angiogram of the IMA demonstrated cessation of flow through the proximal superior rectal artery in the region of the intersection between the artery and ureter with retained perfusion of the rectosigmoid region and resolution of active extravasation	digitally subtracted angiogram of the ima demonstrated cessation of flow through the proximal superior rectal artery in the region of the intersection between the artery and ureter with retained perfusion of the rectosigmoid region and resolution of active extravasation
4	ROCOv2_2023_test_000005	Angle measurement of a Type 1 canal.	angle measurement of a type 1 canal

Reload Vocabulary

In [15]:
```
# load vocabulary
vocabulary = Vocabulary.load("ROCOv2/vocabulary.pt")
```

In [16]:
```
# reconfirm vaocabulary size
len(vocabulary)
```

Out[16]:
```
17602
```

Transformation

In [17]:
```
# image processing pipeline
transform = transforms.Compose([

    transforms.Resize(
        (224, 224), # 224 x 224
```

```
        antialias=True, # to prevent jagged edges, moiré patterns etc
    ),

    transforms.ToTensor(), # PyTorch neural network requires the image as a tensor of numerical values

    # Convert RGB tensor to BGR to match RadImageNet PyTorch preprocessing
    transforms.Lambda(lambda image: image[[2, 1, 0], :, :]),

    transforms.Normalize(
        mean=[0.5, 0.5, 0.5],
        std=[0.5, 0.5, 0.5],
    ),
])
```

Encorder Decoder Fine Tuned Model

In [18]:
```
# fine-tuned encoder-decoder model
encoder_decoder_model =  "encoder_decoder_pipeline_finetuned_best.pth"
```

In [19]:
```
# load test pipeline concepts and training-only CUI vocabulary
concept_vocabulary = ConceptVocabulary.load("lstm_pipeline_cui_vocabulary.json")
test_concepts = ConceptLookup("ROCOv2/pipeline_test.csv", concept_vocabulary, max_concepts=20)
print("Test images with accepted CUIs:", len(test_concepts.by_image))
```

```
Test images with accepted CUIs: 9905
```

In [20]:
```
# load encoder-decoder fine-tuned model
checkpoint = torch.load(
    encoder_decoder_model, # load the saved model checkpoint
    map_location=device, # load checkpoint tensors
    weights_only=False # load full checkpoint i.e., not only weights
)
```

In [21]:
```
# pretrained RadImageNet ResNet50 weights
radimagenet_weights_path="RadImageNet_pytorch/ResNet50.pt"
```

In [22]:
```
# encoder
encoder = Encoder(
    freeze_encoder=True,
    freeze_batch_norm=True,
```

```
    radimagenet_weights_path=radimagenet_weights_path
)
```

In [23]:
```
# load state using the fine-tuned weights to override thepretrained RadImageNet ResNet50 weights
encoder.load_state_dict(
    checkpoint["encoder"], # load the saved encoder parameters
    strict=True # checkpoint parameters must match the encoder architecture
)
```

Out[23]:
```
<All keys matched successfully>
```

In [24]:
```
# move encoder to the selected device
encoder.to(device)
```

Out[24]:

```
Encoder(
  (cnn): Sequential(
    (0): Conv2d(3, 64, kernel_size=(7, 7), stride=(2, 2), padding=(3, 3), bias=False)
    (1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
    (2): ReLU(inplace=True)
    (3): MaxPool2d(kernel_size=3, stride=2, padding=1, dilation=1, ceil_mode=False)
    (4): Sequential(
      (0): Bottleneck(
        (conv1): Conv2d(64, 64, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv3): Conv2d(64, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn3): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (relu): ReLU(inplace=True)
        (downsample): Sequential(
          (0): Conv2d(64, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
          (1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        )
      )
      (1): Bottleneck(
        (conv1): Conv2d(256, 64, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv3): Conv2d(64, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn3): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (relu): ReLU(inplace=True)
      )
      (2): Bottleneck(
        (conv1): Conv2d(256, 64, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv3): Conv2d(64, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn3): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (relu): ReLU(inplace=True)
      )
    )
    (5): Sequential(
      (0): Bottleneck(
        (conv1): Conv2d(256, 128, kernel_size=(1, 1), stride=(1, 1), bias=False)
```

```
      (bn1): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(128, 128, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(128, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
      (downsample): Sequential(
        (0): Conv2d(256, 512, kernel_size=(1, 1), stride=(2, 2), bias=False)
        (1): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      )
    )
    (1): Bottleneck(
      (conv1): Conv2d(512, 128, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(128, 128, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(128, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (2): Bottleneck(
      (conv1): Conv2d(512, 128, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(128, 128, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(128, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (3): Bottleneck(
      (conv1): Conv2d(512, 128, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(128, 128, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(128, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
  )
  (6): Sequential(
    (0): Bottleneck(
      (conv1): Conv2d(512, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
```

```
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
      (downsample): Sequential(
        (0): Conv2d(512, 1024, kernel_size=(1, 1), stride=(2, 2), bias=False)
        (1): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      )
    )
    (1): Bottleneck(
      (conv1): Conv2d(1024, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (2): Bottleneck(
      (conv1): Conv2d(1024, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (3): Bottleneck(
      (conv1): Conv2d(1024, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (4): Bottleneck(
      (conv1): Conv2d(1024, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
```

```
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (5): Bottleneck(
      (conv1): Conv2d(1024, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
  )
  (7): Sequential(
    (0): Bottleneck(
      (conv1): Conv2d(1024, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(512, 512, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(512, 2048, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(2048, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
      (downsample): Sequential(
        (0): Conv2d(1024, 2048, kernel_size=(1, 1), stride=(2, 2), bias=False)
        (1): BatchNorm2d(2048, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      )
    )
    (1): Bottleneck(
      (conv1): Conv2d(2048, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(512, 512, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(512, 2048, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(2048, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (2): Bottleneck(
      (conv1): Conv2d(2048, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(512, 512, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
```

```
      (bn2): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(512, 2048, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(2048, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
  )
 )
)
```

In [25]:

```
# set encoder to evaluation mode
encoder.eval()
```

Out[25]:

```
Encoder(
  (cnn): Sequential(
    (0): Conv2d(3, 64, kernel_size=(7, 7), stride=(2, 2), padding=(3, 3), bias=False)
    (1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
    (2): ReLU(inplace=True)
    (3): MaxPool2d(kernel_size=3, stride=2, padding=1, dilation=1, ceil_mode=False)
    (4): Sequential(
      (0): Bottleneck(
        (conv1): Conv2d(64, 64, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv3): Conv2d(64, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn3): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (relu): ReLU(inplace=True)
        (downsample): Sequential(
          (0): Conv2d(64, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
          (1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        )
      )
      (1): Bottleneck(
        (conv1): Conv2d(256, 64, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv3): Conv2d(64, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn3): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (relu): ReLU(inplace=True)
      )
      (2): Bottleneck(
        (conv1): Conv2d(256, 64, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn1): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv2): Conv2d(64, 64, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
        (bn2): BatchNorm2d(64, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (conv3): Conv2d(64, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
        (bn3): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
        (relu): ReLU(inplace=True)
      )
    )
    (5): Sequential(
      (0): Bottleneck(
        (conv1): Conv2d(256, 128, kernel_size=(1, 1), stride=(1, 1), bias=False)
```

```
      (bn1): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(128, 128, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(128, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
      (downsample): Sequential(
        (0): Conv2d(256, 512, kernel_size=(1, 1), stride=(2, 2), bias=False)
        (1): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      )
    )
    (1): Bottleneck(
      (conv1): Conv2d(512, 128, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(128, 128, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(128, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (2): Bottleneck(
      (conv1): Conv2d(512, 128, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(128, 128, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(128, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (3): Bottleneck(
      (conv1): Conv2d(512, 128, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(128, 128, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(128, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(128, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
  )
  (6): Sequential(
    (0): Bottleneck(
      (conv1): Conv2d(512, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
```

```
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
      (downsample): Sequential(
        (0): Conv2d(512, 1024, kernel_size=(1, 1), stride=(2, 2), bias=False)
        (1): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      )
    )
    (1): Bottleneck(
      (conv1): Conv2d(1024, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (2): Bottleneck(
      (conv1): Conv2d(1024, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (3): Bottleneck(
      (conv1): Conv2d(1024, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (4): Bottleneck(
      (conv1): Conv2d(1024, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
```

```
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (5): Bottleneck(
      (conv1): Conv2d(1024, 256, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(256, 256, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(256, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(256, 1024, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(1024, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
  )
  (7): Sequential(
    (0): Bottleneck(
      (conv1): Conv2d(1024, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(512, 512, kernel_size=(3, 3), stride=(2, 2), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(512, 2048, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(2048, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
      (downsample): Sequential(
        (0): Conv2d(1024, 2048, kernel_size=(1, 1), stride=(2, 2), bias=False)
        (1): BatchNorm2d(2048, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      )
    )
    (1): Bottleneck(
      (conv1): Conv2d(2048, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(512, 512, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
      (bn2): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(512, 2048, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(2048, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
    (2): Bottleneck(
      (conv1): Conv2d(2048, 512, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn1): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv2): Conv2d(512, 512, kernel_size=(3, 3), stride=(1, 1), padding=(1, 1), bias=False)
```

```
      (bn2): BatchNorm2d(512, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (conv3): Conv2d(512, 2048, kernel_size=(1, 1), stride=(1, 1), bias=False)
      (bn3): BatchNorm2d(2048, eps=1e-05, momentum=0.1, affine=True, track_running_stats=True)
      (relu): ReLU(inplace=True)
    )
  )
 )
)
```

In [26]:
```
# relative path to ROCOv2 test images
image_folder = "ROCOv2/test_images/test"
```

In [27]:
```
# instantiate Images object
images = Images(image_folder, '.jpg', transform)
```

In [28]:
```
# extract image features
images.extract_features(encoder, device);
```

Decoder

In [29]:
```
# retrieve saved model configuration
configuration = checkpoint["configuration"]
```

Generate Predictions On Test Data

In [30]:
```
# sample, i.e., for final run all images in the test set
sample_image_ids = (test_captions.captions["ID"].drop_duplicates().tolist())
```

In [31]:
```
# filter captions
sample = test_captions.captions.loc[test_captions.captions["ID"].isin(sample_image_ids), ["ID", "cleaned_caption"]]
```

In [32]:
```
# extracted feature tensors for test images
feature_folder = Path("ROCOv2/test_images/test/pt")
```

In [33]:
```
# dictionary to store the file path for each test image's extracted feature tensor
loaded_features = {}
```

In [34]:
```
# create file path for each test image's extracted feature tensor and store it by image ID
for image_id in sample_image_ids:

    feature_path = (
        feature_folder /
        f"{image_id}.pt"
    )

    loaded_features[image_id] = feature_path
```

In [35]:
```
# instantiate beam-search decoder
beamsearch_decoder = BeamSearchDecoderModel(
    vocab_size=configuration["vocab_size"],
    embed_size=configuration["embed_size"],
    hidden_size=configuration["hidden_size"],
    num_layers=configuration["num_layers"],
    max_seq_length=configuration["max_seq_length"],
    pad_idx=configuration["pad_idx"],
    encoder_dim=configuration["encoder_dim"],
    attention_dim=configuration["attention_dim"],
    dropout=configuration["dropout"],
    concept_vocab_size=configuration["concept_vocab_size"],
    visual_gate_type=configuration["visual_gate_type"]
)
```

In [36]:
```
# apply weights
beamsearch_decoder.load_state_dict(checkpoint['decoder'], strict=True)
```

Out[36]:
```
<All keys matched successfully>
```

In [37]:
```
# move to device
beamsearch_decoder.to(device)
```

Out[37]:
```
BeamSearchDecoderModel(
  (concept_embeddings): Embedding(1810, 256, padding_idx=0)
  (concept_projection): Linear(in_features=256, out_features=2048, bias=False)
  (embedding): Embedding(17602, 256, padding_idx=0)
  (cross_attention): AdditiveCrossAttention(
    (visual_projection): Linear(in_features=2048, out_features=512, bias=True)
    (hidden_projection): Linear(in_features=512, out_features=512, bias=True)
    (attention_score): Linear(in_features=512, out_features=1, bias=False)
  )
  (lstm_cells): ModuleList(
    (0): LSTMCell(2304, 512)
  )
  (initial_hidden): ModuleList(
    (0): Linear(in_features=2048, out_features=512, bias=True)
  )
  (initial_cell): ModuleList(
    (0): Linear(in_features=2048, out_features=512, bias=True)
  )
  (visual_gate): Linear(in_features=512, out_features=1, bias=True)
  (dropout): Dropout(p=0.3, inplace=False)
  (hidden_to_embed): Linear(in_features=512, out_features=256, bias=True)
  (output_layer): Linear(in_features=256, out_features=17602, bias=False)
)
```

In [38]:
```
# set decoder to evaluation mode
beamsearch_decoder.eval()
```

Out[38]:
```
BeamSearchDecoderModel(
  (concept_embeddings): Embedding(1810, 256, padding_idx=0)
  (concept_projection): Linear(in_features=256, out_features=2048, bias=False)
  (embedding): Embedding(17602, 256, padding_idx=0)
  (cross_attention): AdditiveCrossAttention(
    (visual_projection): Linear(in_features=2048, out_features=512, bias=True)
    (hidden_projection): Linear(in_features=512, out_features=512, bias=True)
    (attention_score): Linear(in_features=512, out_features=1, bias=False)
  )
  (lstm_cells): ModuleList(
    (0): LSTMCell(2304, 512)
  )
  (initial_hidden): ModuleList(
    (0): Linear(in_features=2048, out_features=512, bias=True)
  )
  (initial_cell): ModuleList(
    (0): Linear(in_features=2048, out_features=512, bias=True)
  )
  (visual_gate): Linear(in_features=512, out_features=1, bias=True)
  (dropout): Dropout(p=0.3, inplace=False)
  (hidden_to_embed): Linear(in_features=512, out_features=256, bias=True)
  (output_layer): Linear(in_features=256, out_features=17602, bias=False)
)
```

In [39]:
```
# generate image captions using beam search caption generation
beamsearch_generated_captions = beamsearch_decoder.generate_captions(loaded_features, states=None,
max_length=configuration["max_seq_length"],
                                                                     vocab=vocabulary, sample_image_set=False,
concept_lookup=test_concepts);
```

```
Generating captions:   0%|          | 0/9927 [00:00<?, ?image/s]
```

In [40]:
```
# display subset of captions
beamsearch_generated_captions.head()
```

Out[40]:

	ID	generated_caption
0	ROCOv2_2023_test_000001	computed tomography scan of the chest showing a mass in the right lung
1	ROCOv2_2023_test_000002	ct scan of the neck showing a soft tissue mass in the right neck
2	ROCOv2_2023_test_000003	selective angiogram of the left renal artery showing a large pseudoaneurysm with a filling defect in the right renal vein
3	ROCOv2_2023_test_000004	selective angiogram of the left renal artery showing a large pseudoaneurysm with a filling defect in the right renal vein white arrow
4	ROCOv2_2023_test_000005	ultrasound image of the left hip

In [41]:
```
# save beam-search generated captions to CSV file
beamsearch_generated_captions.to_csv("LSTM_pipeline_generated_captions.csv", index=False)
```

References

OCOM5100M Programming For Data Science

OCOM5101M Data Science

OCOM5200M Machine Learning

OCOM5203M Deep Learning

OCOM5203M Deep Learning Module, Summative Assessment 2

OCOM5204M Data Mining And Analytics

Project Jupyter, Jupyter Notebook documentation. Available At: https://jupyter-notebook.readthedocs.io/en/stable/

Python Software Foundation, Python 3.13 documentation (2026). Available At: https://docs.python.org/3.13/