Noise Removal versus Signal Loss in Network Filtering of Daily GNSS Time Series

H. Oğuz Bolat

[a]*Department of Geomatics Engineering, Yıldız Technical University, Istanbul, Türkiye*

Abstract

[Abstract: write last.]

Keywords: GNSS time series, common-mode error, spatial filtering, transient deformation, signal preservation, deep learning

1. Introduction

Daily position solutions from the Global Navigation Satellite System (GNSS) reach formal uncertainties of about 1 mm in the horizontal components and 3–4 mm in the vertical (Nevada Geodetic Laboratory, 2026). The Nevada Geodetic Laboratory (NGL) processed data from more than 17,000 GPS stations worldwide as of 2018 and distributes the resulting time series openly (Blewitt et al., 2018). Using these series to study crustal deformation, such as slow slip or postseismic afterslip, first requires removing noise, part of which is shared between stations.

Common-mode error is noise shared across many stations of a network. It arises from errors in satellite orbits and clocks, in the realisation of the reference frame and from large-scale environmental loading (Wdowinski et al., 1997; Dong et al., 2006; Kreemer and Blewitt, 2021). Several approaches have been used to estimate and remove it, from stacking (Wdowinski et al., 1997) and principal or independent component analysis (Dong et al., 2006; Gruszczynski et al., 2018; Zhou et al., 2022) to weighted averages and medians of neighbouring stations (Tian and Shen, 2016; Kreemer and Blewitt, 2021). These filters are usually evaluated by how much noise they remove, most often measured as the reduction in the root-mean-square (RMS) scatter

Email address: oguz.bolat@std.yildiz.edu.tr (H. Oğuz Bolat)

of the filtered series (Tian and Shen, 2016; Kreemer and Blewitt, 2021; Zhou et al., 2022). Learned filters have been evaluated in different ways. Bachelot et al. (2025) measure noise reduction as the decrease in the average position of the whole network, which should be close to zero in the absence of common-mode noise, and assess signal preservation by comparing 280 slow-slip offsets, each the difference between the mean positions in the ten days after and before an event, measured on raw and denoised series; they note that without ground truth the denoising performance cannot be quantified in an absolute sense. Costantino et al. (2024) add synthetic slow-slip events to noise generated from real GNSS series by principal component analysis and Fourier phase randomisation, which preserves its spatial covariance and spectrum, and report the error of the recovered displacement as a function of the signal-to-noise ratio; on real data, they validate the result by its agreement with tectonic tremor. Mastella et al. (2025), whose method works on single stations, train on synthetic series and evaluate the noise removed from real series against a trajectory-model fit, which they treat as the reference noise, while showing the preservation of a slow-slip transient by example.

The problem with evaluating noise removed using RMS scatter is that the amount of real transient removed isn't accounted for. Kreemer and Blewitt (2021) note that the main reason their filter reduces scatter more than traditional stacking is that it absorbs local common-mode transients. How much small signal survives filtering affects the science. In Cascadia, Costantino et al. (2026) find that the momentduration scaling, b-value and stress-drop distribution of slow-slip events all change with the detection threshold applied to slip inverted from denoised data, a threshold they describe as a proxy for the signal-to-noise ratio.

[Paragraph 4: Bachelot et al. and what remains open.]

[Paragraph 5: what this study does.]

2. Data and processing

[Section 2, paragraph 1: overview of the processing chain (Fig. 1).]

2.1. Data

[Paragraph 2: what one daily solution is.]

[Paragraph 3: station selection and the network (Fig. 2a).]




Figure 1: Processing chain from daily GNSS positions to the signal-loss audit. [Check caption.]

2.2. From positions to residuals

[Paragraph 4: the trajectory model and why it is fitted on the training years only.]

$$x_{i,c}(t) = a + v\,(t - t_0) + \sum_{k=1}^{2} \left[s_k \sin(2\pi k t) + c_k \cos(2\pi k t) \right] + \sum_{j} b_j\, H(t - t_j) + r_{i,c}(t) \tag{1}$$

[Paragraph 5: equipment steps removed, earthquake offsets kept (Fig. 3b).]
[Paragraph 6: outlier screening and quality control.]
[Paragraph 7: the data cube, splits and held-out stations.]
[Paragraph 8: why we filter displacement rather than rates.]

3. The signal-loss audit

3.1. Leave-one-out filtering and the exclusion radius

[Paragraph 1: leave-one-out, the exclusion radius R and leak checks.]




Figure 2: (a) Stations used, held out and excluded. (b) What a prediction for one target may use at $R = 50$ km. [Expand caption.]

3.2. Four measures

[Paragraph 2: reconstruction error.]
[Paragraph 3: noise removed.]
[Paragraph 4: signal kept.]

$$\rho = \frac{\langle \Delta,\, s \rangle}{\langle s,\, s \rangle}, \qquad \Delta = \Big(r + s - P(r+s)\Big) - \Big(r - P(r)\Big) \tag{2}$$

[Paragraph 5: spurious signal.]

3.3. Planted and real signals

[Paragraph 6: Gaussian transients.]
[Paragraph 7: fault-slip events from the event library.]
[Paragraph 8: real earthquake offsets and Ridgecrest.]

3.4. Protocol

[Paragraph 9: decisions, freeze date, bootstrap, seeds.]

Table 1: Filters audited. [Check descriptions.]

Name	Description	Parameters
Target-inclusive		
C1	Mean of the whole network, target included	0
C3	Sub-regional probabilistic PCA; 1, 4 or 8 regions × 1–3 components	∼3.7k/comp.
M2-self	Robust weighted median of the 16 nearest and the target	2
Distance-excluded		
Far stack	Mean of every station beyond R; D1 at $R = 400$ km	0
Leave-one-out over nearest neighbours		
M1	Distance-weighted mean of the 16 (64, 256) nearest beyond R	1
M2	Robust weighted median of the 16 nearest beyond R	2
M3a / M3b	Ridge regression on 16 neighbours, per station / pooled	65/station; 257
M4a / M4b	M3 per time band (under 7, 7–60, 60–400, over 400 days)	4 × M3
Learned		
M3k	Learned kernel: neighbour weight from distance, azimuth and noise level; 16 or 256 neighbours	1,411
M5	Space–time attention: 32 neighbours and the far stack, 64-day window	212,048
M5-aug	M5 trained with planted transients in its inputs	212,048

4. Filters

[Paragraph 1: the three families.]
[Paragraph 2: classical and regression filters.]
[Paragraph 3: learned models.]

5. Results

5.1. The trade-off between noise removed and signal kept

[Paragraph 1: the overall trade-off (Fig. 5).]
[Paragraph 2: what the radius does.]

Table 2: Main results at $R = 0$ unless stated. *Validation years; to be replaced by test-year results after the method freeze.* Error: fast leave-one-out error (lower is better; zero prediction 0.723). Kept: median retention of 25- and 100-km Gaussian transients; afterslip at 15–40 km from the patch; real earthquake offsets.

Filter	Error	Noise removed	Kept 25 / 100 km	Spurious	Afterslip	Real offsets
C1	–	26.7%	0.99 / 0.83	0.11	1.00	0.98
C3 (9 settings)	–	25.1–26.4%	0.88–0.99 / 0.30–0.84	0.27–1.52	0.97–1.00	0.90–0.95
M2-self	–	25.0%	0.24 / 0.00	0.10	0.19	0.60
Far stack	0.509	26.6%	0.99 / 0.83	0.11	1.00	0.98
D1 ($R = 400$ km)	0.526	24.9%	1.00 / 1.00	0.24	1.00	0.99
M1	0.531	22.2%	0.26 / 0.00	0.02	0.09	0.72
M1, 256	0.507	26.4%	0.84 / 0.21	0.10	0.96	0.83
M2	0.558	18.4%	0.27 / 0.00	0.11	0.23	0.69
M3a	0.527	22.6%	0.43 / 0.17	0.04	0.22	0.77
M3b	0.534	21.4%	0.30 / 0.07	0.04	0.24	0.74
M4a	0.517	24.9%	0.56 / 0.37	0.03	0.53	0.75
M4b	0.532	21.5%	0.33 / 0.11	0.04	0.31	0.72
M3k	0.517	23.9%	0.28 / 0.01	0.03	0.11	0.81
M3k, 256	0.499	27.1%	0.71 / 0.22	0.18	0.73	0.88
M5	0.504	26.8%	0.80 / 0.56	0.15	0.87	0.88
M5-aug	0.508	26.5%	0.97 / 0.80	0.17	0.99	0.98

5.2. Number of stations versus distance

[Paragraph 3: count beats distance (Fig. 6).]

[Paragraph 3b: regression on the nearest stations (M3, M4).]

5.3. Realistic transients

[Paragraph 4: near field kept, far field removed (Fig. 7).]

[Paragraph 5: shallow slow slip and the spurious signal it causes.]

5.4. Real earthquake offsets

[Paragraph 6: real offsets confirm the planted results (Fig. 8).]

5.5. Learned models

[Paragraph 7: the learned kernel.]

[Paragraph 8: more neighbours, more noise removed, less signal kept.]

[Paragraph 9: the attention network with and without planted-transient training.]

6. Discussion

[Paragraph 1: what practitioners should do.]
[Paragraph 2: why local filters remove the far field and why it matters.]
[Paragraph 3: relation to Bachelot et al.]
[Paragraph 4: what this means for deep learning.]
[Paragraph 5: limitations and future work.]

7. Conclusions

[Conclusions: write after the discussion.]

Data and code availability

[Data and code availability.]

Declaration of generative AI in the writing process

[AI declaration: write at the end, describing what was actually done.]

References

Bachelot, L., Thomas, A., Melgar, D., Searcy, J., Sun, Y.S., 2025. Cascadia Daily GNSS Time Series Denoising: Graph Neural Network and Stack Filtering. Seismica 4. doi:10.26443/seismica.v2i4.1419.

Blewitt, G., Hammond, W., Kreemer, C., 2018. Harnessing the GPS Data Explosion for Interdisciplinary Science. Eos 99. doi:10.1029/2018EO104623.

Costantino, G., Giffard-Roisin, S., Dalla Mura, M., Socquet, A., 2024. Denoising of Geodetic Time Series Using Spatiotemporal Graph Neural Networks: Application to Slow Slip Event Extraction. IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing 17, 17567–17579. doi:10.1109/JSTARS.2024.3465270.

Costantino, G., Radiguet, M., El Yousfi, Z., Socquet, A., 2026. A Continuum of Slow Slip Events in the Cascadia Subduction Zone Illuminated by High-Resolution Deep-Learning Denoising. Geophysical Research Letters 53, e2025GL117446. doi:10.1029/2025GL117446.

Dong, D., Fang, P., Bock, Y., Webb, F., Prawirodirdjo, L., Kedar, S., Jamason, P., 2006. Spatiotemporal filtering using principal component analysis and Karhunen-Loeve expansion approaches for regional GPS network analysis. Journal of Geophysical Research: Solid Earth 111, 2005JB003806. doi:10.1029/2005JB003806.

Gruszczynski, M., Klos, A., Bogusz, J., 2018. A Filtering of Incomplete GNSS Position Time Series with Probabilistic Principal Component Analysis. Pure and Applied Geophysics 175, 1841–1867. doi:10.1007/s00024-018-1856-3.

Kreemer, C., Blewitt, G., 2021. Robust estimation of spatially varying common-mode components in GPS time-series. Journal of Geodesy 95, 13. doi:10.1007/s00190-020-01466-5.

Mastella, G., Bedford, J., Corbi, F., Funiciello, F., 2025. Denoising daily displacement GNSS time series using deep neural networks in a near real-time framing: a single-station method. Geophysical Journal International 242, ggaf207. doi:10.1093/gji/ggaf207.

Nevada Geodetic Laboratory, 2026. GPS Networks Map Viewer and Time Series Products (IGS20 daily tenv3). https://geodesy.unr.edu. Accessed 6 October 2026.

Tian, Y., Shen, Z.K., 2016. Extracting the regional common-mode component of GPS station position time series from dense continuous network. Journal of Geophysical Research: Solid Earth 121, 1080–1096. doi:10.1002/2015JB012253.

Wdowinski, S., Bock, Y., Zhang, J., Fang, P., Genrich, J., 1997. Southern California permanent GPS geodetic array: Spatial filtering of daily positions for estimating coseismic and postseismic displacements induced by the 1992 Landers earthquake. Journal of Geophysical Research: Solid Earth 102, 18057–18070. doi:10.1029/97JB01378.

Zhou, W., Ding, K., Liu, P., Lan, G., Ming, Z., 2022. Spatiotemporal Filtering for Continuous GPS Coordinate Time Series in Mainland China by Using Independent Component Analysis. Remote Sensing 14, 2904. doi:10.3390/rs14122904.




Figure 3: From positions to residuals at station BSRY. [Expand caption: (a) positions and trajectory, (b) residual, (c) one validation year with the network common mode and the cleaned series.]




Figure 4: Measuring signal kept. [Expand caption; note that P502 is the median station among 17 at 15–40 km.]




Figure 5: [Caption.]




Figure 6: [Caption.]




Figure 7: [Caption.]




Figure 8: [Caption.]