

Intelligent Automation for Scientific Workflows

Scientific facilities like SLAC face a key challenge: as experimental capabilities grow more sophisticated, the complexity of data analysis and decision-making increases dramatically. Modern AI systems, particularly Large Language Models (LLMs), offer promising capabilities for automation and assistance but face fundamental limitations when applied to demanding scientific workflows.

This section of the research program proposes a novel approach inspired by classical ideas from programming language implementation, particularly the metacircular evaluator concept from Lisp and the staged compilation techniques from modern compilers. I will argue that the LLM should be treated as a basic component of a larger system that can, if built in a certain way, be much more capable than the underlying LLM.

If successful, the system would provide a foundation for better AI-assisted scientific workflows, enabling more aggressive automation efforts across SLAC's experimental facilities. The resulting research innovations might also give compounding returns by encouraging collaboration with the broader AI / ML research.

0.1 Example: LLM-Assisted Analysis at XPP

In the last year, I developed an automated analysis pipeline for LCLS's X-ray Pump-Probe (XPP) instrument, working with my PI (Aparva Mehta) and the LCLS analytics group. The pipeline (figure 1) finds CDW signals through a contrast-enhancing transformation of the raw data and uses statistical criteria to maximize signal to noise with respect to the analysis parameters.

This automation approach reduces the user's responsibility to a single numerical input: a region of interest (ROI) on the detector. While this usage is simple, interpreting diagnostic outputs when things go wrong still requires domain expertise. To address this limitation, I experimented with a language model agent to guide users through the diagnostics. In one test, I initialized the analysis with incorrect ROI coordinates. The agent reviewed logged diagnostics and successfully identified the issue:

User: The pump-probe curve for the current run looks weird. What might be wrong?




Figure 1: In low signal-to-background settings background estimation is non-trivial, as is identifying and integrating diffraction peaks (a). Our automated workflow enhances contrast using spectral distribution statistics (b), identifies a bounding mask for the signal ((c), interior red region), estimates background levels, and finally generates a pump-probe delay curve (d). Automatic optimization of the workflow parameters yields better signal to noise than the traditional (manual) analysis.

Agent: Based on the p-value uniformity check results, the designated background ROI [80, 95, 5, 45] appears to contain signal when it should not.

This is evidenced by:

- 1 Mean p-value of 0.394 (should be 0.5)
- 2 Highly significant KS test ($p=6.496e-17$)
- 3 Large z-score deviation (9.0)

This contaminated background ROI would affect the null distribution calculation, which in turn would distort the pump-probe curve. The solution would be to select a different background ROI location that shows proper uniformity in its p-values.

While effective for modest diagnostic tasks, the system revealed fundamental limitations in more difficult situations. Attempting to use it for analyzing large collections of log files or guiding multi-step decision processes exposed a well-known underlying limitation of LLMs: difficulty maintaining analytical context across multiple interaction turns, especially when handling large datasets. This limitation is exacerbated by how LLMs perform reasoning itself - since techniques like reflection and chain of thought demonstrate that LLM ‘thought’ operates through token generation, each step of analysis consumes valuable context window capacity.

1 Technical Innovation: A Language-Model Architecture for Scientific Computing

Such limitations point to a deeper challenge: we lack supporting tools for constructing agent systems in scientific environments because the underlying kernel of a natural language agent – the LLM itself – is on its own insufficient. Conventional automation at light sources depends on robust software design – similarly, we will need principled architectures for composing natural language agents into scientific workflows with sufficient scale, capability and robustness.

The last two years have seen rapid growth in LLM-based agent frameworks like LangChain and AutoGen, these systems rely on ad-hoc combinations of prompts and tools, making them brittle, inconsistent and hard to extend. Rather than systematically addressing the key limitations of LLMs, these agentic approaches reproduce or even compound them. A case in point is reliance on techniques such as retrieval-augmented generation (RAG) that aim to compensate for limited context window capacities but introduce serious tradeoffs in recall and accuracy.

I suggest an alternative that takes inspiration from two fundamental concepts in programming language implementation: the metacircular evaluator pattern first developed for Lisp, and staged compilation techniques used in modern compilers.

The main insight is treating natural language interaction with an LLM as a form of code execution. Suppose that we first ask the LLM to translate natural language instructions into programs written in a DSL (domain specific language). The structure of such a DSL program will represent the decomposition of a complex prompt into multiple tasks. The interpretation of the same program involves distribution of each component task to an LLM instance and the linking together of instances through a calling convention and shared memory system.

More concretely:

Algorithm 1: System Overview

Natural Language Query;
 ↓ [LLM Translation];
 XML Task Structure (equivalent to S-expression);
 ↓ [Parser];
 Abstract Syntax Tree;
 ↓ [tree traversal];
 LLM execution;

In this schema, natural language queries are first translated into composite expressions made up of smaller units (atomic tasks) with the purpose to make the execution tractable while preserving semantics of the original query. A satisfying feature of the setup is that it will be self-hosting in the sense that the LLM evaluates DSL procedures generated by the LLM.

An equivalent perspective is that the framework will dynamically compile the user’s prompt into a directed acyclic graph (DAG). Each node of the DAG is dispatched to a separate LLM session, and data travels down and up the nodes of the graph in the form of environment frames and return values, respectively.

The architecture consists of three main components:

1.1 Execution Model

Two mutually recursive procedures, `eval` and `apply`, work with each other to evaluate DSL expressions:

```
1 ; Evaluates a task in the given environment; returns direct result or ↵
   decomposed tasks
2 (define (eval-task task env)
3   (cond
4     ; For atomic tasks, try direct application; if it fails, decompose
5     ((atomic? task)
6      ; amb tries the first option; if it fails, backtracks to the second
7      (amb (apply-proc task '() env) ; Direct application
8            (eval-task (decompose task) env))) ; Or decomposition
9
10    ; For compound tasks: evaluate arguments, apply procedure
11    (else
12     (let ((proc (task-proc task))
13           (args (map (lambda (arg) (eval-task arg env))
14                      (task-args task))))
15       (apply-proc proc args env))))
16
17 ; Applies a procedure to evaluated arguments in given environment
18 (define (apply-proc proc args env)
19   (cond
20     ; For primitives, try direct execution; if it fails, decompose and retry
21     ((primitive? proc)
22      ; amb tries the first option; if it fails, backtracks to the second
23      (amb (execute-llm proc args env) ; Direct execution
24            (eval-task (decompose proc args) env))) ; Or decomposition
25
26     ; For compound procedures: create new environment, evaluate body
27     (else
28      (let ((new-env (extend-environment proc args env)))
29        (eval-task (procedure-body proc) new-env))))
```

Listing 1: Scheme sketch of the evaluation procedure

When task execution ends with an error (e.g. context window overrun, output validation failure), the executor can retry by generating and evaluating an alternate procedure – for example, a decomposition of the task into multiple subtasks.

The creation of the execution data context `'env'` is mediated by the memory subsystem.

1.2 Associative memory system

The memory system explicitly separates storage and working contexts through a hierarchical design:

- Long-term memory for data and procedures
- Working memory for active computations

- Context frames that capture execution environments (including working memory)

Working memory is instantiated from long-term storage using an associative retrieval mechanism that is itself an (atomic) LLM procedure whose purpose is to match an atomic task to a contextually relevant subset of the data in long-term memory.

1.3 Task Expression Framework

The expression system supports nested procedures and basic functional patterns:

1	AtomicTask	-> Direct LLM execution
2	NestedTask	-> Compositional evaluation
3	MapExpression	-> Parallel processing
4	ReduceExpression	-> Result combination

Listing 2: Task Expression Types

These expressions, which can be extended, provide formal semantics for the DSL.

2 Implementation Plan

The implementation strategy builds on recent work and collaborations at SLAC. Working with LCLS beamline scientist Lingjia Liu and Frederic Poitevin from the LCLS analytics group, I developed the previously mentioned analysis approach for charge density wave dynamics in pump-probe experiments. The project aligns with broader LCLS initiatives, led by Jana Thayer and others, to develop real-time analysis capabilities for experimental beamlines.

Building on these experiences and collaborations, the implementation will proceed in two phases:

First, we will develop the core architectural components: the memory system for managing analysis contexts, the execution model for task decomposition, and initial task libraries. These libraries will include specialized agents for software architecture, code generation, analysis refinement, and experimental log interpretation. We'll work with the LCLS analytics group to ensure the framework complements their efforts, and with beamline scientists to get feedback from the end-user point of view.

Second, we will focus on development across scientific workflows based on reusable task patterns that combine automated processing with human-in-the-loop guidance. The framework will support diverse needs, from real-time experiment optimization to offline analysis and documentation. The goals will include accelerated analysis turnaround and reduced downtime during beamtimes.

3 PL concepts and concrete examples

3.1 Compilation

Staged compilation traditionally refers to breaking down compilation into distinct phases, where each stage transforms the program into a new representation closer to the target execution form:

Source code \rightarrow Parse tree \rightarrow AST \rightarrow Intermediate code \rightarrow Machine code

Our system uses the LLM to parse natural language into structured expressions:

TODO this is incomplete. There should be a cycle connecting 'Task executable' back to 'AST', to represent dynamic / incremental reparsing. See also: the other TODOs, `dynamic reparsing`;

Source code (English) \rightarrow Parse tree (XML) \rightarrow AST (Python) \rightarrow Task data + executable (XML)

In Python the first three steps (Source code (English) \rightarrow Parse tree (XML) \rightarrow AST (Python)) are orchestrated by the class `Compiler`. The remaining portion is generated by the interaction between `Compile` and the evaluation loop (see `Evaluator`, next section):

```
1 from dataclasses import dataclass
2 from typing import List, Any
3
4 @dataclass
5 class ASTNode:
6     operator: Any
7     args: List['ASTNode']
8
9 @dataclass
10 class Operator:
11     """Represents an operation to be performed"""
12     type: str # "atomic" or "compound"
13     task: str # The actual task description
14     params: Optional[Dict] = None # Additional parameters if needed
15
16 from dataclasses import dataclass
17 from typing import List, Any, Optional, Dict
18 from enum import Enum
19 from xml.etree.ElementTree import Element
20
21 from .error_types import ExecutionError, ErrorType, ResourceType
22 from .environment import Environment
23 from .task_system import TaskSystem, TaskType, XMLTaskParser, TaskStructure
24
25 @dataclass
26 class ASTNode:
27     """Represents a node in the Abstract Syntax Tree"""
28     operator: Any
```

```

29     args: List['ASTNode']
30
31 @dataclass
32 class Operator:
33     """Represents an operation to be performed"""
34     type: str # Maps to TaskType values
35     task: str # Task description
36     params: Optional[Dict[str, Any]] = None
37
38 from dataclasses import dataclass
39 from typing import Protocol, Dict, Optional
40 from enum import Enum
41 from xml.etree.ElementTree import Element
42
43 from .error_types import ResourceType, ExecutionError
44
45 class TaskSystem(Protocol):
46     """Interface for task management and prompt generation"""
47
48     def get_decomposition_prompt(self, task: str, resource: ResourceType) -> str:
49         """Generate prompt for decomposing a task that exceeded resources
50
51         Args:
52             task: The task description that failed
53             resource: Which resource was exhausted
54
55         Returns:
56             Prompt for LLM to generate decomposed task structure
57         """
58         ...
59
60     def get_alternative_prompt(self, task: str, failure_reason: str) -> str:
61         """Generate prompt for alternative approach after task failure
62
63         Args:
64             task: The task description that failed
65             failure_reason: Why the task failed
66
67         Returns:
68             Prompt for LLM to generate alternative approach
69         """
70         ...
71
72 class TaskType(Enum):
73     """Types of tasks in decomposition"""
74     ATOMIC = "atomic" # Direct LLM execution
75     MAP = "map" # Parallel subtasks
76     REDUCE = "reduce" # Combine results
77     SEQUENCE = "sequence" # Sequential steps
78
79 @dataclass

```



```

80 class TaskStructure:
81     """Parsed representation of a task from XML"""
82     type: TaskType
83     description: str
84     subtasks: list['TaskStructure'] = None
85     parameters: Optional[Dict[str, str]] = None
86
87 %class XMLTaskParser:
88     """Parses XML task descriptions into structured form"""
89     %
90     % def parse_task(self, xml: Element) -> TaskStructure:
91     %         """Parse XML into TaskStructure
92     %
93     %         Handles both atomic tasks and decompositions.
94     %
95     %         Args:
96     %             xml: XML element representing task
97     %
98     %         Returns:
99     %             Parsed task structure
100    %
101    %         """
102    %         task_type = TaskType(xml.get('type', 'atomic'))
103    %         description = xml.find('description').text
104    %
105    %         # Handle parameters if present
106    %         params = {}
107    %         params_elem = xml.find('parameters')
108    %         if params_elem is not None:
109    %             for param in params_elem:
110    %                 params[param.get('name')] = param.text
111    %
112    %         # Handle subtasks for non-atomic tasks
113    %         subtasks = []
114    %         if task_type != TaskType.ATOMIC:
115    %             for subtask in xml.findall('subtask'):
116    %                 subtasks.append(self.parse_task(subtask))
117    %
118    %         return TaskStructure(
119    %             type=task_type,
120    %             description=description,
121    %             subtasks=subtasks if subtasks else None,
122    %             parameters=params if params else None
123    %         )
124    %
125    % def task_to_ast(self, task: TaskStructure) -> ASTNode:
126    %         """Convert parsed task structure to AST
127    %
128    %         Maps task types to appropriate AST structures:
129    %         - ATOMIC -> single node
130    %         - MAP -> parallel execution structure
131    %         - REDUCE -> result combination structure
132    %         - SEQUENCE -> sequential execution structure

```

```

132 %
133 %
134 %     Args:
135 %         task: Parsed task structure
136 %
137 %     Returns:
138 %         Corresponding AST node
139 %
140 %     """
141 %     operator = Operator(
142 %         type=task.type.value,
143 %         task=task.description,
144 %         params=task.parameters
145 %     )
146 %
147 %     if task.type == TaskType.ATOMIC:
148 %         return ASTNode(operator=operator, args=[])
149 %
150 %     # For non-atomic tasks, recursively convert subtasks
151 %     return ASTNode(
152 %         operator=operator,
153 %         args=[self.task_to_ast(subtask) for subtask in task.subtasks]
154 %     )
155
156 class Compiler:
157     def __init__(self, task_system: TaskSystem):
158         self.task_system = task_system
159         self.parser = XMLTaskParser()
160
161     def compile(self, query: str) -> ASTNode:
162         """Initial compilation of natural language to AST
163
164         Args:
165             query: Natural language query from user
166
167         Returns:
168             ASTNode: Root node of compiled AST
169
170         """
171         # Generate structured task description
172         xml = self.llm_translate(query)
173
174         # Parse into intermediate task structure
175         task_structure = self.parser.parse_task(xml)
176
177         # Convert to AST
178         return self.parser.task_to_ast(task_structure)
179
180     def reparse(self,
181                 failed_task: str,
182                 error: ExecutionError,
183                 env: Environment) -> ASTNode:
184         """Generate new AST nodes when execution fails
185
186         Creates new task decomposition based on error type and context.

```

```

184
185     Args:
186         failed_task: Description of task that failed
187         error: Details about the failure
188         env: Current execution environment
189
190     Returns:
191         ASTNode: New AST subtree to try executing
192
193     Raises:
194         ExecutionError: If reparsing itself fails
195     """
196     # TODO the reparsing prompt shouldn't be exposed to the compiler.
197     # Instead it should construct a specialized Operator for reparsing
198     # And then execute it via Evaluator.execute_llm() (or whatever we're
199     # calling the method that has that responsibility
200
201     # Get specialized prompt for reparsing
202     reparse_prompt = self._get_reparse_prompt(failed_task, error)
203
204     # Generate new task structure via LLM
205     xml = self.llm_translate(reparse_prompt)
206
207     # Parse into intermediate structure
208     task_structure = self.parser.parse_task(xml)
209
210     # Convert to AST
211     node = self.parser.task_to_ast(task_structure)
212
213     # Validate before returning
214     self._validate_reparse(node, error)
215
216     return node
217
218     def _get_reparse_prompt(self, task: str, error: ExecutionError) -> str:
219         """Get appropriate reparse prompt based on error type"""
220         # TODO the reparsing prompt shouldn't be exposed to the compiler.
221         # Instead it should construct a specialized Operator for reparsing.
222         # If we really need to track the error type, then it should be an
223         # attribute of that specialized Operator
224         if error.type == ErrorType.RESOURCE_EXHAUSTED:
225             return self.task_system.get_decomposition_prompt(
226                 task,
227                 error.details["resource"]
228             )
229         elif error.type == ErrorType.TASK_FAILED:
230             return self.task_system.get_alternative_prompt(
231                 task,
232                 error.details["reason"]
233             )
234         else:
235             raise ExecutionError.invalid_reparse(

```

```

236         task=task,
237         validation_error="Unsupported error type for reparsing"
238     )
239
240     def _validate_reparse(self, node: ASTNode, error: ExecutionError) -> ←
241     None:
242         """Validate reparsed AST is acceptable
243
244         TODO: Implement validation logic:
245         - Check structure is valid
246         - Verify resources are bounded
247         - Ensure termination properties
248         """
249         pass
250
251     def llm_translate(self, prompt: str) -> Element:
252         """Translate natural language to XML via LLM
253
254         TODO: Implement LLM interaction:
255         - Format prompt with XML expectations
256         - Handle LLM response parsing
257         - Validate XML structure
258         """
259         pass

```

Example task structure in XML:

```

1  <task>
2    <description>analyze peak patterns across detectors</description>
3    <inputs>
4      <input name="detector1_data">
5        <task>
6          <description>load and preprocess detector 1 data</description>
7          <expected_output>
8            Preprocessed detector 1 data in standard format:
9            - Intensity values
10           - Peak positions
11           - Background levels
12          </expected_output>
13        </task>
14      </input>
15      <input name="detector2_data">
16        <task>
17          <description>load and preprocess detector 2 data</description>
18          <expected_output>
19            Preprocessed detector 2 data in standard format:
20            - Intensity values
21            - Peak positions
22            - Background levels
23          </expected_output>
24        </task>

```

```

25     </input>
26 </inputs>
27 <expected_output>
28     Comparative peak analysis:
29     - Peak correlations between detectors
30     - Intensity pattern matching
31     - Anomaly detection
32 </expected_output>
33 </task>
34 <!--
35 # TODO the above xml is just an example, but we need to clearly define a ↔
36 # mapping between the
37 # structure of xml generated by the llm (when it does <reparsing>) and ↔
38 # AST subtrees. (We could
39 # potentially simplify this by constraining the llm <reparsing> process ↔
40 # so that it can only generate
41 # one ASTNode at a time. In the case of composite nodes, this would mean ↔
42 # generating xml for an outer
43 # task (e.g. a reduction function) and inner task(s) (e.g. the individual ↔
44 # tasks whose outputs the
45 # reduction is operating on)
46 -->

```

In summary:

1. The XML stage lets the LLM express task composition and input / output conventions in a structured way
2. XML provides the interface between LLM and the evaluator
3. Every AST node follows a uniform structure representing operations and their arguments
4. Composite task behavior emerges from AST semantics and atomic task behavior
5. Atomic task behavior emerge from natural-language operator definitions, which are *not* exposed at this level
6. Environments handle local variable bindings and global working memory for LLM operations (see next section)
7. New atomic task patterns can be added without changing the evaluator or execution system

3.2 Environment

An environment represents the complete context needed to evaluate expressions. In traditional programming languages, this mostly means lexical scope—the set of variables accessible from inside a given stack frame.

Our environments support traditional variable scoping while also managing the short-term memory component of the LLM execution context. The basic aspects are:

```
1 class Environment:
2     def __init__(self):
3         """Environment holds bindings and LLM working context"""
4         self.bindings = {} # Current variable bindings
5         self.context = {} # LLM working memory
6
7     def extend(self, names, values):
8         """Create new environment with additional bindings"""
9         new_env = Environment()
10        new_env.bindings = dict(zip(names, values))
11        # The full implementation will update the context using associative
12        # matching via the long term - short term memory system instead of
13        # just cloning it
14        new_env.context = self.context.copy()
15        return new_env
16
17    def lookup(self, name):
18        """Look up value in current bindings"""
19        return self.bindings.get(name)
```

This is sufficient for us to:

1. Track context through nested evaluations
2. Pass relevant state between task executions
3. Allow the evaluator to pass around execution contexts and create new ones using the associative memory procedure

3.3 Metacircular Evaluator

A metacircular evaluator is an interpreter implemented using similar fundamental operations to the ones it aims to interpret. In our context, we implement a domain-specific language (DSL) evaluator using LLM operations as one basic component of the evaluation machinery, and this evaluator in turn coordinates and executes higher-level LLM tasks.

The architecture has two key aspects. First, the environment must be a first-class data structure that can be explicitly introspected by both the evaluator and the LLM. The environment captures not just variable bindings (as in a conventional programming language implementation) but the complete context needed for task interpretation and decomposition. (In contrast, in a traditional language implementation, the execution environment is entangled with the parsing and code generation process in a rather opaque way.)

The second aspect is the self-hosting property mentioned above. The LLM provides the evaluator with primitive capabilities for generating structured out-

put from natural language (as XML task descriptions), and for executing atomic tasks. The evaluator combines these primitive operations to implement higher-level functionality: managing execution environments, parsing and dispatching structured task descriptions, and collecting execution outputs.

Here’s the core evaluator pseudo-implemented in Python:

```

1  from dataclasses import dataclass
2  from typing import List, Any, Optional
3  from enum import Enum
4
5  # Shared type definitions
6  class OperatorType(Enum):
7      ATOMIC = "atomic"      # Direct LLM execution
8      MAP = "map"            # Process multiple inputs
9      REDUCE = "reduce"      # Combine results
10     SEQUENCE = "sequence"   # Execute in order
11
12     # TODO only ATOMIC operators should have (or populate) the task attribute,
13     # because the other operator types aren't directly llm-executable.
14     # Note an asymmetry between llm parsing and llm execution: when parsing,
15     # the llm is locally aware of the AST structure, but when executing the
16     # llm only sees one atomic node at a time. <reparsing>
17     @dataclass
18     class Operator:
19         type: OperatorType
20         task: str          # Task description/prompt
21         params: Dict = None # Optional parameters
22
23     %<errors>
24     %type ExecutionError =
25     % | { type: 'resourceExhaustion'; resource: 'turns' | 'context' | ↵
26         'output' }
27     % | { type: 'taskFailure'; reason: string }
28     % | { type: 'incompleteTask' };
29     %</errors>
30
31     class Evaluator:
32         def eval(self, node: Node, env: 'Environment') -> Any:
33             """Evaluate a node in the given environment"""
34             # TODO <dynamic reparsing> if LLM execution fails (typically bc ↵
35             # of resource exhaustion or verification failure)
36             # we need to recover by reparsing the AST node into one or more ↵
37             # rewritten subtrees
38             # (i.e. either a new atomic expression or a decomposed, compound ↵
39             # expression). See the
40             # Scheme description to get the general idea. also see <errors>
41             # </dynamic reparsing>
42             if self.is_atomic(node.operator):
43                 return self.execute_llm(node.operator, env)
44
45             # For compound expressions, evaluate args then apply

```

```

42     evaluated_args = [self.eval(arg, env) for arg in node.args]
43     return self.apply(node.operator, evaluated_args, env)
44
45     def is_atomic(self, node: ASTNode) -> bool:
46         """Check if node represents direct LLM execution"""
47         return len(node.args) == 0 and node.operator.type == "atomic"
48
49     def execute_llm(self, operator: Any, env: 'Environment') -> Any:
50         """Execute atomic task with LLM"""
51         return self.llm_execute(operator.task, env)
52
53     def apply(self, operator: Any, args: List[Any], env: 'Environment') -> Any:
54         """Apply compound operator to evaluated arguments"""
55         new_env = env.extend(operator.params, args)
56         return self.eval(operator.body, new_env)

```

Note that the dynamic reparsing is spread out as an interaction between Evaluator and Compiler, but it is conceptually equivalent to this simple expression from the Scheme version:

```

1  ...
2  ; For atomic tasks, try direct application; if it fails, decompose
3  ((atomic? task)
4   ; amb tries the first option; if it fails, backtracks to the second
5   (amb (apply-proc task '() env)           ; Direct application
6        (eval-task (decompose task) env))) ; Or decomposition
7  ...

```

Listing 3: nondeterministic evaluation using the amb (ambiguous) operator

3.4 End-to-End Example

Let's examine how the system handles a user request that benefits from natural language understanding:

‘Review our XRD analysis and check if we chose a good background region.’
The LLM first translates this into nested tasks:

```

1  <task>
2    <description>analyze background region quality</description>
3    <inputs>
4      <input name="region_stats">
5        <task>
6          <description>extract statistics from experiment logs</description>
7          <parameters>
8            Extract and analyze:
9            - Background region coordinates
10           - Statistical test p-values
11           - Distribution uniformity metrics

```



```

12     </parameters>
13     <expected_output>
14         Structured statistics including:
15         - ROI coordinates
16         - P-value series
17         - Distribution metrics
18     </expected_output>
19 </task>
20 </input>
21 </inputs>
22 <expected_output>
23     Quality assessment including:
24     - Statistical validity evaluation
25     - Potential signal contamination check
26     - Recommendations for improvement if needed
27 </expected_output>
28 </task>

```

The compiler builds an AST:

```

1 node = ASTNode(
2     operator=Operator(
3         type="atomic",
4         task="analyze_region_quality"
5     ),
6     args=[
7         ASTNode(
8             operator=Operator(
9                 type="atomic",
10                task="extract_stats",
11                params={"instruction": "Find background..."}
12            ),
13            args=[]
14        )
15    ]
16 )

```

The evaluator processes this with environment handling:

```

1 # Initialize environment with both logs and documentation
2 env = Environment(context={
3     "log_contents": """
4     2024-04-06 10:15:32 INFO: Starting analysis of run 123
5     2024-04-06 10:15:33 DEBUG: Background ROI set to [80,95,5,45]
6     2024-04-06 10:15:34 DEBUG: Method: local linear
7     2024-04-06 10:15:35 WARNING: High fit residuals
8     2024-04-06 10:15:36 DEBUG: P-values: [0.394, 0.412, 0.378]
9     ...""",
10
11     "analysis_docs": """

```

```

12 Background Region Quality Assessment Guide:
13 - P-values should follow uniform distribution (mean approximately 0.5)
14 - KS test should show p > 0.05
15 - Region should be at least 20 pixels from any peak
16 - Common failure modes:
17   * Signal contamination causes p-value clustering
18   * Edge effects near beam stop distort background
19   ...""
20 })
21
22 # Evaluate full expression
23 result, final_env = evaluator.eval(node, env)
24
25 # The evaluation proceeds:
26 # 1. Inner extract_stats task receives filtered environment:
27 #   env.context = {
28 #     "log_contents": "...", # Only the log data needed for extraction
29 #   }
30 #   -> Returns structured data like:
31 #     {"roi": [80,95,5,45],
32 #      "pvalues": [0.394, 0.412, 0.378]}
33
34 # 2. Outer analyze_region_quality task receives full context:
35 #   env.context = {
36 #     "analysis_docs": "...", # Documentation for analysis guidance
37 #     "extraction_results": {"roi": [80,95,5,45], ...}
38 #   }
39 #   -> Uses docs to guide analysis:
40 #     "Background region shows signs of signal contamination.
41 #      P-value clustering (mean=0.394) matches known failure mode
42 #      described in analysis guide."

```

In this example, each task gets minimal context needed for its operation and the outer tasks can access both the log-parsing results (as direct input) and reference documentation (as context / short-term memory).