



SMSGW MO LISTENER INTERFACE

Date: 02 Aug 2013

1. Requirement

- a. Web service WSDL
URL: <http://x.x.x.x:yyyy/molistener?wsdl>
Client must implement to handle this link and return webservice description
- b. The Client need to implement **moRequest** function as description below for SMSGW to call.

2. moRequest function:

a. moRequest function

Receive SMS from subscriber.

Prototype:

```
String moRequest (String username, String password,  
                  String source, String dest,  
                  String content)
```

Parameter	Description
username	Username provide to SMSGW .
Password	Password provide to SMSGW
Source	Phone number which sms send from
Dest	Shortcode which SMS Send to
Content	Content of SMS

Return Code & description table

Code	Description
0	SMS put to queue Success
1	SMS put to Queue failed
200	Invalid Parameter(s)
201	Invalid username or password
202	Invalid Request Type
203	Invalid Request Parameter(s)
400	Server too busy

Examples:

```
String r = mtRequest("username", "password",  
                      "84983135221", "8888",  
                      "dangky");
```

Return might be:

- **0** -> Success
- **1** -> Failed
- ...

3. TPS, Time out & retry:

- TPS: 100
- Time out: 5 seconds
- Retry: 2 times

4. Input & ouput XML

a. Input XML (SMGW post to client)

```
<?xml version="1.0" ?>  
<S:Envelope  
  xmlns:S="http://schemas.xmlsoap.org/soap/envelope/">  
  <S:Body>  
    <moRequest xmlns="http://mtws/xsd">  
      <username>xxxxxx</username>  
      <password>yyyyyy</password>
```

```
<source>84983929641</source>
<dest>9237</dest>
<content>Cute</content>
</moRequest>
</S:Body>
</S:Envelope>
```

b. Return XML (Client response)

```
<?xml version="1.0"?>
<S:Envelope xmlns:S="http://schemas.xmlsoap.org/soap/envelope/"
>
  <S:Body>
    <moRequestResponse xmlns="http://mtws/xsd">
      <return>0 </return>
    </moRequestResponse>
  </S:Body>
</S:Envelope>
```