



EU DECLARATION OF CONFORMITY

**Suzhou Inovance Technology Co., Ltd.**

No. 52, Tian E Dang Road, Wuzhong District, 215104, Suzhou City, Jiangsu Province,
P.R. China declares under sole responsibility conformity of the following products

Product	Industrial Robot
Model	See Annex for model list
Machinery Directive (MD)	2006/42/EC
Electromagnetic Compatibility Directive (EMC)	2014/30/EU
RoHS Directive (RoHS)	2011/65/EU
Applied Harmonized Standards	Amended by (EU)2015/863
	EN 60204-1:2018
	EN ISO 10218-1:2011
	EN61000-6-2:2019
	EN61000-6-4:2019

The product(s) listed above are in conformity with the essential requirements of the EC Directive(s) mentioned above when installed in accordance with the installation instructions contained in the product documentation and manufactured in accordance with the European harmonised standards.

Trade Mark
The CE-marking was first affixed in
Name, Surname
Position/Title
Signature

INOVANCE

24

Yuchuan Liu
President, R&D

Date
European Authorised Representative
Address

2025-04-30
Inovance Technology Europe GmbH
Gottlieb-Daimler-
Straße 17/2, 74385 Pleidelsheim, Germany
Hans-Peter Abel

Contact

ANNEX

Model list:

Model	Manipulator model	Cabinet Model
IR-S4-40Zbcd (*)-INT	IRB-S4-40Zbcd (*)-INT	IRCB501-4AD (*)-INT
IR-S7-aZbcd (*)-INT	IRB-S7-aZbcd (*)-INT	IRCB501-4CD (*)-INT
IR-GS10-aZbcd (*)-INT	IRB-GS10-aZbcd (*)-INT	IRCB501-4CD (*)-INT
IR-S10-aZbcd (*)-INT	IRB-S10-aZbcd (*)-INT	IRCB501-4CD (*)-INT
IR-S7-60Z20S3-C2	IRB-S7-60Z20S3-C2	IRCB501-4CD (*)-INT
IR-S20-aZbcd (*)-INT	IRB-S20-aZbcd (*)-INT	IRCB501-4ED (*)-INT
IR-GS20-aZbcd (*)-INT	IRB-GS20-aZbcd (*)-INT	IRCB501-4ED (*)-INT
IR-S25-aZbcd (*)-INT	IRB-S25-aZbcd (*)-INT	IRCB501-4ED (*)-INT
IR-GS25-aZbcd (*)-INT	IRB-GS25-aZbcd (*)-INT	IRCB501-4ED (*)-INT
IR-S30-aZbcd (*)-INT	IRB-S30-aZbcd (*)-INT	IRCB501-4ED (*)-INT
IR-GS30-aZbcd (*)-INT	IRB-GS30-aZbcd (*)-INT	IRCB501-4ED (*)-INT
IR-S35-aZbcd (*)-INT	IRB-S35-aZbcd (*)-INT	IRCB501-4ED (*)-INT
IR-GS35-aZbcd (*)-INT	IRB-GS35-aZbcd (*)-INT	IRCB501-4ED (*)-INT
IR-CS3-40Zbcd (*)-INT	IRB-CS3-40Zbcd (*)-INT	IRCB501-4AD (*)-INT
IR-CS6-aZbcd (*)-INT	IRB-CS6-aZbcd (*)-INT	IRCB501-4CD (*)-INT
IR-CS10-aZbcd (*)-INT	IRB-CS10-aZbcd (*)-INT	IRCB501-4CD (*)-INT
IR-CS20-aZbcd (*)-INT	IRB-CS20-aZbcd (*)-INT	IRCB501-4ED (*)-INT
IR-CS50-120Zbcd (*)-INT	IRB-CS50-120Zbcd (*)-INT	IRCB501-4ED (*)-INT
IR-CTS3-35Zbcd (*)-INT	IRB-CTS3-35Zbcd (*)-INT	IRCB501-4CD (*)-INT
IR-CTS4-35Zbcd (*)-INT	IRB-CTS4-35Zbcd (*)-INT	IRCB501-4CD (*)-INT
IR-C8-62Zbcd (*)-INT	IRB-C8-62Zbcd (*)-INT	IRCB501-4ED (*)-INT
IR-TS4-35Zbcd (*)-INT	IRB-TS4-35Zbcd (*)-INT	IRCB501-4CD (*)-INT
IR-TS5-55Zbcd (*)-INT	IRB-TS5-55Zbcd (*)-INT	IRCB501-4CD (*)-INT
IRS111-3-aZbTSd (*)-INT	IRB111-3-aZbTSd (*)-INT	IRCB501-4AD (*)-INT
IRS111-10-50ZbTSd (*)-INT	IRB111-10-50ZbTSd (*)-INT	IRCB501-4CD (*)-INT
IRS111-20-aZbTSd (*)-INT	IRB111-20-aZbTSd (*)-INT	IRCB501-4CD (*)-INT

IR-S50-120Zbcd (*)-INT	IRB-S50-120Zbcd (*)-INT	IRCB501-4ED (*)-INT
IR-GS50-120Zbcd (*)-INT	IRB-GS50-120Zbcd (*)-INT	IRCB501-4ED (*)-INT
IRS311-3-60TSd (*)-INT	IRB311-3-60TSd (*)-INT	IRCB501-6LD (*)-INT
IRS311-7-aTSd (*)-INT	IRB311-7-aTSd (*)-INT	IRCB501-6LD (*)-INT
IRS311-7-90TS5-GJ-B1	IRB311-7-90TS5-GJ-B1	IRCB501-6LD (*)-INT
IR-R4-acd (*)-INT	IRB-R4-acd (*)-INT	IRCB501-6LD (*)-INT
IR-R4H-54cd (*)-INT	IRB-R4H-54cd (*)-INT	IRCB501-6LD (*)-INT
IR-R7-acd (*)-INT	IRB-R7-acd (*)-INT	IRCB501-6LD (*)-INT
IR-R7H-acd (*)-INT	IRB-R7H-acd (*)-INT	IRCB501-6LD (*)-INT
IR-R10-acd (*)-INT	IRB-R10-acd (*)-INT	IRCB501-6FD (*)-INT
IR-R10H-acd (*)-INT	IRB-R10H-acd (*)-INT	IRCB501-6FD (*)-INT
IR-R11-90cd (*)-INT	IRB-R11-90cd (*)-INT	IRCB501-6FD (*)-INT
IR-CR4-acd (*)-INT	IRB-CR4-acd (*)-INT	IRCB501-6LD (*)-INT
IR-CR4H-54cd (*)-INT	IRB-CR4H-54cd (*)-INT	IRCB501-6LD (*)-INT
IR-CR7-acd (*)-INT	IRB-CR7-acd (*)-INT	IRCB501-6LD (*)-INT
IR-CR7H-acd (*)-INT	IRB-CR7H-acd (*)-INT	IRCB501-6LD (*)-INT
IR-CR10-acd (*)-INT	IRB-CR10-acd (*)-INT	IRCB501-6FD (*)-INT
IR-CR10H-acd (*)-INT	IRB-CR10H-acd (*)-INT	IRCB501-6FD (*)-INT
IR-CR11-90cd (*)-INT	IRB-CR11-90cd (*)-INT	IRCB501-6FD (*)-INT

Remark:

'a' stand for the Manipulator length; special: 54 stands for 54.5cm.

'b' should be 10-60 for the length of the 3axis Lead screw.

'c' should be the installation environment, C: clean, S: standard, P: high protection, F: die casting, WS: wall+ standard, WC: wall +clean, WP: wall+ high protection, EX: explosionproof.

'd' should be 3-20 or blank for the towing cable information.

'(*)' may include a suffix "XXXXXXXXXX", Where "XXXXXXXXXX" can be blank or combination of alphanumeric and/or symbols that represents customer identity.

Pendant Models: IRTP80-Le (*), IRTP81-Le (*), IR-TP200-Le (*).

'e' should be 3-30 or blank for the towing cable information.

'(*)' may include a suffix "XXXXXXXXXX", Where "XXXXXXXXXX" can be blank or combination of alphanumeric and/or symbols that represents customer identity.

Expansion Board Models: IRCB501-2ENID-BD, IRCB501-1600END-BD, IRCB501-0016ETND-B, IRCB501-FS-01-BD, IRCB501-2PN-BD, IRCB501-6LDI3-BD.