

CERTIFICATE OF CONFORMITY

MD/CoC/25/HEL/010 Issue 1

Product	Industrial Robot
Certificate holder / Manufacturer	Suzhou Inovance Technology Co., Ltd. No. 52, Tian E Dang Road, Wuzhong District, 215104, Suzhou City, Jiangsu Province, China
Manufacturing site	Suzhou Inovance Technology Co., Ltd. No. 52, Tian E Dang Road, Wuzhong District, 215104, Suzhou City, Jiangsu Province, China
Model(s)	See Page 2
Serial number(s)	
Trade mark (if any)	
Technical details / ratings	See Page 2-3
Additional information (if any)	-
Following standards have been applied	EN ISO 12100:2010; EN 60204-1:2018 EN ISO 10218-1:2011; EN ISO 13849-1:2023
Evaluated documentation (reference No., date)	GZES240701356601, GZES240701356602 GZES240701356603, SHFS240700034771

This Certificate of Conformity is based on documentation of the product. Above mentioned Documentation of the product has been evaluated. Based on documentation the product has been found to be in conformity with the above-mentioned standard(s) and applicable parts of the Annex I of the Machinery Directive (2006/42/EC).

It does not imply an assessment of the whole production or fulfilment of other additional requirements in the Directive.

If a standard mentioned on this Certificate is withdrawn or removed from the list of harmonised standards under the Machinery Directive (2006/42/EC), a re-evaluation is needed.

This certificate can be used to demonstrate product compliance until 26 February 2030 with the presumption that standards mentioned remains valid. Surveillance activities are not part of this certificate.

It is the obligation of the certification holder to demonstrate upon request that the product produced is identical to the certified product. Use of the CE marking requires actions set in Article 5 clause 1 of Machinery Directive (2006/42/EC), completion of an EU Declaration of Conformity, internal production control (Annex VIII, item 3) and compliance with all relevant EU Directives.

Date of issue 26 February 2025

SGS Fimko Oy

Signature



Baris Bagci



CERTIFICATE OF CONFORMITY



MD/CoC/25/HEL/010 Issue 1

Model(s)

IR-R4-acd-fhi-INT, IR-R4H-54cd-fhi-INT, IR-R7-acd-fhi-INT, IR-R7H-acd-fhi-INT,
IR-R10-acd-fhi-INT, IR-R10H-acd-fhi-INT, IR-R11-90cd-fhi-INT, IR-CR4-acd-fhi-INT,
IR-CR4H-54cd-fhi-INT, IR-CR7-acd-fhi-INT, IR-CR7H-acd-fhi-INT,
IR-CR10-acd-fhi-INT, IR-CR10H-acd-fhi-INT, IR-CR11-90cd-fhi-INT

Technical details / ratings

Model Name	Manipulator Model	Cabinet Model	Payload (kg)	Manipulator length (cm)	Rating
IR-R4-acd-fhi-INT	IRB-R4-acd-fhi-INT	IRCB501-6ND-INT	4	56/54/60	1PH 220-240VAC 23A
		IRCB501-6LD-INT			1PH 220-240VAC 10A
IR-R4H-54cd-fhi-INT	IRB-R4H-54cd-fhi-INT	IRCB501-6ND-INT	4	54	1PH 220-240VAC 23A
		IRCB501-6LD-INT			1PH 220-240VAC 10A
IR-R7-acd-fhi-INT	IRB-R7-acd-fhi-INT	IRCB501-6ND-INT	7	70/90/140	1PH 220-240VAC 23A
		IRCB501-6LD-INT			1PH 220-240VAC 10A
IR-R7H-acd-fhi-INT	IRB-R7H-acd-fhi-INT	IRCB501-6ND-INT	7	70/90/140	1PH 220-240VAC 23A
		IRCB501-6LD-INT			1PH 220-240VAC 10A
IR-R10-acd-fhi-INT	IRB-R10-acd-fhi-INT	IRCB501-6ND-INT	10	110/120	1PH 220-240VAC 23A
		IRCB501-6FD-INT			1PH 220-240VAC 10A
IR-R10H-acd-fhi-INT	IRB-R10H-acd-fhi-INT	IRCB501-6ND-INT	10	110/120	1PH 220-240VAC 23A
		IRCB501-6FD-INT			1PH 220-240VAC 10A
IR-R11-90cd-fhi-INT	IRB-R11-90cd-fhi-INT	IRCB501-6ND-INT	11	90	1PH 220-240VAC 23A
		IRCB501-6FD-INT			1PH 220-240VAC 10A
IR-CR4-acd-fhi-INT	IRB-CR4-acd-fhi-INT	IRCB501-6ND-INT	4	56/54/60	1PH 220-240VAC 23A
		IRCB501-6LD-INT			1PH 220-240VAC 10A

CERTIFICATE OF CONFORMITY

MD/CoC/25/HEL/010 Issue 1



Technical details / ratings

Model Name	Manipulator Model	Cabinet Model	Payload (kg)	Manipulator length (cm)	Rating
IR-CR4H-54cd-fhi-INT	IRB-CR4H-54cd-fhi-INT	IRCB501-6ND-INT	4	54	1PH 220-240VAC 23A
		IRCB501-6LD-INT			1PH 220-240VAC 10A
IR-CR7-acd-fhi-INT	IRB-CR7-acd-fhi-INT	IRCB501-6ND-INT	7	70/90/140	1PH 220-240VAC 23A
		IRCB501-6LD-INT			1PH 220-240VAC 10A
IR-CR7H-acd-fhi-INT	IRB-CR7H-acd-fhi-INT	IRCB501-6ND-INT	7	70/90/140	1PH 220-240VAC 23A
		IRCB501-6LD-INT			1PH 220-240VAC 10A
IR-CR10-acd-fhi-INT	IRB-CR10-acd-fhi-INT	IRCB501-6ND-INT	10	110/120	1PH 220-240VAC 23A
		IRCB501-6FD-INT			1PH 220-240VAC 10A
IR-CR10H-acd-fhi-INT	IRB-CR10H-acd-fhi-INT	IRCB501-6ND-INT	10	110/120	1PH 220-240VAC 23A
		IRCB501-6FD-INT			1PH 220-240VAC 10A
IR-CR11-90cd-fhi-INT	IRB-CR11-90cd-fhi-INT	IRCB501-6ND-INT	11	90	1PH 220-240VAC 23A
		IRCB501-6FD-INT			1PH 220-240VAC 10A

'a' should be 20~3100 for the Manipulator length; special: 54 stands for 54.5cm.

'c' should be the installation environment, C: clean, S: standard, P: high protection, F: die casting, WS: wall+ standard, WC: wall+ clean, WP: wall+ high protection.

'd' should be 3-20 or blank for the towing cable information.

'f' stands for customization cabinets information which should be C/Blank; C: Indicates a non-standard cabinet, IRCB501-6ND-INT. Blank: Indicates a standard cabinet, IRCB501-6LD-INT, IRCB501-6FD-INT.

'h' stands for customization of Manipulator which should be SV/A/AD/HXW/Blank; SV: Built-in solenoid valve, A :90 Degree Bellow, AD: Using a low base, HXW :Including optional accessories, such as aviation plug, IO cable, network cable; Blank: No customization of manipulator.

'i' stands for information on usage scenarios which should be GJ/Blank; GJ: Silicone crystal industry, Blank: No Customized Information.