Algorithms for NP-Hard Problems

Summary note, Lectured by Eunjung Kim, KAIST

Hojune Lee

School of Computing, KAIST

Contents

1 Parameterized Algorithm **3**

2 Branching Algorithms **5**

2.1 $\mathcal{O}(2^k)$-time Algorithm for Vertex Cover 5

2.2 $\mathcal{O}((3k)^k)$-time Algorithm for Feedback Vertex Set 6

2.3 $\mathcal{O}(4^{k-lp^*(G)})$-time Algorithm for Vertex Cover 8

Chapter 1

Parameterized Algorithm

Parameterization

The *parameterization* is a map defined by

$$\kappa : \Sigma^* \to \mathbb{N}_0$$

With this definition, *parameterized problem* is an ordered pair decision problem for language $\mathfrak{L} \subseteq \Sigma^*$ and parameterization κ, $(\mathfrak{L}, \kappa)$. Since κ is a map, we can take any well-defined function for κ. So, we can claim that for wrong encoded instance in Σ^*, they goes to some fixed value, e.g. 0.
Here, it is important that why we take this definition. I'll write the intuition later, after introducing the example.

Vertex Cover

All problems are defined in red-colored box. First problem is Vertex Cover. For a graph $G = (V, E)$ and $k \in \mathbb{N}_0$, *vertex cover* is a set $S \subseteq V$ such that $\forall uv \in E, u \in S \vee v \in S$. i.e. All edges in E are covered by S.
Here, Vertex Cover is a decision problem of following encoded language $\mathfrak{L}$:

$$\mathfrak{L}_{VC} = \{(G, k) | G = (V, E), k \in \mathbb{N}_0, G \text{ has vertex cover whose size at most } k\}$$

Since $(G, k) \in \Sigma^*$ is a encoded string, they are together. Means that, when we describe the input size $|x|$ of algorithm, it doesn't contain the seperated meaning of size of G and magnitude of k. So we parameterization κ here, to extract the meaning of k.

$$\kappa : (G, k) \mapsto k$$

As we'll see later, another information also can be extracted :

$$\kappa : (G, k) \mapsto k - lp^*(G)$$

This is conceptual meaning of parameterization of a problem.

Fixed Parameter Tractable

A parameterized problem $(\mathfrak{L}, \kappa)$ is *fixed parameter tractable* if there is an algorithm such that for every $x \in \Sigma^*$, decides whether $x \in \mathfrak{L}$ or not in time $f(\kappa(|x|)) \cdot |x|^{\mathcal{O}(1)}$

Chapter 2

Branching Algorithms

2.1 $\mathcal{O}(2^k)$-time Algorithm for Vertex Cover

Algorithm 1 $\mathcal{O}(2^k)$-time Algorithm for Vertex Cover

1: **procedure VC**(G, k)

Input: $G = (V, E)$ is a graph, $k \in \mathbb{N}_0$

Output: Decide $(G, k) \in \mathfrak{L}_{VC}$ or not

2: **if** $|E| = 0$ **then return** Yes

3: **else if** $k = 0$ **then return** No

4: **else**

5: $uv \leftarrow Pick(E)$ ▷ Pick any edge

6: **return VC**$(G - u, k - 1) \vee$ **VC**$(G - v, k - 1)$

This is very fundamental algorithm for Vertex Cover. We can prove following:

Algorithm 1

Algorithm 1 is *correct*(i.e., decides whether $(G, k) \in \mathfrak{L}_{VC}$ or not correctly) in time $\mathcal{O}(2^k \cdot poly(n))$

Proof. We can say that algorithm 1 is correct means that

$$\mathbf{VC}(G, k) = \text{Yes} \iff (G, k) \in \mathfrak{L}_{VC}$$

We'll prove via mathematical induction on $k \in \mathbb{N}_0$. If $k = 0$, it is trivial. Then assume that for any $G = (V, E)$, $VC(G, i) = \text{Yes} \iff (G, i) \in \mathfrak{L}_{VC}, 0 \leq i < k$. And one easy fact is that, if S is a vertex cover of G, and $u \in S$, then $S \setminus \{u\}$ is a vertex cover of $G - u$.
($\Leftarrow$) Let $(G, k) \in fL_{VC}$. Then, exists a vertex cover S of G such that $|S| \leq k$. Suppose that given instance is non-trivial, so reach at line 4. Then pick $\forall uv \in E$, and W.L.O.G., $u \in S$. Then by fact, $S \setminus \{u\}$ is a vertex cover of $G - u$ whose size is at most $k - 1$. Then, we can determine that $\mathbf{VC}(G - u, k - 1) = \text{Yes}$ by hypothesis.
($\Rightarrow$) Suppose that $\mathbf{VC}(G, k) = \text{Yes}$. Then for non-trivial cases, W.L.O.G., $\mathbf{VC}(G - u, k -$

1) is Yes. It implies that $(G-u, k-1) \in \mathfrak{L}_{VC}$. Then, let S' be the vertex cover of $G-u$ whose size is at most $k-1$. Then, let $S = S' \cup \{u\}$. It is clearly a vertex cover of G whose size is at most k. So $(G, k) \in \mathfrak{L}_{VC}$.

Now, for the running time. It is obvious that line 2,3,5 effects polynomial time w.r.t. input size. And there are at most k-depth of binary recursion, so running time is $\mathcal{O}(2^k \cdot poly(n))$.

□

2.2 $\mathcal{O}((3k)^k)$-time Algorithm for Feedback Vertex Set

Now we define next problem to solve, which is called Feedback Vertex Set.

Feedback Vertex Set

For any graph $G = (V, E)$, a *feed-back vertex set* of G is a set $S \subseteq V$ such that

$$\forall C \in Cycle(G), S \cap C \neq \emptyset$$

i.e., set of vertices that intersect with all of cycles in G. So, we can define decision problem Feedback Vertex Set by

$$\mathfrak{L}_{FVS} = \{(G, k) | G = (V, E), k \in \mathbb{N}_0, G \text{ has FVS whose size at most } k\}$$

Algorithm 2 $\mathcal{O}((3k)^k)$-time Algorithm for Feedback Vertex Set

```
1: procedure FVS(G, k)
2:     if |E| = 0 then return Yes
3:     if k = 0 then return No
4:     while ∃v ∈ V(G), d_G(v) ≤ 2 do
5:         if d_G(v) ≤ 1 then
6:             G ← G − v
7:         else if |N_G(v) \ {v}| = 2 then
8:             {x, y} ← N_G(v) \ {v}
9:             G ← G − v + xy                          ▷ Allow multigraphs
10:        else
11:            G ← G \ N_G(v)
12:            k ← k − 1          ▷ Assume that we choose the adjacent vertex of v
13:    {v_n, ··· , v_1} ← Sort(V(G))                   ▷ Note: Decreasing Order
14:    return ⋁_{i=1}^{3k} FVS(G − v_i, k − 1)
```

Algorithm 2

Algorithm 2 is correct for FEEDBACK VERTEX SET in time $\mathcal{O}((3k)^k \cdot poly(n))$

Lemma 2.2.1. *For any feed-back vertex set X of $G = (V, E)$ holds that*

$$\sum_{x \in X} (d_G(x) - 1) \geq |E| - |V| + 1$$

Proof. One easily obtained fact is that, $G[V \setminus X]$ is a forest. Means that,

$$|E(G[V \setminus X])| \leq |V(G[V \setminus X])| - 1 = |V| - |X| - 1$$

However,

$$|E| = \underbrace{|E(G[X])| + |E(X, V \setminus X)|}_{\leq \sum_{x \in X} d_G(x)} + |E(G[V \setminus X])|$$

So,

$$\sum_{x \in X} d_G(x) \geq |E| - |E(G[V \setminus X])| \geq |E| - |V| + |X| + 1$$

Implies that

$$\sum_{x \in X} (d_G(x) - 1) \geq |E| - |V| + 1$$

□

Lemma 2.2.2. *Let $G = (V, E)$ such that $\delta(G) \geq 3$. Let $V = \{v_1, v_2, \cdots, v_n\}$ where*

$$d_G(v_1) \geq d_G(v_2) \geq \cdots \geq d_G(v_n)$$

Then, for any feedback vertex set X of G,

$$|X| \leq k \implies X \cap \{v_1, \cdots, v_{3k}\} \neq \emptyset$$

Proof. Suppose not. By hand-shake lemma,

$$\sum_{v \in V} d_G(v) = 2|E| \geq 3|V| \qquad \because \delta(G) \geq 3$$

And since $X \cap \{v_1, \cdots, v_{3k}\} = \emptyset$, We can obtain following from above lemma:

$$\sum_{i=1}^{3k} (d_G(v_i) - 1) \geq 3 \sum_{x \in X} (d_G(x) - 1) \geq 3|E| - 3|V| + 3$$

$$\sum_{i=3k+1}^{n} (d_G(v_i) - 1) \geq \sum_{x \in X} (d_G(x) - 1) \geq |E| - |V| + 1$$

implies that,

$$\sum_{v \in V(G)} (d_G(v) - 1) = 2|E| - |V| \geq 4|E| - 4|V| + 4$$

It deduce

$$3|V| > 2|E|$$

which contradict to first line. □

With second lemma, one can show that Algorithm 2 is correct. And since it generates at most $3k$ branches for each step, and the maximal depth is k, so the running time will be $\mathcal{O}((3k)^k \cdot poly(n))$

2.3 $\mathcal{O}(4^{k-lp^*(G)})$-time Algorithm for Vertex Cover

In this section, we review the VERTEX COVER with another parameterization, which is

$$\kappa : (G, k) \mapsto k - lp^*(G)$$

Here, $lp^*(G)$ is a solution of another problem, which called linear program version of vertex cover.

Linear Program for Vertex Cover

For $G = (V, E)$, linear program for vertex cover is called LPVC, which defined as following.

$$\min \sum_{u \in V(G)} x_u$$

where

$$\forall uv \in E, x_u + x_v \geq 1, \qquad \forall u \in V, x_u \geq 0 \tag{$\star$}$$

holds. Let's call above condition by $\star$. And we denote $lp^*(G)$ be the optimal solution of LPVC.

One fact is that,

$$\text{size of optimal vertex cover of } G \geq lp^*(G)$$

This is because that, optimal vertex cover is very special case of LPVC. It can be easily obtain, since every vertex cover satisfy the condition $\star$. So, this automatically implies that for given (G, k), if $k < lp^*(G)$, (G, k) is No instance of VERTEX COVER.

Now, we'll explore the algorithm which related to these LP problems. Before move on, we'll take a following theorem without proof.

Linear Program is P

Linear Program can be solved in polynomial time. So that, LPVC also solved in polynomial time.

And now we'll define half-integral solution for LPVC.

Half Integral solution for LPVC

We call that the solution x^* for LPVC is *half-integral* when

$$\forall u \in V(G), x_u^* \in \{0, \frac{1}{2}, 1\}$$

With the above fact, we can conduct following decomposition in polynomial time.

Crown Decomposition

Let x^* be the solution of LPVC. Then we can partition $V(G)$ into following 3 sets :

$$C = \{u \in V(G) | x_u^* < 0.5\}$$

$$H = \{u \in V(G) | x_u^* > 0.5\}$$

$$R = \{u \in V(G) | x_u^* = 0.5\}$$

This is called *crown decomposition* of G. This decomposition can be obtained in polynomial time.



Figure 2.1: A graph illustrating the crown decomposition.