

train/station_timetables (singular)

get /v3/uk/train/station_timetables/{id}.json

Returns the timetable of train departures for a specified train station and within a specified time window. By default, this includes only scheduled departures. This is augmented with realtime train departure information (RTI) - where available - if the request specifies live=true. The augmenting RTI is sourced from open data sources, which can include the [Network Rail TRUST system and its Train Movements and VSTP data feeds](#), and the [National Rail Darwin Web Service Staff data feed](#).

This endpoint can be used to generate pocket timetables and power web or mobile app screens with scheduled and realtime train station departures to let end users know when their next train is - or should be - coming.

The time window of interest is specified by the datetime timestamp and the from_offset and to_offset duration parameters:

- the start of the time window is datetime + from_offset;
- the end of the time window is datetime + to_offset.

By default, only train departures for the next two hours are shown, relative to now.

The term "departures" is loosely used in this endpoint to represent not only departures from the station of interest, but also arrivals, and passes (i.e. passing through the station without stopping).

[API Key \(app_key\) + 1 more](#)

OR

[API Key \(X-App-Key\) + 1 more](#)

OR

[HTTP Basic](#)

REQUEST

PATH PARAMETERS

* id

Pattern: ^crs:\w{3}\$|^tiploc:\w{4,7}\$|^w{3}\$

string

The ID of the train station timetable: the station code of the station of interest

[More on station codes and reference schemes](#)

The station code is case sensitive.	
Examples: crs:RMD	
QUERY-STRING PARAMETERS	
datetime date-time	Specifies the basis of the time window of interest. Defaults to the date/time that the API request was made. Note that the further into the past and future datetime is set, the less co Examples: 2022-02-03T20:30:00+01:00
from_offset string	Default: PT00:00:00 Specifies an offset relative to datetime which can shift the start of the ti For instance, from_offset=-PT02:00:00 shifts the start of the time window Minimum -PT24:00:00, i.e. 24 hours in the past. Maximum PT24:00:00, i.e. 24 hours in the future. Examples: PT00:30:00
to_offset string	Default: PT02:00:00 Specifies an offset relative to datetime which can shift the end of the tin For instance, to_offset=PT06:00:00 shifts the end of the time window of Minimum -PT24:00:00, i.e. 24 hours in the past. Maximum PT24:00:00, i.e. 24 hours in the future. Examples: PT01:30:00
limit integer	Default: 50 Min 1 Max 1000

		Specifies the maximum total number of train departures to be returned. Examples: 20
live		Default: false
boolean		Specifies whether to augment the scheduled departures information with real time information. When live=true, each departure is augmented with RTI, where this is available. Examples: true
source_config		Allowed: dws_staff
enum		When live=true, this parameter specifies which data source should be used for real time information. When omitted, this means that Network Rail TRUST system and its Train Protection and Warning System is used for real time data. When source_config=dws_staff, this means that National Rail Darwin VMS is used for real time data.
train_status		Default: passenger Allowed: passenger freight
enum		This parameter specifies the train status of the departures returned: can be passenger or freight. Examples: passenger
station_detail	origin	Allowed: origin destination called_at calling_at
array of string		This parameter requests that additional detail for the departures returned is provided. The additional station detail provided for those stations is the station's name, the aimed_arrival_time, aimed_departure_time, aimed_pass_time of the train. The allowed values are origin, destination, called_at and calling_at. In case origin or destination is specified, additional station detail is provided for those stations. station_detail=called_at can be specified in conjunction with the called_at parameter. Likewise station_detail=calling_at can be used in conjunction with the calling_at parameter.

	These individual values can be combined using a comma separated list to get station detail for all the specified values. Examples: [origin] [destination]
type array of string	arrival Allowed: arrival departure pass This parameter specifies the type of the departures returned. Allowed types are arrival, departure or pass which correspondingly mean arrival, departure or pass are returned. Examples: [arrival] [departure] [pass]
origin string	Pattern: ^crs:\w{3}\$ ^tiploc:\w{4,7}\$ ^w{3}\$ This parameter specifies the origin of the departures returned i.e. only departures from stations which the train services have already called at, works only on the departure parameter. More on station codes and reference schemes The station code is case sensitive.
destination string	Pattern: ^crs:\w{3}\$ ^tiploc:\w{4,7}\$ ^w{3}\$ This parameter specifies the destination of the departures returned i.e. only departures to stations which the train services will call at, works only on the departure parameter. More on station codes and reference schemes The station code is case sensitive.
called_at string	Pattern: ^crs:\w{3}\$ ^tiploc:\w{4,7}\$ ^w{3}\$ This parameter specifies to only return departures for train services which have already performed to use the origin parameter for that. More on station codes and reference schemes

	The station code is case sensitive.
calling_at string	Pattern: ^crs:\w{3}\$ ^tiploc:\w{4,7}\$ ^w{3}\$ This parameter specifies to only return departures for train services which performant to use the destination parameter for that. More on station codes and reference schemes The station code is case sensitive.
operator string	This parameter specifies the operator of the departures returned. The operator is specified using its ATOC code. The ATOC code is case sensitive.
service string	This parameter specifies the Network Rail service code of the departure.
source_detail boolean	This parameter specifies whether additional cancellation information will be returned.

API Server

https://transportapi.com

Authentication

2 API keys applied

RESPONSE

train/station_timetables response

EXAMPLESCHEMA

application/json

Copy

```
{
  "date": "2022-08-04",
  "time_of_day": "15:23",
  "request_time": "2022-08-04T15:23:18+01:00",
  "station_name": "Richmond",
  "station_code": "crs:RMD",
  "departures":
  {
    "all":
    [
      {
        "mode": "train",
        "service": "24671105",
        "train_uid": "Y70941",
        "platform": "2",
        "operator": "SW",
        "operator_name": "South Western Railway",
        "aimed_departure_time": "15:28",
        "aimed_arrival_time": "15:28",
        "aimed_pass_time": null,
        "origin_name": "Windsor & Eton Riverside",
        "destination_name": "London Waterloo",
        "source": "Network Rail",
        "category": "OO",
        "service_timetable":
        {
```

"id": "http://transportapi.com/v3/uk/train/service_timetables/Y70941:2022-08-04?live=true"

},

"status": "EARLY",

"expected_arrival_time": "15:28",

"expected_departure_time": "15:28",

"best_arrival_estimate_mins": 4,

"best_departure_estimate_mins": 4

},

{

"mode": "train",

"service": "22214000",

"train_uid": "Y21211",

"platform": "4",

"operator": "LO",

"operator_name": "London Overground",

"aimed_departure_time": "15:32",

"aimed_arrival_time": null,

"aimed_pass_time": null,

"origin_name": "Richmond",

"destination_name": "Stratford",

"source": "Network Rail",

"category": "OO",

"service_timetable":

{

"id": "http://transportapi.com/v3/uk/train/service_timetables/Y21211:2022-08-04?live=true"

},

"status": "STARTS HERE",

```
"expected_arrival_time": null,  
"expected_departure_time": "15:32",  
"best_arrival_estimate_mins": null,  
"best_departure_estimate_mins": 8  
}  
]  
}  
}
```

train/service_timetables (singular)

get /v3/uk/train/service_timetables/{service}.json

Returns the timetable of a train service for all stations on its route. By default, this includes only scheduled times. This is augmented with realtime train departure information (RTI) - where available - if the request specifies live=true. The augmenting RTI is sourced from open data sources, which can include the [Network Rail TRUST system and its Train Movements and VSTP data feeds](#), and the [National Rail Darwin Web Service Staff data feed](#).

The service of interest should be specified by the service parameter.

[API Key \(app_key\) + 1 more](#)

OR

[API Key \(X-App-Key\) + 1 more](#)

OR

[HTTP Basic](#)

REQUEST

PATH PARAMETERS

* service

string

Identifier used to specify the train service. Its current format is concatenated service ID and date. Its format might change in future.

Examples: Y66771:2022-12-24

QUERY-STRING PARAMETERS

source_config	enum	Allowed: dws_staff	When omitted, this means that Network Rail TRUST system and its Train the response attribute service contains TRUST Train Service Code. When source_config=dws_staff, this means that National Rail Darwin W response attribute service contains Darwin Train_uid.
live	boolean	Default: false	Specifies whether to augment the scheduled timetables information with When live=true, each departure is augmented with RTI, where this is ava Examples: true
type	array of string	Allowed: arrival departure pass	This parameter specifies the type of the journeys returned. Allowed types are arrival, departure or pass which correspondingly mea Examples: [arrival] [departure] [pass]

API Server

https://transportapi.com

Authentication

2 API keys applied

RESPONSE

train/service_timetable response

EXAMPLESCHEMA

application/json

Copy

```
{
  "request_time": "2022-08-04T15:23:18+01:00",
  "service": "25505005",
  "train_uid": "L03365",
  "headcode": "1024",
  "toc":
  {
    "atoc_code": "SR"
  },
  "train_status": "1",
  "mode": "train",
  "category": "OO",
  "operator": "13",
  "operator_name": "Scotrail",
  "stop_of_interest": "PAD",
  "origin_name": "London Paddington",
  "destination_name": "Heathrow Airport Terminal 5",
  "stops":
  [
    {
      "station_code": "PAD",
      "tiploc_code": "PADTON",
      "station_name": "London Paddington",
      "status": "LATE",
      "stop_type": "LO",
      "platform": "3",
      "aimed_arrival_date": "2022-08-04",
      "aimed_arrival_time": "15:23",
```

```
"aimed_pass_date": "2022-08-04",
"aimed_pass_time": "15:23",
"aimed_departure_date": "2022-08-04",
"aimed_departure_time": "15:24",
"expected_arrival_date": "2022-08-04",
"expected_arrival_time": "15:24",
"expected_pass_date": "2022-08-04",
"expected_pass_time": "15:24",
"expected_departure_date": "2022-08-04",
"expected_departure_time": "15:25"
},
{
"station_code": "EAL",
"tiploc_code": "EALINGB",
"station_name": "Ealing Broadway",
"status": "LATE",
"stop_type": "LI",
"platform": "1",
"aimed_arrival_date": "2022-08-04",
"aimed_arrival_time": "15:33",
"aimed_pass_date": "2022-08-04",
"aimed_pass_time": "15:33",
"aimed_departure_date": "2022-08-04",
"aimed_departure_time": "15:34",
"expected_arrival_date": "2022-08-04",
"expected_arrival_time": "15:34",
"expected_pass_date": "2022-08-04",
"expected_pass_time": "15:34",
```

```
"expected_departure_date": "2022-08-04",  
"expected_departure_time": "15:35"  
}  
]  
}
```

TAPI Rail Performance

Power your app or website screens with historical train service information:

- journey lateness;
- schedule changes and cancellations;
- service punctuality and reliability;
- historical data from traveler's point of view;

train/station_actual_journeys

get /v3/uk/train/station_actual_journeys/{station}.json

Returns a list of train journeys including aimed and actual departure/arrival times for a specified train station. The response includes only journeys that were scheduled to occur or actually occurred at the station within the provided time window.

For each journey, the status and expected times reflect the most recent schedule update available before the specified time of interest.

The station of interest should be specified with an station parameter. The time of interest should be specified with datetime parameter.

[API Key \(app_key\) + 1 more](#)

OR

[API Key \(X-App-Key\) + 1 more](#)

OR

[HTTP Basic](#)

REQUEST

PATH PARAMETERS

* station

Pattern: ^crs:\w{3}\$|^tiploc:\w{4,7}\$|^w{3}\$

string

Specifies the station code of the station of interest. Can be a CRS code

[More on station codes and reference schemes](#)

The station code is case sensitive.

Examples: crs:RMD

QUERY-STRING PARAMETERS

* datetime

date-time

Specifies the time of interest.

With combination of from_offset and to_offset defines the time window

All aimed, actual and expected times will be relevant to this date and time

Examples: 2022-02-03T20:30:00+01:00

from_offset

Default: PT00:00:00

string

Specifies an offset relative to datetime which can shift the start of the time

For instance, from_offset=-PT02:00:00 shifts the start of the time window

The defined window of interest cannot be greater than 48 hours.

Examples: -PT23:59:59

to_offset

Default: PT00:00:00

string

Specifies an offset relative to datetime which can shift the end of the time

For instance, to_offset=PT06:00:00 shifts the end of the time window of

The defined window of interest cannot be greater than 48 hours.

Examples: PT00:00:00

type array of string	arrival	Allowed: arrival departure pass
This parameter specifies the type of the journeys returned. Allowed types are arrival, departure or pass which correspondingly mean arrival, departure or pass. Examples: [arrival] [departure] [pass]		
origin string		Pattern: ^crs:\w{3}\$ ^tiploc:\w{4,7}\$ ^w{3}\$
This parameter specifies the origin of the departures returned i.e. only departures from stations which the train services have already called at, works only on the departure type. More on station codes and reference schemes The station code is case sensitive.		
destination string		Pattern: ^crs:\w{3}\$ ^tiploc:\w{4,7}\$ ^w{3}\$
This parameter specifies the destination of the departures returned i.e. only departures to stations which the train services will call at, works only on the departure type. More on station codes and reference schemes The station code is case sensitive.		
called_at string		Pattern: ^crs:\w{3}\$ ^tiploc:\w{4,7}\$ ^w{3}\$
This parameter specifies to only return departures for train services which are required to performant to use the origin parameter for that. More on station codes and reference schemes The station code is case sensitive.		
operator string		

	This parameter specifies the operator of the departures returned. The operator is specified using its ATOC code. The ATOC code is case sensitive.
expected boolean	This parameter specifies whether expected times will be included in the response. The operator is specified using its ATOC code.
limit integer	Default: 10 Min 1 Max 25 Specifies the maximum total number of train journeys to be returned. Examples: 10
page integer	Default: 1 Min 1 This parameter specifies the number of the page of results to return from the search results. Examples: 1

API Server

https://transportapi.com

Authentication

2 API keys applied

RESPONSE

train/station_actual_journeys response

EXAMPLESCHEMA

application/json

Copy

```
{
  "request_time": "2023-08-04T15:23:18+01:00",
```

```
"id": "https://transportapi.com/v3/uk/train/station_actual_journeys/LYM.json?datetime=2023-07-10T08:55:00+01:00",

"station_name": "Lympstone Village",

"station_code": "LYM",

"tiploc_code": "LYMPSTN",

"datetime": "2023-07-10T08:55:00+01:00",

"member":

[

{

"service":

{

"id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068745030.json",

"origin_name": "Exmouth",

"destination_name": "Paignton",

"category": "OO",

"mode": "train",

"rid": "202212068745030",

"headcode": "5053",

"train_uid": "W45030",

"retail_service_identifier": "CH144300",

"toc":

{

"atoc_code": "GW",

"name": "Great Western Railway"

},

"train_status": "P",

"cancellation":

{
```



```
"code": 138,
"reason": "This train has been cancelled because of an obstruction on the line",
"cancelled": true
},
"running_late": null,
"coaches":
[
{
"number": "B1",
"class": "Standard"
},
{
"number": "A1",
"class": "First"
}
],
"stop_type": "IP",
"cancelled": false,
"platform": "1",
"reverse_formation": true,
"route_change_delay": 0,
"aimed":
{
"departure":
{
"date": "2022-12-06",
"time": "08:58"
```

```
},
"arrival":
{
  "date": "2022-12-06",
  "time": "08:56"
},
"pass": null
},
"actual":
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "08:57"
  },
  "arrival":
  {
    "date": "2022-12-06",
    "time": "08:56"
  },
  "pass": null
},
"expected":
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "08:57"
```

```
},  
"arrival":  
{  
  "date": "2022-12-06",  
  "time": "08:56"  
},  
"pass": null  
}  
},  
{  
  "service":  
{  
    "id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068744240.json",  
    "origin_name": "Exmouth",  
    "destination_name": "Paignton",  
    "category": "OO",  
    "mode": "train",  
    "rid": "202212068744240",  
    "headcode": "4240",  
    "train_uid": "W44240",  
    "retail_service_identifier": "CH144301",  
    "toc":  
    {  
      "atoc_code": "GW",  
      "name": "Great Western Railway"  
    },  
    "train_status": "P",  
    "cancellation":
```

```
{
  "code": null,
  "reason": null,
  "cancelled": false
},
"running_late":
{
  "code": 330,
  "reason": "This train has been delayed by high winds"
},
"coaches":
[
  {
    "number": "B1",
    "class": "Standard"
  },
  {
    "number": "A1",
    "class": "First"
  }
],
"stop_type": "LI",
"cancelled": false,
"platform": "1",
"reverse_formation": false,
"route_change_delay": 1,
"aimed":
```

```
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "09:14"
  },
  "arrival":
  {
    "date": "2022-12-06",
    "time": "09:14"
  },
  "pass": null
},
"actual":
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "09:20"
  },
  "arrival":
  {
    "date": "2022-12-06",
    "time": "09:20"
  },
  "pass": null
},
"expected":
```

```
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "09:22"
  },
  "arrival":
  {
    "date": "2022-12-06",
    "time": "09:21"
  },
  "pass": null
}
],
"view":
{
  "id": "https://transportapi.com/v3/uk/train/station_actual_journeys/LYM.json?datetime=2023-07-10T08:55:00+01:00&page=2",
  "page": 2,
  "page_size": 50,
  "previous": "https://transportapi.com/v3/uk/train/station_actual_journeys/LYM.json?datetime=2023-07-10T08:55:00+01:00&page=1",
  "next": "https://transportapi.com/v3/uk/train/station_actual_journeys/LYM.json?datetime=2023-07-10T08:55:00+01:00&page=3"
}
}
```

train/actual_journeys (singular)

get /v3/uk/train/actual_journeys/{rid}.json

Returns a historical train journey, including basic service information and details for all stations along its route. Aimed (scheduled), actual, and expected times are provided where available.

The journey's status (e.g., cancelled or late), as well as the scheduled and expected times, reflect the information that was current at the specified time of interest.

The response also includes links to snapshots of the same service at moments when its schedule was updated.

[API Key \(app_key\) + 1 more](#)

OR

[API Key \(X-App-Key\) + 1 more](#)

OR

[HTTP Basic](#)

REQUEST

PATH PARAMETERS

* rid

string

Unique train service identifier

Examples: 202212068745030

QUERY-STRING PARAMETERS

datetime

date-time

Specifies the time of interest. The returned schedule, aimed times, actual

Defaults to the date/time that the API request was made.

Examples: 2022-02-03T20:30:00+01:00

expected

boolean

This parameter specifies whether expected times will be included in the

The operator is specified using its ATOC code.

API Server

<https://transportapi.com>

Authentication

2 API keys applied

RESPONSE

train/actual_journeys (singular) response

EXAMPLESCHEMA

application/json

Copy

```
{
  "request_time": "2023-08-04T15:23:18+01:00",
  "id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068745030.json",
  "datetime": "2022-12-06T12:05:37+00:00",
  "rid": "202212068745030",
  "train_uid": "V51006",
  "headcode": "2C73",
  "retail_service_identifier": "CH144300",
  "toc": {
    "atoc_code": "GW",
    "name": "Great Western Railway"
  },
  "train_status": "P",
  "origin_name": "Bristol Temple Meads",
  "destination_name": "Plymouth",
  "date": "2022-12-06",
```



```
"category": "OO",
"mode": "train",
"cancellation":
{
"code": 138,
"reason": "This train has been cancelled because of an obstruction on the line",
"cancelled": true
},
"running_late": null,
"coaches":
[
{
"number": "B1",
"class": "Standard"
},
{
"number": "A1",
"class": "First"
}
],
"stops":
[
{
"station_code": "BRI",
"tiploc_code": "BRSTLTM",
"station_name": "Bristol Temple Meads",
"stop_type": "OR",
"cancelled": false,
```

```
"platform": "6",
"reverse_formation": false,
"route_change_delay": 0,
"aimed":
{
"departure":
{
"date": "2022-12-06",
"time": "11:58"
},
"arrival": null,
"pass": null
},
"actual":
{
"departure":
{
"date": "2022-12-06",
"time": "12:00"
},
"arrival": null,
"pass": null
},
"expected":
{
"departure":
{
"date": "2022-12-06",
```

```
"time": "11:57"
},
"arrival": null,
"pass": null
}
},
{
"station_code": "PSN",
"tiploc_code": "PARSNST",
"station_name": "Parson Street",
"stop_type": "IP",
"cancelled": false,
"platform": "1",
"reverse_formation": false,
"route_change_delay": 0,
"aimed":
{
"departure":
{
"date": "2022-12-06",
"time": "12:05"
},
"arrival":
{
"date": "2022-12-06",
"time": "12:04"
},
"pass": null
```

```
},
"actual":
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "12:05"
  },
  "arrival":
  {
    "date": "2022-12-06",
    "time": "12:03"
  },
  "pass": null
},
"expected":
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "12:05"
  },
  "arrival":
  {
    "date": "2022-12-06",
    "time": "12:03"
  },
  "pass": null
}
```

```

}
}
],
"schedule_updates":
[
{
"id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068745030.json?datetime=2022-12-06T11:05:17+00:00"
},
{
"id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068745030.json?datetime=2022-12-06T12:10:37+00:00"
}
]
}

```

train/actual_journeys (collection)

get /v3/uk/train/actual_journeys.json

Returns information about multiple historical train journeys.

The response contains details for all train stations, including the aimed (scheduled) times, actual (historic) times and expected (forecast) times.

Historical journeys can be retrieved in two mutually exclusive ways:

- by defining a time of interest and a time window, using respectively the datetime and the from_offset and to_offset parameters. If choosing this option all journeys that were scheduled to travel in the defined time window will be retrieved. All times in the response are relevant for the specified time of interest i.e. the times from the latest known schedule before the time of interest will be returned. The same is valid for the expected times - the latest known forecast times before the time of interest will be returned.
- by specifying a date. If choosing this option all train journeys that start on the specified date will be retrieved. All aimed, actual and expected times in the response will be relevant to the latest known schedule and forecast times.

[API Key \(app_key\) + 1 more](#)

OR

[API Key \(X-App-Key\) + 1 more](#)

OR

[HTTP Basic](#)

REQUEST

QUERY-STRING PARAMETERS

datetime date-time	Specifies the time of interest. With combination of from_offset and to_offset defines the time window All aimed, actual and expected times will be relevant to this date and time Examples: 2022-02-03T20:30:00+01:00
from_offset string	Default: PT00:00:00 Specifies an offset relative to datetime which can shift the start of the time window For instance, from_offset=-PT02:00:00 shifts the start of the time window The defined window of interest cannot be greater than 48 hours. Examples: -PT23:59:59
to_offset string	Default: PT00:00:00 Specifies an offset relative to datetime which can shift the end of the time window For instance, to_offset=PT06:00:00 shifts the end of the time window of interest The defined window of interest cannot be greater than 48 hours. Examples: PT00:00:00

operator	
string	
	This parameter specifies the operator of the departures returned. The operator is specified using its ATOC code. The ATOC code is case sensitive.
expected	
boolean	
	This parameter specifies whether expected times will be included in the results. The operator is specified using its ATOC code.
date	
date	
	This parameter specifies the date of interest in yyyy-mm-dd format. Only one date can be specified. Cannot be used in combination with time window related parameters i.e. time_start, time_end, time_delta.
train_uid	
string	
	This parameter specifies the train uid of the searched train journey. Only one train uid can be specified. Examples: L65515
headcode	
string	
	This parameter specifies the headcode of the searched train journey. Only one headcode can be specified. Examples: 1A48
retail_service_identifier	
string	
	This parameter specifies the retail service identifier of the searched train journey. Only one retail service identifier can be specified. Examples: SR834600

limit	Default: 10
integer	Min 1 Max 25
Specifies the maximum total number of train journeys to be returned.	
Examples: 10	
page	Default: 1
integer	Min 1
This parameter specifies the number of the page of results to return from	
Examples: 1	

API Server

<https://transportapi.com>

Authentication

2 API keys applied

RESPONSE

train/actual_journeys (collection) response

EXAMPLESCHEMA

application/json

Copy

```
{
  "request_time": "2023-08-04T15:23:18+01:00",
  "id": "https://transportapi.com/v3/uk/train/actual_journeys.json?datetime=2022-12-06T11:05:17+00:00&to_offset=PT03:45:00",
  "datetime": "2022-12-06T11:05:17+00:00",
  "member":
  [
    {
      "service":
      {
```



```
"id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068745030.json",
"rid": "202212068745030",
"train_uid": "W45030",
"headcode": "5030",
"retail_service_identifier": "CH144300",
"toc":
{
  "atoc_code": "GW",
  "name": "Great Western Railway"
},
"train_status": "P",
"origin_name": "Exmouth",
"destination_name": "Paignton",
"date": "2022-12-06",
"category": "OO",
"mode": "train",
"cancellation":
{
  "code": 138,
  "reason": "This train has been cancelled because of an obstruction on the line",
  "cancelled": true
},
"running_late": null,
"coaches":
[
  {
    "number": "B1",
    "class": "Standard"
```

```
},  
{  
  "number": "A1",  
  "class": "First"  
}  
],  
"stops":  
[  
  {  
    "station_code": "EXM",  
    "tiploc_code": "EXMOUTH",  
    "station_name": "Exmouth",  
    "stop_type": "OR",  
    "cancelled": false,  
    "platform": "6",  
    "reverse_formation": false,  
    "route_change_delay": 0,  
    "aimed":  
    {  
      "departure":  
      {  
        "date": "2022-12-06",  
        "time": "11:58"  
      },  
      "arrival": null,  
      "pass": null  
    },  
    "actual":
```

```
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "12:00"
  },
  "arrival": null,
  "pass": null
},
"expected":
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "11:57"
  },
  "arrival": null,
  "pass": null
}
},
{
  "station_code": "PSN",
  "tiploc_code": "PARSNST",
  "station_name": "Parson Street",
  "stop_type": "IP",
  "cancelled": false,
  "platform": "1",
  "reverse_formation": false,
```

"route_change_delay": 0,

"aimed":

{

"departure":

{

"date": "2022-12-06",

"time": "12:05"

},

"arrival":

{

"date": "2022-12-06",

"time": "12:04"

},

"pass": null

},

"actual":

{

"departure":

{

"date": "2022-12-06",

"time": "12:05"

},

"arrival":

{

"date": "2022-12-06",

"time": "12:03"

},

"pass": null

```
},
"expected":
{
"departure":
{
"date": "2022-12-06",
"time": "12:05"
},
"arrival":
{
"date": "2022-12-06",
"time": "12:03"
},
"pass": null
}
},
"schedule_updates":
[
{
"id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068745030.json?date=2022-12-06T11:05:17+00:00"
},
{
"id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068745030.json?date=2022-12-06T12:10:37+00:00"
}
]
}
```

```
},
{
  "service":
  {
    "id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068744240.json",
    "rid": "202212068745030",
    "train_uid": "W44240",
    "headcode": "4240",
    "retail_service_identifier": "CH144200",
    "toc":
    {
      "atoc_code": "GW",
      "name": "Great Western Railway"
    },
    "train_status": "P",
    "origin_name": "Paignton",
    "destination_name": "Exmouth",
    "date": "2022-12-06",
    "category": "OO",
    "mode": "train",
    "cancellation":
    {
      "code": null,
      "reason": null,
      "cancelled": false
    },
    "running_late":
    {
```

```
"code": 330,
"reason": "This train has been delayed by high winds"
},
"coaches":
[
{
"number": "B1",
"class": "Standard"
},
{
"number": "A1",
"class": "First"
}
],
"stops":
[
{
"station_code": "PGN",
"tiploc_code": "PAIGNTN",
"station_name": "Paignton",
"stop_type": "OR",
"cancelled": false,
"platform": "6",
"reverse_formation": false,
"route_change_delay": 0,
"aimed":
{
"departure":
```

```
{
  "date": "2022-12-06",
  "time": "11:58"
},
"arrival": null,
"pass": null
},
"actual":
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "12:00"
  },
  "arrival": null,
  "pass": null
},
"expected":
{
  "departure":
  {
    "date": "2022-12-06",
    "time": "11:57"
  },
  "arrival": null,
  "pass": null
}
},
```



```
{
  "station_code": "PSN",
  "tiploc_code": "PARSNST",
  "station_name": "Parson Street",
  "stop_type": "IP",
  "cancelled": false,
  "platform": "1",
  "reverse_formation": false,
  "route_change_delay": 0,
  "aimed":
  {
    "departure":
    {
      "date": "2022-12-06",
      "time": "12:05"
    },
    "arrival":
    {
      "date": "2022-12-06",
      "time": "12:04"
    },
    "pass": null
  },
  "actual":
  {
    "departure":
    {
      "date": "2022-12-06",
```

```
"time": "12:05"

},

"arrival":

{

  "date": "2022-12-06",

  "time": "12:03"

},

"pass": null

},

"expected":

{

  "departure":

  {

    "date": "2022-12-06",

    "time": "12:05"

  },

  "arrival":

  {

    "date": "2022-12-06",

    "time": "12:03"

  },

  "pass": null

}

},

"schedule_updates":

[

  {
```

```
"id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068744240.json?datetime=2022-12-06T11:05:17+00:00"
```

```
},
```

```
{
```

```
"id": "https://transportapi.com/v3/uk/train/actual_journeys/202212068744240.json?datetime=2022-12-06T12:10:37+00:00"
```

```
}
```

```
]
```

```
}
```

```
}
```

```
],
```

```
"view":
```

```
{
```

```
"id": "https://transportapi.com/v3/uk/train/actual_journeys.json?datetime=2022-12-06T11:05:17+00:00&to_offset=PT03:45:00&page=3",
```

```
"page": 3,
```

```
"page_size": 20,
```

```
"previous": "https://transportapi.com/v3/uk/train/actual_journeys.json?datetime=2022-12-06T11:05:17+00:00&to_offset=PT03:45:00&page=2",
```

```
"next": "https://transportapi.com/v3/uk/train/actual_journeys.json?datetime=2022-12-06T11:05:17+00:00&to_offset=PT03:45:00&page=4"
```

```
}
```

```
}
```