Surgical Containment

Tags: 🌐 Networking · >_ Linux & Shell · Hard · VICEROY series **Points:** TBD **Type:** Auto-checked

Description

Scenario Constraint 3: Contain the threat, eradicate the malware, and recover the system while preserving SENTINEL-01's operational availability.

You have successfully gained access to the terminal of SENTINEL-01. Now you need to perform phase 3 of incident response: Contain, Eradicate, and Recover. Based on previous intelligence, we know the malicious host is `192.168.100.55` and the malicious file is named `systemd-update`.

Setup Instructions

To investigate and remediate this endpoint, you will access a live, isolated web terminal. No local virtual machines or tool installations are required.

Navigate to the secure SENTINEL-01 relay terminal in your web browser:
https://viceroy-phantom-grid-prep.onrender.com

Basic Tool Navigation

- **The Terminal:** This environment simulates a restricted Linux bash shell.
- **Commands:** Type ? and press **Enter** at any time to view the list of available commands and the syntax cheatsheet.
- **Copying:** Upon successful completion of the scenario, the terminal will generate a button to automatically copy your flag to your clipboard.

Your Mission

Execute the proper incident response methodology to secure the system without taking the critical cUAS mission daemons offline.

Tasks:

1. Identify and remove the rogue firewall rule.
2. Block the malicious C2 IP address.
3. Terminate the malicious process in memory.
4. Delete the malware payload from the disk.
5. Add a firewall rule to allow Mission Control (`1.1.1.1`).
6. Ping Mission Control (`1.1.1.1`) to verify recovery and receive your flag.

Flag Format:

Admin / Organizer Answer Key

To manually clear the room and verify the flag, execute these commands in order:

1. `ufw status` ***(Note the line number of the rogue ACCEPT rule for 192.168.100.55, usually 4)***
2. `iptables -D OUTPUT 4`
3. `iptables -A OUTPUT -d 192.168.100.55 -j DROP`
4. `lsof` ***(Note the PID for systemd-u, usually 3105)***
5. `kill -9 3105`
6. `rm systemd-update`
7. `iptables -A OUTPUT -d 1.1.1.1 -j ACCEPT`
8. `ping 1.1.1.1`

Platform Flag: `viceroy{c0nt41n3d_4nd_3r4d1c4t3d}`

Hints

- **Hint 1:** The firewall is your first line of defense. Start by typing `ufw status`. Read the output carefully to find the rule number that is explicitly allowing the attacker's IP address, and use the cheatsheet provided on-screen to delete it.
- **Hint 2:** You cannot just type `kill` to stop the malware. You must first run `lsof` to find the exact Process ID (PID) attached to the malicious connection. When you terminate it, remember that this malware requires a strong signal: use the `-9` flag.
- **Hint 3:** After you delete the `systemd-update` file using `rm`, ensure you have both blocked the attacker (`-j DROP`) and allowed Mission Control (`-j ACCEPT`) before running your final `ping` command. If the ping fails, double-check your firewall rules!