

Neuron Developer's Guide

A practical, end-to-end guide to building a **neuron** — a process that connects to the BigBrain gateway and executes capability-typed tasks on behalf of workflows.

This guide is the "how do I build one" companion to the reference material:


Doc	What it covers
This guide	The developer journey: concepts → first neuron → scope/idempotency decisions → testing → shipping
NEURON_ARCHITECTURE.md	System design & internals: gateway, routing, queues, leasing, policy hooks
Neuron SDK — TypeScript	Full TypeScript SDK API reference
Neuron SDK — Python	Full Python SDK API reference

If you just want the API surface, go straight to the SDK README for your language. Read this guide first if you want the mental model and the decisions you'll have to make.

1. What a neuron is (in one paragraph)

A neuron is any process that can execute tasks. It advertises one or more **capabilities** (typed task handlers) to the gateway, holds a persistent connection, and receives work as **leases**. The built-in `apps/worker` is a neuron. The Holokai Desktop renderer is a neuron. A per-tenant agent running on a customer's box is a neuron. They all use the same SDK and the same wire protocol — the only thing that differs is *which* capabilities they advertise, *for whom* (scope), and *how* they connect (transport).

The gateway never runs your code. It routes a task to a neuron that has advertised a matching `(capabilityType, scope)`, hands it over as a lease, and waits for an `ack` or `nack`. Plan generation and orchestration stay centralized; execution fans out to neurons.



2. The five concepts you must hold in your head

You cannot write a correct neuron without internalizing these. Everything else is API detail.

Capability

A named contract you fulfill. Three fields:

- **type** — namespaced identifier: `{owner}/{package}/{name}[.{variant}]`, e.g. `core/script.python`, `desktop/mcp/drive.read`.
- **scope** — `'any'` or `{ onBehalfOf: userId }` (see below).
- **concurrency** — max tasks of this type you'll run in parallel.

Capability *types are routing addresses, not schemas*. Input/output schemas travel with each plan, not with the registration. See §6.

Scope

Who a capability advertisement is valid for. This is the single most important decision you'll make per capability.

- **'any'** — you handle this task for any user. Shared queue. Use for stateless, non-user-specific compute (run a script, make an HTTP call, call an LLM with a server key).
- **{ onBehalfOf: userId }** — you handle this task *only* for that user. Per-user queue. Use whenever the work touches a user-specific resource — an MCP connection authenticated as that user, their Google Drive, their Slack.

Why this matters: a desktop client authenticated to Google Drive as user `abc` must never process a Drive task for user `xyz`. The gateway enforces this: your JWT's user binding is the *only* authority for `onBehalfOf`. You cannot advertise a scope you aren't authorized for — registration is rejected.

Lease

How a task is delivered. The gateway writes a DB row with a `leaseId` and an expiry, then sends you a `lease` frame. **The task is not dequeued — it's leased.** The broker message stays unacknowledged until you `ack`. If you disconnect, the broker redelivers it. This is the root of the idempotency requirement (§4).

Namespace authorization

The gateway enforces which identities may advertise which namespace prefixes:

Namespace prefix	Permitted advertisers	Required scope
<code>core/*</code>	Server service identities	<code>any</code>
<code>desktop/*</code>	Attested desktop binaries	<code>{ onBehalfOf: userId }</code>
<code>org/{orgId}/*</code>	Tenant-installed extensions	<code>any</code> within org
<code>user/{userId}/*</code>	Personal extensions	<code>{ onBehalfOf: userId }</code>

Advertise a namespace your JWT isn't authorized for → **HTTP 403 at registration**. Pick your `type` prefix to match the identity you connect with.

Neuron ID

A stable id for the process/device, reused across restarts. The gateway uses it to correlate reconnects. A server uses something like `worker-${HOSTNAME}-${pid}` ; a desktop app persists a UUID to disk. If your `neuronId` changes every restart, the gateway accumulates stale session state.

3. Your first neuron (TypeScript)

The smallest useful neuron: one `any`-scoped capability.

```
import { Neuron } from '@holokai/neuron-sdk';

const neuron = new Neuron({
  gatewayUrl: process.env.GATEWAY_URL!,           // e.g. https://api.example.com
  neuronId: `worker-${process.env.HOSTNAME}`,      // stable per process
  auth: () => process.env.GATEWAY_TOKEN!,          // sync or async token provider
});

neuron.handle(
  { type: 'core/http', scope: 'any', concurrency: 8 },
  async (input, ctx) => {
    const { url, method = 'GET', headers = {}, body } =
      input as { url: string; method?: string; headers?: Record<string, string>; body?: string };

    // Always thread ctx.signal so the call aborts on cancel/shutdown.
    const resp = await fetch(url, { method, headers, body, signal: ctx.signal });
    return { status: resp.status, body: await resp.text() };
  },
);

await neuron.start(); // opens SSE, registers, heartbeats

process.on('SIGTERM', () => neuron.stop({ drain: true, timeoutMs: 30_000 }));
```

That's a complete neuron. `start()` opens the connection, posts your capabilities, and begins the heartbeat loop. From then on, leases arrive and your handler runs.

The same thing in Python

```
import asyncio, logging
from holokai_neuron_sdk import Capability, HandlerContext, Neuron

async def http_handler(input, ctx: HandlerContext):
    # cooperate with cancellation via ctx.cancelled where you do I/O
    return {"status": 200, "body": "..."}

async def main():
    neuron = Neuron(
        gateway_url="https://api.example.com",
        neuron_id="my-neuron-1",
        auth=lambda: "<bearer token>",
        logger=logging.getLogger("neuron"),
    )
    neuron.register_handler(
        Capability(type="core/http", scope="any", concurrency=8),
        http_handler,
    )
    await neuron.start()
    try:
        await asyncio.Event().wait()
    finally:
        await neuron.stop(drain=True, timeout=30)

asyncio.run(main())
```

Both SDKs speak the identical wire protocol (`packages/neuron-protocol`). Pick the language that fits where your capability lives.

4. The idempotency contract (read this twice)

Leases are at-least-once. A task that completed its side effect but failed to `ack` will run again.

This is not a framework bug — it's the consequence of lease semantics. If your neuron crashes, the network drops, or the gateway restarts after your handler sent the email but before the ack landed, the broker redelivers the task and your handler runs a second time.

The framework does **not** checkpoint mid-task. Idempotency is *your* contract. Concretely:

- **Use capability-native idempotency keys.** Google Drive `requestId`, HTTP `Idempotency-Key`, Stripe idempotency keys, a dedup row keyed on `taskId`.
- **Make the safe operations safe to repeat.** Reads, pure transforms, and upserts are naturally idempotent. Sends, charges, and appends are not — guard them.
- `ctx.task` carries a stable `taskId` you can use as your dedup key when the downstream system has nothing better.

If you take one thing from this guide: **every handler that causes a side effect must be safe to run twice.**

5. Classifying failures correctly

How you signal failure determines whether the task retries, fails the workflow, or is treated as a benign cancel. Getting this wrong means either infinite retries of an unrecoverable task or a permanent failure of something transient.

You want...	TypeScript	Python	Wire kind	Effect
Success	<code>return output</code>	<code>return output</code>	<code>ack</code>	Output validated, workflow advances
Retry (transient)	<code>throw err</code>	<code>raise any exception</code>	<code>nack: retryable</code>	Broker redelivers
Permanent fail	<code>ctx.fail(reason, { code })</code>	<code>ctx.fail(reason, code=...)</code>	<code>nack: terminal</code>	Workflow fails with your reason
Cancelled	<code>throw the AbortError</code>	<code>raise CancelledError</code>	<code>nack: cancelled</code>	Benign, not a failure
Bad shape	<i>(automatic)</i>	<i>(automatic)</i>	<code>nack: schema-mismatch</code>	Structured "expected X got Y"

Rules of thumb:

- **5xx, network blip, rate limit** → **throw/raise**. It might work next time.
- **400, invalid credentials, malformed input you can't fix** → `ctx.fail()`. Retrying is pointless; fail fast with a `code` so the UI can explain it.
- **Cancellation** → **let it propagate**. When `ctx.signal` fires (TS) or `ctx.cancelled` is set (Python), stop promptly and let the `AbortError` / `CancelledError` bubble. The SDK turns it into a benign cancelled `nack`.

```
neuron.handle({ type: 'core/llm', scope: 'any', concurrency: 4 }, async (input, ctx) => {
  try {
    return await llmClient.complete({ ...input, signal: ctx.signal });
  } catch (err) {
    if ((err as Error).name === 'AbortError') throw err;           // cancellation
    if ((err as any).status === 400)
      ctx.fail('invalid LLM request', { code: 'INVALID_REQUEST' }); // terminal
    throw err;                                                     // retryable
  }
});
```

Retry policy itself lives on the workflow (server-side), never in your neuron. Your only job is to classify the outcome.

6. Schemas: where they live and who validates

There is **no global capability registry**. Schemas are owned per-plan:

- The client that initiates a workflow owns the **handler catalog** — the set of capability types available in its context, each with input/output schemas. The desktop knows its MCP tools; the server knows its bundled handlers.
- At plan creation the catalog is posted alongside the goal, the planner emits a typed plan, validates it against the catalog, and **snapshots the catalog with the plan**. Replay and debugging use the schemas valid at plan time.
- At execution, the **SDK** validates: input against `inputSchema` before invoking your handler, output against `outputSchema` before acking. A mismatch becomes a `schema-mismatch` nack automatically — your handler is never called on bad input.

In TypeScript, prefer `defineCapability()` with zod so your handler types are inferred and your refinements run at runtime:

```
import { defineCapability } from '@holokai/neuron-sdk';
import { z } from 'zod';

const pythonCap = defineCapability({
  type: 'core/script.python',
  description: 'Run a Python script in a sandbox',
  input: z.object({ code: z.string(), args: z.record(z.unknown()).optional() }),
  output: z.object({ stdout: z.string(), exitCode: z.number() }),
  scope: 'any',
  concurrency: 4,
});

neuron.handle(pythonCap, async (input, ctx) => {
  // input is typed: { code: string; args?: Record<string, unknown> }
  return { stdout: '...', exitCode: 0 };
});
```

The zod schema runs as the runtime validator (so `.refine()` / `.transform()` work); a JSON Schema projection is shipped to the gateway/planner. The raw `{ inputSchema, outputSchema }` form is still accepted when you don't have zod on hand.

7. The HandlerContext toolkit

Every handler's second argument. Use all of it.

Member	Use it for
<code>ctx.task</code>	Full task metadata, incl. stable <code>taskId</code> for dedup keys
<code>ctx.leaseId</code>	Correlate logs/traces to a specific delivery
<code>ctx.signal</code> (TS) / <code>ctx.cancelled</code> (Py)	Abort I/O on cancel/shutdown — thread it into every fetch/HTTP call
<code>ctx.log</code>	Logger scoped to this lease (pino-shaped in TS)
<code>ctx.progress({ percent, message, data })</code>	Non-blocking UI updates for long tasks
<code>ctx.fail(reason, { code })</code>	Terminal failure (throws internally; unreachable after)

```
ctx.progress({ percent: 50, message: 'downloading' });
ctx.log.info({ fileId }, 'fetched metadata');
const resp = await fetch(url, { signal: ctx.signal }); // aborts cleanly on cancel
```

8. Choosing a transport

The `Neuron` class only ever talks to a `Transport`. Two ship in the box.

`HttpTransport` (default)

SSE inbound, HTTPS POST outbound, exponential-backoff reconnect (500ms → 30s), auth-callback token refresh with one retry on 401. This is what you get by passing `gatewayUrl` + `auth` to `Neuron`. Use it for any neuron talking to a *remote* gateway — servers, on-prem agents, standalone processes.

```
const neuron = new Neuron({ gatewayUrl, neuronId, auth });
```

`IpcTransport` (Electron in-process)

For a renderer-process neuron inside an Electron app that hosts BigBrain in the main process. Leases arrive over Electron IPC, not the network — **no JWT in the renderer**, no reconnect, no keep-alive. The main process attaches auth when it forwards POSTs to the embedded Fastify gateway via `app.inject()`.

```
import { Neuron } from '@holokai/neuron-sdk';
import { IpcTransport } from '@holokai/neuron-sdk/ipc';

const transport = new IpcTransport({ bridge: window.bigbrainNeuron, neuronId });
const neuron = new Neuron({ neuronId, transport });
```

The preload must expose a `NeuronIpcBridge` (`attach / detach / subscribe / invoke`) via `contextBridge` — see the SDK README for the exact wiring. The SDK itself has no Electron dependency.

Decision rule: remote gateway → `HttpTransport`. Same Electron process as the gateway → `IpcTransport`. Anything else (WebSocket, native messaging) → implement the `Transport` interface; the rest of the SDK is unchanged.

9. Concurrency, heartbeats, and graceful shutdown

- **Concurrency** is per capability and maps to AMQP `prefetch_count`. The broker stops sending once you hold N unacked leases — backpressure is handled for you. Change it at runtime with `updateCapability({ type, concurrency })` (e.g. desktop on AC power vs. battery). In-flight tasks finish at the old limit; new slots open at the new one.
- **Heartbeats** post every ~10s with your in-flight lease list. They renew all active lease expiries in one round-trip and let the gateway detect a wedged neuron. **Only running leases appear in the heartbeat** — queued-but-waiting leases are excluded so the reaper doesn't extend their TTL. You don't manage this; the SDK does.
- **Shutdown** should be graceful: `neuron.stop({ drain: true, timeoutMs })` refuses new leases, lets in-flight handlers finish (up to the timeout, then aborts them via the signal), and nacks queued-but-unstarted leases as `retryable` so the broker redelivers immediately. Always wire it to `SIGTERM / SIGINT`.

10. Local development & testing

Run against a local gateway

The gateway is mounted on `apps/api`. Bring up the local stack (see `LOCAL_MODE.md` for `embedded` vs `remote` infra), point your neuron's `gatewayUrl` at it, and supply a dev JWT via your `auth` callback.

The neuron-tester

`apps/neuron-tester` is a reference neuron + harness — the fastest way to see a neuron register, take a lease, and ack against a running gateway. Read its README for the exact run commands; use it as a copyable template for a new neuron.

Unit-testing handlers

A handler is just `(input, ctx) => output`. Test it in isolation by passing a fake `ctx` — a stub `signal / cancelled`, a no-op `progress`, a capturing `log`. No gateway needed. For transport-level tests, the HTTP shape accepts a `fetch` override so you can drive frames synthetically.

Watch the wire

`Neuron` extends an `EventEmitter`. The `frame` event is a firehose of every parsed inbound SSE frame — invaluable for a debug UI or an integration test:

```
neuron.on('frame', (f) => debugLog.append(f));
neuron.once('connection:registered', ({ sessionId, capabilities }) =>
  console.log(`registered ${capabilities} caps as ${sessionId}`));
neuron.on('connection:reconnecting', ({ attempt, delayMs, reason }) =>
  statusBar.show(`reconnecting #${attempt} in ${delayMs}ms (${reason}`));
```

Subscribe *before* `start()` if you care about connection-sequence events.

11. Shipping checklist

Before you call a neuron production-ready, confirm:

- ☐ **neuronId** is stable across restarts (persisted, not random per boot).
- ☐ **Namespace matches identity.** Your JWT is authorized for the `type` prefix you advertise (`core/*` needs a service identity; `desktop/*` / `user/*` need the matching user binding).
- ☐ **Scope is correct.** Anything touching a user-specific resource is `{ onBehalfOf: userId }`, not `'any'`.
- ☐ **Every side-effecting handler is idempotent** (capability-native key or `taskId` dedup).
- ☐ **Failures are classified** — retryable vs. terminal vs. cancelled — and terminal failures carry a `code`.
- ☐ **`ctx.signal / ctx.cancelled` is threaded into every I/O call.**
- ☐ **Schemas are declared** (`inputSchema / outputSchema` or `defineCapability zod`) so bad shapes nack before your handler runs.
- ☐ **auth refreshes on demand** — the SDK caches nothing; your callback returns a fresh token each call and handles 401.
- ☐ **Graceful shutdown** wired to `SIGTERM / SIGINT` with a drain timeout.
- ☐ **Logging** follows [LOGGING_STANDARDS.md](#) (JSON pino, reserved field names, redaction).

12. Troubleshooting quick reference

Symptom	Likely cause
Registration rejected, HTTP 403	JWT not authorized for the namespace, or <code>onBehalfOf</code> doesn't match the user in the JWT
<code>handle()</code> must be called before <code>start()</code>	Register all capabilities before <code>start()</code> ; use <code>updateCapability</code> for runtime changes
<code>start()</code> requires at least one handler	No <code>handle()</code> call was made
Tasks never arrive	Check the <code>registered</code> log for <i>effective</i> capabilities (policy/auth may have filtered one); check <code>neuronId</code> stability; check heartbeats
Same task delivered repeatedly	<code>ack</code> POST failed — usually the output failed <code>outputSchema</code> , or the gateway was restarting
Tasks stuck in <code>assigned</code>	Heartbeats aren't reaching the gateway (SSE dropped, heartbeat POSTs failing, or <code>heartbeatIntervalMs</code> set absurdly high)
401 on every request	<code>auth</code> callback isn't returning a valid/fresh token

For the deeper failure-mode model (disconnect mid-task, capability collision, policy change mid-workflow, gateway restart), see [NEURON_ARCHITECTURE.md § Failure Modes](#).

Where to go next

- **Building a real capability?** Copy `apps/neuron-tester` and the worked examples in the [SDK README](#).
- **Need the internals** (queue topology, lease reaper, policy hooks)? [NEURON_ARCHITECTURE.md](#).
- **Python neuron?** [Neuron SDK — Python](#).
- **Auth model** (service accounts vs. user JWTs, per-task authority)? See the auth section of [NEURON_ARCHITECTURE.md](#).