

mac的终端与远程服务器连接之后，可能由于一段时间没有与服务器进行数据上的交互便断开了连接，现在可以利用如下的方法，保持终端与远程服务器的长期连接。

编辑“ssh_config”文件：

```
sudo vi /etc/ssh/ssh_config
```

在Host * 下面加入：

```
ServerAliveInterval 60
```

最后用 `:wq!` 保存并退出即可。

这句话的含义是，每隔60s客户端向服务器发送一个空包，这样就可以保持连接不被断开了。

```
yu — vim — sudo — 80x24
# $OpenBSD: ssh_config,v 1.30 2016/02/20 23:06:23 sobrado Exp $

# This is the ssh client system-wide configuration file.  See
# ssh_config(5) for more information.  This file provides defaults for
# users, and the values can be changed in per-user configuration files
# or on the command line.

# Configuration data is parsed as follows:
# 1. command line options
# 2. user-specific file
# 3. system-wide file
# Any configuration value is only changed the first time it is set.
# Thus, host-specific definitions should be at the beginning of the
# configuration file, and defaults at the end.

# Site-wide defaults for some commonly used options.  For a comprehensive
# list of available options, their meanings and defaults, please see the
# ssh_config(5) man page.

Host *
    SendEnv LANG LC_*
    ServerAliveInterval 60
# Host *
"/etc/ssh/ssh_config" 53L, 1705C
```