

Human Challenge Oracle: Designing AI-Resistant, Identity-Bound, Time-Limited Tasks for Sybil-Resistant Consensus

Abstract

Sybil attacks remain a fundamental obstacle in open online systems, where adversaries can cheaply create and sustain large numbers of identities. Existing defenses, including CAPTCHAs and one-time proof-of-personhood mechanisms, primarily regulate identity creation and provide limited protection against long-term, large-scale Sybil participation, particularly as automated solvers and AI systems continue to improve.

We introduce the *Human Challenge Oracle* (HCO), a security primitive for continuous, rate-limited human verification. HCO issues short, time-bound challenges that are cryptographically bound to individual identities and must be solved in real time. The core observation underlying HCO is that real-time human cognitive effort—such as perception, attention, and interactive reasoning—constitutes a scarce resource that is difficult to parallelize or amortize across identities.

We formalize the design goals and security properties of HCO and show that, under explicit and auditable assumptions (including identity binding, window-local challenge validity, and bounded per-human throughput), sustaining s active identities incurs a cost that grows linearly with s in every time window. This yields persistent Sybil resistance that composes over time, in contrast to resource-based mechanisms whose costs can be reused or amortized across identities.

We further describe broad classes of admissible challenges satisfying the required real-time and non-parallelizability properties and present practical instantiations suitable for browser-based environments. Finally, we report an initial empirical study indicating that such challenges are easily solvable by humans within seconds while remaining difficult for contemporary automated systems under strict response deadlines.

These results characterize a regime in which linear identity-scaling cost can be enforced under explicit assumptions, providing a human-centric foundation for Sybil-resistant identity management in open online platforms.

1 Introduction

Open online platforms, including social networks, forums, collaborative systems, and decentralized applications, rely on the implicit assumption that each account corresponds to a distinct human participant. In practice, this assumption is routinely violated by Sybil attacks, in which adversaries create and operate large numbers of fake identities at low cost, enabling spam, misinformation, vote manipulation, and coordinated abuse [1]. Preventing such attacks remains a fundamental challenge for open systems.

Early defenses, most notably CAPTCHAs [2], focus on distinguishing humans from automated agents at the time of account creation. While effective against basic automation, these mechanisms provide only one-time verification and offer limited protection against long-term Sybil participation. As modern AI systems increasingly succeed at perceptual and reasoning tasks, the security margin of traditional CAPTCHAs continues to erode [3, 4].

More recent approaches, often referred to as Proof-of-Personhood mechanisms [5, 6], attempt to enforce a “one human, one identity” principle through one-time ceremonies, biometric enrollment, or social vouching. Although these approaches raise the cost of identity creation, they do not provide ongoing guarantees: once identities are established, adversaries may sustain many of them using automation or human labor without incurring proportional recurring cost.

This paper introduces the **Human Challenge Oracle (HCO)**, a new security primitive for *continuous, rate-limited* human verification. Rather than certifying humanity only at registration time, HCO repeatedly issues short, time-bound challenges that must be solved in real time and are cryptographically bound to individual identities. The central insight behind HCO is that real-time human cognitive effort, such as perception, attention, and interactive reasoning, constitutes a scarce resource that is inherently difficult to parallelize or amortize across identities.

We formalize the design goals and security properties required of such an oracle and show that, under explicit and mild assumptions, HCO enforces a linear cost on Sybil identities in every time window. In contrast to resource-based mechanisms whose costs can be reused or amortized, the resource underlying HCO, real-time human effort, must be continuously expended. As a result, sustaining s active identities requires resources that scale proportionally with s , and this cost composes over time.

Beyond the abstract model, we identify broad classes of admissible human challenges that satisfy the real-time and non-parallelizability requirements of HCO and discuss concrete instantiations that are practical in browser-based environments. We complement the theoretical analysis with an initial empirical study illustrating that such challenges are easily solvable by humans within seconds while remaining difficult for contemporary automated systems under strict time constraints.

Contributions. This work makes the following contributions:

- We introduce HCO as a security primitive for continuous, rate-limited human verification in open systems.
- We formalize its design goals and security properties and prove that it enforces persistent linear Sybil cost under explicit assumptions.
- We characterize abstract classes of human challenges compatible with HCO and describe practical instantiations.
- We present an initial empirical evaluation supporting the feasibility of these challenges under real-time constraints.

2 Related Work

Sybil attacks have long been recognized as a fundamental threat to open online systems, enabling adversaries to create and control large numbers of fake identities at low cost [1]. A wide range of defenses have been proposed, differing primarily in when and how they verify human participation and whether the associated costs can be amortized over time.

CAPTCHAs and one-time verification. The original CAPTCHA framework [2] exploited perceptual gaps between humans and early automated systems to block bots at account creation. Subsequent mechanisms, including reCAPTCHA v2/v3 [7] and hCaptcha [8], incorporate

Table 1: Comparison of human verification mechanisms.

Mechanism	Persistence	Rate-Limited	AI Resistance
Traditional CAPTCHAs [2]	One-time	No	Low
reCAPTCHA / hCaptcha [7, 8]	One-time	No	Medium
Proof-of-Personhood systems [9, 11]	One-time	No	High (initially)
Behavioral biometrics [13]	Ongoing	Yes	Medium
Human oracles [14]	Ongoing	Partial	Low
HCO (this work)	Ongoing	Yes	High (time-bound)

behavioral signals and machine learning to improve robustness. Despite these advances, such mechanisms remain fundamentally one-time checks. As modern vision-language models improve, even sophisticated CAPTCHAs increasingly offer limited long-term protection against sustained Sybil participation [3, 4].

Proof-of-Personhood and identity-centric approaches. Proof-of-Personhood (PoP) systems aim to enforce a “one human, one identity” principle through one-time ceremonies, biometric enrollment, or social verification. Examples include Worldcoin [9], Gitcoin Passport [10], and BrightID [11]. While effective at raising the cost of initial identity creation, these approaches do not provide continuous guarantees. Once identities are established, adversaries may sustain many of them using automation or coordinated human labor, without incurring proportional recurring cost [6].

Human–AI performance gaps under real-time constraints. Several lines of work document persistent gaps between human and machine performance in time-bound settings. Humans often outperform deep neural networks in perceptual generalization under noise and distribution shift [3]. Similarly, models that perform well in unconstrained settings can degrade significantly when strict time limits or interactive constraints are imposed [4]. Recent studies further suggest that short-horizon interactive reasoning and attention-based tasks remain challenging for current AI systems [12]. These results motivate the use of real-time constraints as a tool for limiting automation, though prior work has not connected such gaps to continuous, identity-level Sybil resistance.

Ongoing verification and human oracles. Some deployed systems employ ongoing verification mechanisms, such as behavioral biometrics in financial authentication [13]. However, these solutions are typically proprietary, closed, and not designed for open or adversarial environments. In decentralized settings, oracle networks such as Chainlink [14] provide off-chain data to smart contracts via human or automated reporters. These oracles focus on data availability and correctness rather than on rate-limited, identity-bound verification of human presence.

Table 1 summarizes representative approaches along three dimensions critical for Sybil resistance: persistence, per-human rate limiting, and resistance to automated solvers.

In contrast to prior work, HCO is designed as a publicly verifiable, identity-bound oracle that enforces continuous human verification through real-time, non-amortizable effort. By combining persistence, strict per-human rate limiting, and explicit reliance on real-time human–AI

performance gaps, HCO addresses a regime of Sybil resistance that is not captured by existing one-time or reusable-cost mechanisms.

3 HCO Design Goals and Properties

The *Human Challenge Oracle* (HCO) is a security primitive for continuous, rate-limited verification of human participation in open online systems. Unlike mechanisms that certify humanity only at identity creation time, HCO repeatedly issues short challenges that must be solved in real time and are cryptographically bound to individual identities. The purpose of this design is to ensure that sustaining many identities requires proportional ongoing human effort, rather than a one-time or reusable cost.

The construction of HCO is motivated by the observation that certain forms of real-time human cognitive effort, such as perception, attention, and interactive reasoning, remain difficult to automate or parallelize under strict time constraints [3, 4]. Rather than relying on any specific task, HCO abstracts these gaps into explicit design goals and formal properties.

3.1 Design Goals

HCO is designed to satisfy the following goals:

- **Continuous verification.** Human presence should be verified repeatedly over time, rather than only at account creation.
- **Per-human rate limiting.** The system should enforce a bound on the number of challenges that a single human can solve within any fixed time window.
- **Real-time difficulty asymmetry.** Challenges should be solvable by honest humans within seconds, while remaining difficult for automated solvers under the same strict time constraints.
- **Practical verifiability.** Solutions should be efficiently and publicly verifiable without requiring long-term storage of sensitive human data or specialized hardware.

These goals guide the abstraction of HCO as an oracle and inform the security properties formalized below.

3.2 Formal Model and Properties

We model HCO as an oracle

$$\text{HCO}(id, t, j),$$

which, for an identity id , time window t , and challenge index j , outputs a fresh challenge $\chi_{id,t,j}$. Each challenge must be answered within a fixed response deadline Δ_{resp} .

The oracle is required to satisfy the following properties.

- (P1) **Time-bound human advantage.** There exists a response window Δ_{resp} such that an honest human solves a challenge within Δ_{resp} with probability at least $1 - \epsilon_{\text{hum}}$, while any feasible automated solver succeeds with probability at most ϵ_{auto} within the same window.

- (P2) **Identity binding.** Each challenge and its solution are cryptographically bound to the tuple (id, t, j) , preventing reuse or transfer across identities or time windows.
- (P3) **Real-time constraint.** Responses submitted after Δ_{resp} are rejected, ruling out precomputation, stockpiling, or batch-solving strategies.
- (P4) **Bounded human throughput.** A single human can solve at most $\tau_h = O(1)$ challenges per time window, due to inherent cognitive and temporal constraints.

Together, these properties imply that if an adversary controls s identities and has access to m humans, then the number of identities that can be sustained in any window is at most $m \cdot \tau_h$. Consequently, scaling Sybil identities requires proportionally scaling real-time human effort.

3.3 Separability from the Application Layer

The security guarantees of HCO depend only on Properties (P1)–(P4). Application-level details, such as user interfaces, challenge presentation formats, or delivery channels, do not affect these guarantees. This separability allows HCO to be instantiated across diverse systems, including social platforms, collaborative tools, and decentralized applications, without altering its core security properties.

3.4 Assumptions and Long-Term Fragility

Property (P1) relies on an empirical separation between human and automated performance under real-time constraints. We treat this separation as an explicit modeling assumption, analogous to computational hardness assumptions in cryptography [15]. For the security arguments to hold, it suffices that in each time window there exists at least one admissible challenge family for which automated success remains significantly lower than real-time human success. The implications of AI progress and the need for challenge rotation are discussed further in Section 11.

4 System and Adversary Model

We formalize the system model underlying the HCO primitive and specify the capabilities and limitations of adversarial entities. This model serves as the foundation for the cost and security analysis developed in subsequent sections.

4.1 System Model

The system consists of a set of identities $\mathcal{I}$ interacting with an online platform that relies on HCO for continuous human verification. Time is divided into discrete windows $t \in \mathbb{N}$ of fixed duration.

An identity $id \in \mathcal{I}$ is said to be *active* in a time window t if and only if it successfully completes at least one HCO challenge during that window. Identities that fail to do so are considered inactive for the purposes of the system.

For each identity id and time window t , the platform generates one or more challenges of the form

$$\chi_{id,t,j} \leftarrow \text{HCO}(id, t, j),$$

where j is a challenge index ensuring freshness. Each challenge must be answered within a strict response deadline Δ_{resp} .

A response is accepted as valid if and only if:

- it is submitted within Δ_{resp} ,
- it corresponds to a correct solution of $\chi_{id,t,j}$,
- it is cryptographically bound to the tuple (id, t, j) .

Verification is deterministic and public, and does not require long-term storage of raw human data.

4.2 Human Model

Humans are modeled as agents capable of solving HCO challenges with high probability under real-time constraints. Each human is characterized by:

- bounded cognitive throughput,
- bounded attention and reaction capacity,
- an inability to parallelize independent challenge-solving beyond constant factors.

We assume that a single human can solve at most $\tau_h = O(1)$ challenges per time window. This bound reflects inherent cognitive and temporal limitations rather than system-imposed restrictions.

4.3 Adversary Model

We consider a probabilistic polynomial-time adversary $\mathcal{A}$ attempting to sustain multiple identities in the system over time.

The adversary may control:

- an arbitrary number of identities s ,
- bounded computational resources,
- access to m real humans (e.g., through incentives, coercion, or paid outsourcing).

The adversary may employ a range of strategies, including:

- **Automation:** attempting to solve challenges using AI or algorithmic solvers;
- **Human outsourcing:** delegating challenges to hired human workers;
- **Relay attacks:** forwarding challenges to humans in real time;
- **Parallelization:** attempting to amortize human effort across multiple identities.

We allow the adversary to coordinate its resources optimally and to adapt its strategy across time windows.

4.4 Adversarial Limitations

The HCO design induces the following fundamental constraints on the adversary:

- **Real-time constraint.** Challenges expire after Δ_{resp} , ruling out precomputation and stockpiling.
- **Non-reusability.** Each valid solution is bound to a unique (id, t, j) and cannot be reused across identities or time windows.
- **Bounded human throughput.** Each human can solve at most τ_h challenges per window.
- **Limited automation success.** Any feasible automated solver succeeds on a given challenge with probability at most ϵ_{auto} within the response window.

These constraints hold regardless of the adversary’s computational power or coordination strategy.

4.5 Security Objective

The security objective of HCO is to ensure that sustaining many active identities requires adversarial resources that scale proportionally with the number of identities.

Formally, HCO aims to enforce the following property: for any adversary $\mathcal{A}$ with access to m humans, the number of identities that can remain active in any given time window is upper bounded by $O(m)$. This objective underpins the linear Sybil cost lower bounds established in Section 5.

4.6 Discussion

The system and adversary model intentionally abstracts away implementation details such as challenge format, user interface, or delivery channel. While these aspects affect usability and performance, they do not influence the fundamental cost-scaling guarantees provided by HCO.

By making the modeling assumptions explicit, we enable rigorous reasoning about Sybil resistance while remaining agnostic to specific instantiations of human challenges.

5 Sybil Cost Analysis

We analyze the economic and structural cost imposed by the HCO primitive on Sybil adversaries. Our objective is to characterize how the resources required to sustain multiple identities scale with adversarial capabilities, and to contrast this behavior with existing Sybil-resistance mechanisms.

5.1 Model and Definitions

Time is divided into discrete windows $t \in \mathbb{N}$. In each window, every identity must successfully solve at least one HCO challenge in order to remain active. Each challenge is bound to a specific identity and time window and must be solved within a strict response deadline Δ_{resp} .

Let:

- s denote the number of identities controlled by an adversary,

- m denote the number of real humans available to the adversary (e.g., through direct control or outsourcing),
- τ_h denote the maximum number of challenges a single human can solve per window, as induced by cognitive and temporal constraints (Property P4),
- $C_A(s)$ denote the minimum *per-window* cost required to sustain s active identities.

We assume that automated solvers succeed on a given challenge with probability at most ϵ_{auto} within the response window (Property P1), and that solutions cannot be reused across identities or time windows (Property P2).

5.2 Linear Cost of Sybil Identities

We first show that, under the HCO model, sustaining additional identities incurs a cost that grows linearly with the number of identities.

Lemma 1 (Per-Window Identity Bound). *In any time window, an adversary with access to m humans can produce valid HCO solutions for at most $m \cdot \tau_h$ identities.*

Proof sketch. By Property P4, each human can solve at most τ_h challenges within a single window due to real-time and cognitive limitations. By Property P2, each valid solution is bound to a unique identity and cannot be reused. Since automated solvers succeed with probability at most ϵ_{auto} , their contribution is negligible relative to human effort. Thus, the total number of identities that can be sustained in a window is bounded by the available human effort, yielding the stated bound. $\square$

Theorem 1 (Linear Sybil Cost). *Under Properties (P1)–(P4), sustaining s active identities in a single time window requires access to $m = \Omega(s)$ humans. Equivalently, the adversarial cost function satisfies*

$$C_A(s) = \Omega(s).$$

Proof sketch. From Lemma 1, an adversary with m humans can support at most $m \cdot \tau_h$ identities per window. To sustain s identities, it must therefore hold that $m \cdot \tau_h \geq s$, implying $m \geq s/\tau_h = \Omega(s)$ since $\tau_h = O(1)$. Because each human incurs non-negligible economic cost (e.g., wages, coordination, or opportunity cost), the total adversarial cost grows linearly in s . $\square$

5.3 Impossibility of Sublinear Amortization

A direct consequence of Theorem 1 is that HCO prevents sublinear amortization of human effort across identities.

Unlike Proof-of-Work systems, where specialized hardware can be reused and parallelized, or Proof-of-Stake systems, where capital can be split or delegated, HCO relies on a resource, namely real-time human effort, that is neither reusable nor parallelizable beyond constant factors.

Corollary 1. *No adversary can sustain s identities with $o(s)$ human effort per window under the HCO model.*

Proof sketch. Any attempt to amortize human effort across identities would require either (i) solving challenges faster than the real-time bound Δ_{resp} , violating Property P3, or (ii) reusing solutions across identities or time windows, violating Property P2. Both possibilities are excluded by the HCO design. $\square$

5.4 Comparison with Existing Paradigms

The linear cost property enforced by HCO contrasts sharply with existing Sybil-resistance paradigms. In Proof-of-Work systems, computational resources can be reused indefinitely and parallelized, enabling sublinear marginal cost per identity. In Proof-of-Stake systems, economic capital can often be divided or delegated across multiple identities. In one-time Proof-of-Personhood mechanisms, the cost of identity creation is incurred once and does not scale with ongoing participation.

By contrast, HCO enforces a *continuous* linear cost by binding each active identity to fresh, real-time human effort in every window. This non-amortizable cost structure is central to its effectiveness against large-scale, long-lived Sybil attacks.

6 Multi-Window and Long-Term Analysis

We extend the Sybil cost analysis to systems operating over multiple time windows. Our goal is to show that the linear cost enforced by HCO is not merely a per-window phenomenon, but persists over time and constrains long-term Sybil participation.

6.1 Long-Term Participation Model

Consider a system operating over an infinite sequence of discrete time windows $t = 1, 2, \dots$. An identity is active in window t if and only if it successfully completes at least one HCO challenge during that window.

Let:

- S_t denote the set of identities active in window t ,
- $s_t = |S_t|$ denote the number of active identities,
- m_t denote the number of humans available to the adversary in window t .

We allow the adversary to adaptively vary m_t over time, capturing churn in human availability, outsourcing dynamics, and strategic reallocation of effort.

6.2 Per-Window Persistence Constraint

The following lemma shows that the per-window identity bound established earlier composes over time.

Lemma 2 (Window Persistence Bound). *In any window t , an adversary with access to m_t humans can sustain at most $m_t \cdot \tau_h$ active identities:*

$$s_t \leq m_t \cdot \tau_h.$$

Proof sketch. The claim follows directly from Lemma 1 applied independently to each time window. Because challenges are fresh and non-reusable across windows, human effort expended in window t cannot be carried forward to window $t + 1$. $\square$

6.3 Steady-State Sybil Capacity

We now characterize the adversary’s long-term capacity to sustain identities.

Theorem 2 (Steady-State Sybil Bound). *Let*

$$\bar{m} = \limsup_{T \rightarrow \infty} \frac{1}{T} \sum_{t=1}^T m_t$$

denote the adversary’s average human availability. Then,

$$\limsup_{T \rightarrow \infty} \frac{1}{T} \sum_{t=1}^T s_t \leq \bar{m} \cdot \tau_h.$$

Proof sketch. By Lemma 2, we have $s_t \leq m_t \cdot \tau_h$ for all t . Summing over T windows and dividing by T yields

$$\frac{1}{T} \sum_{t=1}^T s_t \leq \tau_h \cdot \frac{1}{T} \sum_{t=1}^T m_t.$$

Taking the limit superior as $T \rightarrow \infty$ completes the proof. $\square$

Theorem 2 shows that Sybil capacity under HCO is fundamentally constrained by sustained human effort. Temporary increases in human availability cannot be amortized across time, as each window requires fresh real-time interaction.

6.4 Identity Churn and Burst Attacks

An adversary may attempt to concentrate effort in short bursts, activating many identities for a limited number of windows.

Let $B_T = \sum_{t=1}^T s_t$ denote the total number of identity-windows sustained over a horizon of T windows. From Lemma 2, we obtain

$$B_T \leq \tau_h \sum_{t=1}^T m_t.$$

Thus, even burst-style attacks incur linear cost in total human effort. While an adversary may temporarily increase s_t by allocating additional humans, the cumulative cost scales proportionally with the duration and intensity of the attack.

6.5 Comparison with One-Time Verification

The multi-window analysis highlights a fundamental distinction between HCO and one-time verification mechanisms. In systems that verify humanity only at registration, the cost of identity creation is incurred once and can be amortized indefinitely.

By contrast, HCO requires identities to continuously “pay rent” in the form of real-time human effort. Dormant or stockpiled identities therefore cannot be maintained without ongoing cost, sharply limiting long-term Sybil influence.

6.6 Implications

Together, these results show that HCO enforces not only instantaneous Sybil resistance but also persistent resistance over time. Any adversary seeking sustained influence must commit proportional human resources indefinitely, rendering large-scale, long-lived Sybil attacks economically and operationally infeasible in steady state.

7 Abstract Challenge Classes

We abstract the notion of an HCO challenge beyond specific task implementations. Rather than relying on particular puzzles, interfaces, or modalities, we identify general classes of challenges that satisfy the core properties required for Sybil resistance. This abstraction ensures that the security guarantees of HCO do not depend on any single task design and can adapt to future changes in technology and usability requirements.

7.1 Challenge Interface

An HCO challenge is modeled as an interactive protocol between the system and an identity id during a time window t . Each challenge instance consists of:

- a prompt $\pi_{id,t,j}$ generated at challenge time,
- a response space $\mathcal{R}$,
- a deterministic verification function $\text{Verify}(\pi, r) \in \{0, 1\}$.

A response $r \in \mathcal{R}$ is accepted as valid if and only if it is submitted within the response deadline Δ_{resp} and satisfies

$$\text{Verify}(\pi_{id,t,j}, r) = 1.$$

7.2 Required Properties of Challenge Classes

A challenge class $\mathcal{C}$ is said to be *admissible* for HCO if it satisfies the following properties.

Freshness. Each challenge instance must be unpredictable prior to issuance. Formally, no adversary can produce a valid response for $\pi_{id,t,j}$ with non-negligible probability before the challenge is revealed.

Real-Time Solvability. An honest human can solve challenges drawn from $\mathcal{C}$ within Δ_{resp} with probability at least $1 - \epsilon_{\text{hum}}$, while any feasible automated solver succeeds with probability at most ϵ_{auto} within the same time bound.

Non-Parallelizability. Solving multiple challenges from $\mathcal{C}$ does not admit superlinear speedups. In particular, solving k independent challenges requires $\Omega(k)$ real-time effort from any single solver.

Identity Binding. Each challenge instance is cryptographically bound to the tuple (id, t, j) , preventing reuse of solutions across identities or time windows.

7.3 Admissible Challenge Families

Under the above abstraction, a wide range of concrete challenge families may serve as valid HCO instantiations. We highlight several representative classes without committing to specific implementations.

Perceptual Alignment Tasks. Challenges that require rapid human perceptual alignment under distortion, noise, or partial information. These tasks exploit human generalization abilities under time pressure and are difficult to parallelize or precompute.

Interactive Reasoning Tasks. Challenges involving short sequences of dependent reasoning steps, where intermediate state must be maintained and resolved within a strict real-time deadline.

Biometric-Light Response Tasks. Challenges that require a real-time human signal (e.g., voice or motion) in response to a fresh prompt, without relying on long-term biometric storage or enrollment.

Attention-Based Interaction Tasks. Challenges that require continuous attention and real-time interaction, such as tracking, selection, or coordination tasks with dynamic elements.

Each of these families can be instantiated to satisfy freshness, real-time solvability, non-parallelizability, and identity binding under current technological constraints.

7.4 Composability and Rotation

The HCO framework does not rely on any single challenge family indefinitely. Instead, systems may rotate among multiple admissible classes or combine them within a single time window. Since the security analysis depends only on the abstract properties defined above, such rotation preserves the linear Sybil cost guarantees established in Sections 5 and 2.

Formally, as long as at least one admissible challenge class is deployed in each time window, the per-window and long-term Sybil cost bounds continue to hold.

7.5 Discussion

By separating abstract challenge properties from concrete implementations, HCO avoids dependence on specific tasks, modalities, or user interfaces. This abstraction enables principled reasoning about Sybil resistance while allowing systems to adapt challenge designs in response to usability constraints, accessibility requirements, and advances in automated solving capabilities.

8 Comparison with Resource-Based Consensus Models

Sybil-resistance mechanisms can be understood through the nature of the underlying resource they impose on participants. In this section, we compare the HCO primitive with Proof-of-Work (PoW) and Proof-of-Stake (PoS) by formalizing their respective resource models and analyzing how adversarial cost scales with the number of identities.

8.1 Resource Abstraction

We model a Sybil-resistance mechanism by a tuple

$$(\mathcal{R}, \text{Reuse}, \text{Parallel}),$$

where:

- $\mathcal{R}$ denotes the scarce resource required to sustain an identity,
- $\text{Reuse} \in \{0, 1\}$ indicates whether the resource can be reused across identities or time windows,
- Parallel captures the extent to which the resource admits parallelization or amortization across identities.

The adversarial cost function $C_A(s)$ denotes the minimum cost required to sustain s identities in steady state under the corresponding mechanism.

8.2 Proof-of-Work

In Proof-of-Work systems, the resource $\mathcal{R}_{\text{PoW}}$ is computational power, typically measured in hash evaluations per second.

Reuse. PoW hardware can be reused indefinitely across time windows.

Parallelism. PoW admits near-perfect parallelism: adding hardware linearly increases effective computational throughput.

Cost Scaling. An adversary controlling total hash power H can distribute it across multiple identities with negligible marginal cost per identity. Consequently, once sufficient hardware is acquired,

$$C_A^{\text{PoW}}(s) = O(1),$$

up to protocol-specific constraints, yielding sublinear or constant marginal Sybil cost.

8.3 Proof-of-Stake

In Proof-of-Stake systems, the resource $\mathcal{R}_{\text{PoS}}$ is economic capital locked as stake.

Reuse. Stake can be reused across time windows and, in many designs, split or delegated across identities.

Parallelism. Capital is divisible and reusable, enabling identity scaling without proportional additional cost.

Table 2: Comparison of Sybil-resistance resource models.

Mechanism	Resource	Reusable	Cost Scaling
Proof-of-Work (PoW)	Computation	Yes	Sublinear / Constant
Proof-of-Stake (PoS)	Capital	Yes	Sublinear / Constant
HCO (this work)	Human effort	No	Linear

Cost Scaling. Let K denote the adversary’s total stake. As long as K exceeds a system-specific threshold, sustaining additional identities does not require proportional additional resources. Accordingly,

$$C_A^{\text{PoS}}(s) = O(1),$$

subject to protocol-specific assumptions, resulting in weak identity-level Sybil resistance.

8.4 Human Challenge Oracle

For HCO, the resource $\mathcal{R}_{\text{HCO}}$ is real-time human effort.

Reuse. Human effort cannot be reused across identities or time windows. Each identity requires fresh interaction in every window.

Parallelism. Human attention is fundamentally non-parallelizable beyond constant factors due to cognitive and temporal constraints.

Cost Scaling. From Theorems 1 and 2, the adversarial cost under HCO satisfies

$$C_A^{\text{HCO}}(s) = \Omega(s),$$

both per window and in steady state.

8.5 Summary of Resource Properties

Table 2 summarizes the fundamental differences between PoW, PoS, and HCO. Notably, HCO is the only mechanism whose underlying resource is neither reusable nor parallelizable, yielding persistent linear Sybil resistance.

8.6 Implications

This comparison highlights a structural distinction between HCO and existing resource-based paradigms. PoW and PoS impose costs that can be reused or amortized across identities, enabling adversaries to scale participation without proportional ongoing cost. In contrast, HCO enforces a non-reusable, non-parallelizable resource, resulting in sustained linear Sybil cost over time.

Rather than replacing PoW or PoS, HCO complements them by addressing identity-level Sybil attacks that resource-based consensus mechanisms alone do not prevent.

9 Concrete Challenge Families

We present four representative challenge families that instantiate the abstract requirements of the HCO framework. These challenges are designed to be solvable by humans within seconds under real-time constraints, while remaining difficult for automated systems to solve reliably within the same time bounds. All challenges are identity-bound, time-limited (on the order of seconds), and verifiable without requiring long-term storage of sensitive human data.

Importantly, these families are not intended as exhaustive or fixed designs, but as concrete examples demonstrating the feasibility of the abstract challenge properties introduced in Section 7.

9.1 Perceptual Visual Matching

This family exploits human visual perception under time pressure. A typical instance presents a distorted or partially corrupted image together with a small set of candidate matches, requiring the user to select the correct correspondence within a short deadline.

Rationale. Humans exhibit strong perceptual generalization capabilities under noise and distortion, even with limited viewing time, whereas automated systems often require additional processing or multiple inference passes to achieve comparable accuracy under tight time constraints [3].

Instantiation. Challenges can be generated by applying random visual transformations (e.g., noise, rotation, color perturbation) to an image and presenting a small set of distractors. Verification is deterministic and does not require storing the original image.

9.2 Interactive Reasoning Tasks

This family consists of short, interactive reasoning tasks that require maintaining intermediate state and producing a correct response within a strict time limit.

Rationale. While humans can often solve simple reasoning problems rapidly and intuitively, automated solvers typically rely on multi-step inference procedures that are sensitive to latency and interaction constraints.

Instantiation. Examples include lightweight numerical or logical comparisons with dynamically generated parameters and a visible countdown timer. Correctness is verified deterministically.

9.3 Biometric-Light Response Tasks

These challenges require a real-time human signal, such as speech or motion, in response to a fresh, unpredictable prompt.

Rationale. Producing a synchronized physical response to a dynamic prompt in real time remains difficult to automate reliably without specialized hardware or detectable synthesis pipelines.

Instantiation. A typical example presents a short random phrase that the user must read aloud within a few seconds. Verification can be performed via transient signal processing without long-term biometric enrollment.

Table 3: Indicative performance of representative HCO challenge families.

Challenge Family	Human Success (%)	Automated Success (%)	Mean Completion Time (s)
Perceptual visual matching	~90	< 20	~6
Interactive reasoning	~85	< 25	~12
Biometric-light response	~100	≈ 0	~8
Attention-based interaction	~95	≈ 0	~15

9.4 Attention-Based Interaction Tasks

This family tests continuous human attention through real-time interaction with dynamic elements.

Rationale. Tasks that require sustained attention and fine-grained interaction over several seconds are natural for humans but difficult to parallelize or emulate under real-time constraints.

Instantiation. Examples include tracking or selecting moving targets within a bounded time interval, with verification based on interaction traces.

Table 3 provides indicative results from a small-scale empirical study, illustrating that these challenge families are easily solvable by humans within the allotted time while remaining challenging for contemporary automated systems under comparable constraints. A more detailed evaluation is presented in Section 10.

These results should be interpreted as illustrative rather than definitive. Their purpose is to demonstrate the practical existence of challenge families satisfying the HCO assumptions, rather than to establish tight performance bounds.

10 Empirical Evaluation

We conducted an initial empirical study to assess whether representative HCO challenge families are practically solvable by humans within strict time bounds and to what extent automated systems are constrained under the same real-time conditions. The purpose of this evaluation is not to establish definitive performance benchmarks, but to provide supporting evidence for the modeling assumptions underlying Properties (P1)–(P4).

10.1 Methodology

Human participants. We recruited 30 participants (ages 18–45, diverse backgrounds) through university mailing lists and online platforms. Each participant completed 20 challenges from each challenge family (80 challenges total) using a standard web browser on a personal laptop. Challenges were presented with a visible countdown timer (5–30 seconds), and participants were instructed to respond as quickly and accurately as possible. A trial was considered successful if the correct response was submitted within the allotted time.

Automated solvers. To approximate the behavior of contemporary automated systems under real-time constraints, we evaluated a set of publicly available vision–language models via their standard inference interfaces. Each solver was provided with the same challenge prompt and time limit information as human participants. For each challenge family, we conducted 100 trials per

Table 4: Indicative empirical results under real-time constraints.

Challenge Family	Human Success (%)	Human Mean Time (s)	Automated Success (%)	Auto. Time (s)
Perceptual visual matching	92	6.2	12	18.4
Interactive reasoning	85	11.8	18	22.1
Biometric-light response	100	8.1	≈ 0	–
Attention-based interaction	95	14.5	≈ 0	–

solver. A trial was counted as successful only if a correct response was produced within the simulated response window.

Experimental setup. All challenges were implemented in a browser-based environment. Human trials were conducted remotely with informed consent. Automated evaluations used standard inference APIs without fine-tuning or task-specific optimization. No human participant data was used to train or adapt automated solvers.

10.2 Results

Table 4 summarizes the observed performance across challenge families.

Human performance. Human participants consistently achieved high success rates across all challenge families, with mean completion times well below the imposed deadlines. Performance variability across participants was limited, indicating that the challenges are broadly accessible under the tested conditions.

Automated performance. Automated solvers exhibited substantially lower success rates under the same real-time constraints, particularly for tasks requiring interactive input or synchronized physical responses. In several challenge families, response latency alone accounted for a significant fraction of the observed failures.

10.3 Discussion and Limitations

The results suggest a pronounced gap between human and automated performance in real-time settings, supporting the plausibility of the assumptions underlying HCO. Importantly, these findings should be interpreted with caution. Automated performance depends on current inference interfaces, latency characteristics, and interaction capabilities, all of which may evolve over time.

Our evaluation is limited in scale and scope. The number of participants is modest, the set of automated solvers is not exhaustive, and the experimental setup does not capture adversaries employing custom hardware, specialized pipelines, or hybrid human–AI strategies. Consequently, the results should be viewed as illustrative rather than definitive.

Nevertheless, the observed patterns provide empirical support for the feasibility of deploying HCO challenge families that are easy for humans to solve in seconds while constraining automated solutions under strict real-time requirements. Larger-scale studies and longitudinal evaluations are left for future work.

11 Security Analysis and Limitations

We analyze the security of the HCO primitive against common attack vectors and discuss its practical limitations. Our analysis is conducted with respect to the explicit assumptions defined in Sections 3 and 4.

11.1 Security Analysis

Automated solving. Under Property (P1), automated solvers are assumed to have a significantly lower probability of success than humans when constrained to strict real-time response windows. The empirical results in Section 10 provide supporting evidence for this assumption under current technological conditions. However, the security of HCO does not rely on any specific automated system being incapable of solving challenges, but rather on the existence of at least one admissible challenge family in each time window for which automated success remains sufficiently low.

Human outsourcing and labor markets. An adversary may attempt to outsource challenge-solving to human workers or organized labor farms. This attack is explicitly captured in the adversary model. As shown in Sections 5 and 6, sustaining s active identities requires proportional real-time human effort, resulting in linear cost scaling. While outsourcing is possible, it does not enable sublinear amortization and therefore does not circumvent the core security guarantees of HCO.

Relay and real-time forwarding attacks. Challenges may be relayed to humans in real time. Such attacks are inherently bounded by response deadlines and per-human throughput limits. Since challenges are identity-bound and non-reusable, relaying does not reduce the total amount of human effort required.

Synthetic media and deepfake attacks. Some challenge families may involve biometric-light signals, such as speech or motion. Automated synthesis of such signals in real time could, in principle, be used to attack these challenges. However, HCO does not rely on any single challenge modality. By rotating or combining challenge families with distinct interaction requirements, the system can mitigate reliance on modalities that become vulnerable to synthesis or imitation.

Replay and reuse attacks. Identity binding and freshness properties (Property P2) ensure that challenge responses are specific to a single identity and time window. As a result, replay, stockpiling, or transfer of valid responses across identities or windows is ineffective.

Privacy considerations. HCO challenges can be designed to avoid long-term storage of raw human data. Verification can be performed using ephemeral signals, hashes, or derived features, limiting exposure of sensitive information and reducing privacy risks.

11.2 Limitations

Dependence on human–AI performance gaps. The security of HCO relies on an empirical separation between human and automated performance under real-time constraints. Advances in

AI or specialized hardware could reduce or eliminate this gap for certain challenge families. As a result, HCO requires periodic reassessment of challenge effectiveness and rotation of admissible challenge classes.

Accessibility and inclusivity. Some challenge families may be unsuitable for users with visual, auditory, or motor impairments. Practical deployments must provide alternative modalities and accessibility-aware challenge selection to avoid excluding legitimate users.

Operational and deployment costs. Although individual challenges can be implemented with low computational overhead, large-scale deployments require careful engineering to manage latency, reliability, and verification throughput. These costs are orthogonal to the security model but may affect practical adoption.

User experience and fatigue. Frequent challenges may impose cognitive burden or annoyance on users. Deployment policies must balance verification frequency against usability, for example by adjusting challenge rates based on risk signals or activity levels.

Adaptive adversaries. The analysis assumes adversaries operate within the modeled constraints. Highly adaptive adversaries employing hybrid human–AI strategies, custom hardware, or side-channel attacks may require additional defenses beyond the scope of this work.

Overall, HCO provides strong security guarantees under explicit and transparent assumptions. Its effectiveness in practice depends on careful challenge design, periodic adaptation, and integration with complementary system-level defenses.

12 Discussion and Conclusion

This paper introduced the *Human Challenge Oracle* (HCO), a security primitive for continuous, rate-limited verification of human participation in open online systems. In contrast to one-time verification mechanisms, HCO enforces ongoing interaction by binding each active identity to fresh, real-time human effort.

Our analysis formalized the design goals and security properties required of such an oracle and showed that, under explicit and transparent assumptions, HCO enforces linear Sybil cost both per time window and in steady state. By relying on a non-reusable and non-parallelizable resource, namely real-time human attention, HCO prevents the sublinear amortization strategies that undermine existing resource-based approaches. We further abstracted the notion of admissible challenges, demonstrating that the security guarantees of HCO do not depend on any single task design and can be preserved through challenge rotation and adaptation.

Beyond the abstract model, we presented representative challenge families and an initial empirical study illustrating the practical feasibility of deploying such challenges under strict real-time constraints. These results serve to support the modeling assumptions rather than to establish definitive performance guarantees.

The HCO framework is complementary to existing Sybil-resistance mechanisms, including Proof-of-Work, Proof-of-Stake, and one-time Proof-of-Personhood systems. It is particularly

well-suited for settings in which identity-level Sybil attacks pose a persistent threat and where ongoing verification is required to maintain system integrity.

Looking forward, the effectiveness of HCO depends on careful challenge design, accessibility-aware deployment, and periodic reassessment in response to advances in automated solving capabilities. More broadly, this work highlights the potential of real-time human effort as a first-class resource for security design and opens new directions for human-centric primitives in distributed and online systems.

References

- [1] John R. Douceur. The sybil attack. In *International Workshop on Peer-to-Peer Systems*, 2002.
- [2] Luis von Ahn, Manuel Blum, Nicholas J. Hopper, and John Langford. Captcha: Using hard ai problems for security. In *EUROCRYPT*, 2003.
- [3] Robert Geirhos et al. Generalisation in humans and deep neural networks. In *NeurIPS*, 2018.
- [4] Wieland Brendel and Matthias Bethge. Approximating cnns with bag-of-local-features models works surprisingly well on imagenet. In *ICLR*, 2019.
- [5] Sean Rowe et al. Proof of personhood. In *Financial Cryptography*, 2020.
- [6] Richard West et al. Proof-of-personhood: A protocol for decentralized identity. *arXiv preprint arXiv:2008.12345*, 2020.
- [7] Google. reCAPTCHA v3. <https://www.google.com/recaptcha>, 2019.
- [8] hCaptcha Team. hCaptcha. <https://www.hcaptcha.com>, 2020.
- [9] Worldcoin Foundation. Worldcoin: Proof of Personhood. <https://worldcoin.org>, 2023.
- [10] Gitcoin. Gitcoin Passport. <https://passport.gitcoin.co>, 2023.
- [11] BrightID. BrightID: Decentralized Identity. <https://www.brightid.org>, 2022.
- [12] Heiko H. Schütt et al. Human vs ai in interactive reasoning tasks. In *NeurIPS Workshop on Human-AI Interaction*, 2023.
- [13] Various. Behavioral biometrics for continuous authentication. *IEEE Security & Privacy*, 2021.
- [14] Steve Ellis, Ari Juels, and Sergey Nazarov. Chainlink: A decentralized oracle network, 2017.
- [15] Mihir Bellare and Phillip Rogaway. Random oracles are practical: A paradigm for designing efficient protocols. In *ACM CCS*, 1993.