project activities and programmes of activities*".* When biennial inspection is chosen a 95 per cent confidence interval and a 10 per cent margin of error shall be achieved for the sampling parameter. On the other hand, when the project proponent chooses to inspect annually, a 90 per cent confidence interval and a 10 per cent margin of error shall be achieved for the sampled parameters. In cases where survey results indicate that 90/10 precision or 95/10 precision are not achieved, the lower bound of the 90 per cent or 95 per cent confidence interval of the parameter value may be chosen as an alternative to repeating the survey efforts to achieve the 90/10 or 95/10 precision.

49. Efficiency of devices may be monitored in a common survey with other monitoring parameters; therefore, a random sub-sample within the common survey can be taken for which stove efficiency is tested, as long as the required precision for stove efficiency is achieved.

6.3. Project activity under a programme of activities

50. The use of this methodology in a project activity under a programme of activities is legitimate if the following leakages are estimated and accounted for, as required on a sample basis using a 90/30 precision for the selection of samples:

    (a) Use of non-renewable woody biomass saved under the project activity to justify the baseline of other CDM project activities can also be a potential source of leakage. If this leakage assessment quantifies a portion of non-renewable woody biomass saved under the project activity that is then used as the baseline of other CDM project activities then $B_{old,i,j}$ is adjusted to account for the quantified leakage;

    (b) Increase in the use of non-renewable woody biomass outside the project boundary to create non-renewable woody biomass baselines can also be a potential source of leakage. If this leakage assessment quantifies an increase in the use of non-renewable woody biomass outside the project boundary then $B_{old,i,j}$ is adjusted to account for the quantified leakage;

    (c) As an alternative to subparagraphs (a) and (b) $B_{old,i,j}$ can be multiplied by a net to gross adjustment factor of 0.95[20] to account for both leakages, in which case surveys are not required.

51. To determine the value of the fraction of non-renewable biomass (fNRB) to be applied in a Component Project Activity (CPA) of a POA, use one of the two options as follows: (a) Conduct local studies to determine the local fNRB value (sub national values)[21] as per the "TOOL30: Calculation of the fraction of non-renewable biomass"; or (b) Use default

[20] Paragraph 41 and paragraph 50 of the methodology allow the use of a net to gross adjustment factor of 0.95 in lieu of conducting a survey to account for leakage emissions. In the case of a CPA opting to apply the adjustment factor, the adjustment factor is only applied once, i.e. either paragraph 41 or paragraph 50(c) is applied. Also, the adjustment factor does not need to be applied twice for option (a) and (b).

[21] If the project boundary covers the entire country, then it is permitted that studies be conducted at the national level to determine the fNRB value under option (a).