# An efficient kinetic modeling in hydrodynamics using the AWBS transport equation

#### Authors<sup>a,1</sup>

<sup>a</sup>Centre Lasers Intenses et Applications, Universite de Bordeaux-CNRS-CEA, UMR 5107, F-33405 Talence, France

#### Abstract

The AWBS Boltzmann transport equation for electrons equipped with a simplified e-e collision operator [1] provides an efficient, yet physically relevant, kinetic extension compared the classical Spitzer-Harm heat flux (SH) based on local approximation and flux-limiting. This classical approach is widely used in plasma kinetics models coupled to hydrodynamics. Even though SH reflects the electron-electron collision effect, the essential physical properties of the electron transport cannot be modeled with an explicitly local model. A simple form of the AWBS model opens a way to couple kinetics to hydrodynamic codes while describing the important physics correctly. Since the electron-electron collision effect becomes especially important in the case of low ion potential, we focus on presenting results related to low Z plasmas.

*Keywords:* kinetics; hydrodynamics; nonlocal electron transport; laser-heated plasmas.

### Contents

2	1	AWBS-P1 modeling of laser heated plasmas		
3		1.1	Model equations	
4		1.2	A consistent treatment of $\tilde{m{E}}$ field $\dots \dots \dots \dots \dots$	
5		1.3	AWBS model analysis	
6	2	Sim	ulation results	2

E-mail address: milan.holec@u-bordeaux.fr

<sup>\*</sup>Corresponding author.

## 1. AWBS-P1 modeling of laser heated plasmas

8 1.1. Model equations

The AWBS electron transport equation reads

$$v\boldsymbol{n}\cdot\nabla f + \tilde{\boldsymbol{E}}\cdot\boldsymbol{n}\frac{\partial f}{\partial v} + \frac{\tilde{\boldsymbol{E}}\cdot\boldsymbol{e}_{\phi} - v\tilde{\boldsymbol{B}}\cdot\boldsymbol{e}_{\theta}}{v}\frac{\partial f}{\partial \phi} = v\nu_{e}\frac{\partial}{\partial v}(f - f_{M}) + (\nu_{ei} + \nu_{e})(f_{0} - f),$$

where  $\nu_e$  is the electron-electron collision frequency,  $\nu_{ei}$  is the electron-ion collision frequency, and  $\nu_{ei} = \bar{Z}\nu_e$ .

In order to eliminate the dimensions of the above transport problem the first-two-moment model based on approximation

$$f = \frac{f_0}{4\pi} + \frac{3}{4\pi} \boldsymbol{n} \cdot \boldsymbol{f_1},$$

can be adopted and reads

$$\nu_{e}v\frac{\partial}{\partial v}\left(f_{0}-\tilde{f}_{M}\right) = v\nabla\cdot\boldsymbol{f_{1}}+\tilde{\boldsymbol{E}}\cdot\frac{\partial\boldsymbol{f_{1}}}{\partial v}+\frac{2}{v}\tilde{\boldsymbol{E}}\cdot\boldsymbol{f_{1}},$$

$$\nu_{e}v\frac{\partial}{\partial v}\boldsymbol{f_{1}}-\nu_{t}\boldsymbol{f_{1}} = v\nabla\cdot\left(\boldsymbol{A}f_{0}\right)+\tilde{\boldsymbol{E}}\cdot\frac{\partial\left(\boldsymbol{A}f_{0}\right)}{\partial v}+\tilde{\boldsymbol{B}}\times\boldsymbol{f_{1}},$$

where  $\tilde{f}_M = 4\pi f_M$  and the closure matrix takes the form

$$\mathbf{A} = \frac{1}{3}\mathbf{I}.$$

Since in the laser heated plasmas the Knudsen number  $Kn = \frac{v_{th}}{\nu_t(v_{th})L} \in$  (0,1), i.e. the collisionality in the kinetics of electrons plays always an important effect for thermal-like particles, the electron distribution function can be treated as out-of-equilibrium approximation

$$f = f_M + \delta f, \tag{1}$$

where the consequent AWBS model reads

$$v\boldsymbol{n}\cdot\nabla(f_{M}+\delta f)+\tilde{\boldsymbol{E}}\cdot\boldsymbol{n}\frac{\partial f_{M}}{\partial v}+\tilde{\boldsymbol{E}}\cdot\boldsymbol{n}\frac{\partial \delta f}{\partial v}+\frac{\tilde{\boldsymbol{E}}\cdot\boldsymbol{e}_{\phi}-v\tilde{\boldsymbol{B}}\cdot\boldsymbol{e}_{\theta}}{v}\frac{\partial \delta f}{\partial \phi}=$$

$$v\nu_{e}\frac{\partial \delta f}{\partial v}+(\nu_{ei}+\nu_{e})(f_{0}-f_{M}-\delta f), \quad (2)$$

or its P1 approximation equivalent

$$f = \frac{4\pi f_M + \delta f_0}{4\pi} + \frac{3}{4\pi} \boldsymbol{n} \cdot \boldsymbol{f_1}.$$
 (3)

where the moment model reads

$$\nu_e v \frac{\partial \delta f_0}{\partial v} = v \nabla \cdot \mathbf{f_1} + \tilde{\mathbf{E}} \cdot \frac{\partial \mathbf{f_1}}{\partial v} + \frac{2}{v} \tilde{\mathbf{E}} \cdot \mathbf{f_1}, \tag{4}$$

$$\nu_{e}v\frac{\partial \mathbf{f_{1}}}{\partial v} - \nu_{t}\mathbf{f_{1}} = \frac{v}{3}\nabla\delta f_{0} + \frac{\tilde{\mathbf{E}}}{3}\frac{\partial\delta f_{0}}{\partial v} + \tilde{\mathbf{B}}\times\mathbf{f_{1}}$$
$$+\frac{v}{3}\nabla\tilde{f}_{M} + \frac{\tilde{\mathbf{E}}}{3}\frac{\partial\tilde{f}_{M}}{\partial v}.$$
 (5)

21 1.2. A consistent treatment of  $ilde{m{E}}$  field

The plasma conditions providing an appropriate electric field are the best expressed via the definition of current

$$\boldsymbol{q}_c(\boldsymbol{x}) = \int_{v} v \boldsymbol{f_1}(\boldsymbol{x}) v^2 \, \mathrm{d}v,$$

which can be directly expressed from (5) as

$$\boldsymbol{q}_{c} = \int_{v} \left( \frac{\nu_{e} v^{2}}{\nu_{t}} \frac{\partial \boldsymbol{f}_{1}}{\partial v} - \frac{v^{2}}{3\nu_{t}} \nabla \left( \tilde{f}_{M} + \delta f_{0} \right) - \frac{v}{3\nu_{t}} \frac{\partial \left( \tilde{f}_{M} + \delta f_{0} \right)}{\partial v} \tilde{\boldsymbol{E}} \right) v^{2} \, \mathrm{d}v, \quad (6)$$

where the  $m{B}$  field and  $m{E}$  field scattering effect (angular) have been omitted.

Then, the current can be easily evaluated based on

$$a_0(\boldsymbol{x}) = \int_v \frac{v}{3\nu_t} \frac{\partial \left(\tilde{f}_M + \delta f_0\right)}{\partial v} (\boldsymbol{x}) v^2 dv,$$

$$\boldsymbol{b}_0(\boldsymbol{x}) = \int_v \left(\frac{v^2}{3\nu_t} \nabla \left(\tilde{f}_M(\boldsymbol{x}) + \delta f_0(\boldsymbol{x})\right) - \frac{\nu_e v^2}{\nu_t} \frac{\partial \boldsymbol{f_1}}{\partial v} (\boldsymbol{x})\right) v^2 dv,$$

27 as the following generalization of the Ohm's law

$$\boldsymbol{q}_c(\boldsymbol{x}) = -\boldsymbol{b}_0(\boldsymbol{x}) - a_0(\boldsymbol{x})\tilde{\boldsymbol{E}}(\boldsymbol{x}),$$

where one needs the actual distribution function f values.

It is straightforward to find the zero current formula for the electric field

$$\tilde{E}(x) = -\frac{b_0(x)}{a_0(x)}. (7)$$

# $^{1}$ 1.3. AWBS model analysis

The AWBS transport equation can be written as the following

$$\left(v\nu_{e} - \tilde{\boldsymbol{E}} \cdot \boldsymbol{n}\right) \frac{\partial \delta f}{\partial v} = v\boldsymbol{n} \cdot \nabla (f_{M} + \delta f) + \tilde{\boldsymbol{E}} \cdot \boldsymbol{n} \frac{\partial f_{M}}{\partial v} + (\nu_{ei} + \nu_{e})(f_{M} + \delta f - f_{0}),$$
(8)

in order to stress the effect of force applied to electrons, i.e. the effect of friction described by  $\nu_e$  and the Lorentz force effect via  $\tilde{E}$ , and their competition.

The same reformulation can be written for the moment AWBS model

$$\frac{\partial \delta f_0}{\partial v} = \frac{1}{\nu_e v} \left( v \nabla \cdot \boldsymbol{f_1} + \tilde{\boldsymbol{E}} \cdot \frac{\partial \boldsymbol{f_1}}{\partial v} \right),$$

$$\nu_e v \frac{\partial \boldsymbol{f_1}}{\partial v} - \nu_t \boldsymbol{f_1} = \frac{v}{3} \nabla \delta f_0 + \frac{\tilde{\boldsymbol{E}}}{3} \frac{\partial \delta f_0}{\partial v} + \frac{v}{3} \nabla \tilde{f}_M + \frac{\tilde{\boldsymbol{E}}}{3} \frac{\partial \tilde{f}_M}{\partial v},$$

36 and it takes the following form

$$\left(\nu_e v \mathbf{I} - \frac{\tilde{\boldsymbol{E}}\tilde{\boldsymbol{E}}}{3\nu_e v}\right) \cdot \frac{\partial \boldsymbol{f_1}}{\partial v} = \frac{v}{3} \nabla \delta f_0 + \frac{\tilde{\boldsymbol{E}}}{3\nu_e} \nabla \cdot \boldsymbol{f_1} + \frac{v}{3} \nabla \tilde{f}_M + \frac{\tilde{\boldsymbol{E}}}{3} \frac{\partial \tilde{f}_M}{\partial v} + \nu_t \boldsymbol{f_1},$$

which is especially instructive in 1D

$$\left(\nu_e v - \frac{\tilde{E}_z^2}{3\nu_e v}\right) \frac{\partial f_{1_z}}{\partial v} = \frac{v}{3} \frac{\partial \delta f_0}{\partial z} + \frac{\tilde{E}_z}{3\nu_e} \frac{\partial f_{1_z}}{\partial z} + \frac{v}{3} \frac{\partial \tilde{f}_M}{\partial z} + \frac{\tilde{E}_z}{3} \frac{\partial \tilde{f}_M}{\partial v} + \nu_t f_{1_z}. \tag{9}$$

## 2. Simulation results

Three cases:

40

41

- constant  $n_e = 5 \times 10^{20}$  [1/cm<sup>3</sup>], constant  $\bar{Z} = 4$ ,  $T_e$  temperature profile taken from IMPACT simulation at 12 ps, see Figure 1
- $n_e, T_e, \bar{Z}$  profiles taken from HYDRA simulation of Gadolinium hohlraum at 10 ps, see Figure 2 and Figure 3
- Detail of distribution function under diffusive conditions of hydrogen raising the question of potentially outstanding properties of AWBS, since the uncorrected AWBS result is very close to KIPP full collision operator, see Figure 4 (consult Eq. (41) in Tzoufras OSHUN JCP 2011)





Figure 1: Philippe's preferred test  $\bar{Z}=4$  at 12 ps.






Figure 2:




Figure 3: Kinetics profiles for max(flux) point and 1605 microns point for the case of 10ps VFP temperature profile, ne and Z Hydra profiles.




Figure 4: KIPP (by Johnathan) vs AWBS using  $\lambda_{ei}^* = \frac{\bar{Z} + 0.24}{\bar{Z} + 4.2} \lambda_{ei}, \bar{Z} = 1, v_{th} = \sqrt{\frac{k_B T_e}{m_e}}$   $f_1^{SH} = -\lambda_{ei}^*(v) \left(\frac{v^2}{2v_{th}^2} - 4\right) \frac{\boldsymbol{n} \cdot \nabla T_e}{T_e} f_M, \quad f_1^{KIPP} = -\lambda_{ei}^*(v) \left(\frac{3}{16} \frac{v^2}{v_{th}^2} - 1 - \frac{3}{2} \frac{v_{th}^2}{v^2}\right) \frac{\boldsymbol{n} \cdot \nabla T_e}{T_e} f_M.$ 




Figure 5: Decelerating (top) vs. accelerating (bottom) computations. Zeroth E field iteration, i.e. no E field effect, of the diffusion regime conditions.

[1] J. R. Albritton, E. A. Williams, I. B. Bernstein, Nonlocal electron heat transport by not quite maxwell-boltzmann distributions, Phys. Rev. Lett.
 57 (1986) 1887–1890.