

Bài 1: Hô Minh Tài

2 method sendMail(), log()

Class mailImpl

Bài làm

```
public interface MailImpl {  
    void method sendMail();  
    void method log();  
}
```

```
Class MailImpl implement Mail {
```

@Override

```
public void sendMail() {  
    System.out.println("Đang gửi mail");  
}
```

@Override

```
public void log() {  
    System.out.println("Đang ghi log");  
}
```

```
Public void static main (String args) {  
    - sendMail - MailImpl  
    - log - MailImpl
```


Q. 9:

```
Public interface Shape {  
    void draw();  
}  
  
Public Rectangle extends implement Shape {  
    @Override  
    public
```

```
Interface Shape {  
    public function get Area();  
    public function get Perimeter();  
    public function get draw();  
}
```

```
Class Rectangle implement Shape {  
    private width,  
    — height;
```

```
    public function  
    Construct (width, height) {  
        this → width = width;  
        this → height = height;  
    }
```


Q.2:

```
Interface Shape {
```

```
    public function getArea ();  
    getPerimeter ();
```

```
}
```

```
Class Rectangle implement Shape {
```

```
    @private  
    private width, height;
```

```
    public function construct (width, height) {
```

```
        this.width = width;
```

```
        this.height = height;
```

```
}
```

```
    public function getArea () {
```

```
        return this.width * this.height;
```

```
}
```

```
    public function getPerimeter () {
```

```
        return (this.width + this.height * 2);
```

```
}
```

```
}
```



```
Class Circle implement shape {  
    @Override  
    private radius ;
```

```
    public construct (radius) ;  
        this.radius = radius ;  
    }
```

```
    public construct get Area () {  
        return 3.14 * this.radius * this.radius ;  
    }
```

```
    public get Perimeter () {  
        return 2 * 3.14 * this.radius ;  
    }  
}
```

```
Class Triangle implement shape {  
    private side ;  
    private perimeter ;
```

```
    public  
    public construct (sides) {  
        this.sides = sides ; this.perimeter = perimeter ;  
    }
```

```
    public construct get Perimeter () {  
        return
```


Bài 3:

Interface PhuongTienDiChuyen {

~~public String Loai PT~~

~~public String Hang SX~~

public String lay ten hang SX

public void bat dau ();

public void tay toa ();

public void duy tat ();

public function lay kien toa ();

}

May Bay Interface May Bay PTren DC {

~~@Override~~
private width, height;

public Construct (width, height) {

this.width = width;

this.height = height;

}

public void cat can () {

System.out.println "Da bay";

return

}


```
public void haCach () {
```

```
    System.out.println "Maybay ha cach" ;
```

```
    return ;
```

```
}
```

```
public double layVanToc () {
```

```
    System.out.println "lay van toc" ;
```

```
    return ;
```

```
}
```

```
public oto implement PlienDC {
```

```
    @Override  
    private void Nieuu ;
```

```
public construct (loaiNieuu) {
```

```
    this.loaiNieuu = vanToc loaiNieuu ;
```

```
}
```

```
public double layVanToc () {
```

```
    System.out.println "lay van toc" ;
```

```
    return ;
```

```
}
```

```
or
```


~~Java~~

Public ~~class~~ Dap implement PTironDC {

~~private~~

public double layvinhoc () {

System.out.print("lấy vin hoc");

return i;

}

Bài 4:

```
class car {  
    protected color;  
    protected speed;  
  
    public function __construct (color, speed) {  
        @override  
        this.color = color;  
        this.colorspeed = speed;  
    }  
  
    public function accelerate () {  
        echo "xét máy hơi" ;  
    }  
  
    public function getcolor () {  
        return this.color;  
    }  
  
    public function getspeed () {  
        return this.speed;  
    }  
}
```

```
class BMW extend car {  
    public function accelerate () {  
        this.speed += 20;  
        echo "Chức hơi hơ len: " ;  
        this.speed . "km/h\n";  
    }  
}
```



```
public function to-string () {  
    return "đây là BMW màu this color";  
}  
}
```

```
public function accelerate () {  
    this.speed += 10;  
    echo "Còn tiếp nữa, " this.speed . "km/h\n";  
}
```


Prac 5

```
Interface Moveable {  
    public & function move Up ();  
    ← move Down ();  
    — move Left ();  
    — move Right ();  
}
```

```
Class Move Point implement Moveable {  
    public x, y, x speed, y speed;  
    public construct (x, y, x speed, y speed) {  
        this.x = x;  
        this.y = y;  
        this.x speed = x speed;  
        this.y speed = y speed;  
    }  
    public construct move Up () {  
        this.y -= this.y speed;  
    }  
    — move Down () {  
        this.y += this.y speed;  
    }  
}
```



```
moveLeft() {
```

```
    this.x -= this.xspeed;
```

```
}
```

```
moveRight() {
```

```
    this.x += this.xspeed;
```

```
}
```

```
public function toString() {
```

```
    return "Point at (" + this.x + ", " + this.y + ")";
```

```
}
```

```
}
```

```
class MovableCircle implements Movable {
```

```
    private radius;
```

```
    private center;
```

```
    public construct (radius, MovePoint center) {
```

```
        this.radius = radius;
```

```
        this.center = center;
```

```
}
```

```
    public construct moveUp() {
```

```
        this.center = moveUp();
```

```
}
```