

0035SAM, froid, juillet  
26 journées, plaque 276 W, 10 critères tenus sur 10

|                                        |                                 |                                        |                                  |                                      |
|----------------------------------------|---------------------------------|----------------------------------------|----------------------------------|--------------------------------------|
| <b>NRMSE</b><br>10,1 % ≤ 11,0          | <b>LDC</b><br>7,3 % ≤ 10,0      | <b>FFT</b><br>16,5 % ≤ 20,0            | <b>Énergie</b><br>+1,7 % ≤ 12,5  | <b>Pointe</b><br>−18,0 % ≤ 18,2      |
| <b>Fact. de charge</b><br>8,2 % ≤ 10,0 | <b>CORR_h</b><br>3,1 % ≤ 5,0    | <b>TVD_h</b><br>9,2 % ≤ 10,4           | <b>EXT_prof</b><br>21,5 % ≤ 25,0 | <b>Heure des pics</b><br>0,0 h ≤ 1,0 |
| <b>Forme 1 h</b><br>5,5 σ > 3,3        | <b>Forme 2 h</b><br>4,2 σ > 3,3 | <b>Pire écart 1 h</b><br>24,2 % ≤ 28,8 | <b>Verdict</b><br>rejetée        | <b>Pointe jour. P95</b><br>74 / 70 W |

