```c
#include <stdio.h>
int main()
{
    int n, m;
    int allocation[10][10], max[10][10], need[10][10];
    int available[10], work[10], finish[10];
    int safe[10], count = 0;

    printf("Enter number of processes: ");
    scanf("%d", &n);

    printf("Enter number of resources: ");
    scanf("%d", &m);

    printf("Enter Allocation Matrix:\n");
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            scanf("%d", &allocation[i][j]);

    printf("Enter Max Matrix:\n");
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            scanf("%d", &max[i][j]);

    printf("Enter Available Resources:\n");
    for (int j = 0; j < m; j++)
        scanf("%d", &available[j]);

    // Calculate Need Matrix
    for (int i = 0; i < n; i++)
        for (int j = 0; j < m; j++)
            need[i][j] = max[i][j] - allocation[i][j];

    // Initialize Work and Finish
    for (int j = 0; j < m; j++)
        work[j] = available[j];

    for (int i = 0; i < n; i++)
        finish[i] = 0;

    // Find Safe Sequence
    while (count < n)
    {
        int found = 0;

        for (int i = 0; i < n; i++)
        {
            if (finish[i] == 0)
            {
                int j;

                for (j = 0; j < m; j++)
                {
```

```
                    if (need[i][j] > work[j])
                        break;
                }

                if (j == m)
                {
                    for (j = 0; j < m; j++)
                        work[j] += allocation[i][j];

                    safe[count++] = i;
                    finish[i] = 1;
                    found = 1;
                }
            }
        }

        if (found == 0)
        {
            printf("System is not in a safe state.\n");
            return 0;
        }
    }

    printf("System is in a safe state.\n");
    printf("Safe Sequence: ");

    for (int i = 0; i < n; i++)
        printf("P%d ", safe[i]);

    printf("\n");

    return 0;
}
```