

BENCH TOP VIBRATION ISOLATOR

COMPACT. STABLE. RELIABLE.

The **μLSI** Bench Top Vibration Isolator is designed to provide a stable and low-vibration platform for precision equipment in research and industrial environments.

KEY FEATURES



LOW RESONANCE FREQUENCY

Vertical resonance frequency ≤ 1 Hz across entire load range

Force Noise Floor : ~ 100 nN



MANUAL LOAD ADJUSTMENT

Simple and precise control using a front adjustment crank



COMPACT DESIGN

Ideal for benchtop applications



RELIABLE PERFORMANCE

Built for demanding laboratory environments



SPECIFICATIONS

Weight	Approximately 21 kg
Dimensions (W × D × H)	426 mm × 426 mm × 240 mm
Payload Range	30 – 50 kg
Performance	- Vertical natural frequency of 1 Hz or less can be achieved over the entire load range. - Horizontal natural frequency is load dependent. 1 Hz or less can be achieved at or near the upper limits of the payload range.

APPLICATIONS

IDEAL FOR



Research & Development



Sensitive Instrumentation



Metrology Equipment



Surface Analysis



Microscopy

CONTACT US

INDUSTRON TECHNICAL SERVICES PVT. LTD.

 info@industronnano.com
 +91 471 278 6500
 401, 4th Floor, Thejaswini Building,
 Technopark, Trivandrum, Kerala,
 India – PIN: 695 581.

INDUSTRON TECHNICAL SERVICES INC.

 Suite 132,
 4445 West 77th Street,
 Edina, MN 55435
 www.industronnano.com



Scan to Explore

 in Action