

Omitted Labels Induce Nontransitive Paradoxes in Causality

Bijan Mazaheri¹ Siddharth Jain² Matthew Cook³ Jehoshua Bruck⁴

¹Dartmouth Engineering ²Ripple Medical Inc. ³University of Groningen ⁴California Institute of Technology




Computing Average Treatment Effect

Original Data:

T	X	Y		Total
		👎	👍	
🚫	😞	3	7	10
	😓	1	0	1
💊	😞	0	1	1
	😓	7	3	10

IPW Data:

T	X	Y		Total
		👎	👍	
🚫	😞	3	7	10
	😓	10×1	10×0	10×1
💊	😞	10×0	10×1	10×1
	😓	7	3	10



$$\Pr(\text{👍} \mid \text{do}(\text{💊})) = \sum_x \Pr(x) \Pr(\text{👍} \mid x, \text{💊})$$

$$= \frac{1/1 + 3/10}{2} = 13/20$$

$$\text{ATE} = \Pr(\text{👍} \mid \text{do}(\text{💊})) - \Pr(\text{👍} \mid \text{do}(\text{🚫})) = 3/10$$

Backdoor Adjustment (Pearl, 2009) Inverse Propensity Weighting (Horvitz and Thompson, 1952)


Simpon's Paradox from Omitted Labels

Original Data:

T	X	Y			Total
		👎	👍	🏠	
🚫	😞	3	7	0	10
	😓	1	0	99	100
💊	😞	0	1	99	100
	😓	7	3	0	10

IPW Weighted Data:


T	X	Y			Total
		👎	👍	🏠	
🚫	😞	10×3	10×7	10×0	10×10
	😓	1	0	99	100
💊	😞	0	1	99	100
	😓	10×7	10×3	10×0	10×10




Context ATE = $\frac{31}{101} - \frac{70}{101} \approx -39\%$

Context ATE = $\frac{13}{20} - \frac{7}{20} = +30\%$


Networks of Experts




Condorcet Paradox in Voting (Nicolas et al., 1785)




Condorcet Paradox in Causality



T	X	Y		
		$y^{(0)}$	$y^{(1)}$	$y^{(2)}$
🚫	$x^{(0)}$	0	1	2
	$x^{(1)}$	2	0	1
	$x^{(2)}$	1	2	0
💊	$x^{(0)}$	2	1	0
	$x^{(1)}$	0	2	1
	$x^{(2)}$	1	0	2




T	X	Y		
		$y^{(0)}$	$y^{(1)}$	$y^{(2)}$
🚫	$x^{(0)}$	0	1	2
	$x^{(1)}$	2	0	1
	$x^{(2)}$	1	2	0
💊	$x^{(0)}$	2	1	0
	$x^{(1)}$	0	2	1
	$x^{(2)}$	1	0	2



T	X	Y		
		$y^{(0)}$	$y^{(1)}$	$y^{(2)}$
🚫	$x^{(0)}$	0	1	2
	$x^{(1)}$	2	0	1
	$x^{(2)}$	1	2	0
💊	$x^{(0)}$	2	1	0
	$x^{(1)}$	0	2	1
	$x^{(2)}$	1	0	2

The Linear Ordering Polytope




$$1 \leq a + b + c \leq 2$$

"Triangle inequality" (Fishburn, 1992), or "curl condition" (Mazaheri, Jain, and Bruck, 2021)


Equivalence

Theorem (Informal)
 Networks of potential outcomes calculated relative to two labels have the same structure as the linear ordering polytope.

Individual voter preferences can be asymptotically ($\varepsilon \rightarrow 0$) approximated as a row of a table.



A table can be decomposed (recursively) into populations of voters.



Thanks

The work for this project was done while Bijan Mazaheri, Siddharth Jain, and Matthew Cook were all at Caltech at the Paradise Lab. Bijan Mazaheri was supported by an Amazon AI4Science fellowship and NSF Graduate Research Fellowship.

References

Castanedo, Federico (2013). ``A review of data fusion techniques'', In: *The scientific world journal* 2013.

Fishburn, Peter C (1992). ``Induced binary probabilities and the linear ordering polytope: A status report'', In: *Mathematical Social Sciences* 23.1, pp. 67–80.

Horvitz, Daniel G and Donovan J Thompson (1952). ``A generalization of sampling without replacement from a finite universe'', In: *Journal of the American statistical Association* 47.260, pp. 663–685.

Mazaheri, Bijan, Siddharth Jain, and Jehoshua Bruck (2021). ``Synthesizing New Expertise via Collaboration'', In: *2021 IEEE International Symposium on Information Theory (ISIT)*, pp. 2447–2452. DOI: 10.1109/ISIT45174.2021.9517822.

Nicolas, Jean Antoine et al. (1785). *Essai sur l'application de l'analyse à la probabilité des décisions rendues à la pluralité des voix*. Par m. le marquis de Condorcet.... de l'Imprimerie Royale.

Pearl, Judea (2009). *Causality*. Cambridge university press.