# 🦓 Zebraw

Zebraw is a lightweight and fast package for displaying code blocks with line numbers in typst, supporting code line highlighting. The term ***Zebraw*** is a combination of ***zebra*** and ***raw***, for the highlighted lines will be displayed in the code block like a zebra lines.

## Starting

Import `zebraw` package by `#import "@preview/zebraw:0.4.1": *` then follow with `#show: zebraw` to start using zebraw in the simplest way. To manually display some specific code blocks in zebraw, you can use `#zebraw()` function:

```
```typ
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

#zebraw(
  ```typ
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
)

#show: zebraw

```typ
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```
```

```
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

```typ
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

```typ
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

## Features

### Line Highlighting

You can highlight specific lines in the code block by passing the `highlight-lines` parameter to the `zebraw` function. The `highlight-lines` parameter can be a single line number or an array of line numbers.

```
#zebraw(
  // Single line number:
  highlight-lines: 2,
  ```typ
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
)

#zebraw(
  // Array of line numbers:
  highlight-lines: (6, 7) + range(9, 15),
  ```typ
```

```
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

```
= Fibonacci sequence
The Fibonacci sequence is defined through the
recurrence relation $F_n = F_(n-1) + F_(n-2)$.
It can also be expressed in _closed form:_

```
```

```
  = Fibonacci sequence
  The Fibonacci sequence is defined through the
  recurrence relation $F_n = F_(n-1) + F_(n-2)$.
  It can also be expressed in _closed form:_

  $ F_n = round(1 / sqrt(5) phi.alt^n), quad
    phi.alt = (1 + sqrt(5)) / 2 $

  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  The first #count numbers of the sequence are:

  #align(center, table(
    columns: count,
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
  ))
  ```
)
```

```typ
$ F_n = round(1 / sqrt(5) phi.alt^n), quad
  phi.alt = (1 + sqrt(5)) / 2 $

#let count = 8
#let nums = range(1, count + 1)
#let fib(n) = (
  if n ≤ 2 { 1 }
  else { fib(n - 1) + fib(n - 2) }
)

The first #count numbers of the sequence are:

#align(center, table(
  columns: count,
  ..nums.map(n => $F_#n$),
  ..nums.map(n => str(fib(n))),
))
```

### Comment

You can add comments to the highlighted lines by passing an array of line numbers and comments to the `highlight-lines` parameter.

```
#zebraw(
  highlight-lines: (
    (1, [The Fibonacci sequence is defined through the recurrence relation $F_n = F_(n-1) + F_(n-2)$\
    It can also be expressed in _closed form:_ $ F_n = round(1 / sqrt(5) phi.alt^n), quad
    phi.alt = (1 + sqrt(5)) / 2 $]),
    // Passing a range of line numbers in the array should begin with `..`
    ..range(9, 14),
    (13, [The first \#count numbers of the sequence.]),
  ),
  ```typ
  = Fibonacci sequence
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
```

**= Fibonacci sequence**

> The Fibonacci sequence is defined through the recurrence relation $F_n = F_{n-1} + F_{n-2}$
> It can also be expressed in closed form:

$$F_n = \left\lfloor \frac{1}{\sqrt{5}} \phi^n \right\rceil, \quad \phi = \frac{1 + \sqrt{5}}{2}$$

```typ
#let count = 8
#let nums = range(1, count + 1)
#let fib(n) = (
  if n ≤ 2 { 1 }
  else { fib(n - 1) + fib(n - 2) }
)

#align(center, table(
  columns: count,
  ..nums.map(n => $F_#n$),
  ..nums.map(n => str(fib(n))),
))
```

> The first #count numbers of the sequence.

```
    columns: count,
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
  ))
  ```
)
```

Comments can begin with a flag, which is `">"` by default. You can change the flag by passing the `comment-flag` parameter to the `zebraw` function:

```
#zebraw(
  highlight-lines: (
    // Comments can only be passed when highlight-lines is an array, so at the end of the single element array, a comma is needed.
    (6, [The Fibonacci sequence is defined through the recurrence relation $F_n = F_(n-1) + F_(n-2)$]),
  ),
  comment-flag: "⇝",
  ```typ
  = Fibonacci sequence
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
    columns: count,
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
  ))
  ```
)
```

```
1  = Fibonacci sequence
2  #let count = 8
3  #let nums = range(1, count + 1)
4  #let fib(n) = (
5    if n ≤ 2 { 1 }
6    else { fib(n - 1) + fib(n - 2) }
     ⇝ The Fibonacci sequence is defined through the recurrence relation $F_n = F_{n-1} + F_{n-2}$
7  )
8
9  #align(center, table(
10   columns: count,
11   ..nums.map(n => $F_#n$),
12   ..nums.map(n => str(fib(n))),
13 ))
```

To disable the flag feature, pass `""` to the `comment-flag` parameter (the indentation of the comment will be disabled as well):

```
#zebraw(
  highlight-lines: (
    (6, [The Fibonacci sequence is defined through the recurrence relation $F_n = F_(n-1) + F_(n-2)$]),
  ),
  comment-flag: "",
  ```typ
  = Fibonacci sequence
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
    columns: count,
```

```
1  = Fibonacci sequence
2  #let count = 8
3  #let nums = range(1, count + 1)
4  #let fib(n) = (
5    if n ≤ 2 { 1 }
6    else { fib(n - 1) + fib(n - 2) }
     The Fibonacci sequence is defined through the recurrence relation $F_n = F_{n-1} + F_{n-2}$
7  )
8
9  #align(center, table(
10   columns: count,
11   ..nums.map(n => $F_#n$),
12   ..nums.map(n => str(fib(n))),
13 ))
```

```
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
  ))
  ```
)
```

### Header and Footer

Usually, the comments passing by a dictionary of line numbers and comments are used to add a header or footer to the code block:

```
#zebraw(
  highlight-lines: (
    (header: [*Fibonacci sequence*]),
    ..range(8, 13),
    // Numbers can be passed as a string in the dictionary, but it's too ugly.
    ("12": [The first \#count numbers of the sequence.]),
    (footer: [The fibonacci sequence is defined through the recurrence relation $F_n = F_(n-1) + F_(n-2)$]),
  ),
  ```typ
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
    columns: count,
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
  ))
  ```
)
```

**Fibonacci sequence**

```
1  #let count = 8
2  #let nums = range(1, count + 1)
3  #let fib(n) = (
4    if n ≤ 2 { 1 }
5    else { fib(n - 1) + fib(n - 2) }
6  )
7
8  #align(center, table(
9    columns: count,
10   ..nums.map(n => $F_#n$),
11   ..nums.map(n => str(fib(n))),
12 ))
```

> The first #count numbers of the sequence.

The fibonacci sequence is defined through the recurrence relation $F_n = F_{n-1} + F_{n-2}$

Or you can use `header` and `footer` parameters to add a header or footer to the code block:

```
#zebraw(
  highlight-lines: (
    ..range(8, 13),
    (12, [The first \#count numbers of the sequence.]),
  ),
  header: [*Fibonacci sequence*],
  ```typ
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
    columns: count,
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
```

**Fibonacci sequence**

```
1  #let count = 8
2  #let nums = range(1, count + 1)
3  #let fib(n) = (
4    if n ≤ 2 { 1 }
5    else { fib(n - 1) + fib(n - 2) }
6  )
7
8  #align(center, table(
9    columns: count,
10   ..nums.map(n => $F_#n$),
11   ..nums.map(n => str(fib(n))),
12 ))
```

> The first #count numbers of the sequence.

```
  ))
  ```
    ,
  footer: [The fibonacci sequence is
defined through the recurrence relation
$F_n = F_(n-1) + F_(n-2)$],
)
```

**Fibonacci sequence**

The fibonacci sequence is defined through the recurrence relation $F_n = F_{n-1} + F_{n-2}$

### Language Tab

If `lang` is set to `true`, then there will be a language tab on the top right corner of the code block:

```
#zebraw(
  lang: true,
  ```typst
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
)
```

typst

```
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

### Copyable

Line numbers will not be selected when selecting exported code in one page.

`copyable: false`

```
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

`copyable: true`

```
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

### Theme

PRs are welcome!

```
#show: zebraw-init.with(..zebraw-
themes.zebra, lang: false)
#show: zebraw

```rust
pub fn fibonacci_reccursive(n: i32) →
u64 {
    if n < 0 {
        panic!("{} is negative!", n);
    }
    match n {
        0 ⇒ panic!("zero is not a right
argument to fibonacci_reccursive()!"),
        1 | 2 ⇒ 1,
        3 ⇒ 2,
        _ ⇒ fibonacci_reccursive(n - 1)
+ fibonacci_reccursive(n - 2),
    }
}
```
```

```
pub fn fibonacci_reccursive(n:
i32) → u64 {
    if n < 0 {
        panic!("{} is negative!",
n);
    }
    match n {
        0 ⇒ panic!("zero is not a
right argument to
fibonacci_reccursive()!"),
        1 | 2 ⇒ 1,
        3 ⇒ 2,
        _ ⇒
fibonacci_reccursive(n - 1) +
fibonacci_reccursive(n - 2),
    }
}
```

```
#show: zebraw-init.with(..zebraw-
themes.zebra-reverse, lang: false)
#show: zebraw
```

```
pub fn fibonacci_reccursive(n:
i32) → u64 {
```
```

```
```rust
pub fn fibonacci_reccursive(n: i32) →
u64 {
    if n < 0 {
        panic!("{} is negative!", n);
    }
    match n {
        0 ⇒ panic!("zero is not a right
argument to fibonacci_reccursive()!"),
        1 | 2 ⇒ 1,
        3 ⇒ 2,
        _ ⇒ fibonacci_reccursive(n - 1)
+ fibonacci_reccursive(n - 2),
    }
}
```
```

```
    if n < 0 {
        panic!("{} is negative!", n);
    }
    match n {
        0 ⇒ panic!("zero is not a right argument to fibonacci_reccursive()!"),
        1 | 2 ⇒ 1,
        3 ⇒ 2,
        _ ⇒ fibonacci_reccursive(n - 1) + fibonacci_reccursive(n - 2),
    }
}
```

## Customization

There are 3 ways to customize code blocks in your document:

- Manually render some specific blocks by `#zebraw()` function and passing parameters to it.
- By passing parameters to `#show: zebraw.with()` will affect every raw block after the `#show` rule, **except** blocks created manually by `#zebraw()` function.
- By passing parameters to `#show: zebraw-init.with()` will affect every raw block after the `#show` rule, **including** blocks created manually by `#zebraw()` function. By using `zebraw-init` without any parameters, the values will be reset to default.

### Inset

Customize the inset of each line by passing a `dictionary` to the `inset` parameter:

```
#zebraw(
  inset: (top: 6pt, bottom: 6pt),
  ```typ
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
)
```

```
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

### Colors

Customize the background color by passing a `color` or an `array` of `colors` to the `background-color` parameter.

```
#zebraw(
  background-color: luma(235),
  ```typ
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
    ,
)

#zebraw(
  background-color: (luma(235),
```

```
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

```
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

```
luma(245), luma(255), luma(245)),
  ```typ
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
    ,
)
```

Customize the highlight color by passing a `color` to the `highlight-color` parameter:

```
#zebraw(
  highlight-lines: 1,
  highlight-color: blue.lighten(90%),
  ```text
  I'm so blue!
              -- George III
  ```
    ,
)
```

```
1 I'm so blue!
2               -- George III
```

Customize the comments' background color by passing a `color` to the `comment-color` parameter:

```
#zebraw(
  highlight-lines: (
    (2, "auto indent!"),
  ),
  comment-color: yellow.lighten(90%),
  ```text
  I'm so blue!
              -- George III
  I'm not.
              -- Hamilton
  ```
    ,
)
```

```
1 I'm so blue!
2               -- George III
                > auto indent!
3 I'm not.
4               -- Hamilton
```

Customize the language tab's background color by passing a `color` to the `lang-color` parameter.

```
#zebraw(
  lang: true,
  lang-color: teal,
  ```typst
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
)
```

typst

```
1 #grid(
2   columns: (1fr, 1fr),
3   [Hello], [world!],
4 )
```

**Font**

To customize the arguments of comments' font and the language tab's font, pass a dictionary to `comment-font-args` parameter and `lang-font-args` parameter.

Language tab will be rendered as comments if nothing is passed.

```
#zebraw(
  highlight-lines: (
    (2, "columns ... "),
  ),
```

typst

```
1 #grid(
2   columns: (1fr, 1fr),
```

```
  lang: true,
  comment-color: white,
  comment-font-args: (
    font: "IBM Plex Sans",
    style: "italic"
  ),
  ```typst
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
)
```

```
    > columns...
3   [Hello], [world!],
4 )
```

```
#zebraw(
  highlight-lines: (
    (2, "columns ... "),
  ),
  lang: true,
  lang-color: eastern,
  lang-font-args: (
    font: "libertinus serif",
    weight: "bold",
    fill: white,
  ),
  comment-font-args: (
    font: "IBM Plex Sans",
    style: "italic"
  ),
  ```typst
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
)
```

typst

```
1 #grid(
2   columns: (1fr, 1fr),
    > columns...
3   [Hello], [world!],
4 )
```

**Extend**

Extend at vertical is enabled at default. When there's header or footer it will be automatically disabled.

```
#zebraw(
  extend: false,
  ```typst
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
)
```

```
1 #grid(
2   columns: (1fr, 1fr),
3   [Hello], [world!],
4 )
```

## Documentation

The default value of most parameters are `none` for it will use the default value in `zebraw-init`.

- zebraw-init()
- zebraw()

**zebraw-init**

Initialize the `zebraw` block in global.

**Parameters**

```
zebraw-init(
  inset: dictionary,
  background-color: color array,
  highlight-color: color,
  comment-color: color,
  lang-color: color,
  comment-flag: string content,
  lang: boolean,
  comment-font-args: dictionary,
  lang-font-args: dictionary,
  extend: boolean,
  body: content
) -> content
```

**inset** `dictionary`

The inset of each line.

Default: `(top: 0.34em, right: 0.34em, bottom: 0.34em, left: 0.34em)`

**background-color** `color` or `array`

The background color of the block and normal lines.

Default: `luma(245)`

**highlight-color** `color`

The background color of the highlighted lines.

Default: `rgb("#94e2d5").lighten(70%)`

**comment-color** `color`

The background color of the comments. When it's set to `none`, it will be rendered in a lightened `highlight-color`.

Default: `none`

**lang-color** `color`

The background color of the language tab. The color is set to `none` at default and it will be rendered in comments' color.

Default: `none`

**comment-flag** `string` or `content`

The flag at the beginning of comments.

Default: `">"`

**lang** `boolean`

Whether to show the language tab.

Default: `true`

**comment-font-args** `dictionary`

The arguments passed to comments' font.

Default: `(:)`

**lang-font-args** `dictionary`

The arguments passed to the language tab's font.

Default: `(:)`

**extend** `boolean`

Whether to extend the vertical spacing.

Default: `true`

**body** `content`

The body

**zebraw**

Block of code with highlighted lines and comments.

**Parameters**

```
zebraw(
  highlight-lines: array int,
  header: string content,
  footer: string content,
  inset: dictionary,
  background-color: color array,
  highlight-color: color,
  comment-color: color,
  lang-color: color,
  comment-flag: string content,
  lang: boolean,
  comment-font-args: dictionary,
  lang-font-args: dictionary,
  extend: boolean,
  body: content
) -> content
```

### highlight-lines `array` or `int`

Lines to highlight or comments to show.

```
#zebraw(
  highlight-lines: range(3, 7),
  header: [*Fibonacci sequence*],
  ```typst
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
    columns: count,
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
  ))
  ```
  ,
  footer: [The fibonacci sequence is
defined through the recurrence relation
$F_n = F_(n-1) + F_(n-2)$],
)
```

**Fibonacci sequence**

```
1 #let count = 8
2 #let nums = range(1, count + 1)
3 #let fib(n) = (
4   if n ≤ 2 { 1 }
5   else { fib(n - 1) + fib(n -
  2) }
6 )
7
8 #align(center, table(
9   columns: count,
10   ..nums.map(n => $F_#n$),
11   ..nums.map(n => str(fib(n))),
12 ))
```

The fibonacci sequence is defined through the recurrence relation $F_n = F_{n-1} + F_{n-2}$

Default: ( )

### header `string` or `content`

The header of the code block.

Default: none

**footer** `string` or `content`

The footer of the code block.

Default: `none`

**inset** `dictionary`

The inset of each line.

```
#zebraw(
  inset: (top: 6pt, bottom: 6pt),
  ```typst
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
    columns: count,
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
  ))
  ```
    ,
)
```

```
#let count = 8
#let nums = range(1, count + 1)
#let fib(n) = (
  if n ≤ 2 { 1 }
  else { fib(n - 1) + fib(n - 2) }
)

#align(center, table(
  columns: count,
  ..nums.map(n => $F_#n$),
  ..nums.map(n => str(fib(n))),
))
```

Default: `none`

**background-color** `color` or `array`

The background color of the block and normal lines.

```
#zebraw(
  background-color: (luma(240),
luma(245), luma(250), luma(245)),
  ```typst
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
    columns: count,
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
  ))
  ```
    ,
)
```

```typst
#let count = 8
#let nums = range(1, count + 1)
#let fib(n) = (
  if n ≤ 2 { 1 }
  else { fib(n - 1) + fib(n - 2) }
)

#align(center, table(
  columns: count,
  ..nums.map(n => $F_#n$),
  ..nums.map(n => str(fib(n))),
))
```

Default: none

**highlight-color** `color`

The background color of the highlighted lines.

Default: none

### comment-color `color`

The background color of the comments. The color is set to `none` at default and it will be rendered in a lightened `highlight-color`.

```
#zebraw(
  highlight-color: yellow.lighten(80%),
  comment-color: yellow.lighten(90%),
  highlight-lines: (
    (1, [The Fibonacci sequence is
defined through the recurrence relation
$F_n = F_(n-1) + F_(n-2)$]),
    ..range(9, 14),
    (13, [The first \#count numbers of
the sequence.]),
  ),
  ```typ
  = Fibonacci sequence
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
    columns: count,
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
  ))
  ```
)
```

```typ
= Fibonacci sequence
#let count = 8
#let nums = range(1, count + 1)
#let fib(n) = (
  if n ≤ 2 { 1 }
  else { fib(n - 1) + fib(n - 2) }
)

#align(center, table(
  columns: count,
  ..nums.map(n => $F_#n$),
  ..nums.map(n => str(fib(n))),
))
```

> The Fibonacci sequence is defined through the recurrence relation $F_n = F_{n-1} + F_{n-2}$

> The first #count numbers of the sequence.

Default: `none`

### lang-color `color`

The background color of the language tab. The color is set to `none` at default and it will be rendered in comments' color.

```
#zebraw(
  lang: true,
  lang-color: eastern,
  lang-font-args: (
    font: "libertinus serif",
    weight: "bold",
    fill: white
  ),
  ```typst
  #grid(
    columns: (1fr, 1fr),
    [Hello], [world!],
  )
  ```
)
```

typst

```typst
#grid(
  columns: (1fr, 1fr),
  [Hello], [world!],
)
```

Default: `none`

**comment-flag** `string` or `content`

The flag at the beginning of comments. The indentation of codes will be rendered before the flag. When the flag is set to `""`, the indentation before the flag will be disabled as well.

```
#zebraw(
  comment-flag: "",
  highlight-lines: (
    (1, [The Fibonacci sequence is
defined through the recurrence relation
$F_n = F_(n-1) + F_(n-2)$]),
    ..range(9, 14),
    (13, [The first \#count numbers of
the sequence.]),
  ),
  ```typ
  = Fibonacci sequence
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
    columns: count,
    ..nums.map(n ⇒ $F_#n$),
    ..nums.map(n ⇒ str(fib(n))),
  ))
  ```
)
```

```
1 = Fibonacci sequence
  The Fibonacci sequence is
  defined through the recurrence
  relation F_n = F_{n-1} + F_{n-2}
2 #let count = 8
3 #let nums = range(1, count + 1)
4 #let fib(n) = (
5   if n ≤ 2 { 1 }
6   else { fib(n - 1) + fib(n -
  2) }
7 )
8
9 #align(center, table(
10   columns: count,
11   ..nums.map(n ⇒ $F_#n$),
12   ..nums.map(n ⇒ str(fib(n))),
13 ))
  The first #count numbers of the
  sequence.
```

Default: none

**lang** `boolean`

Whether to show the language tab on the top-right corner of the code block.

```
#zebraw(
  lang: true,
  ```typ
  #grid(
    columns: (1fr, 1fr),
    [Hello,], [world!],
  )
  ```
)
```

typ

```
1 #grid(
2   columns: (1fr, 1fr),
3   [Hello,], [world!],
4 )
```

Default: none

**comment-font-args** `dictionary`

The arguments passed to comments' font.

Default: none

**lang-font-args** `dictionary`

The arguments passed to the language tab's font.

```
#zebraw(
  lang: true,
  comment-font-args: (font: "IBM Plex Serif", style: "italic"),
  lang-font-args: (font: "IBM Plex Sans", weight: "bold"),
  highlight-lines: (
    (1, [The Fibonacci sequence is defined through the recurrence relation $F_n = F_(n-1) + F_(n-2)$]),
    ..range(9, 14),
    (13, [The first \#count numbers of the sequence.]),
  ),
  ```typ
  = Fibonacci sequence
  #let count = 8
  #let nums = range(1, count + 1)
  #let fib(n) = (
    if n ≤ 2 { 1 }
    else { fib(n - 1) + fib(n - 2) }
  )

  #align(center, table(
    columns: count,
    ..nums.map(n => $F_#n$),
    ..nums.map(n => str(fib(n))),
  ))
  ```
)
```

typ

```
= Fibonacci sequence
```

> *The Fibonacci sequence is defined through the recurrence relation $F_n = F_{n-1} + F_{n-2}$*

```
#let count = 8
#let nums = range(1, count + 1)
#let fib(n) = (
  if n ≤ 2 { 1 }
  else { fib(n - 1) + fib(n - 2) }
)

#align(center, table(
  columns: count,
  ..nums.map(n => $F_#n$),
  ..nums.map(n => str(fib(n))),
))
```

> *The first #count numbers of the sequence.*

Default: `none`

**extend** `boolean`

Whether to extend the vertical spacing.

```
#zebraw(
  extend: false,
  ```typ
  #grid(
    columns: (1fr, 1fr),
    [Hello,], [world!],
  )
  ```
)
```

```
#grid(
  columns: (1fr, 1fr),
  [Hello,], [world!],
)
```

Default: `none`

**body** `content`

The body.

## Example

rust

Calculate Fibonacci number using reccursive function

```rust
pub fn fibonacci_reccursive(n: i32) -> u64 {
    if n < 0 {
        panic!("{} is negative!", n);
        > to avoid negative numbers
    }
    match n {
        0 => panic!("zero is not a right argument to fibonacci_reccursive()!"),
        1 | 2 => 1,
        3 => 2,
        _ => fibonacci_reccursive(n - 1) + fibonacci_reccursive(n - 2),
        > 50 => 12586269025
    }
}
```