

# AFB Gaming System Integration API Document

| Version | Desc       | Date       |
|---------|------------|------------|
| V 1.00  | Start      | 2025.02.28 |
| V 1.10  | Statistics | 2025.03.27 |
|         |            |            |
|         |            |            |
|         |            |            |
|         |            |            |
|         |            |            |
|         |            |            |
|         |            |            |
|         |            |            |

# Chapters

|                                              |           |
|----------------------------------------------|-----------|
| <b>1. About API Call.....</b>                | <b>4</b>  |
| 1.1 Game Type.....                           | 4         |
| 1.2 Request Parameters.....                  | 4         |
| 1.3 Response Parameters.....                 | 4         |
| 1.4 The domain of API Call.....              | 4         |
| 1.5 Timeout.....                             | 4         |
| <b>2. Request verification.....</b>          | <b>5</b>  |
| 2.1 Site ID.....                             | 5         |
| 2.1 Timestamp Verification.....              | 5         |
| 2.2 Hash Verification.....                   | 5         |
| 2.3 Signature Verification.....              | 5         |
| 2.4 Complete Validation Example.....         | 6         |
| 2.5 Curl command.....                        | 6         |
| <b>3. New Account.....</b>                   | <b>7</b>  |
| <b>4. Get Launcher Url.....</b>              | <b>8</b>  |
| <b>5. Seamless API.....</b>                  | <b>9</b>  |
| 5.1 Get Balance.....                         | 9         |
| 5.2 Bet.....                                 | 10        |
| 5.3 Paid.....                                | 11        |
| 5.4 Bet Paid.....                            | 13        |
| 5.5 Refund.....                              | 14        |
| 5.6 Game Open Notify(optional).....          | 15        |
| 5.7 Game Close Notify(optional).....         | 16        |
| 5.8 Bonus Status Notify(optional).....       | 16        |
| <b>6. Transfer API.....</b>                  | <b>17</b> |
| 6.1 Deposit.....                             | 17        |
| 6.2 Withdraw.....                            | 18        |
| 6.3 Balance.....                             | 19        |
| 6.4 Check Transaction.....                   | 19        |
| <b>7. Block.....</b>                         | <b>20</b> |
| <b>8. Unblock.....</b>                       | <b>21</b> |
| <b>9. Bet Records.....</b>                   | <b>21</b> |
| <b>10. Fishing Transfer Records.....</b>     | <b>23</b> |
| <b>11. Game List.....</b>                    | <b>24</b> |
| <b>12. Free Rounds Bonus(optional).....</b>  | <b>25</b> |
| 12.1 Set.....                                | 25        |
| 12.2 Cancel.....                             | 26        |
| 12.3 Get Game List.....                      | 27        |
| 12.4 Get Account.....                        | 28        |
| <b>13. Unfinished Games.....</b>             | <b>28</b> |
| <b>14. Get Record by Transaction ID.....</b> | <b>29</b> |

- 15. Statistics..... 30**
  - 15.1 pullStatisticsBetMinute..... 30
  - 15.2 pullStatisticsBetDay..... 32
  - 15.3 pullStatisticsAccount.....33
- 16. Support Language List..... 36**
- 17. Support Currency List..... 36**

# 1. About API Call

## 1.1 Game Type

AFB Gaming now has types of games: Slots/ BlockChain/Finishing.

## 1.2 Request Parameters

This API uses HTTP form submission. The request will be sent according to the following content format:

Content-Type: application/json

## 1.3 Response Parameters

The API returns the result in JSON format. For successful and failed API requests, the operator needs to return an API response with HTTP status code 200.

The API uses the global JSON format for all API methods. The content types are as follows:

Content-Type: application/json

## 1.4 The domain of API Call

For stage:

<https://testapi.afbgaming.net/api/integration>

For prod:

<https://api.afbgaming.net/api/integration>

## 1.5 Timeout

Regarding the API request response time, for bet requests, the server should return within 10 seconds, and for requests to obtain a bet list, the result should be returned within 60 seconds

## 2. Request verification

### 2.1 Site ID

Each request needs to transmit the site ID

Example:

X-Site-ID: 11111111

### 2.1 Timestamp Verification

Each request will transmit the timestamp HTTP header and pass in the current timestamp in Unix time seconds. For the test system, the timestamp will not be verified to facilitate system integration. For the production system, the timestamp will be checked and the error will not exceed 60 seconds.

Example:

X-Timestamp: 1733223286

### 2.2 Hash Verification

The hash check uses the sha256 algorithm to calculate the transmitted HTTP body content, get the hex value, and put it into the HTTP header.

Example:

body:

```
"{"gameCode\\":\\"kingArthur\\",\\"key\\":\\"wzK982mA00vHrP3xtT6lMCjfea7bJdSL\\",\\"method\\":\\"getBalance\\",\\"username\\":\\"V3-TEST\\"}"
```

X-Content-Hash:

adfb5eba9ff1c31391c089c198d3170a775a0f7bc208f91111cec2122b6b49ae

### 2.3 Signature Verification

The signature verification uses the HMAC-SHA256 algorithm, where the secret is issued by AFB Gaming and the content is Host+SiteID+Timestamp+ContentHash

hmac-sha256({secret}, {Host}-{X-Site-ID}-{X-Timestamp}-{X-Content-Hash})

Example:

X-Signature:

44647fc73d1c91e2e7b0d590f3732dd3ead126faf0d904cb9d7072c0e2c081e7

## 2.4 Complete Validation Example

AFB Gaming issued:

Site ID: 11111111

Secret: ZL7PBTUr06wo9Z8GttQDCTYLKwGCRIBO

Http request header verification:

Host: testapi.afbgaming.net

X-Site-ID: 11111111

X-Timestamp: 1733223286

X-Content-Hash:

93f62b4f43b47d07c09ca9882c8ffe2ed83c4145a7f06c70d48f50556c2d7840

X-Signature:

44647fc73d1c91e2e7b0d590f3732dd3ead126faf0d904cb9d7072c0e2c081e7

## 2.5 Curl command

```
curl -X POST \
  "https://testapi.afbgaming.net/api/integration" \
  -H "Content-Type: application/json" \
  -H "X-Site-ID: 11111111" \
  -H "X-Timestamp: 1733223286" \
  -H "X-Content-Hash:
93f62b4f43b47d07c09ca9882c8ffe2ed83c4145a7f06c70d48f50556c2d7840" \
  -H "X-Signature:
44647fc73d1c91e2e7b0d590f3732dd3ead126faf0d904cb9d7072c0e2c081e7" \
  -d
{"gameCode\":\"kingArthur\",\"key\":\"wzK982mA00vHrP3xtT6lMCjfea7bJd
SL\",\"method\":\"getBalance\",\"username\":\"V3-TEST\"}"
```

### 3. New Account

Optional, Create a new Account, Agent Call AFB Gaming

This API is optional. If you have not created an Account, you need to pass in the currency when calling getLauncherUrl.

#### 1) Request

| Name     | Type   | Description                                                                                                                |
|----------|--------|----------------------------------------------------------------------------------------------------------------------------|
| method   | string | newAccount                                                                                                                 |
| account  | string | account name<br>Alphanumeric characters, underscores,<br>no spaces or special characters,<br>maximum length 100 characters |
| nick     | string | nick name                                                                                                                  |
| currency | string | upper case, USD PHP IDR AUD EUR etc.                                                                                       |
| agent_id | int    | Optional, the ID of subagent                                                                                               |

#### 2) Response

| Name    | Type   | Description               |
|---------|--------|---------------------------|
| status  | int    | 0: Success, other : Error |
| message | string | Error description         |

Example:

Request:

```
{
  "method": "newAccount",
  "account": "V3-TEST",
  "nick": "",
  "currency": "USD",
  "agent_id": 0
}
```

Response success:

```
{
  "status": 0,
  "message": "success"
}
```

response failure:

```
{
```

```

    "status": -1,
    "message": "currency error"
}

```

## 4. Get Launcher Url

Get the launcher url of game, Agent Call AFB Gaming Slots

### 1) Request

| Name       | Type   | Description                                                                                                                                                      |
|------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| method     | string | getLauncherUrl                                                                                                                                                   |
| account    | string | account name                                                                                                                                                     |
| nick       | string | Optional, nick name                                                                                                                                              |
| currency   | string | Optional, upper case, USD PHP IDR AUD EUR etc.<br>This parameter is optional. If no Account is created, you must pass in Currency to create an account.          |
| agent_id   | int    | Optional, the ID of subagent                                                                                                                                     |
| game       | string | game code                                                                                                                                                        |
| ip         | string | ip address of player                                                                                                                                             |
| lobbyUrl   | string | the Lobby url for return                                                                                                                                         |
| lang       | string | en id ja km ko ms my ph pt th vi etc.                                                                                                                            |
| app        | bool   | is app or not, default is false                                                                                                                                  |
| homeAction | string | optional parameter. currently available values:<br>suggest: the home button in the game displays the game list, only for afb games<br>hidden: hidden home button |
| speed      | string | optional parameter: game speed mode normal/quick/turbo, default is turbo                                                                                         |
| windowOpen | int    | optional parameter:<br>1: lobby open the game in the same tab instead<br>other: default                                                                          |

### 1) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| code    | int    | 0: Success, other: Error |
| message | string | Error description        |
| link    | string | The launcher url of game |

Example:

Request:

```
{
```

```

"method": "getLauncherUrl",
"account": "V3-TEST",
"nick": "",
"currency": "USD",
"agent_id": 0,
"game": "kingArthur",
"ip": "10.8.8.137",
"lobbyUrl": "",
"lang": "en"
}

```

Response:

```

{
  "status": 0,
  "message": "success",
  "link":
    "https://games.luckyinc.net/lgc/adaptor.html?game=kingArthur&lang=en&sid=
    session-48U3FE729BKT&gameName=King Arthur's
    Excalibur&token=afb-48U3FF418LP9&lobbyUrl=&app=false&brand=&homeActi
    on=lobby"
}

```

## 5. Seamless API

Seamless API is a single wallet interface, all calls are AFB Gaming calls Agent

### 5.1 Get Balance

1) Request

| Name     | Type   | Description |
|----------|--------|-------------|
| method   | string | getBalance  |
| key      | string | API Key     |
| username | string | User Name   |
| gameCode | string | Game Code   |

2) Response

| Name           | Type   | Description                   |
|----------------|--------|-------------------------------|
| status         | int    | 0: Success, other: Error      |
| message        | string | Error Description             |
| balance        | float  | Balance                       |
| specialBalance | float  | Promotional balance for games |
| currency       | string | Currency Code                 |

Example :

Request:

```
{
  "gameCode": "kingArthur",
  "key": "wzK982mA00vHrP3xtT6lMCjfea7bJdSL",
  "method": "getBalance",
  "username": "V3-TEST"
}
```

Response:

```
{
  "status": 0,
  "message": "success",
  "balance": 100000
}
```

## 5.2 Bet

### 1) Request

| Name                | Type   | Description                                                                                                                                                                                   |
|---------------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| method              | string | bet                                                                                                                                                                                           |
| key                 | string | API Key                                                                                                                                                                                       |
| username            | string | User Name                                                                                                                                                                                     |
| amount              | string | Amount of bet                                                                                                                                                                                 |
| currency            | string | Currency Code                                                                                                                                                                                 |
| sessionId           | string | Session ID                                                                                                                                                                                    |
| transactionId       | string | Transaction ID                                                                                                                                                                                |
| referenceId         | string | Reference ID                                                                                                                                                                                  |
| gameCode            | string | Game Code                                                                                                                                                                                     |
| gameName            | string | Game Name                                                                                                                                                                                     |
| gameType            | string | Game Type                                                                                                                                                                                     |
| ip                  | string | Customer IP Address                                                                                                                                                                           |
| lineCount           | string | Game line                                                                                                                                                                                     |
| lineBet             | string | Game line bet                                                                                                                                                                                 |
| mode                | string | Bet Mode                                                                                                                                                                                      |
| business            | string | Business Mode: normal, buyFree, buyBonus, useCard, freeRoundBonus, activityBonus, ultraChampionship                                                                                           |
| lastTime            | string | optional,"true"or"false",slot game track the last paid.example<br>normal bet: bet(true)...<br>free:bet(false)-free(false)-free(false )...free(true, end free)<br>bonus:bet(false)-bonus(true) |
| freeRoundBonusCode  | string | optional, Free round bonus code, This field will only be sent if set free rounds                                                                                                              |
| freeRoundBonusTimes | string | optional, Free round bonus times set, This field will only be sent if set                                                                                                                     |

|                           |        |                                                                                             |
|---------------------------|--------|---------------------------------------------------------------------------------------------|
|                           |        | free rounds                                                                                 |
| freeRoundBonusRemainTimes | string | optional, Free round bonus remaining times, This field will only be sent if set free rounds |

## 2) Response

| Name           | Type    | Description                   |
|----------------|---------|-------------------------------|
| status         | int     | 0: Success, other: Error      |
| message        | varchar | Error Description             |
| balance        | float   | Balance                       |
| specialBalance | float   | Promotional balance for games |

Example :

Request:

```
{
  "amount": "0.0100",
  "business": "normal",
  "currency": "USD",
  "gameCode": "kingArthur",
  "gameName": "King Arthur's Excalibur",
  "gameType": "slot",
  "gameVendor": "afb",
  "ip": "10.8.8.137",
  "jackpotCommission": "0.0000",
  "key": "wzK982mA00vHrP3xtT6lMCjfea7bJdSL",
  "lastTime": "false",
  "lineBet": "0.0000",
  "lineCount": "20",
  "method": "bet",
  "mode": "main",
  "referenceId": "",
  "sessionId": "session-48Q45AV9J465",
  "transactionId": "1740622680016562010",
  "username": "V3-TEST"
}
```

Response:

```
{
  "status": 0,
  "message": "success",
  "balance": 99999.99
}
```

## 5.3 Paid

### 1) Request

| Name          | Type   | Description                                                                                                                                                                                  |
|---------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| method        | string | paid                                                                                                                                                                                         |
| key           | string | API Key                                                                                                                                                                                      |
| username      | string | User Name                                                                                                                                                                                    |
| amount        | string | Amount                                                                                                                                                                                       |
| currency      | string | Currency Code                                                                                                                                                                                |
| sessionId     | string | Session ID                                                                                                                                                                                   |
| transactionId | string | Transaction ID                                                                                                                                                                               |
| gameCode      | string | Game Code                                                                                                                                                                                    |
| gameName      | string | Game Name                                                                                                                                                                                    |
| gameType      | string | Game Type                                                                                                                                                                                    |
| ip            | string | Customer IP Address                                                                                                                                                                          |
| lastTime      | string | optional,"true"or"false",slot game track the last paid.example<br>normal bet: bet(true)...<br>free:bet(false)-free(false)-free(false)...free(true, end free)<br>bonus:bet(false)-bonus(true) |
| realBet       | string | optional,<br>singleBaccarat/classicBaccarat/bullBul: realBet = min(bet, abs(win -bet))<br>other games:<br>realBet = bet                                                                      |
| realPaid      | string | optional, realPaid = win                                                                                                                                                                     |

### 2) Response

| Name           | Type   | Description                   |
|----------------|--------|-------------------------------|
| status         | int    | 0: Success, other : Error     |
| message        | string | Error Description             |
| balance        | float  | Balance                       |
| specialBalance | float  | Promotional balance for games |

Example:

Request:

```
{
  "amount": "0.0000",
  "currency": "USD",
  "gameCode": "kingArthur",
  "gameName": "King Arthur's Excalibur",
  "gameType": "slot",
  "gameVendor": "afb",
  "ip": "10.8.8.137",
  "key": "wzK982mA00vHrP3xtT6lMCjfea7bJdSL",
```

```

"lastTime": "false",
"method": "paid",
"sessionId": "session-48Q45AV9J465",
"transactionId": "1740622680016562010",
"username": "V3-TEST"
}

```

Response:

```

{
  "status": 0,
  "message": "success",
  "balance": 99999.99
}

```

## 5.4 Bet Paid

Controlled by the site parameter betPaid, If this interface is implemented, bet/paid will be combined into the same request and sent, and bet/paid will not be sent. If your site needs to set up betPaid, please contact afb customer service for the corresponding settings.

### 1) Request

| Name          | Type   | Description                                                                                                                                                                                      |
|---------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| method        | string | betPaid                                                                                                                                                                                          |
| key           | string | API Key                                                                                                                                                                                          |
| username      | string | User Name                                                                                                                                                                                        |
| betAmount     | string | Amount of bet                                                                                                                                                                                    |
| paidAmount    | string | Amount of paid                                                                                                                                                                                   |
| currency      | string | Currency Code                                                                                                                                                                                    |
| sessionId     | string | Session ID                                                                                                                                                                                       |
| transactionId | string | Transaction ID                                                                                                                                                                                   |
| referenceId   | string | Reference ID                                                                                                                                                                                     |
| gameCode      | string | Game Code                                                                                                                                                                                        |
| gameName      | string | Game Name                                                                                                                                                                                        |
| gameType      | string | Game Type                                                                                                                                                                                        |
| ip            | string | Customer IP Address                                                                                                                                                                              |
| lineCount     | string | Game line                                                                                                                                                                                        |
| lineBet       | string | Game line bet                                                                                                                                                                                    |
| mode          | string | Bet Mode                                                                                                                                                                                         |
| business      | string | Business Mode: normal, buyFree, buyBonus, useCard, freeRoundBonus, activityBonus                                                                                                                 |
| lastTime      | string | optional,"true"or"false",slot game track the last paid.example<br>normal bet: bet(true)...<br>free:bet(false)-free(false)-free(false)...fr<br>ee(true, end free)<br>bonus:bet(false)-bonus(true) |

## AFB Gaming

|                           |        |                                                                                                                                                                                   |
|---------------------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| freeRoundBonusCode        | string | optional, Free round bonus code, This field will only be sent if set free rounds                                                                                                  |
| freeRoundBonusTimes       | string | optional, Free round bonus times set, This field will only be sent if set free rounds                                                                                             |
| freeRoundBonusRemainTimes | string | optional, Free round bonus remaining times, This field will only be sent if set free rounds                                                                                       |
| realBet                   | string | optional,<br>singleBaccarat/classicBaccarat/bullBul:<br>$\text{realBet} = \min(\text{bet}, \text{abs}(\text{win} - \text{bet}))$<br>other games:<br>$\text{realBet} = \text{bet}$ |
| realPaid                  | string | optional, $\text{realPaid} = \text{win}$                                                                                                                                          |

### 2) Response

| Name           | Type   | Description                   |
|----------------|--------|-------------------------------|
| status         | int    | 0: Success, other: Error      |
| message        | string | Error Description             |
| balance        | float  | Balance                       |
| specialBalance | float  | Promotional balance for games |

Example:

Request

```
{
  "method": "betPaid",
  "key": "key1234567890",
  "username": "demo001",
  "betAmount": "5.0",
  "paidAmount": "1.0",
  "currency": "USD",
  "sessionId": "CTX02BE2F0DD94E63CFA7",
  "transactionId": "21470192840451222",
  "gameCode": "bib",
  "gameName": "Great Blue",
  "gameType": "slots",
  "ip": "1.1.1.1",
  "mode": "spin",
  "lineCount": "20",
  "lineBet": "0.01",
}
```

Response

```
{
  "status": 0,
  "balance": 1000,
}
```

## 5.5 Refund

### 1) Request

| Name          | Type   | Description         |
|---------------|--------|---------------------|
| method        | string | refund              |
| key           | string | API Key             |
| username      | string | User Name           |
| amount        | string | Amount              |
| currency      | string | Currency Code       |
| sessionId     | string | Session ID          |
| transactionId | string | Transaction ID      |
| gameCode      | string | Game Code           |
| gameName      | string | Game Name           |
| gameType      | string | Game Type           |
| ip            | string | Customer IP Address |

### 2) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| status  | int    | 0: Success, other: Error |
| message | string | Error Description        |
| balance | float  | Balance                  |

Example:

Request:

```
{
  "method": "refund",
  "key": "key1234567890",
  "username": "demo001",
  "amount": 3.0,
  "currency": "USD",
  "sessionId": "CTX02BE2F0DD94E63CFA7",
  "transactionId": "21470192840451222",
  "gameCode": "bib",
  "gameName": "Great Blue",
  "gameType": "slots",
  "ip": "1.1.1.1"
}
```

Response:

```
{
  "status": 0,
  "balance": 1000
}
```

## 5.6 Game Open Notify(optional)

notify game open. controlled by game\_status params

### 1) Request

| Name     | Type   | Description         |
|----------|--------|---------------------|
| method   | string | open                |
| username | string | username            |
| gameCode | string | game code           |
| gameName | string | game name           |
| ip       | string | customer ip address |

### 2) Response

| Name    | Type   | Description             |
|---------|--------|-------------------------|
| status  | int    | 0: Success other: Error |
| message | string | Error Description       |

Example:

Request:

```
{
  "method": "open",
  "username": "demo001",
  "gameCode": "alice",
  "gameName": "Alice",
  "ip": "1.1.1.1"
}
```

Response:

```
{
  "status": 0
}
```

## 5.7 Game Close Notify(optional)

notify game close. controlled by game\_status params

### 1) Request

| Name     | Type   | Description         |
|----------|--------|---------------------|
| method   | string | close               |
| username | string | username            |
| gameCode | string | game code           |
| gameName | string | game name           |
| ip       | string | customer ip address |

### 2) Response

| Name   | Type | Description              |
|--------|------|--------------------------|
| status | int  | 0: Success, other: Error |

|         |        |                   |
|---------|--------|-------------------|
| message | string | Error Description |
|---------|--------|-------------------|

Example:

Request:

```
{
  "method": "open",
  "username": "demo001",
  "gameCode": "alice",
  "gameName": "Alice",
  "ip": "1.1.1.1"
}
```

Response:

```
{
  "status": 0
}
```

## 5.8 Bonus Status Notify(optional)

notify game special mode in and out. controlled by game\_status params

1) Request

| Name        | Type   | Description       |
|-------------|--------|-------------------|
| method      | string | bonusStatusNotify |
| username    | string | username          |
| gameCode    | string | game code         |
| action      | string | in or out         |
| mode        | string | game mode         |
| referenceId | string | referenceId       |

2) Response

| Name    | Type    | Description              |
|---------|---------|--------------------------|
| status  | int     | 0: Success, other: Error |
| message | varchar | Error Description        |

Example:

Request:

```
{
  "method": "bonusStatusNotify",
  "username": "demo001",
  "gameCode": "alice",
  "action": "in",
  "mode": "bonus",
  "referenceId": "1662374830621841005"
}
```

Response:

```
{
  "status": 0
}
```

## 6. Transfer API

Transfer API is a multiple wallet interface, Agent Call AFB Gaming

### 6.1 Deposit

1) Request

| Name           | Type   | Description                         |
|----------------|--------|-------------------------------------|
| method         | string | deposit                             |
| transaction_id | string | the unique deposit ID               |
| account        | string | Account Name                        |
| amount_cent    | int    | Amount of deposit, the unit is cent |
| desc           | string | the description                     |

2) Response

| Name         | Type   | Description              |
|--------------|--------|--------------------------|
| status       | int    | 0: Success, other: Error |
| message      | string | Error description        |
| balance_cent | int    | Balance cent             |

Example:

Request:

```
{
  "method": "deposit",
  "account": "V3-TEST",
  "transaction_id": "10000000000001",
  "amount_cent": 100000,
  "desc": "xxx"
}
```

Response:

```
{
  "status": 0,
  "message": "success",
  "balance_cent": 100000
}
```

## 6.2 Withdraw

### 1) Request

| Name           | Type   | Description                         |
|----------------|--------|-------------------------------------|
| method         | string | withdraw                            |
| transaction_id | string | The unique withdraw ID              |
| account        | string | Account Name                        |
| amount_cent    | int    | Amount of deposit, the unit is cent |
| desc           | string | the description                     |

### 2) Response

| Name         | Type   | Description              |
|--------------|--------|--------------------------|
| status       | int    | 0: Success, other: Error |
| message      | string | Error description        |
| balance_cent | int    | Balance cent             |

Example :

Request:

```
{
  "method": "withdraw",
  "account": "V3-TEST",
  "transaction_id": "10000000000004",
  "amount_cent": 55000,
  "desc": "xxx"
}
```

Response:

```
{
  "status": 0,
  "message": "success",
  "balance_cent": 45000
}
```

## 6.3 Balance

### 1) Request

| Name    | Type   | Description  |
|---------|--------|--------------|
| method  | string | balance      |
| account | string | Account Name |

### 2) Response

| Name         | Type   | Description              |
|--------------|--------|--------------------------|
| status       | int    | 0: Success, other: Error |
| message      | string | Error Description        |
| balance_cent | int    | Balance cent             |

Example:

Request:

```
{
  "method": "balance",
  "account": "V3-TEST"
}
```

Response:

```
{
  "status": 0,
  "message": "success",
  "balance_cent": 10000000
}
```

## 6.4 Check Transaction

1) Request

| Name           | Type   | Description                                      |
|----------------|--------|--------------------------------------------------|
| method         | string | checkTransaction                                 |
| transaction_id | string | the unique transaction ID of deposit or withdraw |
| account        | string | Account Name                                     |

2) Response

| Name                | Type   | Description              |
|---------------------|--------|--------------------------|
| status              | int    | 0: Success, other: Error |
| message             | string | Error description        |
| account             | string | Account name             |
| amount_cent         | int    | Amount cent              |
| method              | string | deposit or withdraw      |
| timestamp           | int    | Unix seconds             |
| balance_cent_before | int    | Balance before           |
| balance_cent_after  | int    | Balance after            |

Example :

Request:

```
{
  "method": "checkTransaction",
  "transaction_id": "10000000000004",
  "account": "V3-TEST"
}
```

Response:

```
{
```

```

"status": 0,
"Message": "found",
"account": "V3-TEST",
"amount_cent": -55000,
"method": "withdraw",
"timestamp": 1740716018,
"balance_cent_before": 100000,
"balance_cent_after": 45000
}

```

## 7. Block

Block member account

### 1) Request

| Name    | Type   | Description  |
|---------|--------|--------------|
| method  | string | block        |
| account | string | Account Name |

### 2) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| status  | int    | 0: Success, other: Error |
| message | string | Error description        |

Example :

Request:

```

{
  "method": "block",
  "account": "V3-TEST"
}

```

Response:

```

{"status":0}

```

## 8. Unblock

Unblock member account

### 1) Request

| Name    | Type   | Description  |
|---------|--------|--------------|
| method  | string | unblock      |
| account | string | Account Name |

### 2) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| status  | int    | 0: Success, other: Error |
| message | string | Error description        |

Example :

Request:

```
{
  "method": "unblock",
  "account": "V3-TEST"
}
```

Response:

```
{"status":0}
```

## 9. Bet Records

Get the bet list, The bet is normally kept for one month

1) Request

| Name             | Type   | Description         |
|------------------|--------|---------------------|
| method           | string | betRecords          |
| timestamp_ms     | int    | Unix microseconds   |
| timestamp_ms_end | int    | Unix microseconds   |
| count            | int    | Max count, max 3000 |

2) Response

| Name              | Type   | Description                                  |
|-------------------|--------|----------------------------------------------|
| status            | int    | 0: Success, other: Error                     |
| message           | string | Error description                            |
| record_list       | array  | The bet records list                         |
| next_timestamp_ms | int    | The unix microsecond timestamp for next call |

Example :

Request:

```
{
  "method": "betRecords",
  "timestamp_ms": 1740211265336169,
  "timestamp_ms_end": 1740643265353855,
  "count": 1000
}
```

Response:

```
{
  "status": 0,
  "record_list": [
```

```

{
  "account": "V3-TEST",
  "balance": 0,
  "game_code": "kingArthur",
  "bet_id": "1740473528000183010",
  "bet": 1,
  "win": 0,
  "line_bet": 0,
  "line_count": 20,
  "mode": "main",
  "currency": "USD",
  "bet_time_ms": 1740473528000000,
  "win_time_ms": 1740473528000000,
  "business": "normal"
},
{
  "account": "V3-TEST",
  "balance": 9999999,
  "game_code": "kingArthur",
  "bet_id": "1740473609000184010",
  "bet": 1,
  "win": 0,
  "line_bet": 0,
  "line_count": 20,
  "mode": "main",
  "currency": "USD",
  "bet_time_ms": 1740473609000000,
  "win_time_ms": 1740473609000000,
  "business": "normal"
}
],
"next_timestamp_ms": 1740473612000
}

```

## 10. Fishing Transfer Records

### 1) Request

| Name             | Type   | Description            |
|------------------|--------|------------------------|
| method           | string | fishingTransferRecords |
| timestamp_ms     | int    | Unix microseconds      |
| timestamp_ms_end | int    | Unix microseconds      |
| count            | int    | Max count, max 3000    |

### 2) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| status  | int    | 0: Success, other: Error |
| message | string | Error description        |

|                   |       |                                              |
|-------------------|-------|----------------------------------------------|
| record_list       | array | The bet records list                         |
| next_timestamp_ms | int   | The unix microsecond timestamp for next call |

Example :

Request:

```
{
  "method": "fishingTransferRecords",
  "timestamp_ms": 1740295418016248,
  "timestamp_ms_end": 1740727418034633,
  "count": 2
}
```

Response:

```
{
  "status": 0,
  "message": "",
  "record_list": [
    {
      "siteId": 10396,
      "userId": "V3-TEST",
      "amount": 10,
      "point": 100000,
      "pointRate": 10000,
      "betPoint": 0,
      "winPoint": 0,
      "transactionId": "1740727290000005050",
      "time": "2025-02-28 15:21:30",
      "method": "bet",
      "currency": "USD"
    },
    {
      "siteId": 10396,
      "userId": "V3-TEST",
      "amount": 10.5,
      "point": 105000,
      "pointRate": 10000,
      "betPoint": 13300,
      "winPoint": 18300,
      "transactionId": "1740727290000005050",
      "time": "2025-02-28 15:22:50",
      "method": "paid",
      "currency": "USD"
    }
  ],
  "next_timestamp_ms": 1740727370001000
}
```

# 11. Game List

Get game list

## 1) Request

| Name   | Type   | Description                                |
|--------|--------|--------------------------------------------|
| method | string | gameList                                   |
| lang   | string | Language code, see Supported language list |

## 2) Response

| Name      | Type   | Description              |
|-----------|--------|--------------------------|
| status    | int    | 0: Success, other: Error |
| message   | string | Error description        |
| game_list | array  | The game list            |

Example :

Request:

```
{
  "method": "gameList",
  "lang": "en"
}
```

Response:

```
{
  "status": 0,
  "game_list": [
    {
      "code": "luckyFrog",
      "name": "Lucky Frog",
      "vendor": "afb",
      "type": "slot",
      "line": 40,
      "picture": "https://games.luckyinc.net/icons/308x218/luckyFrog.png",
      "hot": true,
      "new": false,
      "maxMultiple": "x8000",
      "desc": "Traveling money frogs from all over the world have recently come
to your city, and it is said that they can bring wealth to people!"
    },
    {
      "code": "manekiNeko",
      "name": "Maneki Neko",
      "vendor": "afb",
      "type": "slot",
      "line": 20,
      "picture": "https://games.luckyinc.net/icons/308x218/manekiNeko.png",
```

```

    "hot": false,
    "new": false,
    "maxMultiple": "x25000",
    "desc": "Maneki Neko can be seen everywhere in life. As a symbol of Asian
culture, it is regarded as a mascot for good luck and has a long history. Now you
can see it in the game. Also, it has a lot going for it in terms of gameplay, and you
can enjoy free spins with win multipliers, stacked symbols, Wilds, and more."
  }
]
}

```

## 12. Free Rounds Bonus(optional)

Customer can set the free rounds bonus, the resulting compensation needs to be borne by yourself

### 12.1 Set

this method is set the player free rounds, will create new player if player not exist

#### 1) Request

| Name            | Type    | Description                                                            |
|-----------------|---------|------------------------------------------------------------------------|
| method          | string  | frbSet                                                                 |
| account         | varchar | Player username                                                        |
| game_list       | array   | Game List                                                              |
| rounds          | int     | Number of free rounds                                                  |
| features        | int     | The number of feature games will be triggered and will appear randomly |
| bonus_code      | varchar | unique identifier within the operator system                           |
| expiration_date | int     | Second timestamp, date and time when the free rounds will expire.      |
| currency        | varchar | player currency                                                        |

#### 2) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| status  | int    | 0: Success, other: Error |
| message | string | Error description        |

request:

```

{
  "method": "frbSet",
  "account": "V3-TEST",
  "rounds": 10,
  "features": 0,
  "bonus_code": "abc001",

```

```

"game_list": [
  "luckyFrog",
  "moneyTree"
],
"expiration_date": 1740735881,
"currency": "USD"
}

```

```

response:
{
  "status": 0,
  "message": "success"
}

```

## 12.2 Cancel

this method is cancel the player free rounds

### 1) Request

| Name      | Type    | Description                                  |
|-----------|---------|----------------------------------------------|
| method    | string  | frbCancel                                    |
| account   | varchar | Player username                              |
| bonusCode | varchar | unique identifier within the operator system |

### 2) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| status  | int    | 0: Success, other: Error |
| message | string | Error description        |

```

request:
{
  "method": "frbCancel",
  "account": "V3-TEST",
  "bonus_code": "abc001"
}

```

```

response:
{
  "status": 0,
  "message": "success"
}

```

## 12.3 Get Game List

get valid games of free rounds bonus

### 1) Request

| Name   | Type   | Description    |
|--------|--------|----------------|
| method | string | frbGetGameList |

## 2) Response

| Name      | Type   | Description              |
|-----------|--------|--------------------------|
| status    | int    | 0: Success, other: Error |
| message   | string | Error description        |
| game_list | array  | Game list                |

request:

```
{
  "method": "frbGetGameList"
}
```

response:

```
{
  "status": 0,
  "message": "success",
  "game_list": [
    "luckyFrog",
    "moneyTree"
  ]
}
```

## 12.4 Get Account

get player info of free rounds bonus, remain rounds is not 0

## 1) Request

| Name    | Type    | Description     |
|---------|---------|-----------------|
| method  | string  | frbGetAccount   |
| account | varchar | Player username |

## 2) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| status  | int    | 0: Success, other: Error |
| message | string | Error description        |
| list    | array  |                          |

request:

```
{
  "method": "frbGetAccount",
  "account": "V3-TEST"
}
```

response:

```
{
  "status": 0,
```

```

"message": "success",
"game_list": [
  {
    "account": "V3-TEST",
    "currency": "USD",
    "rounds": 10,
    "game_list": [
      "luckyFrog",
      "moneyTree"
    ],
    "bonus_code": "abc001",
    "created_at": "2025-02-27T17:44:41+08:00",
    "remain_rounds": 10,
    "expiration_date": "2025-02-28T17:44:41+08:00"
  }
]
}

```

## 13. Unfinished Games

Get unfinished games of player

### 1) Request

| Name    | Type   | Description     |
|---------|--------|-----------------|
| method  | string | unfinishedGames |
| account | string | Account Name    |

### 2) Response

| Name             | Type   | Description              |
|------------------|--------|--------------------------|
| status           | int    | 0: Success, other: Error |
| message          | string | Error description        |
| unfinished_games | array  | The unfinished games     |

Example :

request:

```

{
  "method": "unfinishedGames",
  "account": "V3-TEST"
}

```

response:

```

{
  "status": 0,
  "message": "success",
  "unfinished_games": ["moneyTree"]
}

```

## 14. Get Record by Transaction ID

Get transaction record by transaction id, The palyback function only supports slots games. Some slots games are third-party games and will not have replay links. The playback will only playback winning transaction. and if the transaction is in special mode, the playback will be the entire special mode.

### 1) Request

| Name           | Type   | Description              |
|----------------|--------|--------------------------|
| method         | string | getRecordByTransactionId |
| transaction_id | string | Transaction Id           |

### 2) Response

| Name               | Type   | Description              |
|--------------------|--------|--------------------------|
| status             | int    | 0: Success, other: Error |
| message            | string | Error description        |
| record             |        | Transaction record       |
| transaction_status | int    | 1. exist 2. not exist    |
| playback           | string | Transaction playback     |
| detailUrl          | string | Transaction detail       |

Example :

request:

```
{
  "method": "getRecordByTransactionId",
  "transaction_id": "1741337892030590010"
}
```

response:

```
{
  "status": 0,
  "message": "success",
  "record": {
    "transaction_id": "1741337892030590010",
    "username": "wu01",
    "timestamp": 1741337892,
    "gameCode": "olympianZeus",
    "currency": "USD",
    "bet_amount": "0",
    "paid_amount": "0",
    "siteId": 10086,
    "reference_id": "1741337889030585010",
    "mode": "respin"
  },
  "transaction_status": 1,
  "playback":
  "https://games.luckyinc.net/lgc/index.html?game=olympianZeus&isPlayback=tr"
```

```
ue&betId=1741337889030585010"
}
```

## 15. Statistics

### 15.1 pullStatisticsBetMinute

This method is to pull minute statistics

#### 3) Request

| Name            | Type   | Description                                                             |
|-----------------|--------|-------------------------------------------------------------------------|
| method          | string | pullStatisticsBetMinute                                                 |
| site_ids        | string | ids of site                                                             |
| update_start_ts | int    | The starting timestamp, in seconds, is the statistical data update time |
| update_end_ts   | int    | End timestamp, in seconds, this is the statistical data update time     |
| page            | int    | Data is obtained by paging. Which page is this?                         |
| page_size       | int    | Number of data pages                                                    |

#### 4) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| status  | int    | 0: Success, other: Error |
| message | string | Error description        |
| data    | array  | Returned data list       |

request:

```
{
  "method":"pullStatisticsBetMinute",
  "page":"1",
  "site_ids":"30163009
,30163010,30163011",
  "update_end_ts":"1742947242",
  "update_start_ts":"1742947182"
}
```

response:

```
{
  "code":0,
  "message":"success",
  "data":[
    {
      "siteId":30163009,
      "account":"2514108791",
```

```

    "gameCode":"goldVolcano",
    "gameTypeId":1,
    "business":"normal",
    "currency":"IDR",
    "bet":"1.6",
    "betUsd":"0.1024",
    "win":"0",
    "winUsd":"0",
    "betCount":16,
    "mainBetCount":16,
    "time":"2025-03-25 15:13:00",
    "updateAt":"2025-03-26 08:00:19"
  },
  {
    "siteId":30163009,
    "account":"2514108791",
    "gameCode":"goldVolcano",
    "gameTypeId":1,
    "business":"normal",
    "currency":"IDR",
    "bet":"0",
    "betUsd":"0",
    "win":"17.2",
    "winUsd":"1.0935",
    "betCount":1,
    "time":"2025-03-25 15:14:00",
    "updateAt":"2025-03-26 08:00:19"
  }
]
}

```

## 15.2 pullStatisticsBetDay

This method is to pull day statistics

### 5) Request

| Name            | Type   | Description                                                             |
|-----------------|--------|-------------------------------------------------------------------------|
| method          | string | pullStatisticsBetDay                                                    |
| site_ids        | string | ids of site                                                             |
| update_start_ts | int    | The starting timestamp, in seconds, is the statistical data update time |
| update_end_ts   | int    | End timestamp, in seconds, this is the statistical data update time     |
| page            | int    | Data is obtained by paging. Which page is this?                         |
| page_size       | int    | Number of data pages                                                    |

### 6) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| status  | int    | 0: Success, other: Error |
| message | string | Error description        |
| data    | array  | Returned data list       |

request:

```
{
  "method":"pullStatisticsBetDay",
  "page":"1",
  "site_ids":"30163009
,30163010,30163011",
  "update_end_ts":"1742947242",
  "update_start_ts":"1742947182"
}
```

response:

```
{
  "code":0,
  "message":"success",
  "data":[
    {
      "siteId":30163009,
      "account":"138605",
      "gameCode":"goldVolcano",
      "business":"normal",
      "currency":"IDR",
      "bet":"0.4",
      "betUsd":"0.0256",
      "win":"0",
      "winUsd":"0",
      "betCount":4,
      "mainBetCount":4,
      "time":"2025-03-25",
      "updateAt":"2025-03-26 08:00:27"
    },
    {
      "siteId":30163009,
      "account":"2514108791",
      "gameCode":"goldVolcano",
      "business":"normal",
      "currency":"IDR",
      "bet":"42.9",
      "betUsd":"2.7456",
      "win":"44.7",
      "winUsd":"2.8418",
      "betCount":437,
      "mainBetCount":429,
      "time":"2025-03-25",
      "updateAt":"2025-03-26 08:00:27"
    }
  ]
}
```

```

    }
  ]
}

```

### 15.3 pullStatisticsAccount

This method is to pull account statistics

#### 7) Request

| Name     | Type   | Description                  |
|----------|--------|------------------------------|
| method   | string | pullStatisticsAccount        |
| from_day | string | From date, format yyyy-mm-dd |
| to_day   | string | End date, format yyyy-mm-dd  |
| account  | string | Account name                 |

#### 8) Response

| Name    | Type   | Description              |
|---------|--------|--------------------------|
| status  | int    | 0: Success, other: Error |
| message | string | Error description        |
| data    | array  | Returned data list       |

request:

```

{
  "method":"pullStatisticsAccount",
  "from_day":"2025-02-",
  "to_day":"1742947182"
}

```

response:

```

{
  "code":0,
  "message":"success",
  "totalBet":"18.0000",
  "totalWin":"2.7400",
  "totalBetUsd":"1.1454",
  "totalWinUsd":"0.1743",
  "data":[
    {
      "siteId":30163009,
      "account":"138605",
      "gameCode":"akira",
      "business":"normal",
      "currency":"IDR",
      "bet":"4",
      "betUsd":"0.2545",
      "win":"2.4",

```

```

"winUsd":"0.1526",
"betCount":5,
"mainBetCount":5,
"time":"2025-03-25",
"updateAt":"2025-03-26 08:00:27"
},
{
"siteId":30163009,
"account":"138605",
"gameCode":"luckyFrog",
"business":"normal",
"currency":"IDR",
"bet":"2.4",
"betUsd":"0.1527",
"win":"0.1",
"winUsd":"0.0064",
"betCount":3,
"mainBetCount":3,
"time":"2025-03-25",
"updateAt":"2025-03-26 08:00:27"
},
{
"siteId":30163009,
"account":"138605",
"gameCode":"wallowInMoney",
"business":"normal",
"currency":"IDR",
"bet":"1.6",
"betUsd":"0.1018",
"win":"0.24",
"winUsd":"0.0153",
"betCount":3,
"mainBetCount":2,
"time":"2025-03-25",
"updateAt":"2025-03-26 08:00:27"
},
{
"siteId":30163009,
"account":"138605",
"gameCode":"manekiNeko",
"business":"normal",
"currency":"IDR",
"bet":"2.4",
"betUsd":"0.1527",
"win":"0",
"winUsd":"0",
"betCount":3,
"mainBetCount":3,
"time":"2025-03-25",

```

```
"updateAt":"2025-03-26 08:00:27"
},
{
  "siteId":30163009,
  "account":"138605",
  "gameCode":"fiveDragonKings",
  "business":"normal",
  "currency":"IDR",
  "bet":"7.2",
  "betUsd":"0.4581",
  "win":"0",
  "winUsd":"0",
  "betCount":9,
  "mainBetCount":9,
  "time":"2025-03-25",
  "updateAt":"2025-03-26 08:00:27"
},
{
  "siteId":30163009,
  "account":"138605",
  "gameCode":"goldVolcano",
  "business":"normal",
  "currency":"IDR",
  "bet":"0.4",
  "betUsd":"0.0256",
  "win":"0",
  "winUsd":"0",
  "betCount":4,
  "mainBetCount":4,
  "time":"2025-03-25",
  "updateAt":"2025-03-26 08:00:27"
}
]
}
```

16. Support Language List

| Code | Country    |
|------|------------|
| en   | English    |
| id   | Indonesian |
| ja   | Japanese   |
| ko   | Korean     |
| ms   | Malay      |
| th   | Thai       |

|              |                     |
|--------------|---------------------|
| <b>vi</b>    | Vietnamese          |
| <b>my</b>    | Burman              |
| <b>km</b>    | Kampuchean          |
| <b>pt</b>    | Portuguese          |
| <b>zh-tw</b> | Traditional Chinese |

## 17. Support Currency List

| Code        | Name                        | Symbol | Country |
|-------------|-----------------------------|--------|---------|
| <b>AED</b>  | United Arab Emirates dirham | د.إ.   | AE      |
| <b>ARS</b>  | Argentine Peso              | Arg\$  | AR      |
| <b>AUD</b>  | Australian Dollar           | A\$    | AU      |
| <b>BDT</b>  | Bangladeshi taka            | টাকা   | BD      |
| <b>BND</b>  | Bruneian Dollar             | B\$    | BN      |
| <b>BRL</b>  | Brazilian Real              | R\$    | BR      |
| <b>BT4</b>  | Bitcoin 4 (BTC 1:10000)     | ฿      |         |
| <b>BT5</b>  | Bitcoin 5(BTC 1:100000)     | ฿      |         |
| <b>CAD</b>  | Canadian Dollar             | \$     | CA      |
| <b>CLP</b>  | Chilean peso                | \$     | CL      |
| <b>COP</b>  | Colombian peso 1:1000       | \$     | CO      |
| <b>COP2</b> | Colombian peso 1:1          | \$     | CO      |
| <b>DZD</b>  | Algerian dinar              | DA     | DZ      |
| <b>EUR</b>  | Euro                        | €      |         |
| <b>EGP</b>  | Egyptian Pound              | €      | EG      |
| <b>FRF</b>  | French franc                | F      | FR      |
| <b>GBP</b>  | British pound               | £      | GB      |
| <b>HKD</b>  | Hong Kong Dollar            | HK\$   | HK      |
| <b>IDR</b>  | Indonesia Rupiah 1:1000     | Rp     | ID      |
| <b>IDR2</b> | Indonesia Rupiah 1:1        | Rp     | ID      |
| <b>INR</b>  | Indian National Rupee       | ₹      | IN      |
| <b>JPY</b>  | Japanese Yen                | ¥      | JP      |

|               |                         |                |    |
|---------------|-------------------------|----------------|----|
| <b>KHR</b>    | Camboddian Riel 1:1000  | ៛              | KH |
| <b>KHR2</b>   | Camboddian Riel 1:1     | ៛ <sub>2</sub> | KH |
| <b>KRW</b>    | Korea                   | ₩              | KR |
| <b>LAK</b>    | Lao Kips 1:1000         | ₭              | LA |
| <b>LAK2</b>   | Lao Kips 1:1            | ₭              | LA |
| <b>LTC</b>    | Litecoin                | Ł              |    |
| <b>MAD</b>    | Moroccan dirham         | DH             | MA |
| <b>MMK</b>    | Myanmar Kyat 1:1000     | K              | MM |
| <b>MMK2</b>   | Myanmar Kyat 1:1        | K              | MM |
| <b>MXN</b>    | Mexican peso            | Mex\$          | MX |
| <b>MYR</b>    | Malaysia Ringgit        | RM             | MY |
| <b>NGN</b>    | Nigerian naira          | ₦              | NG |
| <b>NPR</b>    | Nepalese Rupee          | ₨              | NP |
| <b>PEN</b>    | Peruvian sol            | S/             | PE |
| <b>PGK</b>    | Papua New Guinean kina  | K              | PG |
| <b>PHP</b>    | Philippine Piso         | ₱              | PH |
| <b>PKR</b>    | Pakistani rupee         | Rs             | PK |
| <b>RUB</b>    | Russia Ruble            | ₽              | RU |
| <b>SEK</b>    | Sweden Krona            | kr             | SE |
| <b>TEST</b>   | TEST Coin               |                |    |
| <b>THB</b>    | Thailand Baht           | ฿              | TH |
| <b>TND</b>    | Tunisian dinar          | DT             | TN |
| <b>TRY</b>    | Turkish lira            | ₺              | TR |
| <b>TWD</b>    | Taiwan New Dollar       | NT\$           | TW |
| <b>TWD130</b> | Taiwan New Dollar 130:1 | NT\$           | TW |
| <b>USD</b>    | United States Dollar    | \$             | US |
| <b>VND</b>    | Viet Nam Dong 1:1000    | ₫              | VN |
| <b>VND2</b>   | Viet Nam Dong 1:1       | ₫              | VN |
| <b>ZAR</b>    | South African rand      | R              | ZA |