

API Reference

# MG Plus K2 Common Wallet Api Reference

API Version: 1.62.4

Base URL: <https://api-demo.k2net.io/api/v1>

MG Plus Integration Api.

MG Plus 集成 Api.

STS Token

Token duration is specified by 'expires\_in' property in response.

Data Retention Policy

Detailed data:

Bets – last 10 days

Transactions – last 60 days

Reports aggregated data:

Hourly – last 30 days

Daily – last 6 months

Monthly – last 2 years

Numbers Precision

All amounts accuracy is up to 4 digits after decimal point. Content-type header value for all requests is application/x-www-form-urlencoded unless a different value is explicitly specified.

STS令牌

令牌持续时间由响应中的 'expires\_in' 值指定

数据保留方针 详细数据:

注单- 10天的期限  
交易 - 60天的期限

合计数据报表:  
小时 - 30天的期限  
天 - 6 个月的期限  
月 - 2年的期限

数字精确度  
金额精确度为小数点后4位数字  
除非明确指定了不同的值，否则所有请求的内容类型标头值均为application/x-www-form-urlencoded

# INDEX

|                                                                                                           |     |
|-----------------------------------------------------------------------------------------------------------|-----|
| 1. BETS 投注                                                                                                | 6   |
| 1.1 GET /agents/{agentCode}/bets                                                                          | 6   |
| 1.2 GET /agents/{agentCode}/players/{playerId}/products/{productId}/incompleteBets                        | 8   |
| 1.3 GET /agents/{agentCode}/players/{playerId}/incompleteBets                                             | 9   |
| 1.4 GET /agents/{agentCode}/liveDealerBets                                                                | 11  |
| 2. BETTING PROFILES 投注配置                                                                                  | 34  |
| 2.1 GET /agents/{agentCode}/products/{productId}/bettingProfiles                                          | 34  |
| 2.2 GET /agents/{agentCode}/products/{productId}/players/{playerId}/bettingProfiles                       | 35  |
| 2.3 POST /agents/{agentCode}/products/{productId}/players/{playerId}/bettingProfiles                      | 36  |
| 2.4 DELETE /agents/{agentCode}/products/{productId}/players/{playerId}/bettingProfiles/{bettingProfileId} | 38  |
| 3. DEMOSESSIONS 演示模式会话                                                                                    | 41  |
| 3.1 POST /agents/{agentCode}/demoSessions                                                                 | 41  |
| 4. FREE GAMES - OFFER MANAGEMENT 免费游戏 - 优惠管理                                                              | 43  |
| 4.1 GET /agents/{agentCode}/offers                                                                        | 43  |
| 4.2 POST /agents/{agentCode}/offers                                                                       | 46  |
| 4.3 PATCH /agents/{agentCode}/offers/{offerGuid}                                                          | 51  |
| 4.4 PATCH /agents/{agentCode}/offers/{offerGuid}/close                                                    | 55  |
| 5. FREE GAMES - PLAYER MANAGEMENT 免费游戏 - 玩家管理                                                             | 57  |
| 5.1 POST /agents/{agentCode}/offers/{offerGuid}/players/{playerId}/freeGameInstances                      | 57  |
| 5.2 POST /agents/{agentCode}/offers/{offerGuid}/freeGameBatchInstances                                    | 60  |
| 5.3 PATCH /agents/{agentCode}/players/{playerId}/freeGameInstances/{instanceGuid}                         | 64  |
| 5.4 GET /agents/{agentCode}/players/{playerId}/freeGameOffers                                             | 67  |
| 5.5 GET /agents/{agentCode}/offers/{offerGuid}/players                                                    | 71  |
| 5.6 GET /agents/{agentCode}/offers/batches/{batchGuid}                                                    | 73  |
| 5.7 GET /agents/{agentCode}/offers/batches                                                                | 77  |
| 6. GAME ASSETS 遊戲素材                                                                                       | 82  |
| 6.1 GET /agents/{agentCode}/assets/imageTemplate                                                          | 82  |
| 6.2 GET /agents/{agentCode}/assets/liveDealerTables                                                       | 83  |
| 7. GAME CATEGORIES 游戏类别                                                                                   | 95  |
| 7.1 GET /agents/{agentCode}/gameCategories                                                                | 95  |
| 7.2 GET /agents/{agentCode}/players/{playerId}/gameCategories                                             | 96  |
| 7.3 POST /agents/{agentCode}/players/{playerId}/products/{productId}/gameCategories                       | 97  |
| 7.4 DELETE /agents/{agentCode}/players/{playerId}/products/{productId}/gameCategories/{gameCategoryId}    | 99  |
| 8. GAMES 遊戲                                                                                               | 101 |
| 8.1 GET /agents/{agentCode}/games                                                                         | 101 |
| 8.2 GET /agents/{agentCode}/games/{gameCode}                                                              | 103 |
| 9. HEARTBEAT 实时系统监测                                                                                       | 106 |
| 9.1 GET /heartbeat                                                                                        | 106 |

|                                                                                      |     |
|--------------------------------------------------------------------------------------|-----|
| 10. PLAYERS 玩家                                                                       | 107 |
| 10.1 GET /agents/{agentCode}/players/{playerId}                                      | 107 |
| 10.2 PATCH /agents/{agentCode}/players/{playerId}                                    | 108 |
| 10.3 POST /agents/{agentCode}/players                                                | 110 |
| 10.4 GET /agents/{agentCode}/players/{playerId}/products/{productId}                 | 111 |
| 10.5 GET /agents/{agentCode}/players/{playerId}/products                             | 113 |
| 10.6 POST /agents/{agentCode}/players/{playerId}/products/{productId}/betVisualizers | 114 |
| 10.7 POST /agents/{agentCode}/players/{playerId}/betVisualizers                      | 116 |
| 11. REPORTS 报表                                                                       | 119 |
| 11.1 POST /agents/{agentCode}/reports/ledger                                         | 119 |
| 11.2 POST /agents/{agentCode}/reports/financial                                      | 120 |
| 11.3 POST /agents/{agentCode}/reports/gameAnalysis                                   | 122 |
| 11.4 POST /agents/{agentCode}/reports/playerGameAnalysis                             | 124 |
| 11.5 POST /agents/{agentCode}/reports/progressiveGamePlay                            | 126 |
| 11.6 POST /agents/{agentCode}/reports/progressiveWins                                | 128 |
| 11.7 POST /agents/{agentCode}/reports/fortuneRewards                                 | 130 |
| 11.8 POST /agents/{agentCode}/reports/liveDealerPromotions                           | 131 |
| 11.9 POST /agents/{agentCode}/reports/tournamentWins                                 | 132 |
| 12. SESSIONS 游戏启动                                                                    | 135 |
| 12.1 POST /agents/{agentCode}/players/{playerId}/sessions                            | 135 |
| 13. TRANSACTIONS 交易                                                                  | 138 |
| 13.1 GET /agents/{agentCode}/WalletTransactions                                      | 138 |
| 13.2 POST /agents/{agentCode}/WalletTransactions                                     | 139 |
| 13.3 GET /agents/{agentCode}/WalletTransactions/{walletTransactionId}                | 143 |

## SECURITY SCHEMES

| KEY    | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|--------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OAuth2 | oauth2 | <p>All API methods require a valid <b>JWT</b> (JSON Web Token).</p> <p>In order to get a <b>JWT</b> you must use POST method to <b>[STS URL]/connect/token</b></p> <p>A dedicated <b>[STS URL]</b> will be provided to you by your Account Manager.</p> <p>The following fields are mandatory in the body:</p> <ul style="list-style-type: none"><li><b>client_id</b> (will be provided by your Account Manager)</li><li><b>client_secret</b> (will be provided by your Account Manager)</li><li><b>grant_type=client_credentials</b></li></ul> <p>Header should contain:</p> <ul style="list-style-type: none"><li><b>Content-Type = application/x-www-form-urlencoded</b></li></ul> <p>所有API方法都需要有效的<b>JWT</b>（JSON Web令牌）。</p> <p>要获得<b>JWT</b>，您必须使用POST <b>[STS URL]/connect/token</b></p> <p>您的客户经理将为您提供专用的<b>[STS URL]</b>。</p> <p>以下字段在正文中是必填字段：</p> <ul style="list-style-type: none"><li><b>client_id</b>（将由您的客户经理提供）</li><li><b>client_secret</b>（将由您的客户经理提供）</li><li><b>grant_type = client_credentials</b></li></ul> <p>标题应包含：</p> <ul style="list-style-type: none"><li><b>Content-Type = application/x-www-form-urlencoded</b></li></ul> |

# API

## 1. BETS 投注

### 1.1 GET /agents/{agentCode}/bets

Get bets details (bet by bet) 获取下注信息

Returns specific bet details according to specified search criteria sorted in a sequence of when it was stored on the MG+ system. 根据指定的搜索条件並依照存储在 MG+ 系统上的时间顺序返回有关投注的信息.

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

#### QUERY PARAMETERS

| NAME          | TYPE                         | EXAMPLE | DESCRIPTION                                                                                                                                                                      |
|---------------|------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *limit        | int32<br>between 1 and 20000 |         | Maximum number of returned items, between 1 and 20000.<br>返回记录的最大数量，在 1 到 20000 之间                                                                                               |
| startingAfter | string                       |         | Starting betUid for cursor-based pagination. Mandatory for agents using Multiple Betlogs, input validation apply.<br>为基于光标的分页启动 betUID. 如使用多个Betlogs, 方法必须放入” startingAfter” 的参数 |
| Channel       | boolean                      |         | Add the Channel parameter to the response.<br>响应添加渠道参数                                                                                                                           |

### RESPONSE

STATUS CODE - 200: OK. Bet list returned  
下注列单已经获取

#### RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                                |
|--------------------------------------|--------|----------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                            |
| betUID                               | string | Bet unique ID. Field length is exactly 36.<br>独一下注编号。字段长度应正好是 36 个字符       |
| createdDateUTC                       | string | timestamp of the bet when logged on MG Plus system.<br>在 MG Plus 系统创建下注的时间 |
| gameStartTimeUTC                     | string | timestamp of the bet starting time<br>下注开始的时间                              |
| gameEndTimeUTC                       | string | timestamp of the bet ending time<br>下注结束的时间                                |

| NAME                  | TYPE    | DESCRIPTION                                                                                                                                                                                             |
|-----------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| playerId              | string  | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。                                      |
| productId             | string  | 3 to 3 chars<br>Product ID<br>产品编号                                                                                                                                                                      |
| productPlayerId       | string  | Product Player ID<br>个别产品上的玩家ID                                                                                                                                                                         |
| platform              | enum    | ALLOWED:Unknown, Desktop, Mobile<br>Game platform (Unknown/Desktop/Mobile)<br>游戏平台 (Unknown/Desktop/Mobile)                                                                                             |
| gameCode              | string  | Game code<br>游戏代码                                                                                                                                                                                       |
| channel               | string  | channel<br>渠道                                                                                                                                                                                           |
| currency              | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies. 指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币 |
| betAmount             | number  | Bet amount.<br>下注金额                                                                                                                                                                                     |
| payoutAmount          | number  | Payout amount<br>派彩金额                                                                                                                                                                                   |
| betStatus             | enum    | ALLOWED:Closed, Cancelled<br>Bet status<br>投注状态                                                                                                                                                         |
| PCA                   | number  | Progressive Contribution Amount<br>彩池贡献金额                                                                                                                                                               |
| externalTransactionId | string  | Bet ID as seen in Playcheck<br>Playcheck 中所见的 Bet ID                                                                                                                                                    |
| metadata              | object  |                                                                                                                                                                                                         |
| sessionId             | string  |                                                                                                                                                                                                         |
| TransactionId         | string  |                                                                                                                                                                                                         |
| Description           | string  | Detailed information about the wager that was placed. Note - will only contain data for Virtual Sports games.<br>关于下注的详细信息。请注意-仅会回传虚拟体育 (Virtual Sports) 游戏的数据。                                         |
| IsFreeGame            | boolean | Flag indicating whether the bet is part of a Free Game offer. 当该值为”真”时，则该交易为免费注单的一部分。                                                                                                                   |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                               |
|-----------------------------|--------|-------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                           |
| code                        | string | InputValidationError                                                                      |
| message                     | string | The field Limit must be greater than 0 and less or equal to 20000 字段必须大于 0 并且小于或者等于 20000 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE | DESCRIPTION |
|-----------------------------|------|-------------|
| OBJECT WITH BELOW STRUCTURE |      |             |

| NAME           | TYPE   | DESCRIPTION  |
|----------------|--------|--------------|
| error          | object |              |
| code           | string | GeneralError |
| message        | string | Server error |
| message-zh-CHS | string | 服务器错误        |

## 1.2 GET /agents/{agentCode}/players/{playerId}/products/{productId}/incompleteBets

### Get open bets 获取未结束的下注

Returns open bets for player. 返回玩家的未结束下注。

## REQUEST

### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                             |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| *productId | string |         | The product ID<br>产品编号                                                                                                                                             |

## RESPONSE

STATUS CODE - 200: Open bets list returned.  
未结束下注列单已回复

### RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                                                                                                                                                      |
|--------------------------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                                                                  |
| playerId                             | string | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。                               |
| productId                            | string | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                              |
| gameCode                             | string | Game code<br>游戏代码                                                                                                                                                                                |
| platform                             | string | Platform Type - Please note that the platform parameter is relevant only for most of the Slots games, "unknown" will be returned for all other games.<br>平台 - 请注意，平台参数仅与老虎机游戏有关，对于所有其他游戏，将返回“未知” |
| betAmount                            | number | Bet amount.<br>下注金额                                                                                                                                                                              |
| payoutAmount                         | number | Payout amount ( can be null ).<br>彩金金额（可以为 null）。                                                                                                                                                |
| createdDateUtc                       | string | The exact time of the open bet in UTC ( can be null ).<br>未结束下注的 UTC 准确时间（可以为 null）。                                                                                                             |

| NAME                       | TYPE   | DESCRIPTION                                                                                            |
|----------------------------|--------|--------------------------------------------------------------------------------------------------------|
| estimatedSettlementTimeUtc | string | The estimated time of the open bet settlement in UTC ( can be null ).<br>未结束下注结算的 UTC 大概时间 （可以为 null）。 |
| externalTransactionId      | string | Bet ID as seen in Playcheck<br>Playcheck 中所见的 Bet ID                                                   |
| metadata                   | object |                                                                                                        |
| Description                | string | This property is no longer being used.<br>此属性已被弃用。                                                     |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Player not found  
没有找到玩家

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION           |
|-----------------------------|--------|-----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                       |
| code                        | string | PlayerDoesNotExist    |
| message                     | string | Player does not exist |
| message-zh-CHS              | string | 玩家不存在                 |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 1.3 GET /agents/{agentCode}/players/{playerId}/incompleteBets

Get open bets 获取未结束的下注

Returns open bets for player. 返回玩家的未结束下注。

## REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                         |
|------------|--------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                              |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符号 (-) 和下划线 (\_)。 |

## RESPONSE

STATUS CODE - 200: Open bets list returned.  
未结束下注列单已回复

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                                                                                                                                                      |
|--------------------------------------|--------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                                                                  |
| product                              | string | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                              |
| status                               | enum   | ALLOWED:Success, Failure, NotSupported, Partial<br>Product Response Status<br>产品返回状态                                                                                                             |
| openBets                             | array  |                                                                                                                                                                                                  |
| playerId                             | string | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符号 (-) 和下划线 (\_)。                              |
| productId                            | string | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                              |
| gameCode                             | string | Game code<br>游戏代码                                                                                                                                                                                |
| platform                             | string | Platform Type - Please note that the platform parameter is relevant only for most of the Slots games, "unknown" will be returned for all other games.<br>平台 - 请注意，平台参数仅与老虎机游戏有关，对于所有其他游戏，将返回“未知” |
| betAmount                            | number | Bet amount.<br>下注金额                                                                                                                                                                              |
| payoutAmount                         | number | Payout amount ( can be null ).<br>彩金金额（可以为 null）。                                                                                                                                                |
| createdDateUtc                       | string | The exact time of the open bet in UTC ( can be null ).<br>未结束下注的 UTC 准确时间（可以为 null）。                                                                                                             |
| estimatedSettlementTimeUtc           | string | The estimated time of the open bet settlement in UTC ( can be null ).<br>未结束下注结算的 UTC 大概时间（可以为 null）。                                                                                            |
| externalTransactionId                | string | Bet ID as seen in Playcheck<br>Playcheck 中所见的 Bet ID                                                                                                                                             |
| metadata                             | object |                                                                                                                                                                                                  |
| Description                          | string | This property is no longer being used.<br>此属性已被弃用。                                                                                                                                               |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION          |
|-----------------------------|--------|----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                      |
| code                        | string | InputValidationError |

| NAME    | TYPE   | DESCRIPTION                                                                                                                                    |
|---------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| message | string | The field playerId must be a string with a maximum length of 50. Using only numbers and english alphabets. playerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Player not found  
没有找到玩家

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION           |
|-----------------------------|--------|-----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                       |
| code                        | string | PlayerDoesNotExist    |
| message                     | string | Player does not exist |
| message-zh-CHS              | string | 玩家不存在                 |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

### 1.4 GET /agents/{agentCode}/liveDealerBets

Get liveDealer bets details (bet by bet)  
获取下注信息

Please contact your business representative before integrating this API.

请在集成此 API 前联系您的客户经理或服务经理.

Returns information about liveDealer bets according to specified search criteria.

根据指定的搜索条件返回投注的信息。

### REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

## QUERY PARAMETERS

| NAME          | TYPE                         | EXAMPLE | DESCRIPTION                                                                                                                                                                      |
|---------------|------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| limit         | int32<br>between 1 and 20000 |         | Maximum number of returned items, between 1 and 20000, default value is 1000.<br>返回记录的最大数量，在 1 到 20000 之间, 默认值1000。                                                              |
| startingAfter | string                       |         | Starting betUid for cursor-based pagination. Mandatory for agents using Multiple Betlogs, input validation apply.<br>为基于光标的分页启动 betUID. 如使用多个Betlogs, 方法必须放入” startingAfter” 的参数 |

## RESPONSE

STATUS CODE - 200: OK. Bet list returned  
下注列单已经获取

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                                                                                                                                                              |
|--------------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                                                                          |
| betUID                               | string | Bet unique ID. Field length is exactly 36.<br>独一无二的下注编号。字段长度应正好是 36 个字符                                                                                                                                  |
| createdDateUTC                       | string | timestamp of the bet when logged on MG Plus system.<br>在 MG Plus 系统创建下注的时间                                                                                                                               |
| gameStartTimeUTC                     | string | timestamp of the bet starting time<br>下注开始的时间                                                                                                                                                            |
| gameEndTimeUTC                       | string | timestamp of the bet ending time<br>下注结束的时间                                                                                                                                                              |
| playerId                             | string | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。                                       |
| productId                            | string | 3 to 3 chars<br>Product ID<br>产品编号                                                                                                                                                                       |
| productPlayerId                      | string | Product Player ID<br>个别产品上的玩家ID                                                                                                                                                                          |
| platform                             | enum   | ALLOWED:Unknown, Desktop, Mobile<br>Game platform (Unknown/Desktop/Mobile)<br>游戏平台 (Unknown/Desktop/Mobile)                                                                                              |
| gameCode                             | string | Game code<br>游戏代码                                                                                                                                                                                        |
| currency                             | string | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies. 指定货币时，使用 [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币 |
| betAmount                            | number | Bet amount.<br>下注金额                                                                                                                                                                                      |
| payoutAmount                         | number | Payout amount<br>派彩金额                                                                                                                                                                                    |
| betStatus                            | enum   | ALLOWED:Closed, Cancelled<br>Bet status<br>投注状态                                                                                                                                                          |
| externalTransactionId                | string | Bet ID as seen in Playcheck<br>Playcheck 中所见的 Bet ID                                                                                                                                                     |

| NAME            | TYPE    | DESCRIPTION                     |
|-----------------|---------|---------------------------------|
| metadata        | object  |                                 |
| sessionId       | string  | Session ID<br>会话编号              |
| transactionId   | string  | Transaction ID<br>交易编号          |
| liveDealerInfo  | object  |                                 |
| roundId         | string  | Round ID<br>回合编号                |
| tableCode       | string  | Table Code<br>牌桌编号              |
| transactionInfo | object  |                                 |
| betType         | string  | Bet Type<br>下注类型                |
| betAmount       | number  | Bet Amount<br>下注金额              |
| payoutAmount    | number  | Payout Amount<br>派彩金额           |
| placeBetTimeUtc | string  | Place Bet Time UTC<br>下注时间(UTC) |
| baccaratInfo    | object  |                                 |
| player          | object  |                                 |
| hand            | object  |                                 |
| cards           | array   |                                 |
| suit            | string  | Suit of the cards.<br>牌的花色      |
| rank            | string  | Rank of the cards.<br>牌的等级      |
| banker          | object  |                                 |
| hand            | object  |                                 |
| cards           | array   |                                 |
| suit            | string  | Suit of the cards.<br>牌的花色      |
| rank            | string  | Rank of the cards.<br>牌的等级      |
| result          | object  |                                 |
| outcome         | string  | Outcome of the game.<br>游戏结果    |
| playerScore     | integer | Player' s score.<br>玩家得分        |
| bankerScore     | integer | Banker' s score.<br>庄家得分        |
| sicboInfo       | object  |                                 |
| diceResults     | array   | Dice results.<br>骰子点数结果         |
|                 | integer |                                 |
| result          | object  |                                 |

| NAME              | TYPE    | DESCRIPTION                        |
|-------------------|---------|------------------------------------|
| outcome           | integer | Sum of the dice results.<br>骰子点数总和 |
| rouletteInfo      | object  |                                    |
| result            | object  |                                    |
| number            | integer | Roulette wheel number.<br>轮盘轮号码    |
| colour            | string  | Colour of the number.<br>号码的颜色     |
| dragonTigerInfo   | object  |                                    |
| dragon            | object  |                                    |
| hand              | object  |                                    |
| cards             | array   |                                    |
| suit              | string  | Suit of the cards.<br>牌的花色         |
| rank              | string  | Rank of the cards.<br>牌的等级         |
| tiger             | object  |                                    |
| hand              | object  |                                    |
| cards             | array   |                                    |
| suit              | string  | Suit of the cards.<br>牌的花色         |
| rank              | string  | Rank of the cards.<br>牌的等级         |
| result            | object  |                                    |
| outcome           | string  | Outcome of the game.<br>游戏结果       |
| dragonScore       | integer | Dragon score.<br>龙的得分              |
| tigerScore        | integer | Tiger score.<br>虎的得分               |
| cardsChampionInfo | object  |                                    |
| home              | object  |                                    |
| hand              | object  |                                    |
| cards             | array   |                                    |
| suit              | string  | Suit of the cards.<br>牌的花色         |
| rank              | string  | Rank of the cards.<br>牌的等级         |
| away              | object  |                                    |
| hand              | object  |                                    |
| cards             | array   |                                    |

| NAME          | TYPE    | DESCRIPTION                                            |
|---------------|---------|--------------------------------------------------------|
| suit          | string  | Suit of the cards.<br>牌的花色                             |
| rank          | string  | Rank of the cards.<br>牌的等级                             |
| result        | object  |                                                        |
| outcome       | string  | Outcome of the game.<br>游戏结果                           |
| homeScore     | integer | Home score.<br>主场得分                                    |
| awayScore     | integer | Away score.<br>客场得分                                    |
| blackjackInfo | object  |                                                        |
| dealer        | object  |                                                        |
| hand          | object  |                                                        |
| cards         | array   |                                                        |
| suit          | string  | Suit of the cards.<br>牌的花色                             |
| rank          | string  | Rank of the cards.<br>牌的等级                             |
| players       | array   |                                                        |
| seatNumber    | string  | Player' s seat number.<br>玩家的座位编号                      |
| isBetBehind   | boolean | Indicates if the player has a bet behind.<br>玩家是否有跟随下注 |
| isSplit       | boolean | Indicates if the player splits the cards.<br>指示玩家是否分牌  |
| hands         | array   |                                                        |
| cards         | array   |                                                        |
| suit          | string  | Suit of the cards.<br>牌的花色                             |
| rank          | string  | Rank of the cards.<br>牌的等级                             |
| result        | object  |                                                        |
| playerScores  | array   | Player' s score.<br>玩家总点数                              |
| seatNumber    | string  | Player's seat number.<br>玩家座位编号                        |
| scores        | array   | Score of the individual player.<br>单个玩家的总点数            |
|               | integer |                                                        |
| outcome       | array   | Winner of the game.<br>游戏的获胜者                          |

| NAME                  | TYPE    | DESCRIPTION                                           |
|-----------------------|---------|-------------------------------------------------------|
| string                |         |                                                       |
| dealerScore           | integer | Dealer' s score.<br>荷官的总点数                            |
| scalableBlackjackInfo | object  |                                                       |
| dealer                | object  |                                                       |
| hand                  | object  |                                                       |
| cards                 | array   |                                                       |
| suit                  | string  | Suit of the cards.<br>牌的花色                            |
| rank                  | string  | Rank of the cards.<br>牌的等级                            |
| player                | object  |                                                       |
| hands                 | array   |                                                       |
| cards                 | array   |                                                       |
| suit                  | string  | Suit of the cards.<br>牌的花色                            |
| rank                  | string  | Rank of the cards.<br>牌的等级                            |
| isSplit               | boolean | Indicates if the player splits the cards.<br>指示玩家是否分牌 |
| result                | object  |                                                       |
| playerScores          | array   | Player' s score.<br>玩家总点数                             |
| integer               |         |                                                       |
| outcome               | array   | Winner of the game.<br>游戏的获胜者                         |
| string                |         |                                                       |
| dealerScore           | integer | Dealer' s score.<br>荷官总点数                             |
| holoRouletteInfo      | object  |                                                       |
| result                | array   |                                                       |
| number                | integer | Roulette wheel number.<br>轮盘轮号码                       |
| colour                | string  | Colour of the number.<br>号码的颜色                        |
| wheelType             | string  | Wheel types.<br>轮盘类型                                  |
| diamondRouletteInfo   | object  |                                                       |
| result                | array   |                                                       |
| number                | integer | Roulette wheel number.<br>轮盘轮号码                       |

| NAME                  | TYPE    | DESCRIPTION                                                                                                                  |
|-----------------------|---------|------------------------------------------------------------------------------------------------------------------------------|
| colour                | string  | Colour of the number.<br>号码的颜色                                                                                               |
| wheelType             | string  | Wheel types.<br>钻石轮盘游戏结果                                                                                                     |
| luckyNumbers          | object  |                                                                                                                              |
| bonusGame             | object  |                                                                                                                              |
| totalMultiplier       | integer | Total multiplier of the bonus game.<br>奖励游戏的总倍率                                                                              |
| guaranteedWin         | integer | Guaranteed Win Amount.<br>保证赢取金额                                                                                             |
| guaranteedMultiplier  | integer | Guaranteed Multiplier.<br>保证的倍率                                                                                              |
| rounds                | array   |                                                                                                                              |
| level                 | string  | Level of the bonus game.<br>奖励游戏级别                                                                                           |
| decision              | string  | Player' s selection.<br>玩家选择                                                                                                 |
| multiplier            | integer | Multiplier of the selection.<br>选择的倍率                                                                                        |
| cashWheelCarnivalInfo | object  |                                                                                                                              |
| wheelSegments         | array   |                                                                                                                              |
| betType               | string  | Bet type available for players.<br>玩家可使用的投注类型                                                                                |
| multiplier            | number  | Multiplier of each number.<br>每个数字对应的倍率                                                                                      |
| majesticInfo          | object  |                                                                                                                              |
| multiplier            | number  | Majestic number.<br>豪华数字的倍率                                                                                                  |
| number                | string  | Multiplier of the majestic number.<br>豪华数字                                                                                   |
| boosters              | array   | Multiplier of the booster. It will only be triggered when the wheel stops on the booster sector.<br>增强器的倍率。只有当轮盘停在增强器区时才会触发。 |
|                       | integer |                                                                                                                              |
| result                | object  |                                                                                                                              |
| outcome               | string  | Outcome of the game.<br>游戏结果                                                                                                 |
| finalMultiplier       | number  | Multiplier of the selected number.<br>所选数字的倍率                                                                                |
| pokerInfo             | object  |                                                                                                                              |
| dealer                | object  |                                                                                                                              |
| hand                  | object  |                                                                                                                              |

| NAME           | TYPE    | DESCRIPTION                                                                   |
|----------------|---------|-------------------------------------------------------------------------------|
| holeCards      | array   | Dealer' s hole cards.<br>荷官的盲牌                                                |
| suit           | string  | Suit of the cards.<br>牌的花色                                                    |
| rank           | string  | Rank of the cards.<br>牌的等级                                                    |
| finalHand      | array   | Dealer' s final hand.<br>荷官的最终手牌                                              |
| suit           | string  | Suit of the cards.<br>牌的花色                                                    |
| rank           | string  | Rank of the cards.<br>牌的等级                                                    |
| combination    | string  | Dealer' s combination.<br>荷官的组合                                               |
| isQualified    | boolean | Indicates if the dealer has qualified for the current round.<br>显示荷官在当前回合中的资格 |
| player         | object  |                                                                               |
| hand           | object  |                                                                               |
| holeCards      | array   | Player' s hole cards.<br>玩家的盲牌                                                |
| suit           | string  | Suit of the cards.<br>牌的花色                                                    |
| rank           | string  | Rank of the cards.<br>牌的等级                                                    |
| finalHand      | array   | Player' s final hand.<br>玩家的最终手牌                                              |
| suit           | string  | Suit of the cards.<br>牌的花色                                                    |
| rank           | string  | Rank of the cards.<br>牌的等级                                                    |
| combination    | string  | Player' s combination.<br>玩家的组合                                               |
| communityCards | array   | Community Cards.<br>公共牌                                                       |
| suit           | string  | Suit of the cards.<br>牌的花色                                                    |
| rank           | string  | Rank of the cards.<br>牌的等级                                                    |
| result         | object  |                                                                               |
| outcome        | string  | Outcome of the game.<br>游戏的结果                                                 |
| highlights     | object  |                                                                               |

| NAME         | TYPE   | DESCRIPTION                           |
|--------------|--------|---------------------------------------|
| player       | array  | Player' s cards.<br>玩家的牌              |
| suit         | string | Suit of the cards.<br>牌的花色            |
| rank         | string | Rank of the cards.<br>牌的等级            |
| dealer       | array  | Dealer' s cards.<br>荷官的牌              |
| suit         | string | Suit of the cards.<br>牌的花色            |
| rank         | string | Rank of the cards.<br>牌的等级            |
| kickerCard   | object |                                       |
| suit         | string | Suit of the cards.<br>牌的花色            |
| rank         | string | Rank of the cards.<br>牌的等级            |
| sideBetCards | array  | Side bet cards of the game.<br>游戏的边注牌 |
| suit         | string | Suit of the cards.<br>牌的花色            |
| rank         | string | Rank of the cards.<br>牌的等级            |

EXAMPLE 1:

```
[
{
  "betUID": "0362A2570121470B000100000012101D3C1D",
  "betID": "AIBQAAQAHTINQCQAAAAAGAAAAA",
  "createdDateUTC": "2024-08-08T06:15:20.418",
  "gameStartTimeUTC": "2024-08-08T06:14:06.193",
  "gameEndTimeUTC": "2024-08-08T06:14:05.964",
  "playerId": "qatest",
  "productId": "SMG",
  "productPlayerId": "M0G0993689649",
  "platform": "Mobile",
  "gameCode": "SMG_MGLiveGrand_SpeedBaccarat1",
  "currency": "CNY",
  "betAmount": 50,
  "payoutAmount": 100,
  "betStatus": "Closed",
  "externalTransactionId": "1372831719/24",
  "metadata": {
    "sessionId": 1372831719,
    "transactionId": 24,
    "liveDealerInfo": {
      "roundId": "#06:13:41",
      "tableCode": "Lotus Speed Baccarat 1",
      "transactionInfo": [
        {
          "betType": "player",
          "betAmount": 50,
          "payoutAmount": 100
        }
      ]
    }
  }
}
```

```

    ],
    "baccaratInfo": {
      "player": {
        "hand": {
          "cards": [
            {
              "suit": "diamonds",
              "rank": "Q"
            },
            {
              "suit": "diamonds",
              "rank": "9"
            }
          ]
        }
      },
      "banker": {
        "hand": {
          "cards": [
            {
              "suit": "clubs",
              "rank": "3"
            },
            {
              "suit": "clubs",
              "rank": "4"
            }
          ]
        }
      },
      "result": {
        "outcome": "Player",
        "playerScore": 9,
        "bankerScore": 7
      }
    }
  ]
}

```

## EXAMPLE 2:

```

[
  {
    "betUID": "03963E400126470B0001000000121ECFA2D1",
    "betID": "AIBQAAQAHTINQCQAAAAAAKQAAAA",
    "createdDateUTC": "2024-08-13T05:49:47.542",
    "gameStartTimeUTC": "2024-08-13T05:48:23.533",
    "gameEndTimeUTC": "2024-08-13T05:47:38.543",
    "playerId": "qatest",
    "productId": "SMG",
    "productPlayerId": "M0G0993689649",
    "platform": "Desktop",
    "gameCode": "SMG_titaniumLiveGames_Sicbo",
    "currency": "CNY",
    "betAmount": 5,
    "payoutAmount": 10,
    "betStatus": "Closed",
    "externalTransactionId": "1376836877/42",
    "metadata": {
      "sessionId": 1376836877,
      "transactionId": 42,
      "liveDealerInfo": {
        "roundId": "1961077",
        "tableCode": "Sicbo_E1_S2",
        "transactionInfo": [
          {
            "betType": "big",
            "betAmount": 5,
            "payoutAmount": 10
          }
        ]
      },
      "sicboInfo": {
        "diceResults": [

```

```

4,
5,
5
],
"result": {
"outcome": 0
}
}
}
}
}
]

```

### EXAMPLE 3:

```

[
{
"betUID": "039F7FEB0121470B00010000001210732E51",
"betID": "AIBQAAQAHTINQCQAAAAAAHQAAAA",
"createdDateUTC": "2024-08-08T08:56:50.847",
"gameStartTimeUTC": "2024-08-08T08:55:37.593",
"gameEndTimeUTC": "2024-08-08T08:55:37.348",
"playerId": "qatest",
"productId": "SMG",
"productPlayerId": "M0G0993689649",
"platform": "Mobile",
"gameCode": "SMG_MGLiveGrand_Roulette",
"currency": "CNY",
"betAmount": 50,
"payoutAmount": 0,
"betStatus": "Closed",
"externalTransactionId": "1372913224/30",
"metadata": {
"sessionId": 1372913224,
"transactionId": 30,
"liveDealerInfo": {
"roundId": "#08:55:01",
"tableCode": "Roulette OnAir",
"transactionInfo": [
{
"betType": "straight34",
"betAmount": 50,
"payoutAmount": 0
}
]
},
"rouletteInfo": {
"result": {
"number": 25,
"colour": "red"
}
}
}
}
]

```

### EXAMPLE 4:

```

[
{
"betUID": "033FB0630137470B000100000012501A5784",
"betID": "AIBQAAQAHTINQCQAAAAABFQAAAA",
"createdDateUTC": "2024-08-30T06:28:30.399",
"gameStartTimeUTC": "2024-08-30T06:27:27.750",
"gameEndTimeUTC": "2024-08-30T06:27:28.040",
"playerId": "qatest",
"productId": "SMG",
"productPlayerId": "M0G0993689649",
"platform": "Mobile",
"gameCode": "SMG_MGLiveGrand_DragonTiger",
"currency": "CNY",
"betAmount": 10,
"payoutAmount": 0,
"betStatus": "Closed",
"externalTransactionId": "1389607302/150",

```

```

"metadata": {
  "sessionId": 1389607302,
  "transactionId": 150,
  "liveDealerInfo": {
    "roundId": "#06:27:09",
    "tableCode": "Blazing Dragon Tiger",
    "transactionInfo": [
      {
        "betType": "dragonTigerTie",
        "betAmount": 10,
        "payoutAmount": 0
      }
    ],
    "dragonTigerInfo": {
      "dragon": {
        "hand": {
          "cards": [
            {
              "suit": "spades",
              "rank": "A"
            }
          ]
        }
      },
      "tiger": {
        "hand": {
          "cards": [
            {
              "suit": "clubs",
              "rank": "6"
            }
          ]
        }
      }
    ],
    "result": {
      "outcome": "tiger",
      "dragonScore": 1,
      "tigerScore": 6
    }
  }
}

```

#### EXAMPLE 5:

```

[
  {
    "betUID": "03B0A4C7012F470B00010000001239211BCC",
    "betID": "AIBQAAQAHTINQCQAAAAAAZIAAAAA",
    "createdDateUTC": "2024-08-22T08:17:41.040",
    "gameStartTimeUTC": "2024-08-22T08:16:22.310",
    "gameEndTimeUTC": "2024-08-22T08:16:22.623",
    "playerId": "qatest",
    "productId": "SMG",
    "productPlayerId": "M0G0993689649",
    "platform": "Mobile",
    "gameCode": "SMG_MGLiveGrand_CardsChampion",
    "currency": "CNY",
    "betAmount": 50,
    "payoutAmount": 0,
    "betStatus": "Closed",
    "externalTransactionId": "1384171693/101",
    "metadata": {
      "sessionId": 1384171693,
      "transactionId": 101,
      "liveDealerInfo": {
        "roundId": "#08:15:58",
        "tableCode": "Card Matchup",
        "transactionInfo": [
          {
            "betType": "home",
            "betAmount": 50,
            "payoutAmount": 0
          }
        ]
      }
    }
  }
]

```

```

    ],
    "cardsChampionInfo": {
      "home": {
        "hand": {
          "cards": [
            {
              "suit": "hearts",
              "rank": "6"
            }
          ]
        }
      },
      "away": {
        "hand": {
          "cards": [
            {
              "suit": "hearts",
              "rank": "K"
            }
          ]
        }
      }
    },
    "result": {
      "outcome": "away",
      "homeScore": 6,
      "awayScore": 13
    }
  }
}
]

```

#### EXAMPLE 6:

```

[
  {
    "betUID": "03A2EBDD0130470B0001000000123C02267E",
    "betID": "AIBQAAQAHTINQCQAAAAAA4QAAAA",
    "createdDateUTC": "2024-08-23T08:42:00.994",
    "gameStartTimeUTC": "2024-08-23T08:40:34.263",
    "gameEndTimeUTC": "2024-08-23T08:40:39.102",
    "playerId": "qatest",
    "productId": "SMG",
    "productPlayerId": "M0G0993689649",
    "platform": "Mobile",
    "gameCode": "SMG_MGLiveGrand_BlackjackLondon",
    "currency": "CNY",
    "betAmount": 50,
    "payoutAmount": 100,
    "betStatus": "Closed",
    "externalTransactionId": "1384919591/114",
    "metadata": {
      "sessionId": 1384919591,
      "transactionId": 114,
      "liveDealerInfo": {
        "roundId": "#08:39:42",
        "tableCode": "Network CK Blackjack - London",
        "transactionInfo": [
          {
            "betType": "main",
            "betAmount": 50,
            "payoutAmount": 100
          }
        ]
      }
    },
    "blackjackInfo": {
      "dealer": {
        "hand": {
          "cards": [
            {
              "suit": "hearts",
              "rank": "7"
            }
          ]
        },
        {
          "suit": "diamonds",

```

```

"rank": "3"
},
{
  "suit": "clubs",
  "rank": "4"
},
{
  "suit": "spades",
  "rank": "8"
}
]
}
},
"players": [
  {
    "seatNumber": "D",
    "isBetBehind": false,
    "isSplit": false,
    "hands": [
      {
        "cards": [
          {
            "suit": "hearts",
            "rank": "Q"
          },
          {
            "suit": "clubs",
            "rank": "3"
          },
          {
            "suit": "clubs",
            "rank": "7"
          }
        ]
      }
    ]
  },
  {
    "seatNumber": "C",
    "isBetBehind": true,
    "isSplit": false,
    "hands": [
      {
        "cards": [
          {
            "suit": "diamonds",
            "rank": "8"
          },
          {
            "suit": "spades",
            "rank": "4"
          },
          {
            "suit": "spades",
            "rank": "5"
          }
        ]
      }
    ]
  },
  {
    "seatNumber": "E",
    "isBetBehind": true,
    "isSplit": false,
    "hands": [
      {
        "cards": [
          {
            "suit": "diamonds",
            "rank": "10"
          },
          {
            "suit": "diamonds",
            "rank": "J"
          }
        ]
      }
    ]
  }
]
}

```

```

],
"result": {
  "playerScores": [
    {
      "seatNumber": "D",
      "scores": [
        20
      ],
      "outcome": [
        "player"
      ]
    },
    {
      "seatNumber": "C",
      "scores": [
        17
      ],
      "outcome": [
        "player"
      ]
    },
    {
      "seatNumber": "E",
      "scores": [
        20
      ],
      "outcome": [
        "player"
      ]
    }
  ],
  "dealerScore": 22
}
}
}
]

```

#### EXAMPLE 7:

```

[
  {
    "betUID": "035B5283012E470B0001000000123622C121",
    "betID": "AIBQAAQAECIBYCYAAAAABXYBAAAA",
    "createdDateUTC": "2024-08-21T07:03:03.515",
    "gameStartTimeUTC": "2024-08-21T07:01:52.910",
    "gameEndTimeUTC": "2024-08-21T07:01:57.742",
    "playerId": "testkiosk002",
    "productId": "SMG",
    "productPlayerId": "M0G209913364",
    "platform": "Mobile",
    "gameCode": "SMG_MGLiveGrand_EverplayBlackjack",
    "currency": "CNY",
    "betAmount": 10,
    "payoutAmount": 0,
    "betStatus": "Closed",
    "externalTransactionId": "1383418083/479",
    "metadata": {
      "sessionId": 1383418083,
      "transactionId": 479,
      "liveDealerInfo": {
        "roundId": "#07:00:42",
        "tableCode": "Eclipse Blackjack™",
        "transactionInfo": [
          {
            "betType": "split",
            "betAmount": 10,
            "payoutAmount": 0
          }
        ]
      }
    },
    "scalableBlackjackInfo": {
      "dealer": {
        "hand": {
          "cards": [
            {

```

```

"suit": "clubs",
"rank": "6"
},
{
"suit": "diamonds",
"rank": "7"
},
{
"suit": "clubs",
"rank": "8"
}
]
},
"player": {
"hands": [
{
"cards": [
{
"suit": "spades",
"rank": "10"
},
{
"suit": "diamonds",
"rank": "9"
}
]
},
{
"cards": [
{
"suit": "clubs",
"rank": "10"
},
{
"suit": "hearts",
"rank": "K"
}
]
}
],
"isSplit": true
},
"result": {
"playerScores": [
19,
20
],
"outcome": [
"dealer",
"dealer"
],
"dealerScore": 21
}
}
}
}
]

```

#### EXAMPLE 8:

```

[
{
"betUID": "03A01CA20121470B0001000000121048C0CB",
"betID": "AIBQAAQAECIBYCYAAAAANIBAAAA",
"createdDateUTC": "2024-08-08T07:36:41.376",
"gameStartTimeUTC": "2024-08-08T07:35:22.183",
"gameEndTimeUTC": "2024-08-08T07:35:21.942",
"playerId": "testkiosk002",
"productId": "SMG",
"productPlayerId": "M0G209913364",
"platform": "Mobile",
"gameCode": "SMG_MGLiveGrand_HoloRoulette",
"currency": "CNY",
"betAmount": 5,
"payoutAmount": 2,

```

```

"betStatus": "Closed",
"externalTransactionId": "1372880336/309",
"metadata": {
"sessionId": 1372880336,
"transactionId": 309,
"liveDealerInfo": {
"roundId": "#07:34:21",
"tableCode": "Nexus Roulette™",
"transactionInfo": [
{
"betType": "corner5_6_8_9",
"betAmount": 1,
"payoutAmount": 0
},
{
"betType": "holo",
"betAmount": 1,
"payoutAmount": 0
},
{
"betType": "wheelSum_41_74",
"betAmount": 1,
"payoutAmount": 2
},
{
"betType": "line25_26_27_28_29_30",
"betAmount": 1,
"payoutAmount": 0
},
{
"betType": "street31_32_33",
"betAmount": 1,
"payoutAmount": 0
}
]
},
"holoRouletteInfo": {
"result": [
{
"number": 35,
"colour": "black",
"wheelType": "circle"
},
{
"number": 19,
"colour": "red",
"wheelType": "triangle"
},
{
"number": 13,
"colour": "black",
"wheelType": "hexagon"
},
{
"number": 3,
"colour": "red",
"wheelType": "square"
}
]
}
}
]

```

#### EXAMPLE 9:

```

[
{
"betUID": "030D79E40122470B000100000012134E8148",
"betID": "AIBQAAQAEICIBYCYAAAAAAOIBAAAA",
"createdDateUTC": "2024-08-09T08:49:10.413",
"gameStartTimeUTC": "2024-08-09T08:47:52.003",
"gameEndTimeUTC": "2024-08-09T08:47:51.808",
"playerId": "testkiosk002",
"productId": "SMG",
"productPlayerId": "M0G209913364",

```

```

"platform": "Mobile",
"gameCode": "SMG_MGLiveGrand_DiamondRoulette",
"currency": "CNY",
"betAmount": 12,
"payoutAmount": 38.33,
"betStatus": "Closed",
"externalTransactionId": "1373688425/313",
"metadata": {
"sessionId": 1373688425,
"transactionId": 313,
"liveDealerInfo": {
"roundId": "#08:44:46",
"tableCode": "Diamond Rush Roulette",
"transactionInfo": [
{
"betType": "bonusLine_1_2_3_4_5_6",
"betAmount": 2,
"payoutAmount": 0
},
{
"betType": "bonusLine_7_8_9_10_11_12",
"betAmount": 2,
"payoutAmount": 38.3333
},
{
"betType": "bonusLine_13_14_15_16_17_18",
"betAmount": 2,
"payoutAmount": 0
},
{
"betType": "bonusLine_25_26_27_28_29_30",
"betAmount": 2,
"payoutAmount": 0
},
{
"betType": "bonusLine_19_20_21_22_23_24",
"betAmount": 2,
"payoutAmount": 0
},
{
"betType": "bonusLine_31_32_33_34_35_36",
"betAmount": 2,
"payoutAmount": 0
}
]
},
"diamondRouletteInfo": {
"result": [
{
"number": 7,
"colour": "red",
"wheelType": "main"
},
{
"number": 7,
"colour": "red",
"wheelType": "bonusWheel"
}
],
"luckyNumbers": {},
"bonusGame": {
"totalMultiplier": 115,
"guaranteedWin": 999,
"guaranteedMultiplier": 30,
"rounds": [
{
"level": "bronze",
"decision": "B",
"multiplier": 30
},
{
"level": "silver",
"decision": "D",
"multiplier": 60
},
{
"level": "gold",
"decision": "C",
"multiplier": 25
}
]
}
}

```

```

},
{
  "level": "platinum",
  "decision": "CashOut",
  "multiplier": 0
}
]
}
}
}
}
}
]

```

EXAMPLE 10:

```

[
  {
    "betUID": "03FF676F002F470B000100000012386EC4DE",
    "betID": "AIBQAAQAECIBYCYAAAAANICAAAA",
    "createdDateUTC": "2024-08-22T02:01:41.119",
    "gameStartTimeUTC": "2024-08-22T02:00:32.660",
    "gameEndTimeUTC": "2024-08-22T02:00:32.394",
    "playerId": "testkiosk002",
    "productId": "SMG",
    "productPlayerId": "M0G209913364",
    "platform": "Mobile",
    "gameCode": "SMG_MGLiveGrand_CashWheelCarnival",
    "currency": "CNY",
    "betAmount": 2,
    "payoutAmount": 0,
    "betStatus": "Closed",
    "externalTransactionId": "1384011940/565",
    "metadata": {
      "sessionId": 1384011940,
      "transactionId": 565,
      "liveDealerInfo": {
        "roundId": "#01:58:47",
        "tableCode": "Majestic Wheelshow",
        "transactionInfo": [
          {
            "betType": "twenty",
            "betAmount": 2,
            "payoutAmount": 0
          }
        ]
      },
      "cashWheelCarnivalInfo": {
        "wheelSegments": [
          {
            "betType": "one",
            "multiplier": 2
          },
          {
            "betType": "five",
            "multiplier": 10
          },
          {
            "betType": "ten",
            "multiplier": 40
          },
          {
            "betType": "thirtyFive",
            "multiplier": 70
          },
          {
            "betType": "seven",
            "multiplier": 14
          },
          {
            "betType": "twenty",
            "multiplier": 40
          },
          {
            "betType": "two",
            "multiplier": 4
          }
        ]
      }
    }
  }
]

```

```

{
  "betType": "forty",
  "multiplier": 80
},
{
  "betType": "fifteen",
  "multiplier": 30
}
],
"majesticInfo": {
  "multiplier": 20,
  "number": "ten"
},
"boosters": [
  2
],
"result": {
  "outcome": "five",
  "finalMultiplier": 10
}
}
}
}
}
]

```

EXAMPLE 11:

```

[
  {
    "betUID": "0392A139003B470B0001000000125C8BB148",
    "betID": "AIBQAAQAHTINQCQAAAAABIQAAAA",
    "createdDateUTC": "2024-09-03T01:02:56.914",
    "gameStartTimeUTC": "2024-09-03T01:01:33.110",
    "gameEndTimeUTC": "2024-09-03T01:01:33.413",
    "playerId": "qatest",
    "productId": "SMG",
    "productPlayerId": "M0G0993689649",
    "platform": "Mobile",
    "gameCode": "SMG_MGLiveGrand_CasinoHoldem",
    "currency": "CNY",
    "betAmount": 10,
    "payoutAmount": 0,
    "betStatus": "Closed",
    "externalTransactionId": "1392306911/162",
    "metadata": {
      "sessionId": 1392306911,
      "transactionId": 162,
      "liveDealerInfo": {
        "roundId": "#01:00:20",
        "tableCode": "Casino Hold'em",
        "transactionInfo": [
          {
            "betType": "ante",
            "betAmount": 10,
            "payoutAmount": 0
          }
        ]
      },
      "pokerInfo": {
        "dealer": {
          "hand": {
            "holeCards": [
              {
                "suit": "diamonds",
                "rank": "4"
              },
              {
                "suit": "clubs",
                "rank": "J"
              }
            ]
          },
          "finalHand": [
            {
              "suit": "diamonds",
              "rank": "4"
            }
          ]
        }
      }
    }
  }
]

```

```

{
  "suit": "clubs",
  "rank": "4"
},
{
  "suit": "clubs",
  "rank": "K"
},
{
  "suit": "spades",
  "rank": "Q"
},
{
  "suit": "clubs",
  "rank": "J"
}
],
"combination": "onePair"
},
"isQualified": true
},
"player": {
  "hand": {
    "holeCards": [
      {
        "suit": "spades",
        "rank": "4"
      },
      {
        "suit": "spades",
        "rank": "8"
      }
    ],
    "finalHand": [
      {
        "suit": "spades",
        "rank": "4"
      },
      {
        "suit": "clubs",
        "rank": "4"
      },
      {
        "suit": "clubs",
        "rank": "K"
      },
      {
        "suit": "spades",
        "rank": "Q"
      },
      {
        "suit": "spades",
        "rank": "8"
      }
    ],
    "combination": "onePair"
  }
},
"communityCards": [
  {
    "suit": "spades",
    "rank": "7"
  },
  {
    "suit": "spades",
    "rank": "Q"
  },
  {
    "suit": "clubs",
    "rank": "6"
  },
  {
    "suit": "clubs",
    "rank": "4"
  },
  {
    "suit": "clubs",
    "rank": "K"
  }
}

```

```
,
"result": {
  "outcome": "dealer",
  "highlights": {
    "player": [
      {
        "suit": "spades",
        "rank": "4"
      },
      {
        "suit": "clubs",
        "rank": "4"
      }
    ],
    "dealer": [
      {
        "suit": "diamonds",
        "rank": "4"
      },
      {
        "suit": "clubs",
        "rank": "4"
      },
      {
        "suit": "clubs",
        "rank": "J"
      }
    ],
    "kickerCard": {
      "suit": "clubs",
      "rank": "J"
    }
  },
  "sideBetCards": [
    {
      "suit": "spades",
      "rank": "4"
    },
    {
      "suit": "spades",
      "rank": "8"
    },
    {
      "suit": "spades",
      "rank": "7"
    },
    {
      "suit": "spades",
      "rank": "Q"
    },
    {
      "suit": "clubs",
      "rank": "6"
    }
  ]
}
}
```

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION |
|-----------------------------|--------|-------------|
| OBJECT WITH BELOW STRUCTURE |        |             |
| code                        | string |             |
| message                     | string |             |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error

内部服务器错误

| RESPONSE MODEL - application/json |        |              |
|-----------------------------------|--------|--------------|
| NAME                              | TYPE   | DESCRIPTION  |
| OBJECT WITH BELOW STRUCTURE       |        |              |
| error                             | object |              |
| code                              | string | GeneralError |
| message                           | string | Server error |
| message-zh-CHS                    | string | 服务器错误        |

## 2. BETTING PROFILES 投注配置

### 2.1 GET /agents/{agentCode}/products/{productId}/bettingProfiles

Get betting profiles list 获取投注配置列表

Returns betting profile list for agent 返回代理的投注配置列表

#### REQUEST

##### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |
| *productId | string |         | The product ID<br>产品编号 |

#### RESPONSE

STATUS CODE - 200: Betting profiles list returned  
投注资料列单已返回

##### RESPONSE MODEL - application/json

| NAME                                 | TYPE    | DESCRIPTION                                                                                                                                                                                             |
|--------------------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |         |                                                                                                                                                                                                         |
| bettingProfileId                     | integer | Betting profile ID<br>投注资料编号                                                                                                                                                                            |
| gameType                             | enum    | ALLOWED: RNG, Live<br>Game engine type e.g. “RNG” or “Live”<br>游戏引擎类型，例如 “RNG” 或 “Live”                                                                                                                 |
| bettingProfileName                   | string  | Betting profile name<br>投注资料名称                                                                                                                                                                          |
| bettingProfileDescription            | string  | Betting profile description<br>投注资料描述                                                                                                                                                                   |
| currency                             | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies. 指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币 |
| isDefault                            | boolean | Indicates whether this profile is configured to new created players<br>指示此笔投注资料是否已配置给新创建的玩家                                                                                                             |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

##### RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION          |
|-----------------------------|--------|----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                      |
| code                        | string | InputValidationError |
| message                     | string |                      |

STATUS CODE - 401: Unauthorized

未经授权

STATUS CODE - 404: The product id is not supported for method  
此方法不支持产品编号

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                |
|-----------------------------|--------|--------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                            |
| code                        | string | ProductIsNotSupported                      |
| message                     | string | The product id is not supported for method |
| message-zh-CHS              | string | 此方法不支持产品编号。                                |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 2.2 GET /agents/{agentCode}/products/{productId}/players/{playerId}/bettingProfiles

Get player betting profiles list 获取玩家投注资料列单

Returns betting profile list for player 返回玩家的投注资料列单

### REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                         |
|------------|--------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                              |
| *productId | string |         | The product ID<br>产品编号                                                                                                                                              |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和 下划线 (\_)。 |

### RESPONSE

STATUS CODE - 200: Player betting profiles list returned  
玩家投注资料列单已返回

RESPONSE MODEL - application/json

| NAME                                 | TYPE | DESCRIPTION |
|--------------------------------------|------|-------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |      |             |

| NAME                      | TYPE    | DESCRIPTION                                                                                                                                                                                             |
|---------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bettingProfileId          | integer | Betting profile ID<br>投注资料编号                                                                                                                                                                            |
| gameType                  | enum    | ALLOWED: RNG, Live<br>Game engine type e.g. “RNG” or “Live”<br>游戏引擎类型，例如 “RNG” 或 “Live”                                                                                                                 |
| bettingProfileName        | string  | Betting profile name<br>投注资料名称                                                                                                                                                                          |
| bettingProfileDescription | string  | Betting profile description<br>投注资料描述                                                                                                                                                                   |
| currency                  | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies. 指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币 |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                     |
|-----------------------------|--------|-------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                 |
| code                        | string | InputValidationError                                                                            |
| message                     | string | The field ProductId must be a string with a maximum length of 3 letters. ProductID 字段数不能超过三个字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: The product id is not supported for method  
此方法不支持产品编号。

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                |
|-----------------------------|--------|--------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                            |
| code                        | string | ProductIsNotSupported                      |
| message                     | string | The product id is not supported for method |
| message-zh-CHS              | string | 此方法不支持产品编号。                                |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 2.3 POST /agents/{agentCode}/products/{productId}/players/{playerId}/bettingProfiles

Add player betting profile 指定玩家的投注配置

Returns added betting profile 返回添加的投注配置

## REQUEST

### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                             |
| *productId | string |         | The product ID<br>产品编号                                                                                                                                             |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |

### FORM DATA PARAMETERS

| NAME              | TYPE    | DESCRIPTION                  |
|-------------------|---------|------------------------------|
| *bettingProfileId | integer | Betting Profile ID<br>投注资料编号 |

## RESPONSE

STATUS CODE - 200: Betting profile already configured for player'  
玩家已配置投注资料

### RESPONSE MODEL - application/json

| NAME                        | TYPE    | DESCRIPTION                                                                                                                                                                                             |
|-----------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |         |                                                                                                                                                                                                         |
| bettingProfileId            | integer | Betting profile ID<br>投注资料编号                                                                                                                                                                            |
| gameType                    | enum    | ALLOWED: RNG, Live<br>Game engine type e.g. "RNG" or "Live"<br>游戏引擎类型，例如 "RNG" 或 "Live"                                                                                                                 |
| bettingProfileName          | string  | Betting profile name<br>投注资料名称                                                                                                                                                                          |
| bettingProfileDescription   | string  | Betting profile description<br>投注资料描述                                                                                                                                                                   |
| currency                    | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies. 指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币 |

STATUS CODE - 201: Betting profile added successfully  
成功增加投注资料

### RESPONSE MODEL - application/json

| NAME                        | TYPE    | DESCRIPTION                                                                             |
|-----------------------------|---------|-----------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |         |                                                                                         |
| bettingProfileId            | integer | Betting profile ID<br>投注资料编号                                                            |
| bettingProfileName          | string  | Betting profile name<br>投注资料名称                                                          |
| bettingProfileDescription   | string  | Betting profile description<br>投注资料描述                                                   |
| gameType                    | enum    | ALLOWED: RNG, Live<br>Game engine type e.g. "RNG" or "Live"<br>游戏引擎类型，例如 "RNG" 或 "Live" |

| NAME     | TYPE   | DESCRIPTION                                                                                                                                                                                             |
|----------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| currency | string | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies. 指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币 |
| uri      | string | Resource Uri.<br>资料来源链接                                                                                                                                                                                 |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                     |
|-----------------------------|--------|-------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                 |
| code                        | string | InputValidationError                                                                            |
| message                     | string | The field ProductId must be a string with a maximum length of 3 letters. ProductID 字段数不能超过三个字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: The product id is not supported for method  
此方法不支持产品编号

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                |
|-----------------------------|--------|--------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                            |
| code                        | string | ProductIsNotSupported                      |
| message                     | string | The product id is not supported for method |
| message-zh-CHS              | string | 此方法不支持产品编号。                                |

STATUS CODE - 409: The request could not be processed because of conflict in the request, such as player already has betting profile with the same type  
无法处理请求，因为请求中存在冲突，例如玩家已经有 GameType 的个人资料

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                       |
|-----------------------------|--------|-----------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                   |
| code                        | string | BettingProfileTypeAlreadyConfiguredForPlayer                                      |
| message                     | string | Player already has profile for the GameType, please first remove existing profile |
| message-zh-CHS              | string | 玩家已经有 GameType 的个人资料，请先删除现有的个人资料                                                  |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

2.4 DELETE /agents/{agentCode}/products/{productId}/players/{playerId}/bettingProfiles/{bettingProfileId}

Remove player betting profile 移除玩家的投注配置

Returns removed betting profile 返回已移除的投注配置

REQUEST

PATH PARAMETERS

| NAME              | TYPE                                | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|-------------------|-------------------------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode        | string                              |         | The agent code<br>代理人码                                                                                                                                             |
| *productId        | string                              |         | The product ID<br>产品编号                                                                                                                                             |
| *playerId         | string                              |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| *bettingProfileId | integer<br>between 1 and 2147483647 |         | Betting Profile ID<br>投注资料编号                                                                                                                                       |

RESPONSE

STATUS CODE - 200: Betting profile removed successfully  
成功移除投注资料

RESPONSE MODEL - application/json

| NAME                        | TYPE    | DESCRIPTION                                                                                                                                                                                             |
|-----------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |         |                                                                                                                                                                                                         |
| bettingProfileId            | integer | Betting profile ID<br>投注资料编号                                                                                                                                                                            |
| gameType                    | enum    | ALLOWED: RNG, Live<br>Game engine type e.g. “RNG” or “Live”<br>游戏引擎类型，例如 “RNG” 或 “Live”                                                                                                                 |
| bettingProfileName          | string  | Betting profile name<br>投注资料名称                                                                                                                                                                          |
| bettingProfileDescription   | string  | Betting profile description<br>投注资料描述                                                                                                                                                                   |
| currency                    | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies. 指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币 |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                     |
|-----------------------------|--------|-------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                 |
| code                        | string | InputValidationError                                                                            |
| message                     | string | The field ProductId must be a string with a maximum length of 3 letters. ProductID 字段数不能超过三个字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: The product id is not supported for method  
此方法不支持产品编号

| RESPONSE MODEL - application/json |        |                                            |
|-----------------------------------|--------|--------------------------------------------|
| NAME                              | TYPE   | DESCRIPTION                                |
| OBJECT WITH BELOW STRUCTURE       |        |                                            |
| code                              | string | ProductIsNotSupported                      |
| message                           | string | The product id is not supported for method |
| message-zh-CHS                    | string | 此方法不支持产品编号。                                |

STATUS CODE - 500: Internal server error  
内部服务器错误

| RESPONSE MODEL - application/json |        |              |
|-----------------------------------|--------|--------------|
| NAME                              | TYPE   | DESCRIPTION  |
| OBJECT WITH BELOW STRUCTURE       |        |              |
| error                             | object |              |
| code                              | string | GeneralError |
| message                           | string | Server error |
| message-zh-CHS                    | string | 服务器错误        |

## 3. DEMOSESSIONS 演示模式会话

### 3.1 POST /agents/{agentCode}/demoSessions

Launch Demo Play URL 启动演示模式链接

Returns URL to launch specified demo play 返回特定游戏的演示模式的链接

#### REQUEST

##### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

##### FORM DATA PARAMETERS

| NAME         | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| playerId     | string | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| *contentCode | string | Content code<br>内容代码                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| *platform    | string | Playing platform<br>游戏平台                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| *langCode    | string | A Language code consists of: 语言代码包括 [language]-[REGION].<br>* language - A language designator is a code that represents a language. Use the two-letter [ISO 639-1](http://en.wikipedia.org/wiki/List_of_ISO_639-1_codes) standard.<br>* region - A region designator is a code that represents a country. Use the two-letter [ISO 3166-2](https://en.wikipedia.org/wiki/ISO_3166-2) standard.<br>[language]-[REGION].<br>* 语言 - 语言指示符是代表一种语言的代码。使用双字母标准 [ISO 639-1](http://en.wikipedia.org/wiki/List_of_ISO_639-1_codes).<br>* 区域 - 区域指示符是代表一个国家的代码。使用双字母标准 [ISO 3166-2](https://en.wikipedia.org/wiki/ISO_3166-2) |

#### RESPONSE

STATUS CODE - 201: Content url returned  
内容网址返回成功

##### RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                             |
|-----------------------------|--------|-----------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                         |
| url                         | string | The content url<br>内容网址                 |
| gameURL                     | string | The game url (deprecated)<br>游戏网址 (已弃用) |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

| RESPONSE MODEL - application/json |        |                                                                  |
|-----------------------------------|--------|------------------------------------------------------------------|
| NAME                              | TYPE   | DESCRIPTION                                                      |
| OBJECT WITH BELOW STRUCTURE       |        |                                                                  |
| code                              | string | InputValidationError                                             |
| message                           | string | The value 'tablet' is not valid for Platform. 'tablet'对平台来说是个无效值 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 403: Forbidden  
禁止

STATUS CODE - 404: Requested content not available for player  
请求的内容不存在

| RESPONSE MODEL - application/json |        |                                            |
|-----------------------------------|--------|--------------------------------------------|
| NAME                              | TYPE   | DESCRIPTION                                |
| OBJECT WITH BELOW STRUCTURE       |        |                                            |
| code                              | string | ContentNotFoundForPlayer                   |
| message                           | string | Requested content not available for player |
| message-zh-CHS                    | string | 请求的内容不存在                                   |

STATUS CODE - 500: Internal server error  
内部服务器错误

| RESPONSE MODEL - application/json |        |              |
|-----------------------------------|--------|--------------|
| NAME                              | TYPE   | DESCRIPTION  |
| OBJECT WITH BELOW STRUCTURE       |        |              |
| error                             | object |              |
| code                              | string | GeneralError |
| message                           | string | Server error |
| message-zh-CHS                    | string | 服务器错误        |

# 4. FREE GAMES - OFFER MANAGEMENT 免费游戏 - 优惠管理

## 4.1 GET /agents/{agentCode}/offers

Get existing free game offers 获取现有的免费游戏优惠

Returns information about existing free game offers and their associated information.  
返回有关现有免费游戏优惠及其相关资料。

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE                                      | EXAMPLE | DESCRIPTION                                        |
|------------|-------------------------------------------|---------|----------------------------------------------------|
| *agentCode | string<br>PATTERN: ^[a-zA-Z0-9_-]{3,50}\$ |         | The unique identifier for the Agent <br />代理的唯一标识符 |

#### QUERY PARAMETERS

| NAME                 | TYPE                                  | EXAMPLE | DESCRIPTION                                                                                                                                                |
|----------------------|---------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerGuidStartsWith  | string                                |         | Narrow down results by inputting the offer GUID. Partial search is supported as long as the beginning of the string matches. <br />通过搜索提供的GUID，但字符串的开头需要匹配 |
| offerNameContains    | string                                |         | Narrow down results by inputting the offer name. Partial search is supported. <br />在现有的优惠名称中部分搜索                                                          |
| availableFromDateUTC | date-time                             |         | Search for offers that are available from this date<br />搜索从这个日期开始可用的优惠                                                                                    |
| availableToDateUTC   | date-time                             |         | Search for offers that are available to this date<br />搜索从这个日期结束的优惠                                                                                        |
| offerStatus          | enum<br>ALLOWED:<br>Closed,<br>Active |         |                                                                                                                                                            |
| page                 | int32                                 |         | The current page in the response <br />响应中的当前页面                                                                                                            |
| perPage              | int32                                 |         | The number of items returned per page. If not provided, it will return 100 by default. <br />每页返回的项目数量。如果不提供，默认返回100。                                      |

### RESPONSE

STATUS CODE - 200: Offer list returned successfully <br />优惠列表成功返回。

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION |
|--------------------------------------|--------|-------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |             |
| freeGameOfferUsage                   | object |             |

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| numberOfAssignedPlayers             | integer | The number of players that the Free Game Offer has been assigned to <br /> 免费游戏优惠被分配给的玩家数量                                                                                                                                                                                                                                                   |
| numberOfInstances                   | integer | The number of instances that the Free Game Offer has been assigned <br /> 免费游戏优惠已被分配的派发数量                                                                                                                                                                                                                                                    |
| offerStatus                         | enum    | ALLOWED:Closed, Active                                                                                                                                                                                                                                                                                                                       |
| offerAvailableFromDateUTC           | string  | The time in UTC indicating from when the Agent can assign the offer to players. <br /><br /> 代理可以将优惠分配给玩家的UTC时间。                                                                                                                                                                                                                             |
| offerAvailableToDateUTC             | string  | The time in UTC at which Agents can no longer assign offers to players. <br /><br /> 代理无法再将此优惠分配给玩家的UTC时间。                                                                                                                                                                                                                                   |
| offerGuid                           | string  | The unique GUID identifying the new offer that was created. <br /><br /> 识别创建的新优惠的独特GUID.                                                                                                                                                                                                                                                    |
| offerCreateDateUTC                  | string  | The time in UTC when the offer was created. <br /><br /> 创建优惠的UTC时间                                                                                                                                                                                                                                                                          |
| offerGames                          | array   | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                              |
| nearestCostPerBet                   | number  | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的价值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                           | string  | min:1 chars <br /><br /> Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                       |
| offerName                           | string  | 1 to 50 chars <br /><br /> The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                    |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99 <br /><br /> The number of days during which the player can accept the offer, starting from the moment it is granted. <br /><br /> 奖励后，玩家可以使用优惠的天数。                                                                                                                                                                         |
| numberOfRounds                      | integer | between 1 and 100 <br /><br /> The number of games available for the player - this number must be greater than zero. <br /><br /> 这是玩家可用的游戏数量，必须大于零。                                                                                                                                                                                         |

#### EXAMPLE:

```
[
  {
    "freeGameOfferUsage": {
      "numberOfAssignedPlayers": 256,
      "numberOfInstances": 0
    },
    "offerStatus": "Active",
    "offerAvailableFromDateUTC": "2023-01-10T15:25:00Z",
    "offerAvailableToDateUTC": "2023-05-10T23:59:59Z",
    "offerGuid": "00000000-0000-0000-0000-000000000000",
    "offerCreateDateUTC": "0001-01-01T00:00:00Z",
    "offerGames": [
      {
        "nearestCostPerBet": 1,
        "gameCode": "SMG_Game1"
      },
      {
        "nearestCostPerBet": 10,
        "gameCode": "SMG_Game2"
      }
    ],
    "offerName": "Demo Offer One",
    "durationAvailableInDaysAfterAwarded": 2,
    "numberOfRounds": 10
  }
]
```

```

    "offerStatus": "Active",
    "offerAvailableFromDateUTC": "2023-02-08T00:00:00Z",
    "offerAvailableToDateUTC": "2023-03-18T12:00:00Z",
    "offerGuid": "00000000-0000-0000-0000-000000000000",
    "offerCreateDateUTC": "0001-01-01T00:00:00Z",
    "offerGames": [
      {
        "nearestCostPerBet": 5,
        "gameCode": "SMG_Game3"
      }
    ],
    "offerName": "Demo Offer Two",
    "durationAvailableInDaysAfterAwarded": 2,
    "numberOfRounds": 5
  }
]

```

STATUS CODE - 400: Bad request <br /> 错误的请求

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}

```

STATUS CODE - 401: Authorization information is missing or invalid <br /> 授权信息丢失或无效

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}

```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br /> 资源不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "ResourceNotFound",
  "message": "Resource Not Found 找不到资源"
}

```

STATUS CODE - 500: Unexpected error <br /> 未预期的错误

## RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

## 4.2 POST /agents/{agentCode}/offers

### Create a new free game offer 创建新的免费游戏优惠

Returns a newly created offer.

Note that each game in the offer will have a value per round equal to the minimum bet of that game, which may vary across different games.

返回新创建的优惠

备注：优惠的每个游戏的每回合价值与游戏的最小赌注相同。不同游戏可能会不同价值。

## REQUEST

### PATH PARAMETERS

| NAME       | TYPE                                                   | EXAMPLE | DESCRIPTION                                        |
|------------|--------------------------------------------------------|---------|----------------------------------------------------|
| *agentCode | string<br>PATTERN: <code>^[a-zA-Z0-9_-]{3,50}\$</code> |         | The unique identifier for the Agent <br />代理的唯一标识符 |

### REQUEST BODY - application/json-patch+json

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerName*                          | string  | 1 to 50 chars<br>The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                              |
| offerGames*                         | array   | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                              |
| nearestCostPerBet                   | number  | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的价值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                           | string  | min:1 chars<br>Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                                 |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from                                                                                                                                                                                                                                           |

| NAME                      | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                           |
|---------------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                           |         | the moment it is granted. If not provided, it will be set to 7 days by default. The number of days should not be longer than the offer period.<br><br /><br /> 奖励后，玩家可以使用优惠的天数。如果未提供，则默认为7。天数不应长过优惠期限。                                                                                                                |
| numberOfRounds*           | integer | between 1 and 100<br>The number of games available for the player - this number must be greater than zero.<br><br /><br /> 这是玩家可用的游戏数量，必须大于零。                                                                                                                                                                         |
| offerAvailableFromDateUTC | string  | The time in UTC indicating from when the Agent can assign the offer to players. If not specified, it will be the current time by default. <br /><br /> 代理可以将优惠分配给玩家的UTC时间。如果未提供，则默认为当前时间。                                                                                                                             |
| offerAvailableToDateUTC   | string  | The time in UTC at which Agents can no longer assign offers to players. The offer period must be a minimum of 1 day and a maximum of 1 year. If not specified, the default period will be 3 months from the offerAvailableFromDateUTC. <br /><br /> 代理无法再将此优惠分配给玩家的UTC时间。最短期限为 1 天，最长期限为 1 年。如果未提供，则默认结束时间是从优惠开始的3个月。 |

EXAMPLE:

```
{
  "offerName": "TestFreeGameOffer",
  "offerGames": [
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_bigMightyBears"
    },
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_crazyDigginzItsAllMine"
    },
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_ticketToRiches"
    }
  ],
  "durationAvailableInDaysAfterAwarded": 22,
  "numberOfRounds": 11,
  "offerAvailableFromDateUTC": "2023-09-06T08:45:05.3042207Z",
  "offerAvailableToDateUTC": "2023-12-06T08:45:05.3042242Z"
}
```

REQUEST BODY - application/json

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerName*                          | string  | 1 to 50 chars<br>The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                              |
| offerGames*                         | array   | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                              |
| nearestCostPerBet                   | number  | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的价值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                           | string  | min:1 chars<br>Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                                 |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from the moment it is granted. If not provided, it will be set to 7 days by default. The number of days should not be longer than the offer period.<br><br /><br /> 奖励后，玩家可以使用优惠的天数。如果未提供，则默认为7。天数不应长过优惠期限。                                    |
| numberOfRounds*                     | integer | between 1 and 100                                                                                                                                                                                                                                                                                                                            |

| NAME                      | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                           |
|---------------------------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                           |        | The number of games available for the player - this number must be greater than zero.<br><br /><br /> 这是玩家可用的游戏数量，必须大于零。                                                                                                                                                                                              |
| offerAvailableFromDateUTC | string | The time in UTC indicating from when the Agent can assign the offer to players. If not specified, it will be the current time by default. <br /><br /> 代理可以将优惠分配给玩家的UTC时间。如果未提供，则默认为当前时间。                                                                                                                             |
| offerAvailableToDateUTC   | string | The time in UTC at which Agents can no longer assign offers to players. The offer period must be a minimum of 1 day and a maximum of 1 year. If not specified, the default period will be 3 months from the offerAvailableFromDateUTC. <br /><br /> 代理无法再将此优惠分配给玩家的UTC时间。最短期限为 1 天，最长期限为 1 年。如果未提供，则默认结束时间是从优惠开始的3个月。 |

EXAMPLE:

```
{
  "offerName": "TestFreeGameOffer",
  "offerGames": [
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_bigMightyBears"
    },
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_crazyDigginzItsAllMine"
    },
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_ticketToRiches"
    }
  ],
  "durationAvailableInDaysAfterAwarded": 22,
  "numberOfRounds": 11,
  "offerAvailableFromDateUTC": "2023-09-06T08:45:05.3042207Z",
  "offerAvailableToDateUTC": "2023-12-06T08:45:05.3042242Z"
}
```

REQUEST BODY - text/json

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                 |
|-------------------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerName*                          | string  | 1 to 50 chars<br>The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                             |
| offerGames*                         | array   | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                             |
| nearestCostPerBet                   | number  | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                           | string  | min:1 chars<br>Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                                |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from the moment it is granted. If not provided, it will be set to 7 days by default. The number of days should not be longer than the offer period. <br /><br /> 奖励后，玩家可以使用优惠的天数。如果未提供，则默认为7。天数不应长过优惠期限。                                      |
| numberOfRounds*                     | integer | between 1 and 100<br>The number of games available for the player - this number must be greater than zero. <br /><br /> 这是玩家可用的游戏数量，必须大于零。                                                                                                                                                                                                  |
| offerAvailableFromDateUTC           | string  | The time in UTC indicating from when the Agent can assign the offer to players. If not specified, it will be the current time by default. <br /><br /> 代理可以将优惠分配给玩家的UTC时间。如果未提供，则默认为当前时间。                                                                                                                                                   |

| NAME                    | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                          |
|-------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAvailableToDateUTC | string | The time in UTC at which Agents can no longer assign offers to players. The offer period must be a minimum of 1 day and a maximum of 1 year. If not specified, the default period will be 3 months from the offerAvailableFromDateUTC. <br /><br />代理无法再将此优惠分配给玩家的UTC时间。最短期限为 1 天，最长期限为 1 年。如果未提供，则默认结束时间是从优惠开始的3个月。 |

EXAMPLE:

```
{
  "offerName": "TestFreeGameOffer",
  "offerGames": [
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_bigMightyBears"
    },
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_crazyDigginzItsAllMine"
    },
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_ticketToRiches"
    }
  ],
  "durationAvailableInDaysAfterAwarded": 22,
  "numberOfRounds": 11,
  "offerAvailableFromDateUTC": "2023-09-06T08:45:05.3042207Z",
  "offerAvailableToDateUTC": "2023-12-06T08:45:05.3042242Z"
}
```

REQUEST BODY - application/\*+json

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                 |
|-------------------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerName*                          | string  | 1 to 50 chars<br>The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                             |
| offerGames*                         | array   | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                             |
| nearestCostPerBet                   | number  | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                           | string  | min:1 chars<br>Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                                |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from the moment it is granted. If not provided, it will be set to 7 days by default. The number of days should not be longer than the offer period. <br /><br /> 奖励后，玩家可以使用优惠的天数。如果未提供，则默认为7。天数不应长过优惠期限。                                      |
| numberOfRounds*                     | integer | between 1 and 100<br>The number of games available for the player - this number must be greater than zero. <br /><br /> 这是玩家可用的游戏数量，必须大于零。                                                                                                                                                                                                  |
| offerAvailableFromDateUTC           | string  | The time in UTC indicating from when the Agent can assign the offer to players. If not specified, it will be the current time by default. <br /><br /> 代理可以将优惠分配给玩家的UTC时间。如果未提供，则默认为当前时间。                                                                                                                                                   |
| offerAvailableToDateUTC             | string  | The time in UTC at which Agents can no longer assign offers to players. The offer period must be a minimum of 1 day and a maximum of 1 year. If not specified, the default period will be 3 months from the offerAvailableFromDateUTC. <br /><br /> 代理无法再将此优惠分配给玩家的UTC时间。最短期限为 1 天，最长期限为 1 年。如果未提供，则默认结束时间是从优惠开始的3个月。                       |

EXAMPLE:

```
{
  "offerName": "TestFreeGameOffer",
  "offerGames": [
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_bigMightyBears"
    },
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_crazyDigginzItsAllMine"
    },
    {
      "nearestCostPerBet": 0.5,
      "gameCode": "UPG_ticketToRiches"
    }
  ],
  "durationAvailableInDaysAfterAwarded": 22,
  "numberOfRounds": 11,
  "offerAvailableFromDateUTC": "2023-09-06T08:45:05.3042207Z",
  "offerAvailableToDateUTC": "2023-12-06T08:45:05.3042242Z"
}
```

## RESPONSE

STATUS CODE - 200: New offer created or existing offer reused <br /> 已创建新优惠或重复使用现有优惠

RESPONSE MODEL - application/json

| NAME                        | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |
|-----------------------------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| offerGuid                   | string  | The unique GUID identifying the new offer that was created. <br /><br /> 识别创建的新优惠的独特GUID                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| reuse                       | boolean | The term 'Reuse' in this context determines if the Offer returned pertains to a newly generated offer or if it corresponds to an existing offer with identical parameters. When creating a new offer, the system checks for any other offers that have the same input parameters and have been created within the last hour. If a match is found, instead of creating a new offer, the system will provide the GUID of the existing offer. <br /><br /> “Reuse” 是用来检查代理欲创建优惠是否重复，如重复则reuse = true。在创建新的优惠时，系统会检查是否存在具有相同参数且在最近一小时内创建的优惠。如为相同，系统将返回现有优惠的GUID。 |

EXAMPLE:

```
{
  "offerGuid": "2704aa04-b298-4743-9c76-4d4dc2d05f0b",
  "reuse": true
}
```

STATUS CODE - 400: Bad request <br /> 错误的请求

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}
```

STATUS CODE - 401: Authorization information is missing or invalid <br /> 授权信息丢失或无效

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}
```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br /> 资源不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "ResourceNotFound",
  "message": "Resource Not Found 找不到资源"
}
```

STATUS CODE - 500: Unexpected error <br /> 未預期的錯誤

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

### 4.3 PATCH /agents/{agentCode}/offers/{offerGuid}

Update an existing free game offer that has not been used yet 更新尚未使用的免费游戏优惠

Utilize this endpoint to modify the information of the free game offer, on the condition that it has not been utilized yet.

如果免费游戏优惠尚未被使用的情况下，可以使用此端点来修改其资料。

## REQUEST

PATH PARAMETERS

| NAME       | TYPE                                                   | EXAMPLE | DESCRIPTION                                                                |
|------------|--------------------------------------------------------|---------|----------------------------------------------------------------------------|
| *agentCode | string<br>PATTERN: <code>^[a-zA-Z0-9_-]{3,50}\$</code> |         | The unique identifier for the Agent <br />代理的唯一标识符                         |
| *offerGuid | uuid                                                   |         | The unique GUID that identifies the free game offer <br /> 识别免费游戏优惠的独特GUID |

## REQUEST BODY - application/json-patch+json

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerGames                          | array   | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                              |
| nearestCostPerBet                   | number  | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的价值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                           | string  | min:1 chars<br>Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                                 |
| offerName                           | string  | 1 to 50 chars<br>The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                              |
| offerAvailableFromDateUTC           | string  | The time in UTC indicating from when the Agent can assign the offer to players. If not specified, it will be the current time by default. <br /><br /> 代理可以将优惠分配给玩家的UTC时间。如果未提供，则默认为当前时间。                                                                                                                                                    |
| offerAvailableToDateUTC             | string  | The time in UTC at which Agents can no longer assign offers to players. The offer period must be a minimum of 1 day and a maximum of 1 year. If not specified, the default period will be 3 months from the offerAvailableFromDateUTC. <br /><br /> 代理无法再将此优惠分配给玩家的UTC时间。最短期限为 1 天，最长期限为 1 年。如果未提供，则默认结束时间是从优惠开始的3个月。                        |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from the moment it is granted. <br /><br /> 奖励后，玩家可以使用优惠的天数。                                                                                                                                                                                   |
| numberOfRounds                      | integer | between 1 and 100<br>The number of games available for the player - this number must be greater than zero.<br><br /><br /> 这是玩家可用的游戏数量，必须大于零。                                                                                                                                                                                                |

## REQUEST BODY - application/json

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerGames                          | array   | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                              |
| nearestCostPerBet                   | number  | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的价值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                           | string  | min:1 chars<br>Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                                 |
| offerName                           | string  | 1 to 50 chars<br>The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                              |
| offerAvailableFromDateUTC           | string  | The time in UTC indicating from when the Agent can assign the offer to players. If not specified, it will be the current time by default. <br /><br /> 代理可以将优惠分配给玩家的UTC时间。如果未提供，则默认为当前时间。                                                                                                                                                    |
| offerAvailableToDateUTC             | string  | The time in UTC at which Agents can no longer assign offers to players. The offer period must be a minimum of 1 day and a maximum of 1 year. If not specified, the default period will be 3 months from the offerAvailableFromDateUTC. <br /><br /> 代理无法再将此优惠分配给玩家的UTC时间。最短期限为 1 天，最长期限为 1 年。如果未提供，则默认结束时间是从优惠开始的3个月。                        |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from the moment it is granted. <br /><br /> 奖励后，玩家可以使用优惠的天数。                                                                                                                                                                                   |

| NAME           | TYPE    | DESCRIPTION                                                                                                                                 |
|----------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------|
| numberOfRounds | integer | between 1 and 100<br>The number of games available for the player - this number must be greater than zero.<br><br/><br/> 这是玩家可用的游戏数量，必须大于零。 |

#### REQUEST BODY - text/json

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerGames                          | array   | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                              |
| nearestCostPerBet                   | number  | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的价值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                           | string  | min:1 chars<br>Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                                 |
| offerName                           | string  | 1 to 50 chars<br>The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                              |
| offerAvailableFromDateUTC           | string  | The time in UTC indicating from when the Agent can assign the offer to players. If not specified, it will be the current time by default. <br /><br /> 代理可以将优惠分配给玩家的UTC时间。如果未提供，则默认为当前时间。                                                                                                                                                    |
| offerAvailableToDateUTC             | string  | The time in UTC at which Agents can no longer assign offers to players. The offer period must be a minimum of 1 day and a maximum of 1 year. If not specified, the default period will be 3 months from the offerAvailableFromDateUTC. <br /><br /> 代理无法再将此优惠分配给玩家的UTC时间。最短期限为 1 天，最长期限为 1 年。如果未提供，则默认结束时间是从优惠开始的3个月。                        |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from the moment it is granted. <br /><br /> 奖励后，玩家可以使用优惠的天数。                                                                                                                                                                                   |
| numberOfRounds                      | integer | between 1 and 100<br>The number of games available for the player - this number must be greater than zero.<br><br /><br /> 这是玩家可用的游戏数量，必须大于零。                                                                                                                                                                                                |

#### REQUEST BODY - application/\*+json

| NAME                      | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                  |
|---------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerGames                | array  | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                              |
| nearestCostPerBet         | number | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的价值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                 | string | min:1 chars<br>Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                                 |
| offerName                 | string | 1 to 50 chars<br>The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                              |
| offerAvailableFromDateUTC | string | The time in UTC indicating from when the Agent can assign the offer to players. If not specified, it will be the current time by default. <br /><br /> 代理可以将优惠分配给玩家的UTC时间。如果未提供，则默认为当前时间。                                                                                                                                                    |
| offerAvailableToDateUTC   | string | The time in UTC at which Agents can no longer assign offers to players. The offer period must be a minimum of 1 day and a maximum of 1 year. If not specified, the                                                                                                                                                                           |

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                               |
|-------------------------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
|                                     |         | default period will be 3 months from the offerAvailableFromDateUTC. <br /><br />代理无法再将此优惠分配给玩家的UTC时间。最短期为 1 天，最长期为 1 年。如果未提供，则默认结束时间是从优惠开始的3个月。           |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from the moment it is granted. <br /><br />奖励后，玩家可以使用优惠的天数。 |
| numberOfRounds                      | integer | between 1 and 100<br>The number of games available for the player - this number must be greater than zero.<br><br /><br />这是玩家可用的游戏数量，必须大于零。              |

## RESPONSE

STATUS CODE - 200: Offer updated <br />优惠已更新

RESPONSE MODEL - application/json

STATUS CODE - 400: Bad request <br />错误的请求

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}
```

STATUS CODE - 401: Authorization information is missing or invalid <br />授权信息丢失或无效

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}
```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br />资源不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "ResourceNotFound",
}
```

```
{
  "message": "Resource Not Found 找不到资源"
}
```

STATUS CODE - 500: Unexpected error <br /> 未預期的錯誤

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

## 4.4 PATCH /agents/{agentCode}/offers/{offerGuid}/close

### Close free game offer 关闭免费游戏优惠

Utilize this endpoint to close a free game offer.  
使用此端点关闭免费游戏优惠。

## REQUEST

PATH PARAMETERS

| NAME       | TYPE                                      | EXAMPLE | DESCRIPTION                                                                |
|------------|-------------------------------------------|---------|----------------------------------------------------------------------------|
| *agentCode | string<br>PATTERN: ^[a-zA-Z0-9_-]{3,50}\$ |         | The unique identifier for the Agent <br />代理的唯一标识符                         |
| *offerGuid | uuid                                      |         | The unique GUID that identifies the free game offer <br /> 识别免费游戏优惠的独特GUID |

REQUEST BODY - application/json

| NAME                   | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                           |
|------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| cancelAwardedInstances | boolean | Cancel assigned instances. To remove existing instances, use cancelAwardedInstances set to true. To keep existing instances, use cancelAwardedInstances set to false. <br /><br /> 取消已分配的派发。若要移除现有派发，请将 cancelAwardedInstances 设置为 true。若要保留现有派发，请将 cancelAwardedInstances 设置为 false。 |

EXAMPLE:

```
{
  "cancelAwardedInstances": false
}
```

## RESPONSE

STATUS CODE - 200: Offer is closed <br /> 优惠已关闭

RESPONSE MODEL - application/json

STATUS CODE - 400: Bad request <br /> 错误的请求

## RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}
```

STATUS CODE - 401: Authorization information is missing or invalid <br /> 授权信息丢失或无效

## RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}
```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br /> 资源不存在

## RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "ResourceNotFound",
  "message": "Resource Not Found 找不到资源"
}
```

STATUS CODE - 500: Unexpected error <br /> 未预期的错误

## RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

# 5. FREE GAMES - PLAYER MANAGEMENT 免费游戏 - 玩家管理

## 5.1 POST /agents/{agentCode}/offers/{offerGuid}/players/{playerId}/freeGameInstances

Assign a player to an existing free game offer 分配现有的免费游戏优惠给玩家

Utilize this endpoint to assign a player to a free game offer, creating an instance of the offer for the player to use.

Upon successfully assigning a player to the offer, the API should return a 202 response. The response will include the unique instanceGuid.

使用此端点分配免费游戏优惠给玩家，创建一个可用的优惠派发。

成功将玩家分配到优惠后，API应返回202响应。响应将包括独一无二的派发ID。

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE                                      | EXAMPLE | DESCRIPTION                                                                |
|------------|-------------------------------------------|---------|----------------------------------------------------------------------------|
| *agentCode | string<br>PATTERN: ^[a-zA-Z0-9_-]{3,50}\$ |         | The unique identifier for the Agent <br />代理的唯一标识符                         |
| *offerGuid | uuid                                      |         | The unique GUID that identifies the free game offer <br /> 识别免费游戏优惠的独特GUID |
| *playerId  | string<br>1 to 50 chars                   |         | The unique identifier for the Player <br /><br /> 玩家的唯一标识符                 |

#### REQUEST BODY - application/json-patch+json

| NAME                              | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|-----------------------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAvailableToPlayerFromDateUTC | string | The time in UTC from which players can start playing the free game offered. If not specified, it will default to the current date and time. <br /><br /> Remarks: <br /><br /> The date should be from the current date or later but within the range that the offer is valid. <br />- Latest start date of the instance can be the end date of the offer period. <br />- The player can use the instance until the end of the validity period. <br /><br /> Example Use Case: <br /><br /> Offer period: Dec 1 - Dec 31 <br />- Validity period of an instance: 7 days <br />- If a player is assigned to the offer on December 31, the availability period will be set from December 31 - January 6 per the validity period of 7 days. <br />- The Agent will not be able to assign the player to the offer on Jan 1, as this surpasses the offer period. <br /><br /> 玩家可以开始使用免费游戏的时间（使用UTC时间表示）。如果未指定，将默认为当前日期和时间。 <br /><br /> 备注：<br /><br /> • 日期应为当前日期或之后的日期，但必须在优惠有效期之内。 <br /> • 派发的最晚开始日期可以是优惠期的结束日期。 <br /> • 玩家可以在有效期结束前使用该派发。 <br /><br /> 示例：<br /><br /> • 优惠期：12月1日至12月31日 <br /> • 派发的有效期：7天 <br /> • 如果玩家在12月31日被分配到该优惠，根据7天的有效期，可用期将从12月31日到1月6日。 <br /> • 代理将无法在1月1日将玩家分配到该优惠，因为这超出了优惠期。 |

#### REQUEST BODY - application/json

| NAME | TYPE | DESCRIPTION |
|------|------|-------------|
|------|------|-------------|

| NAME                              | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAvailableToPlayerFromDateUTC | string | <p>The time in UTC from which players can start playing the free game offered. If not specified, it will default to the current date and time. &lt;br /&gt;&lt;br /&gt; Remarks:</p> <p>&lt;br /&gt;&lt;br /&gt;- The date should be from the current date or later but within the range that the offer is valid. &lt;br /&gt;- Latest start date of the instance can be the end date of the offer period. &lt;br /&gt;- The player can use the instance until the end of the validity period. &lt;br /&gt;&lt;br /&gt; Example Use Case: &lt;br /&gt;&lt;br /&gt;- Offer period: Dec 1 - Dec 31 &lt;br /&gt;- Validity period of an instance: 7 days &lt;br /&gt;- If a player is assigned to the offer on December 31, the availability period will be set from December 31 - January 6 per the validity period of 7 days. &lt;br /&gt;- The Agent will not be able to assign the player to the offer on Jan 1, as this surpasses the offer period. &lt;br /&gt;&lt;br /&gt; 玩家可以开始使用免费游戏的时间（使用UTC时间表示）。如果未指定，将默认为当前日期和时间。 &lt;br /&gt;&lt;br /&gt; 备注：&lt;br /&gt;&lt;br /&gt; • 日期应为当前日期或之后的日期，但必须在优惠有效期之内。 &lt;br /&gt; • 派发的最晚开始日期可以是优惠期的结束日期。 &lt;br /&gt; • 玩家可以在有效期结束前使用该派发。 &lt;br /&gt;&lt;br /&gt; 示例：&lt;br /&gt;&lt;br /&gt; • 优惠期：12月1日至12月31日 &lt;br /&gt; • 派发的有效期：7天 &lt;br /&gt; • 如果玩家在12月31日被分配到该优惠，根据7天的有效期，可用期将从12月31日到1月6日。 &lt;br /&gt; • 代理将无法在1月1日将玩家分配到该优惠，因为这超出了优惠期。</p> |

#### REQUEST BODY - text/json

| NAME                              | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAvailableToPlayerFromDateUTC | string | <p>The time in UTC from which players can start playing the free game offered. If not specified, it will default to the current date and time. &lt;br /&gt;&lt;br /&gt; Remarks:</p> <p>&lt;br /&gt;&lt;br /&gt;- The date should be from the current date or later but within the range that the offer is valid. &lt;br /&gt;- Latest start date of the instance can be the end date of the offer period. &lt;br /&gt;- The player can use the instance until the end of the validity period. &lt;br /&gt;&lt;br /&gt; Example Use Case: &lt;br /&gt;&lt;br /&gt;- Offer period: Dec 1 - Dec 31 &lt;br /&gt;- Validity period of an instance: 7 days &lt;br /&gt;- If a player is assigned to the offer on December 31, the availability period will be set from December 31 - January 6 per the validity period of 7 days. &lt;br /&gt;- The Agent will not be able to assign the player to the offer on Jan 1, as this surpasses the offer period. &lt;br /&gt;&lt;br /&gt; 玩家可以开始使用免费游戏的时间（使用UTC时间表示）。如果未指定，将默认为当前日期和时间。 &lt;br /&gt;&lt;br /&gt; 备注：&lt;br /&gt;&lt;br /&gt; • 日期应为当前日期或之后的日期，但必须在优惠有效期之内。 &lt;br /&gt; • 派发的最晚开始日期可以是优惠期的结束日期。 &lt;br /&gt; • 玩家可以在有效期结束前使用该派发。 &lt;br /&gt;&lt;br /&gt; 示例：&lt;br /&gt;&lt;br /&gt; • 优惠期：12月1日至12月31日 &lt;br /&gt; • 派发的有效期：7天 &lt;br /&gt; • 如果玩家在12月31日被分配到该优惠，根据7天的有效期，可用期将从12月31日到1月6日。 &lt;br /&gt; • 代理将无法在1月1日将玩家分配到该优惠，因为这超出了优惠期。</p> |

#### REQUEST BODY - application/\*+json

| NAME                              | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
|-----------------------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAvailableToPlayerFromDateUTC | string | <p>The time in UTC from which players can start playing the free game offered. If not specified, it will default to the current date and time. &lt;br /&gt;&lt;br /&gt; Remarks:</p> <p>&lt;br /&gt;&lt;br /&gt;- The date should be from the current date or later but within the range that the offer is valid. &lt;br /&gt;- Latest start date of the instance can be the end date of the offer period. &lt;br /&gt;- The player can use the instance until the end of the validity period. &lt;br /&gt;&lt;br /&gt; Example Use Case: &lt;br /&gt;&lt;br /&gt;- Offer period: Dec 1 - Dec 31 &lt;br /&gt;- Validity period of an instance: 7 days &lt;br /&gt;- If a player is assigned to the offer on December 31, the availability period will be set from December 31 - January 6 per the validity period of 7 days. &lt;br /&gt;- The Agent will not be able to assign the player to the offer on Jan 1, as this surpasses the offer period. &lt;br /&gt;&lt;br /&gt; 玩家可以开始使用免费游戏的时间（使用UTC时间表示）。如果未指定，将默认为当前日期和时间。 &lt;br /&gt;&lt;br /&gt; 备注：&lt;br /&gt;&lt;br /&gt; • 日期应为当前日期或之后的日期，但必须在优惠有效期之内。 &lt;br /&gt; • 派发的最晚开始日期可以是优惠期的结束日期。 &lt;br /&gt; • 玩家可以在有效期结束前使用该派发。 &lt;br /&gt;&lt;br /&gt; 示例：&lt;br /&gt;&lt;br /&gt; • 优惠期：12月1日至12月31日 &lt;br /&gt; • 派发的有效期：7天 &lt;br /&gt; • 如果玩家在12月31日被分配到该优惠，根据7天的有效期，可用期将从12月31日到1月6日。 &lt;br /&gt; • 代理将无法在1月1日将玩家分配到该优惠，因为这超出了优惠期。</p> |

## RESPONSE

STATUS CODE - 202: The assignment request has been accepted for processing. To check the offerAssignmentStatus of an instance, please call the “Get Free Game Offers for a specific player” API or “Get the list of players assigned to a Free Game Offer” API. <br /> 分配请求已被接受并正在处理。如要检查派发的offerAssignmentStatus，请调用“获取特定玩家的免费游戏优惠”API或“获取免费游戏优惠的玩家名单”API。

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                           |
|-----------------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                       |
| instanceGuid                | string | A player can be assigned multiple times to the same free game offer, each with a unique instance ID. <br /><br /> 一个玩家可被多次分配到同一个免费游戏优惠，每次都有一个独特的派发ID。 |
| agentPlayerId               | string | The unique identifier for the Player <br /><br /> 玩家的唯一标识符                                                                                            |

EXAMPLE:

```
{
  "instanceGuid": "ec36e421-6fb2-4b89-85ab-d6071c08e047"
}
```

STATUS CODE - 400: Bad request <br /> 错误的请求

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}
```

STATUS CODE - 401: Authorization information is missing or invalid <br /> 授权信息丢失或无效

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}
```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br /> 资源不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "ResourceNotFound",
  "message": "Resource Not Found 找不到资源"
}
```

STATUS CODE - 500: Unexpected error <br /> 未预期的错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

## 5.2 POST /agents/{agentCode}/offers/{offerGuid}/freeGameBatchInstances

Assign multiple players to an existing free game offer 分配现有的免费游戏优惠给多个玩家

Utilize this endpoint to assign multiple players to a free game offer, creating instances of the offer for the player to use.

Upon successfully assigning a player to the offer, the API should return a 202 response. The response will include the unique instanceGuid.

使用此端点分配免费游戏优惠给多个玩家，创建可用的优惠派发。

成功将玩家分配到优惠后，API应返回202响应。响应将包括独一无二的派发ID。

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE                                      | EXAMPLE | DESCRIPTION                                                                |
|------------|-------------------------------------------|---------|----------------------------------------------------------------------------|
| *offerGuid | uuid                                      |         | The unique GUID that identifies the Free Game Offer <br /> 识别免费游戏优惠的独特GUID |
| *agentCode | string<br>PATTERN: ^[a-zA-Z0-9_-]{3,50}\$ |         | The unique identifier for the Agent <br />代理的唯一标识符                         |

#### REQUEST BODY - application/json-patch+json

| NAME                              | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
|-----------------------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAvailableToPlayerFromDateUTC | string | <p>The time in UTC from which players can start playing the free game offered. If not specified, it will default to the current date and time. &lt;br /&gt;&lt;br /&gt; Remarks: &lt;br /&gt;&lt;br /&gt; The date should be from the current date or later but within the range that the offer is valid. &lt;br /&gt;- Latest start date of the instance can be the end date of the offer period. &lt;br /&gt;- The player can use the instance until the end of the validity period. &lt;br /&gt;&lt;br /&gt; Example Use Case: &lt;br /&gt;&lt;br /&gt;- Offer period: Dec 1 - Dec 31 &lt;br /&gt;- Validity period of an instance: 7 days &lt;br /&gt;- If a player is assigned to the offer on December 31, the availability period will be set from December 31 - January 6 per the validity period of 7 days. &lt;br /&gt;- The Agent will not be able to assign the player to the offer on Jan 1, as this surpasses the offer period. &lt;br /&gt;&lt;br /&gt; 玩家可以开始使用免费游戏的时间（使用UTC时间表示）。如果未指定，将默认为当前日期和时间。 &lt;br /&gt;&lt;br /&gt; 备注：&lt;br /&gt;&lt;br /&gt; • 日期应为当前日期或之后的日期，但必须在优惠有效期之内。 &lt;br /&gt; • 派发的最晚开始日期可以是优惠期的结束日期。 &lt;br /&gt; • 玩家可以在有效期结束前使用该派发。 &lt;br /&gt;&lt;br /&gt; 示例：&lt;br /&gt;&lt;br /&gt; • 优惠期：12月1日至12月31日 &lt;br /&gt; • 派发的有效期：7天 &lt;br /&gt; • 如果玩家在12月31日被分配到该优惠，根据7天的有效期，可用期将从12月31日到1</p> |

| NAME     | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|----------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          |        | 月6日。 <br /> • 代理将无法在1月1日将玩家分配到该优惠，因为这超出了优惠期。                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
| players* | array  | A list of Player Ids. <br /><br /> • The player ID must be alphanumeric (A-Z, 0-9) and can contain a maximum of 50 characters. You may also include underscore ( _ ) or hyphen ( - ) symbols. <br /> • The maximum number of players allowed is 20000. <br /> • Duplicate player IDs have been detected. If a player ID appears multiple times, it will be assigned multiple times instead of updating a single record. <br /><br /> 玩家 ID 列表 <br /><br /> • 玩家代码必须是字母和数字（A-Z，0-9）的组合，最多可以包含50个字符。您还可以包含下划线 ( _ ) 或连字符 ( - ) 符号 <br /> • 支援玩家数量上限为20000 <br /> • 侦测到重复的玩家代码。如果一个玩家代码出现多次，它将被多次分配，而不是只被分配一次 |
|          | string |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| meta     | object |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| fileName | string | 0 to 50 chars<br>.CSV File Name (For internal use only) <br /> .CSV 档案名称（仅供内部使用）                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |

EXAMPLE:

```
{
  "offerAvailableToPlayerFromDateUTC": "2023-02-10T15:25:00Z",
  "players": [
    "ABC123",
    "DEF456"
  ]
}
```

REQUEST BODY - application/json

| NAME                              | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|-----------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAvailableToPlayerFromDateUTC | string | The time in UTC from which players can start playing the free game offered. If not specified, it will default to the current date and time. <br /><br /> Remarks: <br /><br /> The date should be from the current date or later but within the range that the offer is valid. <br /> Latest start date of the instance can be the end date of the offer period. <br /> The player can use the instance until the end of the validity period. <br /><br /> Example Use Case: <br /><br /> Offer period: Dec 1 - Dec 31 <br /> > Validity period of an instance: 7 days <br /> If a player is assigned to the offer on December 31, the availability period will be set from December 31 - January 6 per the validity period of 7 days. <br /> The Agent will not be able to assign the player to the offer on Jan 1, as this surpasses the offer period. <br /><br /> 玩家可以开始使用免费游戏的时间（使用UTC时间表示）。如果未指定，将默认为当前日期和时间。 <br /><br /> 备注： <br /><br /> • 日期应为当前日期或之后的日期，但必须在优惠有效期之内。 <br /> • 派发的最晚开始日期可以是优惠期的结束日期。 <br /> • 玩家可以在有效期结束前使用该派发。 <br /><br /> 示例： <br /><br /> • 优惠期：12月1日至12月31日 <br /> • 派发的有效期：7天 <br /> > • 如果玩家在12月31日被分配到该优惠，根据7天的有效期，可用期将从12月31日到1月6日。 <br /> • 代理将无法在1月1日将玩家分配到该优惠，因为这超出了优惠期。 |
| players*                          | array  | A list of Player Ids. <br /><br /> • The player ID must be alphanumeric (A-Z, 0-9) and can contain a maximum of 50 characters. You may also include underscore ( _ ) or hyphen ( - ) symbols. <br /> • The maximum number of players allowed is 20000. <br /> • Duplicate player IDs have been detected. If a player ID appears multiple times, it will be assigned multiple times instead of updating a single record. <br /><br /> 玩家 ID 列表 <br /><br /> • 玩家代码必须是字母和数字（A-Z，0-9）的组合，最多可以包含50个字符。您还可以包含下划线 ( _ ) 或连字符 ( - ) 符号 <br /> • 支援玩家数量上限为20000 <br /> • 侦测到重复的玩家代码。如果一个玩家代码出现多次，它将被多次分配，而不是只被分配一次                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|                                   | string |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| meta                              | object |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| fileName                          | string | 0 to 50 chars<br>.CSV File Name (For internal use only) <br /> .CSV 档案名称（仅供内部使用）                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |

EXAMPLE:

```
{
  "offerAvailableToPlayerFromDateUTC": "2023-02-10T15:25:00Z",
  "players": [
    "ABC123",
    "DEF456"
  ]
}
```

}

REQUEST BODY - text/json

| NAME                              | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAvailableToPlayerFromDateUTC | string | The time in UTC from which players can start playing the free game offered. If not specified, it will default to the current date and time. <br /><br /> Remarks: <br /><br /> The date should be from the current date or later but within the range that the offer is valid. <br /><br /> Latest start date of the instance can be the end date of the offer period. <br /><br /> The player can use the instance until the end of the validity period. <br /><br /> Example Use Case: <br /><br /> Offer period: Dec 1 - Dec 31 <br /><br /> Validity period of an instance: 7 days <br /><br /> If a player is assigned to the offer on December 31, the availability period will be set from December 31 - January 6 per the validity period of 7 days. <br /><br /> The Agent will not be able to assign the player to the offer on Jan 1, as this surpasses the offer period. <br /><br /> 玩家可以开始使用免费游戏的时间（使用UTC时间表示）。如果未指定，将默认为当前日期和时间。 <br /><br /> 备注：<br /><br /> • 日期应为当前日期或之后的日期，但必须在优惠有效期之内。 <br /><br /> • 派发的最晚开始日期可以是优惠期的结束日期。 <br /><br /> • 玩家可以在有效期结束前使用该派发。 <br /><br /> 示例：<br /><br /> • 优惠期：12月1日至12月31日 <br /><br /> • 派发的有效期：7天 <br /><br /> • 如果玩家在12月31日被分配到该优惠，根据7天的有效期，可用期将从12月31日到1月6日。 <br /><br /> • 代理将无法在1月1日将玩家分配到该优惠，因为这超出了优惠期。 |
| players*                          | array  | A list of Player Ids. <br /><br /> • The player ID must be alphanumeric (A-Z, 0-9) and can contain a maximum of 50 characters. You may also include underscore ( _ ) or hyphen ( - ) symbols. <br /><br /> • The maximum number of players allowed is 20000. <br /><br /> Duplicate player IDs have been detected. If a player ID appears multiple times, it will be assigned multiple times instead of updating a single record. <br /><br /> 玩家 ID 列表 <br /><br /> • 玩家代码必须是字母和数字（A-Z，0-9）的组合，最多可以包含50个字符。您还可以包含下划线（_）或连字符（-）符号 <br /><br /> • 支援玩家数量上限为20000 <br /><br /> • 侦测到重复的玩家代码。如果一个玩家代码出现多次，它将被多次分配，而不是只被分配一次                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|                                   | string |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| meta                              | object |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| fileName                          | string | 0 to 50 chars<br>.CSV File Name (For internal use only) <br /> .CSV 档案名称（仅供内部使用）                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

EXAMPLE:

```
{
  "offerAvailableToPlayerFromDateUTC": "2023-02-10T15:25:00Z",
  "players": [
    "ABC123",
    "DEF456"
  ]
}
```

REQUEST BODY - application/\*+json

| NAME                              | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|-----------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAvailableToPlayerFromDateUTC | string | The time in UTC from which players can start playing the free game offered. If not specified, it will default to the current date and time. <br /><br /> Remarks: <br /><br /> The date should be from the current date or later but within the range that the offer is valid. <br /><br /> Latest start date of the instance can be the end date of the offer period. <br /><br /> The player can use the instance until the end of the validity period. <br /><br /> Example Use Case: <br /><br /> Offer period: Dec 1 - Dec 31 <br /><br /> Validity period of an instance: 7 days <br /><br /> If a player is assigned to the offer on December 31, the availability period will be set from December 31 - January 6 per the validity period of 7 days. <br /><br /> The Agent will not be able to assign the player to the offer on Jan 1, as this surpasses the offer period. <br /><br /> 玩家可以开始使用免费游戏的时间（使用UTC时间表示）。如果未指定，将默认为当前日期和时间。 <br /><br /> 备注：<br /><br /> • 日期应为当前日期或之后的日期，但必须在优惠有效期之内。 <br /><br /> • 派发的最晚开始日期可以是优惠期的结束日期。 <br /><br /> • 玩家可以在有效期结束前使用该派发。 <br /><br /> 示例：<br /><br /> • 优惠期：12月1日至12月31日 <br /><br /> • 派发的有效期：7天 <br /><br /> • 如果玩家在12月31日被分配到该优惠，根据7天的有效期，可用期将从12月31日到1月6日。 <br /><br /> • 代理将无法在1月1日将玩家分配到该优惠，因为这超出了优惠期。 |
| players*                          | array  | A list of Player Ids. <br /><br /> • The player ID must be alphanumeric (A-Z, 0-9) and can contain a maximum of 50 characters. You may also include underscore ( _ ) or hyphen ( - ) symbols. <br /><br /> • The maximum number of players allowed is 20000.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |

| NAME     | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                   |
|----------|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|          |        | <br /> • Duplicate player IDs have been detected. If a player ID appears multiple times, it will be assigned multiple times instead of updating a single record. <br /> ><br /> 玩家 ID 列表 <br /><br /> • 玩家代码必须是字母和数字（A-Z，0-9）的组合，最多可以包含50个字符。您还可以包含下划线（_）或连字符（-）符号 <br /> • 支援玩家数量上限为20000 <br /> • 侦测到重复的玩家代码。如果一个玩家代码出现多次，它将被多次分配，而不是只被分配一次 |
|          | string |                                                                                                                                                                                                                                                                                                                                               |
| meta     | object |                                                                                                                                                                                                                                                                                                                                               |
| fileName | string | 0 to 50 chars<br>.CSV File Name (For internal use only) <br /> .CSV 档案名称（仅供内部使用）                                                                                                                                                                                                                                                              |

EXAMPLE:

```
{
  "offerAvailableToPlayerFromDateUTC": "2023-02-10T15:25:00Z",
  "players": [
    "ABC123",
    "DEF456"
  ]
}
```

## RESPONSE

STATUS CODE - 202: The assignment request has been accepted for processing. To check the offerAssignmentStatus of an instance, please call the “Get Free Game Offers for a specific player” API or “Get the list of players assigned to a Free Game Offer” API. <br /> 分配请求已被接受并正在处理。如要检查派发的offerAssignmentStatus，请调用“获取特定玩家的免费游戏优惠”API或“获取免费游戏优惠的玩家名单”API。

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                           |
|-----------------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                       |
| batchGuid                   | string | The unique GUID that identifies the batch for offer assignment <br /> 批处理作业的唯一 GUID                                                                   |
| instances                   | array  | Instances                                                                                                                                             |
| instanceGuid                | string | A player can be assigned multiple times to the same free game offer, each with a unique instance ID. <br /><br /> 一个玩家可被多次分配到同一个免费游戏优惠，每次都有一个独特的派发ID。 |
| agentPlayerId               | string | The unique identifier for the Player <br /><br /> 玩家的唯一标识符                                                                                            |

EXAMPLE:

```
{
  "batchGuid": "31e5d0f5-81fe-43eb-a394-2beb06baa8ae",
  "instances": [
    {
      "instanceGuid": "cb9084b6-3bc3-4e09-86bf-8e37898b607c",
      "agentPlayerId": "Abc123"
    },
    {
      "instanceGuid": "47ef6ede-fc22-431f-86e8-ddb655d98764",
      "agentPlayerId": "Def456"
    }
  ]
}
```

STATUS CODE - 400: Bad request <br /> 错误的请求

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}
```

STATUS CODE - 401: Authorization information is missing or invalid <br /> 授权信息丢失或无效

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}
```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br /> 资源不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "ResourceNotFound",
  "message": "Resource Not Found 找不到资源"
}
```

STATUS CODE - 500: Unexpected error <br /> 未预期的错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

### 5.3 PATCH /agents/{agentCode}/players/{playerId}/freeGameInstances/{instanceGuid}

Update the status of an existing free game offer instance assigned to a player 更新已分配给玩家的免费游戏优惠的派发状态

Utilize this endpoint to update the status of the free game offer instance.

Only Assigned and Player Rejected instances can be changed to other statuses (within the validity

period).

Assigned → changed to Cancelled (for when an agent wants to cancel an instance assigned to a player)

Player Rejected → changed to Assigned (for when an agent wants to reinstate the offer for the player, the instance GUID will remain unchanged in this scenario)

使用此端点更新免费游戏优惠派发的状态。

只有已分配（Assigned）和玩家拒绝（Player Rejected）的派发可以更改为其他状态（在有效期内）。

Assigned（已分配）→ 更改为Cancelled（取消）（当代理想要取消分配给玩家的派发时）  
Player Rejected（玩家拒绝）→ 更改为Assigned（已分配）（当代理想要为玩家恢复优惠时，派发GUID将保持不变）

REQUEST

PATH PARAMETERS

| NAME          | TYPE                                      | EXAMPLE | DESCRIPTION                                                                                                                                           |
|---------------|-------------------------------------------|---------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode    | string<br>PATTERN: ^[a-zA-Z0-9_-]{3,50}\$ |         | The unique identifier for the Agent <br />代理的唯一标识符                                                                                                    |
| *playerId     | string<br>1 to 50 chars                   |         | The unique identifier for the Player <br /><br /> 玩家的唯一标识符                                                                                            |
| *instanceGuid | uuid                                      |         | A player can be assigned multiple times to the same free game offer, each with a unique instance ID. <br /><br /> 一个玩家可被多次分配到同一个免费游戏优惠，每次都有一个独特的派发ID。 |

REQUEST BODY - application/json-patch+json

| NAME                   | TYPE | DESCRIPTION                                                                                                            |
|------------------------|------|------------------------------------------------------------------------------------------------------------------------|
| offerAssignmentStatus* | enum | ALLOWED:Cancelled, Assigned<br>Status of the free game instance as assigned to the player <br /><br /> 分配给玩家的免费派发优惠的状态 |

REQUEST BODY - application/json

| NAME                   | TYPE | DESCRIPTION                                                                                                            |
|------------------------|------|------------------------------------------------------------------------------------------------------------------------|
| offerAssignmentStatus* | enum | ALLOWED:Cancelled, Assigned<br>Status of the free game instance as assigned to the player <br /><br /> 分配给玩家的免费派发优惠的状态 |

REQUEST BODY - text/json

| NAME                   | TYPE | DESCRIPTION                                                                                                            |
|------------------------|------|------------------------------------------------------------------------------------------------------------------------|
| offerAssignmentStatus* | enum | ALLOWED:Cancelled, Assigned<br>Status of the free game instance as assigned to the player <br /><br /> 分配给玩家的免费派发优惠的状态 |

REQUEST BODY - application/\*+json

| NAME                   | TYPE | DESCRIPTION                                                                                                            |
|------------------------|------|------------------------------------------------------------------------------------------------------------------------|
| offerAssignmentStatus* | enum | ALLOWED:Cancelled, Assigned<br>Status of the free game instance as assigned to the player <br /><br /> 分配给玩家的免费派发优惠的状态 |

| NAME | TYPE | DESCRIPTION |
|------|------|-------------|
|      |      | 态           |

## RESPONSE

STATUS CODE - 200: Instance status updated <br /> 派发状态更新

RESPONSE MODEL - application/json

STATUS CODE - 400: Bad request <br /> 错误的请求

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}
```

STATUS CODE - 401: Authorization information is missing or invalid <br /> 授权信息丢失或无效

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}
```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br /> 资源不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "ResourceNotFound",
  "message": "Resource Not Found 找不到资源"
}
```

STATUS CODE - 409:

RESPONSE MODEL - application/json

| NAME                        | TYPE | DESCRIPTION |
|-----------------------------|------|-------------|
| OBJECT WITH BELOW STRUCTURE |      |             |

| NAME    | TYPE   | DESCRIPTION                |
|---------|--------|----------------------------|
| code    | string | Error Code. <br />错误代码。    |
| message | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "ResourceStateConflict",
  "message": "The request could not be completed due to a conflict with the current state of the resource"
}
```

STATUS CODE - 500: Unexpected error <br /> 未預期的錯誤

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

## 5.4 GET /agents/{agentCode}/players/{playerId}/freeGameOffers

Get free game offers for a specific player获取特定玩家的免费游戏优惠

Returns a list of offers assigned to the specific player.  
返回特定玩家的优惠

## REQUEST

### PATH PARAMETERS

| NAME       | TYPE                                      | EXAMPLE | DESCRIPTION                                                |
|------------|-------------------------------------------|---------|------------------------------------------------------------|
| *agentCode | string<br>PATTERN: ^[a-zA-Z0-9_-]{3,50}\$ |         | The unique identifier for the Agent <br />代理的唯一标识符         |
| *playerId  | string                                    |         | The unique identifier for the Player <br /><br /> 玩家的唯一标识符 |

### QUERY PARAMETERS

| NAME                  | TYPE                                                                                                                            | EXAMPLE | DESCRIPTION                         |
|-----------------------|---------------------------------------------------------------------------------------------------------------------------------|---------|-------------------------------------|
| offerAssignmentStatus | enum<br>ALLOWED: Cancelled, Assigned, PlayerRejected, FullyConsumed, Expired, Assigning, AssignFailed, Cancelling, CancelFailed |         | The status of the offer <br />优惠的状态 |

| NAME                 | TYPE                            | EXAMPLE | DESCRIPTION                                                                                                                                                |
|----------------------|---------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerGuidStartsWith  | string                          |         | Narrow down results by inputting the offer GUID. Partial search is supported as long as the beginning of the string matches. <br />通过搜索提供的GUID，但字符串的开头需要匹配 |
| offerNameContains    | string                          |         | Narrow down results by inputting the offer name. Partial search is supported. <br />在现有的优惠名称中部分搜索                                                          |
| availableFromDateUTC | date-time                       |         | Search for offers that are available from this date<br />搜索从这个日期开始可用的优惠                                                                                    |
| availableToDateUTC   | date-time                       |         | Search for offers that are available to this date<br />搜索从这个日期结束的优惠                                                                                        |
| offerStatus          | enum<br>ALLOWED: Closed, Active |         |                                                                                                                                                            |
| page                 | int32                           |         | The current page in the response <br />响应中的当前页面                                                                                                            |
| perPage              | int32                           |         | The number of items returned per page. If not provided, it will return 100 by default. <br />每页返回的项目数量。如果不提供，默认返回100。                                      |

## RESPONSE

STATUS CODE - 200: Offers of a specific player <br /> 特定玩家的优惠

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                 |
|--------------------------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                                                                                                                                                                                                             |
| freeGameOffer                        | object |                                                                                                                                                                                                                                                                                                                                             |
| offerAvailableFromDateUTC            | string | The time in UTC indicating from when the Agent can assign the offer to players. <br /><br />代理可以将优惠分配给玩家的UTC时间。                                                                                                                                                                                                                             |
| offerAvailableToDateUTC              | string | The time in UTC at which Agents can no longer assign offers to players. <br /><br />代理无法再将此优惠分配给玩家的UTC时间。                                                                                                                                                                                                                                   |
| offerGuid                            | string | The unique GUID identifying the new offer that was created. <br /><br />识别创建的新优惠的独特GUID.                                                                                                                                                                                                                                                    |
| offerStatus                          | enum   | ALLOWED:Closed, Active                                                                                                                                                                                                                                                                                                                      |
| offerCreateDateUTC                   | string | The time in UTC when the offer was created. <br /><br />创建优惠的UTC时间                                                                                                                                                                                                                                                                          |
| offerGames                           | array  | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br />优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                              |
| nearestCostPerBet                    | number | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br />游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的价值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                            | string | min:1 chars<br>Game Code. <br /><br />游戏代码。                                                                                                                                                                                                                                                                                                 |
| offerName                            | string | 1 to 50 chars<br>The name of the offer. <br /><br />优惠的有吸引力的名称                                                                                                                                                                                                                                                                              |

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                     |
|-------------------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from the moment it is granted. <br /><br /> 奖励后，玩家可以使用优惠的天数。                                                                      |
| numberOfRounds                      | integer | between 1 and 100<br>The number of games available for the player - this number must be greater than zero.<br><br /><br /> 这是玩家可用的游戏数量，必须大于零。                                                                                   |
| instanceStartDateUTC                | string  | The time in UTC when the instance starts. <br /> 派发开始的UTC时间                                                                                                                                                                     |
| instanceEndDateUTC                  | string  | The time in UTC when the instance ends. <br /> 派发结束的UTC时间                                                                                                                                                                       |
| instanceGuid                        | string  | A player can be assigned multiple times to the same free game offer, each with a unique instance ID. <br /><br /> 一个玩家可被多次分配到同一个免费游戏优惠，每次都有一个独特的派发ID。                                                                           |
| offerAssignmentStatus               | enum    | ALLOWED:Cancelled, Assigned, PlayerRejected, FullyConsumed, Expired, Assigning, AssignFailed, Cancelling, CancelFailed<br>A status that describes the current state of the offer assignment in the system.<br />描述系统中优惠分配当前的状态。 |
| instanceCreateDateUTC               | string  | The time in UTC when the instance was created. <br /> 创建派发的UTC时间                                                                                                                                                                |

#### EXAMPLE:

```
[
  {
    "freeGameOffer": {
      "offerStatus": "Closed",
      "offerAvailableFromDateUTC": "2023-01-10T15:25:00Z",
      "offerAvailableToDateUTC": "2023-05-10T23:59:59Z",
      "offerGuid": "7fc846a3-712b-422d-83ac-5fbc48b7889a",
      "offerCreateDateUTC": "0001-01-01T00:00:00Z",
      "offerGames": [
        {
          "nearestCostPerBet": 1,
          "gameCode": "SMG_Game1"
        },
        {
          "nearestCostPerBet": 10,
          "gameCode": "SMG_Game2"
        }
      ],
      "offerName": "Demo Offer One",
      "durationAvailableInDaysAfterAwarded": 2,
      "numberOfRounds": 10
    },
    "instanceStartDateUTC": "2023-01-10T15:25:00Z",
    "instanceEndDateUTC": "2023-01-12T15:25:00Z",
    "instanceGuid": "188432c5-95f5-4d81-99cd-e39f8ce00320",
    "offerAssignmentStatus": "Assigned",
    "instanceCreateDateUTC": "2023-02-08T00:00:00Z"
  },
  {
    "freeGameOffer": {
      "offerStatus": "Closed",
      "offerAvailableFromDateUTC": "2023-02-08T00:00:00Z",
      "offerAvailableToDateUTC": "2023-03-18T12:00:00Z",
      "offerGuid": "861482d3-36e4-4d69-b53a-aa37fdb2b05d",
      "offerCreateDateUTC": "0001-01-01T00:00:00Z",
      "offerGames": [
        {
          "nearestCostPerBet": 5,
          "gameCode": "SMG_Game3"
        }
      ],
      "offerName": "Demo Offer Two",
      "durationAvailableInDaysAfterAwarded": 2,
      "numberOfRounds": 5
    },
    "instanceStartDateUTC": "2023-02-08T00:00:00Z",
    "instanceEndDateUTC": "2023-02-10T00:00:00Z",
    "instanceGuid": "089240fb-9bbf-4db1-9af8-b213bed6c188",
  }
]
```

```

    "offerAssignmentStatus": "Assigned",
    "instanceCreateDateUTC": "2023-02-08T00:00:00Z"
  }
]

```

STATUS CODE - 400: Bad request <br /> 错误的请求

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}

```

STATUS CODE - 401: Authorization information is missing or invalid <br /> 授权信息丢失或无效

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}

```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br /> 资源不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "ResourceNotFound",
  "message": "Resource Not Found 找不到资源"
}

```

STATUS CODE - 500: Unexpected error <br /> 未预期的错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{

```

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

## 5.5 GET /agents/{agentCode}/offers/{offerGuid}/players

Get the list of players assigned to a free game offer 获取免费游戏优惠的玩家名单

Returns a list of players assigned to a specific free game offer.  
返回分配给这个优惠的玩家信息

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE                                                   | EXAMPLE | DESCRIPTION                                                                |
|------------|--------------------------------------------------------|---------|----------------------------------------------------------------------------|
| *agentCode | string<br>PATTERN: <code>^[a-zA-Z0-9_-]{3,50}\$</code> |         | The unique identifier for the Agent <br />代理的唯一标识符                         |
| *offerGuid | uuid                                                   |         | The unique GUID that identifies the Free Game Offer <br /> 识别免费游戏优惠的独特GUID |

#### QUERY PARAMETERS

| NAME                      | TYPE                                                                                                                            | EXAMPLE | DESCRIPTION                                                                                                                                                                                                            |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAssignmentStatus     | enum<br>ALLOWED: Cancelled, Assigned, PlayerRejected, FullyConsumed, Expired, Assigning, AssignFailed, Cancelling, CancelFailed |         | The status of the offer <br />优惠的状态                                                                                                                                                                                    |
| playerId                  | string<br>1 to 50 chars                                                                                                         |         | The unique identifier for the Player <br /> <br /> 玩家的唯一标识符                                                                                                                                                            |
| startAvailableFromDateUTC | date-time                                                                                                                       |         | Specify the beginning of the date range to narrow down results. Only players assigned to the offer with instances that align within this specified range will be included.<br />填写日期范围的开始，以缩小结果范围。只有在指定范围内被分配的玩家会包括在内。 |
| endAvailableFromDateUTC   | date-time                                                                                                                       |         | Specify the end of the date range to narrow down results. Only players assigned to the offer with instances that align within this specified range will be included.<br />填写日期范围的结束，以缩小结果范围。只有在指定范围内被分配的玩家会包括在内。       |
| page                      | int32                                                                                                                           |         | The current page in the response <br />响应中的当前页面                                                                                                                                                                        |
| perPage                   | int32                                                                                                                           |         | The number of items returned per page. If not provided, it will return 100 by default. <br />每页返回的项目数量。如果不提供，默认返回100。                                                                                                  |

### RESPONSE

STATUS CODE - 200: Information of players assigned to an offer <br />分配给这个优惠的玩家信息

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                                                                                                                                                                                     |
|--------------------------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                                                                                                 |
| playerId                             | string | The unique identifier for the Player <br /><br /> 玩家的唯一标识符                                                                                                                                                                      |
| instanceGuid                         | string | A player can be assigned multiple times to the same free game offer, each with a unique instance ID. <br /><br /> 一个玩家可被多次分配到同一个免费游戏优惠，每次都有一个独特的派发ID。                                                                           |
| offerAssignmentStatus                | enum   | ALLOWED:Cancelled, Assigned, PlayerRejected, FullyConsumed, Expired, Assigning, AssignFailed, Cancelling, CancelFailed<br>A status that describes the current state of the offer assignment in the system.<br />描述系统中优惠分配当前的状态。 |
| instanceStartDateUTC                 | string | The UTC time when the instance is started <br /> 实例开始的UTC时间                                                                                                                                                                     |
| instanceEndDateUTC                   | string | The UTC time when the instance is ended <br /> 实例结束的UTC时间                                                                                                                                                                       |

EXAMPLE:

```
[
  {
    "playerId": "Player 1",
    "instanceGuid": "293c4a39-8c85-4262-9da0-6c7a8adfc30c",
    "offerAssignmentStatus": "Assigned",
    "instanceStartDateUTC": "2023-01-10T15:25:00Z",
    "instanceEndDateUTC": "2023-01-17T15:25:00Z"
  },
  {
    "playerId": "Player 2",
    "instanceGuid": "1764096c-d783-4cb1-9290-db78c853fb1c",
    "offerAssignmentStatus": "Expired",
    "instanceStartDateUTC": "2023-01-10T15:25:00Z",
    "instanceEndDateUTC": "2023-01-17T15:25:00Z"
  }
]
```

STATUS CODE - 400: Bad request <br /> 错误的请求

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}
```

STATUS CODE - 401: Authorization information is missing or invalid <br /> 授权信息丢失或无效

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}
```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br /> 资源不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "ResourceNotFound",
  "message": "Resource Not Found 找不到资源"
}
```

STATUS CODE - 500: Unexpected error <br /> 未预期的错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

## 5.6 GET /agents/{agentCode}/offers/batches/{batchGuid}

Get batch details 获取批次详细资料

Retrieve the details of a batch upload.  
检索批量上传的详细信息

### REQUEST

PATH PARAMETERS

| NAME       | TYPE                                      | EXAMPLE | DESCRIPTION                                                                           |
|------------|-------------------------------------------|---------|---------------------------------------------------------------------------------------|
| *batchGuid | uuid                                      |         | The unique GUID that identifies the batch for offer assignment<br><br />批处理作业的唯一 GUID |
| *agentCode | string<br>PATTERN: ^[a-zA-Z0-9_-]{3,50}\$ |         | The unique identifier for the Agent <br />代理的唯一标识符                                    |

### RESPONSE

STATUS CODE - 200: Batch details returned successfully.<br />成功返回批量详细资料。

RESPONSE MODEL - application/json

| NAME                              | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                     |
|-----------------------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE       |         |                                                                                                                                                                                                                                                                                                                 |
| players                           | array   | A list of players assigned to the offer in the batch job.<br />批量作业中分配给该优惠的玩家列表。                                                                                                                                                                                                                                |
| instanceGuid                      | string  | A player can be assigned multiple times to the same free game offer, each with a unique instance ID. <br /><br /> 一个玩家可被多次分配到同一个免费游戏优惠，每次都有一个独特的派发ID。                                                                                                                                                           |
| instanceCreateDateUTC             | string  | The time in UTC when the instance was created. <br /> 创建实例的UTC时间                                                                                                                                                                                                                                                |
| offerAssignmentStatus             | enum    | ALLOWED:Cancelled, Assigned, PlayerRejected, FullyConsumed, Expired, Assigning, AssignFailed, Cancelling, CancelFailed<br><br>A status that describes the current state of the offer assignment in the system.<br />描述系统中优惠分配当前的状态。                                                                             |
| playerId                          | string  | The unique identifier for the Player <br /><br /> 玩家的唯一标识符                                                                                                                                                                                                                                                      |
| isNewPlayer                       | boolean | A boolean flag indicating whether the player already existed in the MG+ system before the offer assignment process. If the player did not exist previously, this flag will be set to 'false,' prompting the system to create the player.<br />一个布尔标志，指示在MG+系统中是否在分配优惠过程之前已存在该玩家。如果玩家以前不存在，将显示为'false'，系统便会创建玩家。 |
| isPartiallyConsumed               | boolean | A boolean flag indicating whether an instance is partially consumed by a player. The assigned instance is partially consumed and cannot be cancelled.<br /><br /> 一个布尔标志，指示派发是否部分使用。分配的派发已被部分使用，无法取消。                                                                                                           |
| batchInfo                         | object  |                                                                                                                                                                                                                                                                                                                 |
| batchGuid                         | string  | The unique GUID that identifies the batch for offer assignment <br /> 批处理作业的唯一 GUID                                                                                                                                                                                                                             |
| batchAssignmentStatus             | enum    | ALLOWED:Assigning, Assigned, Cancelling, Cancelled<br><br>A status that describes the current state of the batch assignment in the system.<br />描述系统中批量分配当前的状态。                                                                                                                                                 |
| meta                              | object  |                                                                                                                                                                                                                                                                                                                 |
| fileName                          | string  | 0 to 50 chars<br>.CSV File Name (For internal use only) <br /> .CSV 档案名称（仅供内部使用）                                                                                                                                                                                                                                |
| offerAvailableToPlayerFromDateUTC | string  | The time in UTC from which players can start playing the free game offered. <br /> 玩家可以使用该派发的UTC日期                                                                                                                                                                                                              |
| batchCreateDateUTC                | string  | The date and time when the batch job was started<br />批量作业启动的日期和时间。                                                                                                                                                                                                                                             |
| summary                           | object  |                                                                                                                                                                                                                                                                                                                 |
| totalRequests                     | integer | The total number of players detected from the batch upload.<br />批量上传中检测到的玩家总数。                                                                                                                                                                                                                                 |
| successfulRequests                | integer | The number of players successfully assigned to the offer with an instance status of 'Assigned.'<br />成功分配到该派发的玩家数量，状态为'已分配'（Assigned）。                                                                                                                                                                          |
| failedRequests                    | integer | The number of players who encountered errors during the assignment process resulting in an instance status of 'AssignFailed.' Players with errors will not be assigned to the offer.<br />在分配过程中遇到错误的玩家数量，导致派发状态为'分配失败'（AssignFailed）。出现错误的玩家将不会被分配到该优惠。                                                        |
| newPlayersAdded                   | integer | The number of new players that have been created and assigned to the offer, as the player IDs listed do not exist in the MG+ system.<br />已创建并分配到该优惠的新玩家数量。这些玩家ID之前是不存在 MG+ 系统里。                                                                                                                                |
| cancellationSummary               | object  |                                                                                                                                                                                                                                                                                                                 |
| nonCancellableRequests            | integer | Number of instances that cannot be cancelled (partially or fully consumed instances, player rejection, expired offer, assignment errors, or cancellation API errors). <br /><br /> 无法取消的派发数量（部分或完全使用的派发、玩家拒绝、优惠过期、分配错误或取消 API 错误）。                                                                              |
| cancellingRequests                | integer | Number of instances that are currently being cancelled. <br /><br /> 当前正在取消的派发数量。                                                                                                                                                                                                                               |

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                 |
|-------------------------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| cancelledRequests                   | integer | Number of instances that have been successfully cancelled. <br /><br /> 已成功取消的派发数量。                                                                                                                                                                                                                                                         |
| freeGameOffer                       | object  |                                                                                                                                                                                                                                                                                                                                             |
| offerAvailableFromDateUTC           | string  | The time in UTC indicating from when the Agent can assign the offer to players. <br /><br /> 代理可以将优惠分配给玩家的UTC时间。                                                                                                                                                                                                                            |
| offerAvailableToDateUTC             | string  | The time in UTC at which Agents can no longer assign offers to players. <br /><br /> 代理无法再将此优惠分配给玩家的UTC时间。                                                                                                                                                                                                                                  |
| offerGuid                           | string  | The unique GUID identifying the new offer that was created. <br /><br /> 识别创建的新优惠的独特GUID。                                                                                                                                                                                                                                                   |
| offerStatus                         | enum    | ALLOWED:Closed, Active                                                                                                                                                                                                                                                                                                                      |
| offerCreateDateUTC                  | string  | The time in UTC when the offer was created. <br /><br /> 创建优惠的UTC时间                                                                                                                                                                                                                                                                         |
| offerGames                          | array   | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                             |
| nearestCostPerBet                   | number  | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最近的价值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                           | string  | min:1 chars<br>Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                                |
| offerName                           | string  | 1 to 50 chars<br>The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                             |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from the moment it is granted. <br /><br /> 奖励后，玩家可以使用优惠的天数。                                                                                                                                                                                  |
| numberOfRounds                      | integer | between 1 and 100<br>The number of games available for the player - this number must be greater than zero. <br /><br /> 这是玩家可用的游戏数量，必须大于零。                                                                                                                                                                                                  |

#### EXAMPLE:

```
{
  "players": [
    {
      "instanceGuid": "4ed09161-0f95-4baf-ad0d-506f16341adf",
      "instanceCreateDateUTC": "2023-02-10T15:25:00Z",
      "offerAssignmentStatus": "Cancelled",
      "playerId": "aaaa",
      "isNewPlayer": true
    },
    {
      "instanceGuid": "4981f958-9487-4d08-97d9-573cc252f3b1",
      "instanceCreateDateUTC": "2023-02-10T15:25:00Z",
      "offerAssignmentStatus": "Cancelled",
      "playerId": "bbbb",
      "isNewPlayer": false
    }
  ],
  "batchInfo": {
    "batchGuid": "a7cf45e2-3eb1-42c7-b786-c61bd020101a",
    "batchAssignmentStatus": "Assigned",
    "meta": {
      "fileName": "xxx.csv"
    },
    "offerAvailableToPlayerFromDateUTC": "2023-02-10T15:25:00Z",
    "batchCreateDateUTC": "2023-01-10T15:25:00Z",
    "summary": {
```

```

    "totalRequests": 2,
    "successfulRequests": 2,
    "failedRequests": 0,
    "newPlayersAdded": 2
  },
  "freeGameOffer": {
    "offerAvailableFromDateUTC": "2023-01-10T15:25:00Z",
    "offerAvailableToDateUTC": "2023-05-10T23:59:59Z",
    "offerGuid": "c77338e8-0aa7-40e1-94ef-d31d7dbfaa9a",
    "offerStatus": "Closed",
    "offerCreateDateUTC": "2023-01-10T15:25:00Z",
    "offerGames": [
      {
        "nearestCostPerBet": 1,
        "gameCode": "SMG_Game1"
      },
      {
        "nearestCostPerBet": 10,
        "gameCode": "SMG_Game2"
      }
    ],
    "offerName": "Demo Offer One",
    "durationAvailableInDaysAfterAwarded": 2,
    "numberOfRounds": 10
  }
}

```

STATUS CODE - 400: Bad request <br /> 错误的请求

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}

```

STATUS CODE - 401: Authorization information is missing or invalid <br /> 授权信息丢失或无效

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}

```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br /> 资源不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "ResourceNotFound",
  "message": "Resource Not Found 找不到资源"
}
```

STATUS CODE - 500: Unexpected error <br /> 未預期的錯誤

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

## 5.7 GET /agents/{agentCode}/offers/batches

Get batch list 获取批次清单

Utilize this endpoint to retrieve a list of historical batch uploads.  
利用此端点检索批量上传的列表

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE                                      | EXAMPLE | DESCRIPTION                                        |
|------------|-------------------------------------------|---------|----------------------------------------------------|
| *agentCode | string<br>PATTERN: ^[a-zA-Z0-9_-]{3,50}\$ |         | The unique identifier for the Agent <br />代理的唯一标识符 |

#### QUERY PARAMETERS

| NAME                | TYPE      | EXAMPLE | DESCRIPTION                                                                                                                                                |
|---------------------|-----------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerGuidStartsWith | string    |         | Narrow down results by inputting the offer GUID. Partial search is supported as long as the beginning of the string matches. <br /> 通过搜索提供的GUID，但字串的开头需要匹配 |
| offerNameContains   | string    |         | Narrow down results by inputting the offer name. Partial search is supported. <br /> 在现有的优惠名称中部分搜索                                                         |
| batchGuidStartsWith | string    |         | Narrow down results by inputting the batch GUID. Partial search is supported as long as the beginning of the string matches <br /> 通过搜索提供的GUID，但字串的开头需要匹配  |
| uploadStartDateUTC  | date-time |         | Search for batch job uploads initiated from the specified date.<br />搜索从指定日期开始的批量作业。                                                                       |
| uploadEndDateUTC    | date-time |         | Search for batch job uploads that ended on the specified date.<br />搜索在指定日期结束的批量作业上传。                                                                      |

| NAME                  | TYPE                                                                   | EXAMPLE | DESCRIPTION                                                                                           |
|-----------------------|------------------------------------------------------------------------|---------|-------------------------------------------------------------------------------------------------------|
| batchAssignmentStatus | array of string<br>ALLOWED: Assigning, Assigned, Cancelling, Cancelled |         | A status that describes the current state of the batch assignment in the system.<br />描述系统中批量分配当前的状态。 |
| page                  | int32                                                                  |         | The current page in the response <br />响应中的当前页面                                                       |
| perPage               | int32                                                                  |         | The number of items returned per page <br />每页返回的项目数量                                                 |

## RESPONSE

STATUS CODE - 200: Batch list details returned successfully.<br />成功返回批量列表的详细资料。

RESPONSE MODEL - application/json

| NAME                                 | TYPE    | DESCRIPTION                                                                                                                                                                                                                                               |
|--------------------------------------|---------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |         |                                                                                                                                                                                                                                                           |
| batchInfo                            | object  |                                                                                                                                                                                                                                                           |
| batchGuid                            | string  | The unique GUID that identifies the batch for offer assignment <br /> 批处理作业的唯一 GUID                                                                                                                                                                       |
| batchAssignmentStatus                | enum    | ALLOWED:Assigning, Assigned, Cancelling, Cancelled<br>A status that describes the current state of the batch assignment in the system.<br />描述系统中批量分配当前的状态。                                                                                               |
| meta                                 | object  |                                                                                                                                                                                                                                                           |
| fileName                             | string  | 0 to 50 chars<br>.CSV File Name (For internal use only) <br /> .CSV 档案名称（仅供内部使用）                                                                                                                                                                          |
| offerAvailableToPlayerFromDateUTC    | string  | The time in UTC from which players can start playing the free game offered.<br><br />玩家可以使用该派发的UTC日期                                                                                                                                                      |
| batchCreateDateUTC                   | string  | The date and time when the batch job was started<br />批量作业启动的日期和时间。                                                                                                                                                                                       |
| summary                              | object  |                                                                                                                                                                                                                                                           |
| totalRequests                        | integer | The total number of players detected from the batch upload.<br />批量上传中检测到的玩家总数。                                                                                                                                                                           |
| successfulRequests                   | integer | The number of players successfully assigned to the offer with an instance status of 'Assigned'.<br />成功分配到该派发的玩家数量，状态为'已分配' (Assigned)。                                                                                                                   |
| failedRequests                       | integer | The number of players who encountered errors during the assignment process resulting in an instance status of 'AssignFailed'. Players with errors will not be assigned to the offer.<br />在分配过程中遇到错误的玩家数量，导致派发状态为'分配失败' (AssignFailed)。出现错误的玩家将不会被分配到该优惠。 |
| newPlayersAdded                      | integer | The number of new players that have been created and assigned to the offer, as the player IDs listed do not exist in the MG+ system.<br />已创建并分配到该优惠的新玩家数量。这些玩家ID之前是不存在 MG+ 系统里。                                                                          |
| cancellationSummary                  | object  |                                                                                                                                                                                                                                                           |
| nonCancellableRequests               | integer | Number of instances that cannot be cancelled (partially or fully consumed instances, player rejection, expired offer, assignment errors, or cancellation API errors). <br /><br />无法取消的派发数量（部分或完全使用的派发、玩家拒绝、优惠过期、分配错误或取消 API 错误）。                         |
| cancellingRequests                   | integer | Number of instances that are currently being cancelled. <br /><br />当前正在取消的派发数量。                                                                                                                                                                          |
| cancelledRequests                    | integer | Number of instances that have been successfully cancelled. <br /><br />已成功取消的派发数量。                                                                                                                                                                        |
| freeGameOffer                        | object  |                                                                                                                                                                                                                                                           |

| NAME                                | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                  |
|-------------------------------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| offerAvailableFromDateUTC           | string  | The time in UTC indicating from when the Agent can assign the offer to players.<br><br /><br /> 代理可以将优惠分配给玩家的UTC时间。                                                                                                                                                                                                                          |
| offerAvailableToDateUTC             | string  | The time in UTC at which Agents can no longer assign offers to players.<br><br /><br /> 代理无法再将此优惠分配给玩家的UTC时间。                                                                                                                                                                                                                                |
| offerGuid                           | string  | The unique GUID identifying the new offer that was created. <br /><br /> 识别创建的新优惠的独特GUID.                                                                                                                                                                                                                                                    |
| offerStatus                         | enum    | ALLOWED:Closed, Active                                                                                                                                                                                                                                                                                                                       |
| offerCreateDateUTC                  | string  | The time in UTC when the offer was created. <br /><br /> 创建优惠的UTC时间                                                                                                                                                                                                                                                                          |
| offerGames                          | array   | The list of game codes available in the offer and their value per round. These game codes all need to belong to the same game provider. <br /><br /> 优惠中可用的游戏代码列表及在每个回合中的投注金额。这些游戏代码都属于同一游戏提供商。                                                                                                                                              |
| nearestCostPerBet                   | number  | Value per round in each of the games of the offer. If the desired value per round doesn't exactly match an available option in the game, the system will select the closest possible value. If no value per round is specified, the default is the minimum bet. <br /><br /> 游戏在每个回合中的投注金额。如果没有完全匹配的选项，系统会选择最接近的价值。如果未指定每回合的价值，那默认值就是最小下注金额。 |
| gameCode*                           | string  | min:1 chars<br>Game Code. <br /><br /> 游戏代码。                                                                                                                                                                                                                                                                                                 |
| offerName                           | string  | 1 to 50 chars<br>The name of the offer. <br /><br /> 优惠的有吸引力的名称                                                                                                                                                                                                                                                                              |
| durationAvailableInDaysAfterAwarded | integer | between 1 and 99<br>The number of days during which the player can accept the offer, starting from the moment it is granted. <br /><br /> 奖励后，玩家可以使用优惠的天数。                                                                                                                                                                                   |
| numberOfRounds                      | integer | between 1 and 100<br>The number of games available for the player - this number must be greater than zero.<br><br /><br /> 这是玩家可用的游戏数量，必须大于零。                                                                                                                                                                                                |

#### EXAMPLE:

```
[
  {
    "batchInfo": {
      "batchGuid": "b8597bd2-a6f6-425b-a0f3-7f4e1135d4be",
      "batchAssignmentStatus": "Assigned",
      "meta": {
        "fileName": "xxx.csv"
      },
      "offerAvailableToPlayerFromDateUTC": "2023-02-10T15:25:00Z",
      "batchCreateDateUTC": "2023-01-10T15:25:00Z",
      "summary": {
        "totalRequests": 1000,
        "successfulRequests": 995,
        "failedRequests": 5,
        "newPlayersAdded": 2,
        "cancellationSummary": {
          "nonCancellableRequests": 5,
          "cancellingRequests": 2,
          "cancelledRequests": 8
        }
      }
    },
    "freeGameOffer": {
      "offerAvailableFromDateUTC": "2023-01-10T15:25:00Z",
      "offerAvailableToDateUTC": "2023-05-10T23:59:59Z",
      "offerGuid": "cd301109-6787-4d1c-b448-74d0fbe893bb",
      "offerStatus": "Closed",
      "offerCreateDateUTC": "2023-01-10T15:25:00Z",
      "offerGames": [
        {
          "nearestCostPerBet": 1,
          "gameCode": "SMG_Game1"
        }
      ]
    }
  }
]
```

```

    {
      "nearestCostPerBet": 10,
      "gameCode": "SMG_Game2"
    }
  ],
  "offerName": "Demo Offer One",
  "durationAvailableInDaysAfterAwarded": 2,
  "numberOfRounds": 10
},
{
  "batchInfo": {
    "batchGuid": "fc2f226a-094e-44a0-af83-2bcdda35edf5",
    "batchAssignmentStatus": "Assigned",
    "meta": {
      "fileName": "xxx.csv"
    },
    "offerAvailableToPlayerFromDateUTC": "2023-02-10T15:25:00Z",
    "batchCreateDateUTC": "2023-01-10T15:25:00Z",
    "summary": {
      "totalRequests": 1000,
      "successfulRequests": 995,
      "failedRequests": 5,
      "newPlayersAdded": 2,
      "cancellationSummary": {
        "nonCancellableRequests": 5,
        "cancellingRequests": 2,
        "cancelledRequests": 8
      }
    }
  },
  "freeGameOffer": {
    "offerAvailableFromDateUTC": "2023-01-10T15:25:00Z",
    "offerAvailableToDateUTC": "2023-05-10T23:59:59Z",
    "offerGuid": "c2d50164-e171-499a-bc32-f03ea48c4590",
    "offerStatus": "Closed",
    "offerCreateDateUTC": "2023-01-10T15:25:00Z",
    "offerGames": [
      {
        "nearestCostPerBet": 1,
        "gameCode": "SMG_Game1"
      },
      {
        "nearestCostPerBet": 10,
        "gameCode": "SMG_Game2"
      }
    ],
    "offerName": "Demo Offer two",
    "durationAvailableInDaysAfterAwarded": 5,
    "numberOfRounds": 12
  }
}
]

```

STATUS CODE - 400: Bad request <br /> 错误的请求

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "WrongParameter",
  "message": "Invalid Parameter 参数无效"
}

```

STATUS CODE - 401: Authorization information is missing or invalid <br /> 授权信息丢失或无效

RESPONSE MODEL - application/json

| NAME | TYPE | DESCRIPTION |
|------|------|-------------|
|------|------|-------------|

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "UnauthorizedRequest",
  "message": "The request is not authorized 该请求未经授权"
}
```

STATUS CODE - 403: Forbidden

STATUS CODE - 404: Resource does not exist <br /> 资源不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "ResourceNotFound",
  "message": "Resource Not Found 找不到资源"
}
```

STATUS CODE - 500: Unexpected error <br /> 未預期的錯誤

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "GeneralError",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

## 6. GAME ASSETS 遊戲素材

### 6.1 GET /agents/{agentCode}/assets/imageTemplate

Get image assets for a game 获取游戏的素材

Return a template URL that can be modified to retrieve an image asset. 返回可以修改以取得素材的模板网址。

Replace the variables using the following allowed values. 使用以下允许值替换变数。

- {language}: EN, ZH\_CN
- {Style}: Square, Logo
- {GameCode}: Any valid Game Code (i.e. SMG\_luckyTwins)
- {Size}: Images can be sized from 80x80 to 600x600. This is optional, else default of 600x600 is returned. 图像的尺寸可以从 80x80 到 600x600。这是非必須的，否则返回默认值 600x600。
- {Type}: JPG, PNG

Example

- [https://PrdDomain.com/EN/Square/100x100/SMG\\_LuckyTwins.JPG](https://PrdDomain.com/EN/Square/100x100/SMG_LuckyTwins.JPG)
- [https://PrdDomain.com/EN/Square/SMG\\_LuckyTwins.JPG](https://PrdDomain.com/EN/Square/SMG_LuckyTwins.JPG)

It is recommended to get the latest template URL periodically. This is to ensure that generated image links are using the latest Domain. 建议定期获取最新的模板网址。这是为了确保生成的素材链接使用最新的网域。

### REQUEST

| PATH PARAMETERS |        |         |                        |
|-----------------|--------|---------|------------------------|
| NAME            | TYPE   | EXAMPLE | DESCRIPTION            |
| *agentCode      | string |         | The agent code<br>代理人码 |

### RESPONSE

STATUS CODE - 200: OK. Game images website returned  
游戏素材站台返回

| RESPONSE MODEL - application/json |        |             |
|-----------------------------------|--------|-------------|
| NAME                              | TYPE   | DESCRIPTION |
| OBJECT WITH BELOW STRUCTURE       |        |             |
| gameAsset                         | object |             |

| NAME       | TYPE   | DESCRIPTION                                     |
|------------|--------|-------------------------------------------------|
| default    | string | The default image URL format<br>预设图片            |
| customSize | string | The customized image size URL format<br>客制化图片大小 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 403: Forbidden  
禁止

STATUS CODE - 404: The agent code does not exist  
代理人码不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                   |
|-----------------------------|--------|-------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                               |
| code                        | string | AgentDoesNotExist             |
| message                     | string | The agent code does not exist |
| message-zh-CHS              | string | 代理人码不存在。                      |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 6.2 GET /agents/{agentCode}/assets/liveDealerTables

Get details of the live dealer tables 获取真人游戏荷官桌的详细信息

Retrieve details of the live dealer tables.  
获取真人游戏荷官桌的详细信息。

### REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

### RESPONSE

STATUS CODE - 200: Details of the live dealer table returned<br>真人游戏荷官桌的详细信息已经获取

RESPONSE MODEL - text/plain

| NAME                                 | TYPE    | DESCRIPTION                                                           |
|--------------------------------------|---------|-----------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |         |                                                                       |
| gameCode                             | string  | Game code.<br>游戏编号。                                                   |
| tableCode                            | string  | Table code.<br>桌子编号。                                                  |
| dealerInfo                           | object  |                                                                       |
| name                                 | string  | Dealer' s name.<br>荷官的名字。                                             |
| connectedPlayersCount                | integer | Number of players that are currently online.<br>当前在线玩家数。              |
| blackjackInfo                        | object  |                                                                       |
| totalSeats                           | integer | Total number of seats at the table.<br>桌子的总座位数。                       |
| freeSeats                            | integer | Total number of available seats at the table.<br>桌子上可用座位的总数。          |
| rouletteInfo                         | object  |                                                                       |
| hotNumbers                           | array   | Numbers that have appeared frequently in past spins.<br>过去旋转中频繁出现的数字。 |
|                                      | string  |                                                                       |
| coldNumbers                          | array   | Numbers that have rarely appeared in past spins.<br>过去旋转中很少出现的数字。     |
|                                      | string  |                                                                       |
| winningHistory                       | array   | Winning results from past rounds.<br>过去回合的获胜结果。                       |
|                                      | string  |                                                                       |
| winningNumberHistory                 | array   | Winning numbers in past spins.<br>过去旋转中的获胜号码。                         |
|                                      | string  |                                                                       |

#### EXAMPLE 1:

Blackjack

```
[
{
"gameCode": "SMG_BlackJack",
"tableCode": "BlackJackTable1",
"dealerInfo": {
"name": "John Doe"
},
"connectedPlayersCount": 5,
"blackjackInfo": {
"totalSeats": 7,
"freeSeats": 3
}
}
]
```

#### EXAMPLE 2:

Scalable Blackjack

```
[
{
"gameCode": "SMG_BlackJack",
"tableCode": "BlackJackTable1",
"dealerInfo": {
"name": "John Doe"
},
"connectedPlayersCount": 5
}
]
```

#### EXAMPLE 3:

Roulette / Roulette Multiplier

```
[
{
"gameCode": "SMG_Roulette",
```

```

"tableCode": "RouletteTable1",
"dealerInfo": {
  "name": "Jane Doe"
},
"connectedPlayersCount": 5,
"rouletteInfo": {
  "hotNumbers": [
    "1",
    "2",
    "3"
  ],
  "coldNumbers": [
    "4",
    "5",
    "6"
  ]
},
"winningNumberHistory": [
  "1",
  "2",
  "3"
]
}
]

```

#### EXAMPLE 4:

Baccarat

```

[
  {
    "gameCode": "SMG_Baccarat",
    "tableCode": "BaccaratTable1",
    "dealerInfo": {
      "name": "John Doe"
    },
    "connectedPlayersCount": 5,
    "winningHistory": [
      "payer",
      "banker",
      "tie"
    ]
  }
]

```

#### EXAMPLE 5:

Dragon Tiger

```

[
  {
    "gameCode": "SMG_DragonTiger",
    "tableCode": "Dragon Tiger",
    "dealerInfo": {
      "name": "Jane Doe"
    },
    "connectedPlayersCount": 5,
    "winningHistory": [
      "dragon",
      "tiger",
      "dragonTigerTie",
      "suitedTie"
    ]
  }
]

```

#### EXAMPLE 6:

Cards Champion

```

[
  {
    "gameCode": "SMG_CardsChampion",
    "tableCode": "Cards Champion",
    "dealerInfo": {

```

```

    "name": "John Doe"
  },
  "connectedPlayersCount": 5,
  "winningHistory": [
    "draw",
    "home",
    "away"
  ]
}
]

```

#### EXAMPLE 7:

Casino Holdem

```

[
  {
    "gameCode": "SMG_MGLiveGrand_CasinoHoldem",
    "tableCode": "Casino Holdem",
    "dealerInfo": {
      "name": "Vato"
    },
    "connectedPlayersCount": 20
  }
]

```

#### EXAMPLE 8:

Cash Wheel Carnival

```

[
  {
    "gameCode": "SMG_MGLiveGrand_CashWheelCarnival",
    "tableCode": "Cash Wheel Carnival",
    "dealerInfo": {
      "name": "Randall"
    },
    "connectedPlayersCount": 47,
    "winningHistory": [
      "1",
      "2",
      "2",
      "1",
      "1",
      "5",
      "1",
      "10",
      "2",
      "5"
    ]
  }
]

```

#### RESPONSE MODEL - application/json

| NAME                                 | TYPE    | DESCRIPTION                                                           |
|--------------------------------------|---------|-----------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |         |                                                                       |
| gameCode                             | string  | Game code.<br>游戏编号。                                                   |
| tableCode                            | string  | Table code.<br>桌子编号。                                                  |
| dealerInfo                           | object  |                                                                       |
| name                                 | string  | Dealer' s name.<br>荷官的名字。                                             |
| connectedPlayersCount                | integer | Number of players that are currently online.<br>当前在线玩家数。              |
| blackjackInfo                        | object  |                                                                       |
| totalSeats                           | integer | Total number of seats at the table.<br>桌子的总座位数。                       |
| freeSeats                            | integer | Total number of available seats at the table.<br>桌子上可用座位的总数。          |
| rouletteInfo                         | object  |                                                                       |
| hotNumbers                           | array   | Numbers that have appeared frequently in past spins.<br>过去旋转中频繁出现的数字。 |

| NAME                 | TYPE   | DESCRIPTION                                                       |
|----------------------|--------|-------------------------------------------------------------------|
|                      | string |                                                                   |
| coldNumbers          | array  | Numbers that have rarely appeared in past spins.<br>过去旋转中很少出现的数字。 |
|                      | string |                                                                   |
| winningHistory       | array  | Winning results from past rounds.<br>过去回合的获胜结果。                   |
|                      | string |                                                                   |
| winningNumberHistory | array  | Winning numbers in past spins.<br>过去旋转中的获胜号码。                     |
|                      | string |                                                                   |

#### EXAMPLE 1:

BlackJack

234

```
[
{
"gameCode": "SMG_BlackJack",
"tableCode": "BlackJackTable1",
"dealerInfo": {
"name": "John Doe"
},
"connectedPlayersCount": 5,
"blackjackInfo": {
"totalSeats": 7,
"freeSeats": 3
}
}
]
```

#### EXAMPLE 2:

Scalable Blackjack

```
[
{
"gameCode": "SMG_BlackJack",
"tableCode": "BlackJackTable1",
"dealerInfo": {
"name": "John Doe"
},
"connectedPlayersCount": 5
}
]
```

#### EXAMPLE 3:

Roulette

123

```
[
{
"gameCode": "SMG_Roulette",
"tableCode": "RouletteTable1",
"dealerInfo": {
"name": "Jane Doe"
},
"connectedPlayersCount": 5,
"rouletteInfo": {
"hotNumbers": [
"1",
"2",
"3"
],
"coldNumbers": [
"4",
"5",
"6"
]
}
}
]
```

```
"winningNumberHistory": [
  "1",
  "2",
  "3"
]
}
```

#### EXAMPLE 4:

Baccarat

```
[
{
  "gameCode": "SMG_Baccarat",
  "tableCode": "BaccaratTable1",
  "dealerInfo": {
    "name": "John Doe"
  },
  "connectedPlayersCount": 5,
  "winningHistory": [
    "payer",
    "banker",
    "tie"
  ]
}
]
```

#### EXAMPLE 5:

DragonTiger

```
[
{
  "gameCode": "SMG_DragonTiger",
  "tableCode": "Dragon Tiger",
  "dealerInfo": {
    "name": "Jane Doe"
  },
  "connectedPlayersCount": 5,
  "winningHistory": [
    "dragon",
    "tiger",
    "dragonTigerTie",
    "suitedTie"
  ]
}
]
```

#### EXAMPLE 6:

CardsChampion

```
[
{
  "gameCode": "SMG_CardsChampion",
  "tableCode": "Cards Champion",
  "dealerInfo": {
    "name": "John Doe"
  },
  "connectedPlayersCount": 5,
  "winningHistory": [
    "draw",
    "home",
    "away"
  ]
}
]
```

#### EXAMPLE 7:

Casino Holdem

```
[
  {
    "gameCode": "SMG_MGLiveGrand_CasinoHoldem",
    "tableCode": "Casino Holdem",
    "dealerInfo": {
      "name": "Vato"
    },
    "connectedPlayersCount": 20
  }
]
```

#### EXAMPLE 8:

Cash Wheel Carnival

```
[
  {
    "gameCode": "SMG_MGLiveGrand_CashWheelCarnival",
    "tableCode": "Cash Wheel Carnival",
    "dealerInfo": {
      "name": "Randall"
    },
    "connectedPlayersCount": 47,
    "winningHistory": [
      "1",
      "2",
      "2",
      "1",
      "1",
      "1",
      "5",
      "1",
      "10",
      "2",
      "5"
    ]
  }
]
```

#### RESPONSE MODEL - text/json

| NAME                                 | TYPE    | DESCRIPTION                                                           |
|--------------------------------------|---------|-----------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |         |                                                                       |
| gameCode                             | string  | Game code.<br>游戏编号。                                                   |
| tableCode                            | string  | Table code.<br>桌子编号。                                                  |
| dealerInfo                           | object  |                                                                       |
| name                                 | string  | Dealer' s name.<br>荷官的名字。                                             |
| connectedPlayersCount                | integer | Number of players that are currently online.<br>当前在线玩家数。              |
| blackjackInfo                        | object  |                                                                       |
| totalSeats                           | integer | Total number of seats at the table.<br>桌子的总座位数。                       |
| freeSeats                            | integer | Total number of available seats at the table.<br>桌子上可用座位的总数。          |
| rouletteInfo                         | object  |                                                                       |
| hotNumbers                           | array   | Numbers that have appeared frequently in past spins.<br>过去旋转中频繁出现的数字。 |
|                                      | string  |                                                                       |
| coldNumbers                          | array   | Numbers that have rarely appeared in past spins.<br>过去旋转中很少出现的数字。     |
|                                      | string  |                                                                       |
| winningHistory                       | array   | Winning results from past rounds.<br>过去回合的获胜结果。                       |
|                                      | string  |                                                                       |
| winningNumberHistory                 | array   | Winning numbers in past spins.<br>过去旋转中的获胜号码。                         |
|                                      | string  |                                                                       |

#### EXAMPLE 1:

BlackJack

```
[
  {
    "gameCode": "SMG_BlackJack",
    "tableCode": "BlackJackTable1",
    "dealerInfo": {
      "name": "John Doe"
    },
    "connectedPlayersCount": 5,
    "blackjackInfo": {
      "totalSeats": 7,
      "freeSeats": 3
    }
  }
]
```

## EXAMPLE 2:

Scalable Blackjack

```
[
  {
    "gameCode": "SMG_BlackJack",
    "tableCode": "BlackJackTable1",
    "dealerInfo": {
      "name": "John Doe"
    },
    "connectedPlayersCount": 5
  }
]
```

## EXAMPLE 3:

Roulette

123

```
[
  {
    "gameCode": "SMG_Roulette",
    "tableCode": "RouletteTable1",
    "dealerInfo": {
      "name": "Jane Doe"
    },
    "connectedPlayersCount": 5,
    "rouletteInfo": {
      "hotNumbers": [
        "1",
        "2",
        "3"
      ],
      "coldNumbers": [
        "4",
        "5",
        "6"
      ]
    },
    "winningNumberHistory": [
      "1",
      "2",
      "3"
    ]
  }
]
```

## EXAMPLE 4:

Baccarat

```
[
  {
    "gameCode": "SMG_Baccarat",
    "tableCode": "BaccaratTable1",
    "dealerInfo": {
      "name": "John Doe"
    }
  }
]
```

```

    },
    "connectedPlayersCount": 5,
    "winningHistory": [
      "payer",
      "banker",
      "tie"
    ]
  }
]

```

#### EXAMPLE 5:

DragonTiger

```

[
  {
    "gameCode": "SMG_DragonTiger",
    "tableCode": "Dragon Tiger",
    "dealerInfo": {
      "name": "Jane Doe"
    },
    "connectedPlayersCount": 5,
    "winningHistory": [
      "dragon",
      "tiger",
      "dragonTigerTie",
      "suitedTie"
    ]
  }
]

```

#### EXAMPLE 6:

CardsChampion

```

[
  {
    "gameCode": "SMG_CardsChampion",
    "tableCode": "Cards Champion",
    "dealerInfo": {
      "name": "John Doe"
    },
    "connectedPlayersCount": 5,
    "winningHistory": [
      "draw",
      "home",
      "away"
    ]
  }
]

```

#### EXAMPLE 7:

Casino Holdem

```

[
  {
    "gameCode": "SMG_MGLiveGrand_CasinoHoldem",
    "tableCode": "Casino Holdem",
    "dealerInfo": {
      "name": "Vato"
    },
    "connectedPlayersCount": 20
  }
]

```

#### EXAMPLE 8:

Cash Wheel Carnival

```

[
  {
    "gameCode": "SMG_MGLiveGrand_CashWheelCarnival",

```

```

"tableCode": "Cash Wheel Carnival",
"dealerInfo": {
  "name": "Randall"
},
"connectedPlayersCount": 47,
"winningHistory": [
  "1",
  "2",
  "2",
  "1",
  "1",
  "5",
  "1",
  "10",
  "2",
  "5"
]
}
]

```

STATUS CODE - 400: Bad Request - Input validation failed<br>请求无效 - 输入验证失败

RESPONSE MODEL - text/plain

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "70003",
  "message": "Input validation failed. 请求无效 - 输入验证失败。"
}

```

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "70003",
  "message": "Input validation failed. 请求无效 - 输入验证失败。"
}

```

RESPONSE MODEL - text/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```

{
  "code": "70003",
  "message": "Input validation failed. 请求无效 - 输入验证失败。"
}

```

STATUS CODE - 401: Unauthorized<br>未经授权

RESPONSE MODEL - text/plain

| NAME                        | TYPE | DESCRIPTION |
|-----------------------------|------|-------------|
| OBJECT WITH BELOW STRUCTURE |      |             |

| NAME    | TYPE   | DESCRIPTION                |
|---------|--------|----------------------------|
| code    | string | Error Code. <br />错误代码。    |
| message | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "70004",
  "message": "The request is unauthorized. 该请求未经授权。"
}
```

#### RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "70004",
  "message": "The request is unauthorized. 该请求未经授权。"
}
```

#### RESPONSE MODEL - text/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "70004",
  "message": "The request is unauthorized. 该请求未经授权。"
}
```

STATUS CODE - 404: Table information is not found<br>没有找到桌子的详细信息

#### RESPONSE MODEL - text/plain

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "70002",
  "message": "The requested resource does not exist. 找不到资源。"
}
```

#### RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "70002",
```

```
{
  "message": "The requested resource does not exist. 找不到资源。"
}
```

#### RESPONSE MODEL - text/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "70002",
  "message": "The requested resource does not exist. 找不到资源。"
}
```

#### STATUS CODE - 500: Internal server error<br>内部服务器错误

#### RESPONSE MODEL - text/plain

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "70003",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

#### RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "70003",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

#### RESPONSE MODEL - text/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | Error Code. <br />错误代码。    |
| message                     | string | Error message. <br />错误讯息。 |

EXAMPLE:

```
{
  "code": "70003",
  "message": "A general, non-specific exception occurred. 发生了非特异性的一般例外。"
}
```

# 7. GAME CATEGORIES 游戏类别

## 7.1 GET /agents/{agentCode}/gameCategories

Get game categories list 获取游戏类别

Returns game categories list for agent 返回代理的游戏类别列表  
Currently only returns PROGRESSIVE. 目前只支持查询彩池游戏类别.

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

### RESPONSE

STATUS CODE - 200: Game categories list returned.  
未结束下注列单已回复

#### RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                         |
|--------------------------------------|--------|-------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                     |
| productId                            | string | 3 to 3 chars<br>Product ID.<br>产品编号 |
| gameCategoryCode                     | string | Game category code<br>游戏类别说明        |
| gameCategoryDescription              | string | Game category description<br>游戏类别说明 |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

#### RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION          |
|-----------------------------|--------|----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                      |
| code                        | string | InputValidationError |
| message                     | string |                      |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: The agent code does not exist  
代理人码不存在

#### RESPONSE MODEL - application/json

| NAME | TYPE | DESCRIPTION |
|------|------|-------------|
|------|------|-------------|

| NAME                        | TYPE   | DESCRIPTION                   |
|-----------------------------|--------|-------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                               |
| code                        | string | AgentDoesNotExist             |
| message                     | string | The agent code does not exist |
| message-zh-CHS              | string | 代理人码不存在。                      |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 7.2 GET /agents/{agentCode}/players/{playerId}/gameCategories

Get player game categories list 获取玩家的游戏类别

Returns game categories list for player 返回玩家的游戏类别列表

### REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                             |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |

### RESPONSE

STATUS CODE - 200: Player game categories list returned.  
未结束下注列表已回复

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                         |
|--------------------------------------|--------|-------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                     |
| productId                            | string | 3 to 3 chars<br>Product ID.<br>产品编号 |
| gameCategoryCode                     | string | Game category code<br>游戏类别说明        |
| gameCategoryDescription              | string | Game category description<br>游戏类别说明 |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

| RESPONSE MODEL - application/json |        |                                                                                                                                                |
|-----------------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| NAME                              | TYPE   | DESCRIPTION                                                                                                                                    |
| OBJECT WITH BELOW STRUCTURE       |        |                                                                                                                                                |
| code                              | string | InputValidationError                                                                                                                           |
| message                           | string | The field playerId must be a string with a maximum length of 50. Using only numbers and english alphabets. playerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Player not found  
没有找到玩家

| RESPONSE MODEL - application/json |        |                       |
|-----------------------------------|--------|-----------------------|
| NAME                              | TYPE   | DESCRIPTION           |
| OBJECT WITH BELOW STRUCTURE       |        |                       |
| code                              | string | PlayerDoesNotExist    |
| message                           | string | Player does not exist |
| message-zh-CHS                    | string | 玩家不存在                 |

STATUS CODE - 500: Internal server error  
内部服务器错误

| RESPONSE MODEL - application/json |        |              |
|-----------------------------------|--------|--------------|
| NAME                              | TYPE   | DESCRIPTION  |
| OBJECT WITH BELOW STRUCTURE       |        |              |
| error                             | object |              |
| code                              | string | GeneralError |
| message                           | string | Server error |
| message-zh-CHS                    | string | 服务器错误        |

### 7.3 POST /agents/{agentCode}/players/{playerId}/products/{productId}/gameCategories

Add player game category 增加玩家的游戏类别

Returns added game category 返回增加的游戏类别

### REQUEST

| PATH PARAMETERS |        |         |                                                                                                                                                                    |
|-----------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NAME            | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
| *agentCode      | string |         | The agent code<br>代理人码                                                                                                                                             |
| *playerId       | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *productId | string |         | The product ID<br>产品编号 |

#### FORM DATA PARAMETERS

| NAME              | TYPE   | DESCRIPTION                  |
|-------------------|--------|------------------------------|
| *gameCategoryCode | string | Game category code<br>游戏类别说明 |

## RESPONSE

STATUS CODE - 201: Game category added successfully  
成功增加游戏类别

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                         |
|-----------------------------|--------|-------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                     |
| productId                   | string | 3 to 3 chars<br>Product ID.<br>产品编号 |
| gameCategoryCode            | string | Game category code<br>游戏类别说明        |
| gameCategoryDescription     | string | Game category description<br>游戏类别说明 |
| uri                         | string | Resource Uri.<br>资料来源链接             |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                     |
|-----------------------------|--------|-------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                 |
| code                        | string | InputValidationError                                                                            |
| message                     | string | The field ProductId must be a string with a maximum length of 3 letters. ProductID 字段数不能超过三个字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: The product id is not supported for method  
此方法不支持产品编号

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                |
|-----------------------------|--------|--------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                            |
| code                        | string | ProductIsNotSupported                      |
| message                     | string | The product id is not supported for method |
| message-zh-CHS              | string | 此方法不支持产品编号。                                |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 7.4 DELETE /agents/{agentCode}/players/{playerId}/products/{productId}/gameCategories/{gameCategoryId}

Remove player game category 移除玩家的游戏类别

Returns removed game category 返回移除玩家的游戏类别

### REQUEST

#### PATH PARAMETERS

| NAME            | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|-----------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode      | string |         | The agent code<br>代理人码                                                                                                                                             |
| *playerId       | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| *productId      | string |         | The product ID<br>产品编号                                                                                                                                             |
| *gameCategoryId | string |         | Game category code<br>游戏类别说明                                                                                                                                       |

### RESPONSE

STATUS CODE - 200: Game category removed successfully  
成功移除游戏类别

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                         |
|-----------------------------|--------|-------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                     |
| productId                   | string | 3 to 3 chars<br>Product ID.<br>产品编号 |
| gameCategoryId              | string | Game category code<br>游戏类别说明        |
| gameCategoryDescription     | string | Game category description<br>游戏类别说明 |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                     |
|-----------------------------|--------|-------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                 |
| code                        | string | InputValidationError                                                                            |
| message                     | string | The field ProductId must be a string with a maximum length of 3 letters. ProductID 字段数不能超过三个字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: The product id is not supported for method  
此方法不支持产品编号

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                |
|-----------------------------|--------|--------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                            |
| code                        | string | ProductIsNotSupported                      |
| message                     | string | The product id is not supported for method |
| message-zh-CHS              | string | 此方法不支持产品编号。                                |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 8. GAMES 遊戲

### 8.1 GET /agents/{agentCode}/games

Get game details list 获取游戏详情列表

Returns information about games according to agent permissions and specified search criteria.  
根据代理权限和指定的搜索条件返回游戏相关信息。  
This method can be called a maximum of 5 times in 60 seconds. Any calls exceeding this frequency will result in receiving the response code 429.  
该方法在60秒内最多可以调用5次。超过此频率的任何调用将导致接收到响应代码429。  
Games are ordered by popularity and are updated periodically by Microgaming.  
游戏按熱門遊戲顺序排列，并由Microgaming定期更新。

#### REQUEST

##### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

##### QUERY PARAMETERS

| NAME               | TYPE      | EXAMPLE | DESCRIPTION                                                                                                            |
|--------------------|-----------|---------|------------------------------------------------------------------------------------------------------------------------|
| fromReleaseDateUtc | date-time |         | From Game Release Date. If provided – gameReleaseDate must be greater.<br>从游戏发布日期。若有提供 - gameReleaseDate 必须较大。         |
| toReleaseDateUtc   | date-time |         | To Game Release Date. If provided – fromReleaseDateUtc must also be smaller<br>至游戏发布日期。若有提供 - fromReleaseDateUtc 必须较小。 |
| channelCode        | string    |         | Channel code.<br>渠道代码                                                                                                  |

#### RESPONSE

STATUS CODE - 200: OK. Game list returned  
游戏列表返回

##### RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                      |
|--------------------------------------|--------|----------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                  |
| gameName                             | string | Game name.<br>游戏名称               |
| gameCode                             | string | Game Code.<br>游戏代码               |
| translatedGameName                   | array  | Game name translations<br>游戏名称翻译 |
| code                                 | string |                                  |

| NAME                 | TYPE    | DESCRIPTION                                                                           |
|----------------------|---------|---------------------------------------------------------------------------------------|
| value                | string  |                                                                                       |
| channelCode          | string  | Channel code.<br>渠道代码                                                                 |
| channelName          | string  | Channel name.<br>渠道名称                                                                 |
| gameCategoryCode     | string  | Category code.<br>类别代码                                                                |
| gameCategoryName     | string  | Category name.<br>类别名称                                                                |
| gameSubcategoryCode  | string  | Subcategory code.<br>子类别代码                                                            |
| gameSubcategoryName  | string  | Subcategory name.<br>子类别名称                                                            |
| releaseDateUTC       | string  | Game release date UTC<br>游戏发布日期 UTC                                                   |
| platform             | string  | Game platform (deprecated).<br>游戏平台（已弃用）                                              |
| platforms            | array   | Game platform bet settings.<br>游戏平台投注设置                                               |
| platform             | string  | Platform name                                                                         |
| betSettings          | array   |                                                                                       |
| bettingProfileName   | string  | Betting profile name<br>投注资料名称                                                        |
| maxBet               | number  | Max bet amount<br>最大投注额                                                               |
| minBet               | number  | Min bet amount<br>最小投注额                                                               |
| isDemoEnabled        | boolean | Indicates whether the game has demo mode.<br>指示游戏是否有演示模式                              |
| languages            | array   | The supported languages of the specified game.<br>指定游戏所支持的语言                          |
| code                 | string  | The language code.<br>语言代码                                                            |
| level                | enum    | ALLOWED:Full, Partial<br>The level of the support (Full or Partial)<br>支持语言的程度（完整或部分） |
| rtp                  | string  | The RTP value of the game.<br>游戏的玩家回报率（RTP）                                           |
| gameFeatures         | array   | The supported features of the specific game<br>特定游戏支援的功能                              |
|                      | string  | Game Feature 游戏功能                                                                     |
| gameAssetsUrl        | string  | Game Assets folder URL.<br>游戏资源文件夹网址                                                  |
| isFreeGamesSupported | boolean | Is Free Games Supported<br>支持免费游戏促销                                                   |
| volatility           | string  | Volatility<br>波动性                                                                     |
| linesWays            | string  | Lines/Ways<br>选线/连线                                                                   |
| reels                | string  | Reels<br>转轴                                                                           |
| orientationSupport   | string  | Orientation Support<br>纵横屏支援                                                          |

| NAME | TYPE   | DESCRIPTION                                    |
|------|--------|------------------------------------------------|
| tags | string | Hashtags to help categorize each game.<br>游戏标签 |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                       |
|-----------------------------|--------|---------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                   |
| code                        | string | InputValidationError                                                                              |
| message                     | string | ToReleaseDateUtc must be greater than FromReleaseDateUtc ToReleaseDateUtc 必须大于 FromReleaseDateUtc |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 403: Forbidden  
禁止

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 8.2 GET /agents/{agentCode}/games/{gameCode}

Get a specific game details 获取特定游戏详细信息

Returns information about a specific game according to agent permissions.  
根据代理权限返回特定游戏的信息。  
This method can be called a maximum of 5 times in 60 seconds. Any calls exceeding this frequency will result in receiving the response code 429.  
该方法在60秒内最多可以调用5次。超过此频率的任何调用将导致接收到响应代码429。

### REQUEST

PATH PARAMETERS

| NAME       | TYPE                   | EXAMPLE | DESCRIPTION            |
|------------|------------------------|---------|------------------------|
| *agentCode | string                 |         | The agent code<br>代理人码 |
| *gameCode  | string<br>max:50 chars |         | The game code<br>游戏代码  |

### RESPONSE

STATUS CODE - 200: OK. Game details returned  
游戏详细信息返回

RESPONSE MODEL - application/json

| NAME                        | TYPE    | DESCRIPTION                                                                           |
|-----------------------------|---------|---------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |         |                                                                                       |
| gameName                    | string  | Game name.<br>游戏名称                                                                    |
| gameCode                    | string  | Game Code.<br>游戏代码                                                                    |
| translatedGameName          | array   | Game name translations<br>游戏名称翻译                                                      |
| code                        | string  |                                                                                       |
| value                       | string  |                                                                                       |
| channelCode                 | string  | Channel code.<br>渠道代码                                                                 |
| channelName                 | string  | Channel name.<br>渠道名称                                                                 |
| gameCategoryCode            | string  | Category code.<br>类别代码                                                                |
| gameCategoryName            | string  | Category name.<br>类别名称                                                                |
| gameSubcategoryCode         | string  | Subcategory code.<br>子类别代码                                                            |
| gameSubcategoryName         | string  | Subcategory name.<br>子类别名称                                                            |
| releaseDateUTC              | string  | Game release date UTC<br>游戏发布日期 UTC                                                   |
| platform                    | string  | Game platform (deprecated).<br>游戏平台（已弃用）                                              |
| platforms                   | array   | Game platform bet settings.<br>游戏平台投注设置                                               |
| platform                    | string  | Platform name                                                                         |
| betSettings                 | array   |                                                                                       |
| bettingProfileName          | string  | Betting profile name<br>投注资料名称                                                        |
| maxBet                      | number  | Max bet amount<br>最大投注额                                                               |
| minBet                      | number  | Min bet amount<br>最小投注额                                                               |
| isDemoEnabled               | boolean | Indicates whether the game has demo mode.<br><br>指示游戏是否有演示模式                          |
| languages                   | array   | The supported languages of the specified game.<br>指定游戏所支持的语言                          |
| code                        | string  | The language code.<br>语言代码                                                            |
| level                       | enum    | ALLOWED:Full, Partial<br>The level of the support (Full or Partial)<br>支持语言的程度（完整或部分） |
| rtp                         | string  | The RTP value of the game.<br>游戏的玩家回报率（RTP）                                           |
| gameFeatures                | array   | The supported features of the specific game<br>特定游戏支援的功能                              |
|                             | string  | Game Feature 游戏功能                                                                     |
| gameAssetsUrl               | string  | Game Assets folder URL.<br>游戏资源文件夹网址                                                  |

| NAME                 | TYPE    | DESCRIPTION                                    |
|----------------------|---------|------------------------------------------------|
| isFreeGamesSupported | boolean | Is Free Games Supported<br>支持免费游戏促销            |
| volatility           | string  | Volatility<br>波动性                              |
| linesWays            | string  | Lines/Ways<br>选线/连线                            |
| reels                | string  | Reels<br>转轴                                    |
| orientationSupport   | string  | Orientation Support<br>纵横屏支援                   |
| tags                 | string  | Hashtags to help categorize each game.<br>游戏标签 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 403: Forbidden  
禁止

STATUS CODE - 404: Game not found  
游戏未找到

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                   |
|-----------------------------|--------|-------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                               |
| code                        | string | GameDoesNotExist              |
| message                     | string | Game does not exist for Agent |
| message-zh-CHS              | string | 代理不存在此游戏                      |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

# 9. HEARTBEAT 实时系统监测

## 9.1 GET /heartbeat

Get Heartbeat response from the system 监测系统连线状态

Returns an ‘OK’ response if the system is live and responding.  
如果系统已上线和正在回应，返回 “OK” 回复

### REQUEST

No request parameters

### RESPONSE

STATUS CODE - 200: Ok. System is alive and responds  
OK，系统已上线和正在回应

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

# 10. PLAYERS 玩家

## 10.1 GET /agents/{agentCode}/players/{playerId}

Get player details 获取玩家信息

Returns information about specified player  
返回关于指定玩家的信息

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                             |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |

#### QUERY PARAMETERS

| NAME       | TYPE                                | EXAMPLE | DESCRIPTION                                                                                    |
|------------|-------------------------------------|---------|------------------------------------------------------------------------------------------------|
| properties | array of string<br>ALLOWED: balance |         | Constrain response to the following listed fields: _**balance**_<br>答复限制在以下列单的范围：_**balance**_ |

### RESPONSE

STATUS CODE - 200: OK. Return player details  
玩家信息已经获取

#### RESPONSE MODEL - application/json

| NAME                        | TYPE    | DESCRIPTION                                                                                                                                                                        |
|-----------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |         |                                                                                                                                                                                    |
| isLocked                    | boolean | Indicates whether the player is locked.<br>显示玩家是否被锁定                                                                                                                               |
| playerId                    | string  | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| createdDateUTC              | string  | The player created date (UTC).<br>玩家被创建的日期 (UTC)                                                                                                                                   |
| balance                     | object  |                                                                                                                                                                                    |
| total                       | number  | The player balance<br>玩家余额                                                                                                                                                         |
| isPartial                   | boolean | Indicates whether the balance is partial.<br>显示是否为部分余额                                                                                                                             |
| details                     | object  |                                                                                                                                                                                    |

| NAME            | TYPE   | DESCRIPTION                                               |
|-----------------|--------|-----------------------------------------------------------|
| walletBalance   | object |                                                           |
| total           | number | The player wallet balance<br>玩家钱包余额                       |
| productsBalance | object |                                                           |
| total           | number | The player balance in products wallets<br>玩家在特定产品的钱包余额    |
| details         | array  |                                                           |
| productId       | string | 3 to 3 chars<br>Product ID.<br>产品编号                       |
| balance         | number | The player balance at the requested product<br>被请求产品的玩家余额 |
| uri             | string | Resource Uri.<br>资料来源链接                                   |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Player not found  
没有找到玩家

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION           |
|-----------------------------|--------|-----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                       |
| code                        | string | PlayerDoesNotExist    |
| message                     | string | Player does not exist |
| message-zh-CHS              | string | 玩家不存在                 |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 10.2 PATCH /agents/{agentCode}/players/{playerId}

Update the lock status of the player 更新玩家的锁定状态

Changes the locked/unlocked status of a player  
更改玩家锁定/解锁状态

REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                             |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |

FORM DATA PARAMETERS

| NAME    | TYPE    | DESCRIPTION                                                                             |
|---------|---------|-----------------------------------------------------------------------------------------|
| *isLock | boolean | _**true**_ to lock player. Otherwise, _**false**_.<br>_**true**_ 表示锁定玩家。否则是 _**false**_ |

RESPONSE

STATUS CODE - 200: Player is locked/unlocked  
玩家被锁定/解锁

RESPONSE MODEL - application/json

| NAME                        | TYPE    | DESCRIPTION                                                                                                                                                                        |
|-----------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |         |                                                                                                                                                                                    |
| playerId                    | string  | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| isLocked                    | boolean | Indicates whether the player is locked<br>显示玩家是否被锁定                                                                                                                                |
| createdDateUTC              | string  | The player created date (UTC).<br>玩家被创建的日期 (UTC)                                                                                                                                   |
| uri                         | string  | Resource Uri.<br>资料来源链接                                                                                                                                                            |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Player not found  
没有找到玩家

| RESPONSE MODEL - application/json |        |                       |
|-----------------------------------|--------|-----------------------|
| NAME                              | TYPE   | DESCRIPTION           |
| OBJECT WITH BELOW STRUCTURE       |        |                       |
| code                              | string | PlayerDoesNotExist    |
| message                           | string | Player does not exist |
| message-zh-CHS                    | string | 玩家不存在                 |

STATUS CODE - 500: Internal server error  
内部服务器错误

| RESPONSE MODEL - application/json |        |              |
|-----------------------------------|--------|--------------|
| NAME                              | TYPE   | DESCRIPTION  |
| OBJECT WITH BELOW STRUCTURE       |        |              |
| error                             | object |              |
| code                              | string | GeneralError |
| message                           | string | Server error |
| message-zh-CHS                    | string | 服务器错误        |

### 10.3 POST /agents/{agentCode}/players

#### Create player 创建玩家

Creates a new player  
创建新玩家

#### REQUEST

| PATH PARAMETERS |        |         |                        |
|-----------------|--------|---------|------------------------|
| NAME            | TYPE   | EXAMPLE | DESCRIPTION            |
| *agentCode      | string |         | The agent code<br>代理人码 |

| FORM DATA PARAMETERS |        |                                                                                                                                                                     |
|----------------------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| NAME                 | TYPE   | DESCRIPTION                                                                                                                                                         |
| *playerId            | string | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和 下划线 (\_)。 |

#### RESPONSE

STATUS CODE - 200: Player already exists. Existing player returned.  
玩家已经存在。存在的玩家已经获取。

| RESPONSE MODEL - application/json |      |             |
|-----------------------------------|------|-------------|
| NAME                              | TYPE | DESCRIPTION |

| NAME                        | TYPE    | DESCRIPTION                                                                                                                                                                        |
|-----------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |         |                                                                                                                                                                                    |
| playerId                    | string  | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| isLocked                    | boolean | Indicates whether the player is locked<br>显示玩家是否被锁定                                                                                                                                |
| createdDateUTC              | string  | The player created date (UTC).<br>玩家被创建的日期 (UTC)                                                                                                                                   |
| uri                         | string  | Resource Uri.<br>资料来源链接                                                                                                                                                            |

STATUS CODE - 201: Player created successfully  
成功创建玩家

RESPONSE MODEL - application/json

| NAME                        | TYPE    | DESCRIPTION                                                                                                                                                                        |
|-----------------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |         |                                                                                                                                                                                    |
| playerId                    | string  | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| isLocked                    | boolean | Indicates whether the player is locked<br>显示玩家是否被锁定                                                                                                                                |
| createdDateUTC              | string  | The player created date (UTC).<br>玩家被创建的日期 (UTC)                                                                                                                                   |
| uri                         | string  | Resource Uri.<br>资料来源链接                                                                                                                                                            |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 10.4 GET /agents/{agentCode}/players/{playerId}/products/{productId}

## Get specific product details of a player 获取指定的玩家产品信息

Returns specific product details for specified player  
返回指定玩家的具体产品信息

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                             |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| *productId | string |         | The product ID<br>产品编号                                                                                                                                             |

#### QUERY PARAMETERS

| NAME       | TYPE                                | EXAMPLE | DESCRIPTION                                                                                                                   |
|------------|-------------------------------------|---------|-------------------------------------------------------------------------------------------------------------------------------|
| properties | array of string<br>ALLOWED: balance |         | Constrain response to the following listed fields: <code>_{**balance**_}</code><br>答复限制在以下列单的范围： <code>_{**balance**_}</code> |

### RESPONSE

STATUS CODE - 200: product details returned.  
产品信息已经获取

#### RESPONSE MODEL - application/json

| NAME                        | TYPE    | DESCRIPTION                                               |
|-----------------------------|---------|-----------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |         |                                                           |
| productId                   | string  | 3 to 3 chars<br>Product ID.<br>产品编号                       |
| isLocked                    | boolean | Indicates whether the player is locked.<br>显示玩家是否被锁定      |
| balance                     | number  | The player balance at the requested product<br>被请求产品的玩家余额 |
| uri                         | string  | Resource Uri.<br>资料来源链接                                   |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

#### RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field playerId must be a string with a maximum length of 50. Using only numbers and english alphabets. playerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Player / Product not found  
玩家/产品没有找到

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION           |
|-----------------------------|--------|-----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                       |
| code                        | string | PlayerDoesNotExist    |
| message                     | string | Player does not exist |
| message-zh-CHS              | string | 玩家不存在                 |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

10.5 GET /agents/{agentCode}/players/{playerId}/products

Get products list of a player 获取玩家的产品列单

Returns status of all products of the player  
返回指定玩家所有产品的状态

REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                             |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |

RESPONSE

STATUS CODE - 200: OK. Returned products list for requested player  
指定玩家的产品列单已经获取

RESPONSE MODEL - application/json

| NAME                                 | TYPE | DESCRIPTION |
|--------------------------------------|------|-------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |      |             |

| NAME      | TYPE    | DESCRIPTION                                           |
|-----------|---------|-------------------------------------------------------|
| productId | string  | 3 to 3 chars<br>Product ID.<br>产品编号                   |
| isLocked  | boolean | Indicates whether the player is locked.<br>显示玩家是否被锁定。 |
| uri       | string  | Resource Uri.<br>资料来源链接                               |

STATUS CODE - 400: Bad Request - Input validation failed.  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Player not found  
没有找到玩家

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION           |
|-----------------------------|--------|-----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                       |
| code                        | string | PlayerDoesNotExist    |
| message                     | string | Player does not exist |
| message-zh-CHS              | string | 玩家不存在                 |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 10.6 POST /agents/{agentCode}/players/{playerId}/products/{productId}/betVisualizers

Get bet playcheck. 获取下注 playcheck

Returns a playcheck url per product with all bet info including bet screen shot 返回个别产品的 Playcheck链接以及下注截图

## REQUEST

## PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                             |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| *productId | string |         | The product ID<br>产品编号                                                                                                                                             |

## FORM DATA PARAMETERS

| NAME       | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *utcOffset | integer | Utc Offset.<br>UTC偏移                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| betUid     | string  | Bet unique ID. Field length is exactly 36.<br>独一下注编号。字段长度应正好是 36 个字符                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| game       | string  | Game Code. This parameter is ignored if BetUID is provided. SMG does not support Game Code.<br>游戏码。如果提供了 BetUID,这个参数将被忽略。SMG 不支持游戏码。                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| fromDate   | string  | From Date. This parameter is ignored if BetUID is provided. SMG does not support From Date. If provided – toDate must also be provided<br>开始日期。如果提供了 BetUID,这个参数将被忽略。SMG 不支持开始日期。如需加入此参数时，“toDate”也必须填入参数                                                                                                                                                                                                                                                                                                                                                                                                            |
| toDate     | string  | To Date. This parameter is ignored if BetUID is provided. SMG does not support To Date. If provided – fromDate must also be provided<br>截止日期。如果提供了 BetUID,这个参数将被忽略。SMG 不支持截止日期。如需加入此参数时，“fromDate”也必须填入参数                                                                                                                                                                                                                                                                                                                                                                                                            |
| *langCode  | string  | A Language code consists of: 语言代码包括 [language]-[REGION].<br>* language - A language designator is a code that represents a language. Use the two-letter [ISO 639-1](http://en.wikipedia.org/wiki/List_of_ISO_639-1_codes) standard.<br>* region - A region designator is a code that represents a country. Use the two-letter [ISO 3166-2](https://en.wikipedia.org/wiki/ISO_3166-2) standard.<br>[language]-[REGION].<br>* 语言 - 语言指示符是代表一种语言的代码。使用双字母标准 [ISO 639-1](http://en.wikipedia.org/wiki/List_of_ISO_639-1_codes).<br>* 区域 - 区域指示符是代表一个国家的代码。使用双字母标准 [ISO 3166-2](https://en.wikipedia.org/wiki/ISO_3166-2) |

## RESPONSE

STATUS CODE - 201: Return playcheck URL  
返回 playcheck 链接

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION             |
|-----------------------------|--------|-------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                         |
| url                         | string | Resource Uri.<br>资料来源链接 |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

## RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field playerId must be a string with a maximum length of 50. Using only numbers and english alphabets. playerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Player not found  
没有找到玩家

## RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION           |
|-----------------------------|--------|-----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                       |
| code                        | string | PlayerDoesNotExist    |
| message                     | string | Player does not exist |
| message-zh-CHS              | string | 玩家不存在                 |

STATUS CODE - 500: Internal server error  
内部服务器错误

## RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

# 10.7 POST /agents/{agentCode}/players/{playerId}/betVisualizers

Get bet playcheck. 获取下注 playcheck

Returns a playcheck url per product with all bet info including bet screen shot  
返回个别产品的Playcheck链接以及下注截图

## REQUEST

### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                         |
|------------|--------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                              |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符号 (-) 和下划线 (\_)。 |

### FORM DATA PARAMETERS

| NAME       | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------------|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *utcOffset | integer | Utc Offset.<br>UTC偏移                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| betUid     | string  | Bet unique ID. Field length is exactly 36.<br>独一的下注编号。字段长度应正好是 36 个字符                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
| game       | string  | Game Code. This parameter is ignored if BetUID is provided. SMG does not support Game Code.<br>游戏码。如果提供了 BetUID,这个参数将被忽略。SMG 不支持游戏码。                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| fromDate   | string  | From Date. This parameter is ignored if BetUID is provided. SMG does not support From Date. If provided – toDate must also be provided<br>开始日期。如果提供了 BetUID,这个参数将被忽略。SMG 不支持开始日期。如需加入此参数时, “toDate” 也必须填入参数                                                                                                                                                                                                                                                                                                                                                                                                          |
| toDate     | string  | To Date. This parameter is ignored if BetUID is provided. SMG does not support To Date. If provided – fromDate must also be provided<br>截止日期。如果提供了 BetUID,这个参数将被忽略。SMG 不支持截止日期。如需加入此参数时, “fromDate” 也必须填入参数                                                                                                                                                                                                                                                                                                                                                                                                          |
| *langCode  | string  | A Language code consists of: 语言代码包括 [language]-[REGION].<br>* language - A language designator is a code that represents a language. Use the two-letter [ISO 639-1](http://en.wikipedia.org/wiki/List_of_ISO_639-1_codes) standard.<br>* region - A region designator is a code that represents a country. Use the two-letter [ISO 3166-2](https://en.wikipedia.org/wiki/ISO_3166-2) standard.<br>[language]-[REGION].<br>* 语言 - 语言指示符是代表一种语言的代码。使用双字母标准 [ISO 639-1](http://en.wikipedia.org/wiki/List_of_ISO_639-1_codes).<br>* 区域 - 区域指示符是代表一个国家的代码。使用双字母标准 [ISO 3166-2](https://en.wikipedia.org/wiki/ISO_3166-2) |

## RESPONSE

STATUS CODE - 201: Return playcheck URL per product  
返回特定产品的Playcheck链接

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                         |
|--------------------------------------|--------|-------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                     |
| product                              | string | 3 to 3 chars<br>Product ID.<br>产品编号 |
| url                                  | string | Resource Uri.<br>资料来源链接             |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Player not found

没有找到玩家

| RESPONSE MODEL - application/json |        |                       |
|-----------------------------------|--------|-----------------------|
| NAME                              | TYPE   | DESCRIPTION           |
| OBJECT WITH BELOW STRUCTURE       |        |                       |
| code                              | string | PlayerDoesNotExist    |
| message                           | string | Player does not exist |
| message-zh-CHS                    | string | 玩家不存在                 |

STATUS CODE - 500: Internal server error  
内部服务器错误

| RESPONSE MODEL - application/json |        |              |
|-----------------------------------|--------|--------------|
| NAME                              | TYPE   | DESCRIPTION  |
| OBJECT WITH BELOW STRUCTURE       |        |              |
| error                             | object |              |
| code                              | string | GeneralError |
| message                           | string | Server error |
| message-zh-CHS                    | string | 服务器错误        |

# 11. REPORTS 报表

## 11.1 POST /agents/{agentCode}/reports/ledger

Get detailed deposits/withdrawals transactions report 提供用户存款/提款交易的详细报表

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

#### REQUEST BODY - application/json

| NAME                  | TYPE    | DESCRIPTION                                                                                                                                                                                                               |
|-----------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fromDate*             | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| toDate*               | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| utcOffset*            | integer | Utc Offset.<br>UTC 时间差                                                                                                                                                                                                    |
| currency*             | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies.<br>指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币                |
| playerId              | string  | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。                                        |
| products              | array   |                                                                                                                                                                                                                           |
|                       | string  | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                                                       |
| externalTransactionId | string  | The External Transaction Id.<br>外部交易编号                                                                                                                                                                                    |
| transactionTypes      | array   |                                                                                                                                                                                                                           |
|                       | enum    | ALLOWED:Deposit, Withdraw<br>Transaction type (Deposit/Withdraw)<br>交易种类 (Deposit/Withdraw)                                                                                                                               |
| transactionStatuses   | array   |                                                                                                                                                                                                                           |
|                       | enum    | ALLOWED:InProgress, Succeeded, Unconfirmed, Failed<br>Transaction status (InProgress/Succeeded/Unconfirmed/Failed)<br>交易状态 (InProgress/Succeeded/Unconfirmed/Failed)                                                      |
| endingBefore          | string  | Transaction UID.<br>交易 UID                                                                                                                                                                                                |
| limit*                | integer | between 1 and 1000<br>Number of items to return.<br>需要返回的条录                                                                                                                                                               |

## RESPONSE

STATUS CODE - 200: OK. Returned report details  
报表已经获取

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                                                                                                                          |
|--------------------------------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                                      |
| transactionTime                      | string |                                                                                                                                                                      |
| transactionStatus                    | enum   | ALLOWED:InProgress, Succeeded, Unconfirmed, Failed<br>Transaction status (InProgress/Succeeded/Unconfirmed/Failed)<br>交易状态 (InProgress/Succeeded/Unconfirmed/Failed) |
| productCode                          | string |                                                                                                                                                                      |
| product                              | string |                                                                                                                                                                      |
| agentCode                            | string |                                                                                                                                                                      |
| agent                                | string |                                                                                                                                                                      |
| playerId                             | string |                                                                                                                                                                      |
| transactionType                      | enum   | ALLOWED:Deposit, Withdraw<br>Transaction type (Deposit/Withdraw)<br>交易种类 (Deposit/Withdraw)                                                                          |
| externalTransactionId                | string |                                                                                                                                                                      |
| transactionId                        | string |                                                                                                                                                                      |
| amount                               | number | Transaction amount.<br>交易金额。                                                                                                                                         |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

### 11.2 POST /agents/{agentCode}/reports/financial

Get detailed financial report 获取详细资金报表

# REQUEST

## PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

## REQUEST BODY - application/json

| NAME             | TYPE    | DESCRIPTION                                                                                                                                                                                                               |
|------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fromDate*        | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| toDate*          | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| timeAggregation* | enum    | ALLOWED:Monthly, Daily, Hourly                                                                                                                                                                                            |
| utcOffset*       | integer | Utc Offset.<br>UTC 时间差                                                                                                                                                                                                    |
| currency*        | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies.<br>指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币                |
| playerId         | string  | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和 下划线 (\_)。                                       |
| products         | array   |                                                                                                                                                                                                                           |
|                  | string  | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                                                       |

# RESPONSE

STATUS CODE - 200: OK. Returned report details  
报表已经获取

## RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION |
|--------------------------------------|--------|-------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |             |
| time                                 | string |             |
| productCode                          | string |             |
| productDescription                   | string |             |
| agentCode                            | string |             |
| agentDescription                     | string |             |
| income                               | number |             |
| incomePercentage                     | number |             |
| payout                               | number |             |
| payoutPercentage                     | number |             |
| grossWin                             | number |             |
| grossWinPercentage                   | number |             |
| numOfBets                            | number |             |
| margin                               | number |             |

| NAME             | TYPE   | DESCRIPTION |
|------------------|--------|-------------|
| depositAmount    | number |             |
| withdrawalAMount | number |             |
| netCash          | number |             |
| numOfDeposits    | number |             |
| numOfWithdrawals | number |             |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 11.3 POST /agents/{agentCode}/reports/gameAnalysis

Get detailed games analysis report 获取详细游戏报表

### REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

REQUEST BODY - application/json

| NAME      | TYPE   | DESCRIPTION                                                                                                                                                                                                               |
|-----------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fromDate* | string | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| toDate*   | string | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |

| NAME             | TYPE    | DESCRIPTION                                                                                                                                                                                                |
|------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| timeAggregation* | enum    | ALLOWED:Monthly, Daily, Hourly                                                                                                                                                                             |
| utcOffset*       | integer | Utc Offset.<br>Utc 时间差                                                                                                                                                                                     |
| currency*        | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies.<br>指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币 |
| playerId         | string  | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符号 (-) 和 下划线 (\_)。                       |
| products         | array   |                                                                                                                                                                                                            |
|                  | string  | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                                        |
| channels         | array   |                                                                                                                                                                                                            |
|                  | string  | 1 to 50 chars<br>Channel Code.<br>渠道代码                                                                                                                                                                     |
| platforms        | array   |                                                                                                                                                                                                            |
|                  | enum    | ALLOWED:Unknown, Desktop, Mobile<br>Game platform (Unknown/Desktop/Mobile)<br>游戏平台 (Unknown/Desktop/Mobile)                                                                                                |
| games            | array   |                                                                                                                                                                                                            |
|                  | string  | Game code<br>游戏代码                                                                                                                                                                                          |

RESPONSE

STATUS CODE - 200: OK. Returned report details  
报表已经获取

| RESPONSE MODEL - application/json    |        |                                                                                                             |
|--------------------------------------|--------|-------------------------------------------------------------------------------------------------------------|
| NAME                                 | TYPE   | DESCRIPTION                                                                                                 |
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                                                             |
| time                                 | string |                                                                                                             |
| productCode                          | string |                                                                                                             |
| productDescription                   | string |                                                                                                             |
| agentCode                            | string |                                                                                                             |
| agentDescription                     | string |                                                                                                             |
| gameCode                             | string |                                                                                                             |
| gameName                             | string |                                                                                                             |
| platform                             | enum   | ALLOWED:Unknown, Desktop, Mobile<br>Game platform (Unknown/Desktop/Mobile)<br>游戏平台 (Unknown/Desktop/Mobile) |
| income                               | number |                                                                                                             |
| incomePercentage                     | number |                                                                                                             |
| payout                               | number |                                                                                                             |
| payoutPercentage                     | number |                                                                                                             |
| grossWin                             | number |                                                                                                             |
| grossWinPercentage                   | number |                                                                                                             |
| numOfActivePlayers                   | number | parameter is deprecated and will always return 0<br>打星号*的参数已弃用，并将始终返回0                                      |

| NAME                   | TYPE   | DESCRIPTION |
|------------------------|--------|-------------|
| numOfBets              | number |             |
| numOfBetsPercentage    | number |             |
| numOfPayouts           | number |             |
| numOfPayoutsPercentage | number |             |
| margin                 | number |             |
| maxBet                 | number |             |
| maxPayout              | number |             |
| avgBet                 | number |             |
| avgPayout              | number |             |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 11.4 POST /agents/{agentCode}/reports/playerGameAnalysis

Get detailed player games analysis report 获取详细玩家游戏分析报表

### REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

REQUEST BODY - application/json

| NAME      | TYPE   | DESCRIPTION                                                                                                                                        |
|-----------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| fromDate* | string | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate |

| NAME             | TYPE    | DESCRIPTION                                                                                                                                                                                                               |
|------------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                  |         | 在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate                                                                                                                                                       |
| toDate*          | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| timeAggregation* | enum    | ALLOWED:Monthly, Daily, Hourly                                                                                                                                                                                            |
| utcOffset*       | integer | Utc Offset.<br>Utc 时间差                                                                                                                                                                                                    |
| playerId         | string  | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符号 (-) 和 下划线 (\_)。                                      |
| products         | array   |                                                                                                                                                                                                                           |
|                  | string  | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                                                       |
| channels         | array   |                                                                                                                                                                                                                           |
|                  | string  | 1 to 50 chars<br>Channel Code.<br>渠道代码                                                                                                                                                                                    |
| platforms        | array   |                                                                                                                                                                                                                           |
|                  | enum    | ALLOWED:Unknown, Desktop, Mobile<br>Game platform (Unknown/Desktop/Mobile)<br>游戏平台 (Unknown/Desktop/Mobile)                                                                                                               |
| games            | array   |                                                                                                                                                                                                                           |
|                  | string  | Game code<br>游戏代码                                                                                                                                                                                                         |

## RESPONSE

STATUS CODE - 200: OK. Returned report details  
报表已经获取

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                                                                 |
|--------------------------------------|--------|-------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                                                             |
| time                                 | string |                                                                                                             |
| playerId                             | string |                                                                                                             |
| productCode                          | string |                                                                                                             |
| productDescription                   | string |                                                                                                             |
| channel                              | string |                                                                                                             |
| gameCode                             | string |                                                                                                             |
| gameName                             | string |                                                                                                             |
| platform                             | enum   | ALLOWED:Unknown, Desktop, Mobile<br>Game platform (Unknown/Desktop/Mobile)<br>游戏平台 (Unknown/Desktop/Mobile) |
| income                               | number |                                                                                                             |
| payout                               | number |                                                                                                             |
| grossWin                             | number |                                                                                                             |
| numOfBets                            | number |                                                                                                             |
| numOfPayouts                         | number |                                                                                                             |
| margin                               | number |                                                                                                             |

| NAME                 | TYPE   | DESCRIPTION |
|----------------------|--------|-------------|
| maxBet               | number |             |
| maxPayout            | number |             |
| avgBet               | number |             |
| avgPayout            | number |             |
| progressiveBetAmount | number |             |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                     |
|-----------------------------|--------|-------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                 |
| code                        | string | InputValidationError                                                                            |
| message                     | string | The field ProductId must be a string with a maximum length of 3 letters. ProductID 字段数不能超过三个字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

### 11.5 POST /agents/{agentCode}/reports/progressiveGamePlay

Get detailed progressive game play report 捞取详细彩池游戏记录报表

Data is populated every 10 Min

### REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

REQUEST BODY - application/json

| NAME      | TYPE   | DESCRIPTION                                                                                                                                                                                                               |
|-----------|--------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fromDate* | string | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| toDate*   | string | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to                                                                                                                  |

| NAME             | TYPE    | DESCRIPTION                                                                                                                                                                                                |
|------------------|---------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|                  |         | <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate                                                                                           |
| timeAggregation* | enum    | ALLOWED:Monthly, Daily, Hourly                                                                                                                                                                             |
| utcOffset*       | integer | Utc Offset.<br>Utc 时间差                                                                                                                                                                                     |
| currency*        | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies.<br>指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币 |
| playerId         | string  | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符号 (-) 和 下划线 (\_)。                       |
| products         | array   |                                                                                                                                                                                                            |
|                  | string  | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                                        |
| platforms        | array   |                                                                                                                                                                                                            |
|                  | enum    | ALLOWED:Unknown, Desktop, Mobile<br>Game platform (Unknown/Desktop/Mobile)<br>游戏平台 (Unknown/Desktop/Mobile)                                                                                                |
| games            | array   |                                                                                                                                                                                                            |
|                  | string  | Game code<br>游戏代码                                                                                                                                                                                          |

## RESPONSE

STATUS CODE - 200: OK. Returned report details  
报表已经获取

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                                                                 |
|--------------------------------------|--------|-------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                                                             |
| time                                 | string |                                                                                                             |
| productCode                          | string |                                                                                                             |
| productDescription                   | string |                                                                                                             |
| agentCode                            | string |                                                                                                             |
| agentDescription                     | string |                                                                                                             |
| gameCode                             | string |                                                                                                             |
| gameName                             | string |                                                                                                             |
| platform                             | enum   | ALLOWED:Unknown, Desktop, Mobile<br>Game platform (Unknown/Desktop/Mobile)<br>游戏平台 (Unknown/Desktop/Mobile) |
| income                               | number |                                                                                                             |
| numOfBets                            | number |                                                                                                             |
| PCA                                  | number |                                                                                                             |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION          |
|-----------------------------|--------|----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                      |
| code                        | string | InputValidationError |

| NAME    | TYPE   | DESCRIPTION                                                                                                                                    |
|---------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| message | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 11.6 POST /agents/{agentCode}/reports/progressiveWins

Get detailed progressive wins report 捞取详细彩池中奖报表

### REQUEST

PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

REQUEST BODY - application/json

| NAME         | TYPE    | DESCRIPTION                                                                                                                                                                                                               |
|--------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fromDate*    | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| toDate*      | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| utcOffset*   | integer | Utc Offset.<br>Utc 时间差                                                                                                                                                                                                    |
| currency*    | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies.<br>指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币                |
| playerId     | string  | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。                                        |
| products     | array   |                                                                                                                                                                                                                           |
|              | string  | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                                                       |
| jackpotTypes | array   |                                                                                                                                                                                                                           |

| NAME          | TYPE   | DESCRIPTION                                                    |
|---------------|--------|----------------------------------------------------------------|
|               | enum   | ALLOWED:Mega, Major, Minor, Mini<br>Jackpot types.<br>彩池游戏奖金类别 |
| jackpotNumber | string | max:50 chars<br>Jackpot number.<br>彩池游戏中奖号码                    |

## RESPONSE

STATUS CODE - 200: OK. Returned report details  
报表已经获取

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                                                                 |
|--------------------------------------|--------|-------------------------------------------------------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                                                                             |
| productPlayerId                      | string |                                                                                                             |
| productCode                          | string |                                                                                                             |
| productDescription                   | string |                                                                                                             |
| jackpotDate                          | string |                                                                                                             |
| currency                             | string |                                                                                                             |
| agentCode                            | string |                                                                                                             |
| agentDescription                     | string |                                                                                                             |
| playerId                             | string |                                                                                                             |
| gameCode                             | string |                                                                                                             |
| gameName                             | string |                                                                                                             |
| platform                             | enum   | ALLOWED:Unknown, Desktop, Mobile<br>Game platform (Unknown/Desktop/Mobile)<br>游戏平台 (Unknown/Desktop/Mobile) |
| jackpotAmount                        | number |                                                                                                             |
| jackpotType                          | number |                                                                                                             |
| jackpotNumber                        | string |                                                                                                             |
| transactionId                        | string |                                                                                                             |
| betUID                               | string |                                                                                                             |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE | DESCRIPTION |
|-----------------------------|------|-------------|
| OBJECT WITH BELOW STRUCTURE |      |             |

| NAME           | TYPE   | DESCRIPTION  |
|----------------|--------|--------------|
| error          | object |              |
| code           | string | GeneralError |
| message        | string | Server error |
| message-zh-CHS | string | 服务器错误        |

## 11.7 POST /agents/{agentCode}/reports/fortuneRewards

Gets rewards for the logged in agent 获取已登录代理的奖励

The method can be called a maximum of once every 60 seconds. Calls made at a frequency greater than this will receive response code 429. 报告方法至多可每 60 秒呼叫一次。以高于此频率的呼叫将收到响应代码 429

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

#### REQUEST BODY - application/json

| NAME        | TYPE    | DESCRIPTION                                                                                                                                                                                                               |
|-------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fromDate*   | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| toDate*     | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| utcOffset*  | integer | Utc Offset.<br>UTC 时间差                                                                                                                                                                                                    |
| rewardTypes | array   |                                                                                                                                                                                                                           |
|             | enum    | ALLOWED:Cash, FreeGames<br>Reward Type awarded to player.<br>派给玩家的奖励类型                                                                                                                                                    |

### RESPONSE

STATUS CODE - 200: List of rewards  
奖励列表

#### RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION                                                   |
|--------------------------------------|--------|---------------------------------------------------------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |                                                               |
| campaignName                         | string | Name of the campaign in which the reward was given 奖励所属的活动的名称 |
| playerId                             | string | Identifier of the rewarded account 接收奖励的帐户标识符                 |
| creditDate                           | string | Date of a cash prize reward 现金奖励的日期                           |
| transactionId                        | string | Reference to the transaction related to the reward 与奖励相关的交易代码 |

| NAME                   | TYPE   | DESCRIPTION                                                                                     |
|------------------------|--------|-------------------------------------------------------------------------------------------------|
| rewardAmount           | number | Amount of the reward 奖励金额                                                                       |
| payout                 | number | Payouts are displayed for Free Game spins only 仅显示免费游戏旋转的派彩                                     |
| referenceTransactionId | string | Reference to the debit or credit transaction ID related to the same reward 参考与同一个奖励相关的扣账或入账交易代码 |
| rewardType             | enum   | ALLOWED:Cash, FreeGames<br>Reward Type awarded to player.<br>派给玩家的奖励类型                          |

STATUS CODE - 400: Bad Request. Error codes: EndDateBeforeStartDate, InvalidDates  
错误的请求。错误代码：EndDateBeforeStartDate, InvalidDates

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 403: Forbidden  
被禁止

STATUS CODE - 404: Not Found. Error codes: AgentNotExists  
找不到。错误代码：AgentNotExists

STATUS CODE - 429: Too Many Requests  
请求次数太多

STATUS CODE - 500: Internal server error  
内部服务器错误

## 11.8 POST /agents/{agentCode}/reports/liveDealerPromotions

Get detailed Live Dealer Promotions Report 获取真人游戏优惠活动报表

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

#### REQUEST BODY - application/json

| NAME       | TYPE    | DESCRIPTION                                                                                                                                                                                                               |
|------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fromDate*  | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| toDate*    | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate |
| utcOffset* | integer | Utc Offset.<br>Utc 时间差                                                                                                                                                                                                    |
| currency   | string  | Use [ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) currency codes when specifying currencies, excluding cryptocurrencies.<br>指定货币时，使用[ISO 4217](https://en.wikipedia.org/wiki/ISO_4217) 货币代码表示，不包括加密货币                |
| playerId   | string  | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。                                                        |

| NAME           | TYPE  | DESCRIPTION                                                                                                                                    |
|----------------|-------|------------------------------------------------------------------------------------------------------------------------------------------------|
| promotionTypes | array |                                                                                                                                                |
|                | enum  | 1 to 50 chars<br>ALLOWED: LDBaccaratFortune, LDTimeChest<br>Response will return transactions for specified promotion type<br>系统将提供指定活动类型的交易记录 |

## RESPONSE

STATUS CODE - 200: OK. Returned report details  
报表已经获取

RESPONSE MODEL - application/json

| NAME                                 | TYPE   | DESCRIPTION |
|--------------------------------------|--------|-------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |        |             |
| externalTransactionId                | string |             |
| transactionTime                      | string |             |
| currency                             | string |             |
| winAmount                            | number |             |
| playerId                             | string |             |
| providerPlayerId                     | string |             |
| agentCode                            | string |             |
| agentDescription                     | string |             |
| promotionType                        | string |             |
| promotionDescription                 | string |             |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                    |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                |
| code                        | string | InputValidationError                                                                                                                           |
| message                     | string | The field playerId must be a string with a maximum length of 50. Using only numbers and english alphabets. playerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 11.9 POST /agents/{agentCode}/reports/tournamentWins

Gets tournament wins for the logged in agent 获取已登录的代理的锦标赛获奖

## REQUEST

### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

### REQUEST BODY - application/json

| NAME        | TYPE    | DESCRIPTION                                                                                                                                                                                                                                                                                                   |
|-------------|---------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| fromDate    | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate. This parameter is mandatory if tournament ID is not provided.<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate。如果没有提供锦标赛代码，则此参数是必需的 |
| toDate      | string  | Date/time to be used in search criteria. Search criteria is defined as FromDate greater than or equal to <observed date/time> and less than ToDate. This parameter is mandatory if tournament ID is not provided.<br>在搜索条件中使用的日期/时间。搜索条件定义为起始日期 FromDate 大于或等于 <搜寻日期/时间> 并且小于截止日期 ToDate。如果没有提供锦标赛代码，则此参数是必需的 |
| utcOffset*  | integer | Utc Offset.<br>Utc 时间差                                                                                                                                                                                                                                                                                        |
| playerId    | string  | max:50 chars<br><br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。                                                                                                                        |
| tournaments | array   | If tournament ID provided then time range is ignored.<br>如果已提供锦标赛 ID，则忽略时间范围                                                                                                                                                                                                                                  |
|             | integer | between 1 and 2147483647<br><br>Tournament ID.<br>锦标赛代码                                                                                                                                                                                                                                                       |

## RESPONSE

STATUS CODE - 200: List of tournament wins  
锦标赛获奖名单

### RESPONSE MODEL - application/json

| NAME                                 | TYPE    | DESCRIPTION |
|--------------------------------------|---------|-------------|
| ARRAY OF OBJECT WITH BELOW STRUCTURE |         |             |
| tournamentPeriodId                   | integer |             |
| tournamentId                         | integer |             |
| tournamentName                       | string  |             |
| periodStartDate                      | string  |             |
| periodEndDate                        | string  |             |
| creditDate                           | string  |             |
| currency                             | string  |             |
| playerId                             | string  |             |
| aliasName                            | string  |             |
| rank                                 | integer |             |
| winAmount                            | number  |             |
| winType                              | string  |             |
| prizeType                            | string  |             |

STATUS CODE - 400: Bad Request. Error codes: EndDateBeforeStartDate, InvalidDates  
错误的请求。错误代码：EndDateBeforeStartDate, InvalidDates

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 403: Forbidden  
被禁止

STATUS CODE - 404: Not Found. Error codes: AgentNotExists  
找不到。错误代码：AgentNotExists

STATUS CODE - 500: Internal server error  
内部服务器错误

---

## 12. SESSIONS 游戏启动

### 12.1 POST /agents/{agentCode}/players/{playerId}/sessions

Get content URL 获取内容网址

Returns url to launch specified content 返回可启动指定内容的网址

#### REQUEST

##### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION                                                                                                                                                        |
|------------|--------|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *agentCode | string |         | The agent code<br>代理人码                                                                                                                                             |
| *playerId  | string |         | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |

##### FORM DATA PARAMETERS

| NAME         | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|--------------|--------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| game         | string | The game code (deprecated), Use contentCode instead<br>游戏代码（已弃用），请改用内容代码                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| contentType  | string | Content type. Supported values: Game (default value), Launchpad & Tournament.<br>内容类型。支持的值：游戏（默认值），控制器和擂台赛                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| *contentCode | string | Content code<br>内容代码                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| *platform    | string | Playing platform<br>游戏平台                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| *langCode    | string | A Language code consists of: 语言代码包括 [language]-[REGION].<br>* language - A language designator is a code that represents a language. Use the two-letter [ISO 639-1](http://en.wikipedia.org/wiki/List_of_ISO_639-1_codes) standard.<br>* region - A region designator is a code that represents a country. Use the two-letter [ISO 3166-2](https://en.wikipedia.org/wiki/ISO_3166-2) standard.<br>[language]-[REGION].<br>* 语言 - 语言指示符是代表一种语言的代码。使用双字母标准 [ISO 639-1](http://en.wikipedia.org/wiki/List_of_ISO_639-1_codes).<br>* 区域 - 区域指示符是代表一个国家的代码。使用双字母标准 [ISO 3166-2](https://en.wikipedia.org/wiki/ISO_3166-2) |
| homeUrl      | string | Customize the Lobby link (URL) inside SMG HTML5 Desktop & Mobile games (not including Live Dealer).<br>Absolute URL must be used.<br>e.g. http://www.mydomain.com<br>在SMG的HTML5桌面版和手机版游戏中（不包含真人游戏Live Dealer）自订游戏大厅链接 (URL)<br>必须使用绝对链接                                                                                                                                                                                                                                                                                                                                                                              |

| NAME    | TYPE   | DESCRIPTION                                                                                                                                                                                                                                                 |
|---------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| bankUrl | string | Customize the Bank link (URL) inside SMG HTML5 Desktop & Mobile games (not including Live Dealer).<br>Absolute URL must be used & it must be HTTPS.<br>e.g. https://www.mydomain.com<br>在SMG的HTML5桌面版和手机版游戏中（不包含真人游戏Live Dealer）自订银行链接(URL) 必须使用绝对链接和 https |

## RESPONSE

STATUS CODE - 201: Content url returned  
内容网址返回成功

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                            |
|-----------------------------|--------|----------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                        |
| gameURL                     | string | The game url (deprecated)<br>游戏网址（已弃用） |
| url                         | string | The content url<br>内容网址                |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                      |
|-----------------------------|--------|------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                  |
| code                        | string | InputValidationError                                             |
| message                     | string | The value 'tablet' is not valid for Platform. 'tablet'对平台来说是个无效值 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Requested content not available for player  
请求的内容不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                |
|-----------------------------|--------|--------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                            |
| code                        | string | ContentNotFoundForPlayer                   |
| message                     | string | Requested content not available for player |
| message-zh-CHS              | string | 请求的内容不存在                                   |

STATUS CODE - 409: The request could not be processed because of conflict in the request, such as launch game url for locked player.  
由于冲突无法处理请求，比如为锁定的玩家启动游戏链接

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION      |
|-----------------------------|--------|------------------|
| OBJECT WITH BELOW STRUCTURE |        |                  |
| code                        | string | PlayerIsLocked   |
| message                     | string | Player is locked |
| message-zh-CHS              | string | 玩家帐号被锁定          |

STATUS CODE - 500: Internal server error

内部服务器错误

|                                   |        |              |
|-----------------------------------|--------|--------------|
| RESPONSE MODEL - application/json |        |              |
| NAME                              | TYPE   | DESCRIPTION  |
| OBJECT WITH BELOW STRUCTURE       |        |              |
| error                             | object |              |
| code                              | string | GeneralError |
| message                           | string | Server error |
| message-zh-CHS                    | string | 服务器错误        |

# 13. TRANSACTIONS 交易

## 13.1 GET /agents/{agentCode}/WalletTransactions

Get transaction details by idempotencyKey 通过幂等键获取交易详细信息

Returns information about a specific fund transaction within the last 24 hours. 返回最近24小时内特定资金交易的信息

### REQUEST

#### PATH PARAMETERS

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

#### QUERY PARAMETERS

| NAME            | TYPE                      | EXAMPLE | DESCRIPTION                                                                                                      |
|-----------------|---------------------------|---------|------------------------------------------------------------------------------------------------------------------|
| *idempotencyKey | string<br>max:50<br>chars |         | The agent transaction idempotencyKey, can be a maximum of 50 characters<br>代理人交易幂等密钥 idempotencyKey, 不能超过 50 个字符 |

### RESPONSE

STATUS CODE - 200: OK. Returned transaction details.  
交易信息已经获取

#### RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                                                        |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                                                    |
| id                          | string | The wallet transaction identifier.<br>交易编号                                                                                                                                         |
| status                      | enum   | ALLOWED:Succeeded, Inprogress, Unconfirmed, Failed<br>The wallet transaction status<br>交易状态                                                                                        |
| type                        | enum   | ALLOWED:Deposit, Withdraw<br>Transaction type<br>交易种类                                                                                                                              |
| playerId                    | string | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| amount                      | number | The transaction amount.<br>交易金额                                                                                                                                                    |
| externalTransactionId       | string | The agent transaction id<br>代理人交易编号                                                                                                                                                |
| idempotencyKey              | string | The agent transaction idempotencyKey, can be a maximum of 50 characters<br>代理人交易幂等密钥 idempotencyKey, 不能超过 50 个字符                                                                   |

| NAME           | TYPE   | DESCRIPTION                                                                             |
|----------------|--------|-----------------------------------------------------------------------------------------|
| createdDateUTC | string | The transaction created date (UTC).<br>交易创建时间 (UTC)                                     |
| details        | array  | Withdrawal details                                                                      |
| product        | string | 3 to 3 chars<br>Product ID.<br>产品编号                                                     |
| status         | enum   | ALLOWED:Succeeded, GameInProgress, Unavailable<br>The wallet transaction status<br>交易状态 |
| amount         | number | The transaction amount.<br>交易金额                                                         |
| uri            | string | Resource Uri.<br>资料来源链接                                                                 |

STATUS CODE - 400: Transaction does not exist  
交易不存在

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | TransactionDoesNotExist    |
| message                     | string | Transaction does not exist |
| message-zh-CHS              | string | 交易不存在                      |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |

## 13.2 POST /agents/{agentCode}/WalletTransactions

### Create transaction 创建资金交易

Deposits specific amount to player balance or withdraws all from a player' s available balance. 存入特定金额到玩家账户或是全部取出

## REQUEST

PATH PARAMETERS

| NAME | TYPE | EXAMPLE | DESCRIPTION |
|------|------|---------|-------------|
|------|------|---------|-------------|

| NAME       | TYPE   | EXAMPLE | DESCRIPTION            |
|------------|--------|---------|------------------------|
| *agentCode | string |         | The agent code<br>代理人码 |

#### FORM DATA PARAMETERS

| NAME                  | TYPE   | DESCRIPTION                                                                                                                                                                                          |
|-----------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *playerId             | string | The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和 下划线 (\_)。                                  |
| *type                 | string | Transaction type.<br>交易种类                                                                                                                                                                            |
| amount                | number | The transaction amount. The amount can be null only on withdraw (a.g withdraw all)<br>交易金额。金额只能在取款时为空值（比如全部取出）                                                                                       |
| idempotencyKey        | string | The agent transaction idempotencyKey, can be a maximum of 50 characters<br>代理人交易幂等密钥 idempotencyKey, 不能超过 50 个字符                                                                                     |
| externalTransactionId | string | The agent transaction id. If idempotencyKey is not provided, the externalTransactionId will be used as idempotencyKey<br>代理人交易编号. 如果没有带入 idempotencyKey，系统会把 externalTransactionId 视为 idempotencyKey |

## RESPONSE

STATUS CODE - 200: OK. Returned transaction details.  
交易信息已经获取

#### RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                                                         |
|-----------------------------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                                                     |
| id                          | string | The wallet transaction identifier.<br>交易编号                                                                                                                                          |
| status                      | enum   | ALLOWED:Succeeded, Inprogress, Unconfirmed, Failed<br>The wallet transaction status<br>交易状态                                                                                         |
| type                        | enum   | ALLOWED:Deposit, Withdraw<br>Transaction type<br>交易种类                                                                                                                               |
| playerId                    | string | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和 下划线 (\_)。 |
| amount                      | number | The transaction amount.<br>交易金额                                                                                                                                                     |
| externalTransactionId       | string | The agent transaction id<br>代理人交易编号                                                                                                                                                 |
| idempotencyKey              | string | The agent transaction idempotencyKey, can be a maximum of 50 characters<br>代理人交易幂等密钥 idempotencyKey, 不能超过 50 个字符                                                                    |
| createdDateUTC              | string | The transaction created date (UTC).<br>交易创建时间 (UTC)                                                                                                                                 |
| details                     | array  | Withdrawal details                                                                                                                                                                  |

| NAME    | TYPE   | DESCRIPTION                                                                             |
|---------|--------|-----------------------------------------------------------------------------------------|
| product | string | 3 to 3 chars<br>Product ID.<br>产品编号                                                     |
| status  | enum   | ALLOWED:Succeeded, GamelnProgress, Unavailable<br>The wallet transaction status<br>交易状态 |
| amount  | number | The transaction amount.<br>交易金额                                                         |
| uri     | string | Resource Uri.<br>资料来源链接                                                                 |

STATUS CODE - 201: Transaction created successfully  
交易创建成功

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                                                                                                        |
|-----------------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                                                                                                                    |
| id                          | string | The wallet transaction identifier.<br>交易编号                                                                                                                                         |
| status                      | enum   | ALLOWED:Succeeded, Inprogress, Unconfirmed, Failed<br>The wallet transaction status<br>交易状态                                                                                        |
| type                        | enum   | ALLOWED:Deposit, Withdraw<br>Transaction type<br>交易种类                                                                                                                              |
| playerId                    | string | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| amount                      | number | The transaction amount.<br>交易金额                                                                                                                                                    |
| externalTransactionId       | string | The agent transaction id<br>代理人交易编号                                                                                                                                                |
| idempotencyKey              | string | The agent transaction idempotencyKey, can be a maximum of 50 characters<br>代理人交易幂等密钥 idempotencyKey, 不能超过 50 个字符                                                                   |
| createdDateUTC              | string | The transaction created date (UTC).<br>交易创建时间 (UTC)                                                                                                                                |
| details                     | array  | Withdrawal details                                                                                                                                                                 |
| product                     | string | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                |
| status                      | enum   | ALLOWED:Succeeded, GamelnProgress, Unavailable<br>The wallet transaction status<br>交易状态                                                                                            |
| amount                      | number | The transaction amount.<br>交易金额                                                                                                                                                    |
| uri                         | string | Resource Uri.<br>资料来源链接                                                                                                                                                            |

STATUS CODE - 400: Bad Request - Input validation failed  
请求无效 - 输入验证失败

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION          |
|-----------------------------|--------|----------------------|
| OBJECT WITH BELOW STRUCTURE |        |                      |
| code                        | string | InputValidationError |

| NAME    | TYPE   | DESCRIPTION                                                                                                                                    |
|---------|--------|------------------------------------------------------------------------------------------------------------------------------------------------|
| message | string | The field PlayerId must be a string with a maximum length of 50. Using only numbers and english alphabets. PlayerId 必须不能超过 50 个字符。请只使用数字和英文字母。 |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 409: The request could not be processed because of conflict in the request, such as insufficient funds.  
由于冲突无法处理请求，比如没有足够的资金。

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                             |
|-----------------------------|--------|-----------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                         |
| error                       | object |                                         |
| code                        | string | InsufficientFunds                       |
| message                     | string | Insufficient funds to perform an action |
| message-zh-CHS              | string | 资金不足，无法执行                               |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                             |
|-----------------------------|--------|---------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                         |
| ONE:OF                      | object |                                                         |
| OPTION:1                    | object |                                                         |
| error                       | object |                                                         |
| code                        | enum   | ALLOWED:GeneralError, FailedTransaction<br>GeneralError |
| message                     | string | Server error                                            |
| message-zh-CHS              | string | 服务器错误                                                   |
| OPTION:2                    | object |                                                         |
| id                          | string |                                                         |
| status                      | string |                                                         |
| error                       | object |                                                         |
| code                        | string | UnconfirmedTransaction                                  |
| message                     | string | Unconfirmed Transaction                                 |
| message-zh-CHS              | string | 服务器错误                                                   |

EXAMPLE 1:

General Error

Unexpected error  
Our suggestion: Retry with the same idempotencyKey  
发生意外错误  
建议：使用相同的幂等键重试

```
{
  "error": {
    "code": "GeneralError",
    "message-zh-CHS": "服务器错误",
    "message": "Server Error"
  }
}
```

EXAMPLE 2:

Unconfirmed Transaction

Transaction status is unknown and will be transferred to Succeeded or Failed  
Our suggestion: Retry with the same idempotencyKey  
交易状态未知，将转为成功或失败  
建议：使用相同的幂等键重试

```
{
  "id": "03832C7303DD420B0001000000002459FD73",
  "status": "Unconfirmed",
  "error": {
    "code": "UnconfirmedTransaction",
    "message-zh-CHS": "服务器错误",
    "message": "The transaction status is unconfirmed"
  }
}
```

EXAMPLE 3:

Failed Transaction

Transaction attempt was failed. This the final status of transaction and will not be changed  
Our suggestion: Retry with new idempotencyKey  
交易尝试失败。这是交易的最终状态，不会改变  
建议：使用新的幂等键重试

```
{
  "error": {
    "code": "FailedTransaction",
    "message-zh-CHS": "交易失败",
    "message": "The transaction failed"
  }
}
```

13.3 GET /agents/{agentCode}/WalletTransactions/{walletTransactionId}

Get transaction details 获取交易信息

Returns information about specific fund transaction. 返回指定资金交易的信息

REQUEST

PATH PARAMETERS

| NAME                 | TYPE   | EXAMPLE | DESCRIPTION                        |
|----------------------|--------|---------|------------------------------------|
| *agentCode           | string |         | The agent code<br>代理人码             |
| *walletTransactionId | string |         | The wallet transaction id.<br>交易编号 |

RESPONSE

STATUS CODE - 200: OK. Returned transaction details.  
交易信息已经获取

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                                                                                 |
|-----------------------------|--------|---------------------------------------------------------------------------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                                                                                             |
| id                          | string | The wallet transaction identifier.<br>交易编号                                                  |
| status                      | enum   | ALLOWED:Succeeded, Inprogress, Unconfirmed, Failed<br>The wallet transaction status<br>交易状态 |

| NAME                  | TYPE   | DESCRIPTION                                                                                                                                                                        |
|-----------------------|--------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| type                  | enum   | ALLOWED:Deposit, Withdraw<br>Transaction type<br>交易种类                                                                                                                              |
| playerId              | string | max:50 chars<br>The player ID can be a maximum of 50 characters - only numbers, English letters, hyphen (-) and underscore (\_).<br>玩家编码不能超过 50 个字符。请只使用数字、英文字母、连字符 (-) 和下划线 (\_)。 |
| amount                | number | The transaction amount.<br>交易金额                                                                                                                                                    |
| externalTransactionId | string | The agent transaction id<br>代理人交易编号                                                                                                                                                |
| idempotencyKey        | string | The agent transaction idempotencyKey, can be a maximum of 50 characters<br>代理人交易幂等密钥 idempotencyKey, 不能超过 50 个字符                                                                   |
| createdDateUTC        | string | The transaction created date (UTC).<br>交易创建时间 (UTC)                                                                                                                                |
| details               | array  | Withdrawal details                                                                                                                                                                 |
| product               | string | 3 to 3 chars<br>Product ID.<br>产品编号                                                                                                                                                |
| status                | enum   | ALLOWED:Succeeded, GameInProgress, Unavailable<br>The wallet transaction status<br>交易状态                                                                                            |
| amount                | number | The transaction amount.<br>交易金额                                                                                                                                                    |
| uri                   | string | Resource Uri.<br>资料来源链接                                                                                                                                                            |

STATUS CODE - 401: Unauthorized  
未经授权

STATUS CODE - 404: Transaction not found  
交易没有找到

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION                |
|-----------------------------|--------|----------------------------|
| OBJECT WITH BELOW STRUCTURE |        |                            |
| code                        | string | TransactionDoesNotExist    |
| message                     | string | Transaction does not exist |
| message-zh-CHS              | string | 交易不存在                      |

STATUS CODE - 500: Internal server error  
内部服务器错误

RESPONSE MODEL - application/json

| NAME                        | TYPE   | DESCRIPTION  |
|-----------------------------|--------|--------------|
| OBJECT WITH BELOW STRUCTURE |        |              |
| error                       | object |              |
| code                        | string | GeneralError |
| message                     | string | Server error |
| message-zh-CHS              | string | 服务器错误        |