

于鸿伟_九齿skill创新挑战_中期报告

赛事：2026 春季启元人工智能大赛
赛道：九齿 .skill 创新挑战
报告类型：初赛中期报告
小组名称：于鸿伟（个人参赛）
GitHub ID: hongwei-2026
赛题编号：T3-1-1
仓库：github.com/hongwei-2026/qiyuanbisai
报告日期：2026 年 6 月 8 日

摘要

本作品交付 ntops-forge (v1.0, 主作品) 与 ntops-copilot (v0.5, 轻量备选) 双 Skill 套件，核心创新是将 Agent 写 ntops 算子的过程从「散文化手册」升级为 PLAN→CODEGEN→GUARD→PROVE→SHIP 五段可执行工厂流水线，配套 16+ 脚本、12 张 GPU 实测截图、jsonl 审计与 A/B 量化证据。

在 RTX 4080 环境，forge gate 一键验收 silu / add / gelu 三算子：每算子 pytest 8/8 通过、单算子约 7 秒。相对无 Skill 基线，preflight 通过率 0%→100%，平均步骤 6→1，人工介入 4 次→0 次。

关键词：算子工厂、可执行 Skill、语义对照、A/B 量化、GPU 实测

一、.skill 名称、赛题与小组信息

项目	内容
主 Skill	ntops-forge（九齿算子工厂）
辅助 Skill	ntops-copilot（轻量副驾驶）
赛题编号	T3-1-1（暂定，以赛题组通知为准）
小组名称	于鸿伟
建议 PR 分支	2026-spring-hongwei-2026-T3-1-1
建议 PR 标题	[2026春季][T3-1-1] hongwei-2026

初赛以独立 skill 仓库 + commit + zip 提交；最终提交载体以后续赛题组通知为准。

二、核心创新点总览（本作品 vs 文档型 Skill）

编号	创新点	解决的问题	可验证证据
C1	五段工厂流水线	Agent 命令零散、易漏步骤	forge gate 一键跑通三算子
C2	规格驱动公式注入	手写 application 易错	spec formula 自动写入内核
C3	语义对照顾栏	公式写对但语义不一致	compare_ref matches reference
C4	结构护栏 preflight	Triton 稿混入交卷	Triton 5 项 FAIL / forge OK
C5	失败诊断 fix_cards	报错后不知怎修	FC-001/004/012 自动匹配
C6	jsonl 全链路审计	无法复现 Agent 过程	每阶段 ok+耗时可追溯
C7	自然语言生成 spec	新算子规格起草慢	NL→YAML spec 秒级生成

与文档型 Skill 的本质差异：同类作品多只有 SKILL.md；本作品把规范落到可运行脚本链，失败在秒级本地/GPU 前移到 GUARD，而非推到 CI 才暴露。

三、.skill 目标、设计原则与包结构

3.1 要解决的三大类 Agent 失败

1. 范式错误：生成 Triton @triton.jit，不符合 ntops premake 评审要求
2. 流程断裂：漏 __init__.py 注册、漏 torch 封装、漏 pytest、漏 PR 规范
3. 无法自检：结构/语义错误推到 CI/GPU 才暴露，浪费机时

3.2 设计原则

- ☐ 可执行优先：每个阶段对应脚本，不只写文档
- ☐ 五段闭环：PLAN → CODEGEN → GUARD → PROVE → SHIP
- ☐ 精准测试：只跑 tests/test_<op>.py，禁止全量 pytest
- ☐ 可审计：forge_runs.jsonl 记录每阶段结果与耗时

3.3 包结构

路径	内容
skills/ntops-forge/	SKILL.md, specs/, taxonomy.md, fix_cards.md
skills/ntops-copilot/	SKILL.md, tasks/, formulas.md
scripts/	forge.py 等 16 个可执行脚本
docs/screenshots/	15 张 GPU 实测截图（本报告附图）

脚本	功能
doctor.py	GPU/依赖环境自检
forge_diagnose.py	失败文本→fix_cards
forge_spec.py	自然语言→YAML spec
record_run.py / eval_ab.py	A/B 数据记录与报告

```
(base) root@autodl-container-6764489861-420726ac:~/work/skill# source /root/miniconda3/bin/activate base
cd /root/work/skill
mkdir -p docs/screenshots docs/demo-logs
(base) root@autodl-container-6764489861-420726ac:~/work/skill# nvidia-smi -L
python scripts/doctor.py | tee docs/demo-logs/00-doctor.log
GPU 0: NVIDIA GeForce RTX 4080 (UUID: GPU-d859f103-f602-9b9a-2491-74c92c28cc9b)
ntops-copilot doctor
-----
OK python executable found
OK ninetoothed importable
OK torch importable
OK pytest importable
OK CUDA available: NVIDIA GeForce RTX 4080
OK ntops installed
OK nvidia-smi: GPU 0: NVIDIA GeForce RTX 4080 (UUID: GPU-d859f103-f602-9b9a-2491-74c92c28cc9b)
OK git available
-----
doctor finished
(base) root@autodl-container-6764489861-420726ac:~/work/skill#
```

图2 环境自检 doctor

图2 doctor 确认: ninetoothed / torch / pytest / ntops / RTX 4080 CUDA 就绪

```
OK: prove passed
== [SHIP] ==
PR branch: 2026-spring-hongwei-2026-T1-1-1
PR title: [2026-spring-hongwei-2026-T1-1-1] hongwei-2026
Kernel: /tmp/gelu_forge_kernel.py
HONOR/REFERENCE: update before ntops upstream PR
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task gelu --mode treatment --preflight-pass --pytest-pass --steps 1 --elapsed 60
OK: recorded treatment.gelu -> /root/work/skill/docs/ab_runs.csv

OK: ship pack ready

== FORGE OK (gelu) in 6.8s ==
Audit log: /root/work/skill/docs/forge_runs.jsonl

== GATE SUMMARY ==
OK silu
OK add
OK gelu
GATE OK: all operators passed
WARN: /root/work/ntops/src/ntops/kernels/silu.py exists; using /tmp (pass --force to overwrite)

== [PLAN] ==
op=silu family=elementwise_unary pattern=unary
pytest=tests/test_silu.py reference=src/ntops/kernels/silu.py
OK: plan ready

== [CODEGEN] ==
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_kernel.py --name silu --pattern unary --style ntops --out /tmp/silu_forge_kernel.py --formula output = input / (1 + ntl.exp(-ntl.cast(input, ntl.float32)))
Wrote /tmp/silu_forge_kernel.py [ntops/unary] *formula
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_torch.py --name silu --pattern unary --out /tmp/silu_forge_torch.py
Wrote /tmp/silu_forge_torch.py

OK: codegen finished

== [GUARD] ==
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_forge_kernel.py --kernel --strict
OK: preflight passed
$ /root/miniconda3/bin/python /root/work/skill/scripts/compare_ref.py /tmp/silu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/silu.py
OK: application() matches reference

OK: guard passed

== [PROVE] ==
$ /root/miniconda3/bin/python -m pytest -q tests/test_silu.py
.....
8 passed in 3.56s

OK: prove passed

== [SHIP] ==
PR branch: 2026-spring-hongwei-2026-T1-1-1
PR title: [2026-spring-hongwei-2026-T1-1-1] hongwei-2026
Kernel: /tmp/silu_forge_kernel.py
HONOR/REFERENCE: update before ntops upstream PR
```

图3 单算子五段流水线

图3 forge run silu: PLAN→CODEGEN→GUARD→PROVE→SHIP 全通过, 6.8s

```

OK: application() matches reference
OK: guard passed
== [PROVE] ==
$ /root/miniconda3/bin/python -m pytest -q tests/test_gelu.py
s.s.s.s.s.s.s
8 passed, 8 skipped in 3.52s
OK: prove passed
== [SHIP] ==
PR branch: 2026-spring-hongwei-2026-TI-1-1
PR title: [2026春季][TI-1-1] hongwei-2026
Kernel: tmp/gelu_forge_kernel.py
HONOR/REFERENCE: update before ntops upstream PR
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task gelu --mode treatment --preflight-pass --pytest-pass --steps 1 --elapsed 60
OK: recorded treatment/gelu -> /root/work/skill/docs/ab_runs.csv
OK: ship pack ready
== FORCE OK (gelu) in 6.9s ==
Audit log: /root/work/skill/docs/forge_runs.jsonl
== GATE SUMMARY ==
OK silu
OK add
OK gelu
GATE OK: all operators passed
(base) root@autodl-container-6764489861-420726ac:~/work/skill# grep -E "PLAN|GUARD|PROVE|matches reference|passed|GATE" docs/demo-logs/01-forge-gate.log
== FORCE GATE: silu, add, gelu ==
== [PLAN] ==
== [GUARD] ==
OK: preflight passed
OK: application() matches reference
OK: guard passed
== [PROVE] ==
8 passed in 3.54s
OK: prove passed
== [PLAN] ==
== [GUARD] ==
OK: preflight passed
OK: application() matches reference
OK: guard passed
== [PROVE] ==
8 passed in 3.57s
OK: prove passed
== [PLAN] ==
== [GUARD] ==
OK: preflight passed
OK: application() matches reference
OK: guard passed
== [PROVE] ==
8 passed, 8 skipped in 3.52s
OK: prove passed
== GATE SUMMARY ==
GATE OK: all operators passed
(base) root@autodl-container-6764489861-420726ac:~/work/skill#

```

图4 一键 gate 三算子验收

图4 forge gate: silu / add / gelu 汇总 GATE OK

```

$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task add --mode treatment --preflight-pass --pytest-pass --steps 1 --elapsed 60
OK: recorded treatment/add -> /root/work/skill/docs/ab_runs.csv
OK: ship pack ready

== FORCE OK (add) in 7.0s ==
Audit log: /root/work/skill/docs/forge_runs.jsonl
WARN: /root/work/ntops/src/ntops/kernels/gelu.py exists; using /tmp (pass --force to overwrite)

== [PLAN] ==
op-gelu family=elementwise unary pattern=unary
pytest: tests/test_gelu.py reference=src/ntops/kernels/gelu.py
OK: plan ready

== [CODEGEN] ==
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_kernel.py --name gelu --pattern unary --style ntops --out /tmp/gelu_forge_kernel.py --formula output = input * 0.5 * (1 + ntl.erf(input / ntl.sqrt(2.0)))
Wrote /tmp/gelu_forge_kernel.py [ntops/unary] *formula
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_torch.py --name gelu --pattern unary --out /tmp/gelu_forge_torch.py
Wrote /tmp/gelu_forge_torch.py
OK: codegen finished

== [GUARD] ==
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/gelu_forge_kernel.py --kernel --strict
OK: preflight passed
$ /root/miniconda3/bin/python /root/work/skill/scripts/compare_ref.py /tmp/gelu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/gelu.py
OK: application() matches reference
OK: guard passed

== [PROVE] ==
$ /root/miniconda3/bin/python -m pytest -q tests/test_gelu.py
.s.s.s.s.s.s.s.s
8 passed, 8 skipped in 3.52s [100%]
OK: prove passed

== [SHIP] ==
PR branch: 2026-spring-hongwei-2026-T1-1-1
PR title: [2026春季][T1-1-1] hongwei-2026
Kernel: /tmp/gelu_forge_kernel.py
HONOR/REFERENCE: update before ntops upstream PR
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task gelu --mode treatment --preflight-pass --pytest-pass --steps 1 --elapsed 60
OK: recorded treatment/gelu -> /root/work/skill/docs/ab_runs.csv
OK: ship pack ready

== FORCE OK (gelu) in 6.9s ==
Audit log: /root/work/skill/docs/forge_runs.jsonl

== GATE SUMMARY ==
OK silu
OK add
OK gelu
GATE OK: all operators passed
(base) root@auto01:~/containers-67644689861-490726pc~/work/skill#

```

图5 gelu 流水线与 gate 汇总

图5 gelu 含 default_application 特例，三算子 gate 全部 OK

五、七大创新点实测详解（附图）

创新点 C2：规格驱动公式注入

spec YAML 中 formula 字段自动注入 scaffold 生成的 application()，Agent 无需手写公式行。


```

OK: guard passed
== [PROVE] ==
$ /root/miniconda3/bin/python -m pytest -q tests/test_silu.py
.....
8 passed in 3.54s
OK: prove passed
== [SHIP] ==
PR branch: 2026-spring hongwei-2026-T1-1-1
PR title: [2026春季]T1-1-1 hongwei-2026
Kernel: /tmp/silu_forge_kernel.py
HONOR REFERENCE: update before ntops upstream PR
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task silu --mode treatment --preflight-pass --pytest-pass --steps 1 --elapsed 60
OK: recorded treatment/silu -> /root/work/skill/docs/ab_runs.csv
OK: ship pack ready
== FORCE OK (silu) in 6.8s ==
Audit log: /root/work/skill/docs/forge_runs.jsonl
(base) root@autodl-container-6764489861-420726ac:/work/skill# cat skills/ntops-forge/specs/silu.yaml
echo -
head -30 /tmp/silu_forge_kernel.py
id: forge-silu
op: silu
family: elementwise_unary
pattern: unary
spec: |
  silu(x) = x * sigmoid(x)
  formula: "output = input / (1 + ntl.exp(ntl.cast(input, ntl.float32)))"
  reference: src/ntops/kernels/silu.py
  pytest: tests/test_silu.py
  contest_id: T1-1
  github_id: hongwei-2026
  acceptance:
    preflight_strict: true
    compare_ref: true
    pytest: true
  """NineToothed kernel: silu (ntops/unary scaffold)."""
import functools
import ninetoothed.language as ntl
from ninetoothed import Tensor
from ntops.kernels.element_wise import arrangement
def application(input, output):
    output = input / (1 + ntl.exp(ntl.cast(input, ntl.float32))) # noqa: F841
def premake(ndim, dtype=None, block_size=None):
    arrangement = functools.partial(arrangement, block_size=block_size)
    tensors = (Tensor(ndim, dtype=dtype), Tensor(ndim, dtype=dtype))
    return arrangement._application_tensors
(base) root@autodl-container-6764489861-420726ac:/work/skill#

```

图6 公式注入 spec 与内核一致

图6 silu spec formula 与 /tmp/silu_forge_kernel.py 中 application 一致

创新点 C3：语义对照护栏 compare_ref

生成稿与官方 reference 逐函数比对，gelu 支持 default_application 特例。

```
tensors = (tensor(ndim, dtype=dtype), tensor(ndim, dtype=dtype))
return arrangement_, application, tensors
(base) root@autodl-container-6764489861-420726ac:~/work/skill# python scripts/compare_ref.py /tmp/silu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/silu.py
python scripts/compare_ref.py /tmp/gelu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/gelu.py 2>/dev/null || \
python scripts/forge.py run gelu --ntops-root /root/work/ntops >/dev/null 2>&1 && \
python scripts/compare_ref.py /tmp/gelu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/gelu.py
OK: application() matches reference
OK: application() matches reference
OK: application() matches reference
(base) root@autodl-container-6764489861-420726ac:~/work/skill#
```

图7 compare_ref silu/gelu 通过

图7 三行 OK: application() matches reference

创新点 C4：结构护栏--拦截 Triton 错误范式

无 Skill 时 Agent 常写 Triton; preflight 秒级拒绝并列出 5 项具体违规。

```

(base) root@autodl-container-6764489861-420726ac:~/work/skill# python scripts/compare_ref.py /tmp/silu_forge_kernel.py --ref /root/work/n
python scripts/compare_ref.py /tmp/gelu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/gelu.py 2>/dev/null || \
python scripts/forge.py run gelu --ntops-root /root/work/ntops >/dev/null 2>&1 && \
python scripts/compare_ref.py /tmp/gelu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/gelu.py
OK: application() matches reference
OK: application() matches reference
OK: application() matches reference
(base) root@autodl-container-6764489861-420726ac:~/work/skill# cat > /tmp/baseline_triton.py << 'EOF'
import triton
import triton.language as tl

@triton.jit
def bad_kernel(x_ptr, y_ptr, n, BLOCK: tl.constexpr):
    pass
EOF

echo "=== 无 skill: Triton 稿 ==="
python scripts/preflight.py /tmp/baseline_triton.py --kernel --strict; echo "exit=$?"

echo "=== 有 skill: forge 生成稿 ==="
python scripts/preflight.py /tmp/silu_forge_kernel.py --kernel --strict; echo "exit=$?"
=== 无 skill: Triton 稿 ===
FAIL: found Triton @triton.jit —use NineToothed premake/application instead
FAIL: missing function: application
FAIL: kernel must use premake (ntops) or arrangement+make (examples)
FAIL: missing ninetoothed import/usage
FAIL: missing # noqa: F841 on output assignment (ntops convention)
exit=1
=== 有 skill: forge 生成稿 ===
OK: preflight passed
exit=0
(base) root@autodl-container-6764489861-420726ac:~/work/skill#

```

图8 Triton FAIL vs forge OK

图8 左: Triton 稿 exit=1; 右: forge 稿 preflight OK

创新点 C5: 失败诊断 fix_cards

forge_diagnose 将错误文本映射到 FC-xxx 修复动作, 降低人工查文档成本。

```

import triton.language as tl

@triton.jit
def bad_kernel(x_ptr, y_ptr, n, BLOCK: tl.constexpr):
    pass
EOF

echo "=== 无 skill: Triton 稿 ==="
python scripts/preflight.py /tmp/baseline_triton.py --kernel --strict; echo "exit=$?"

echo "=== 有 skill: forge 生成稿 ==="
python scripts/preflight.py /tmp/silu_forge_kernel.py --kernel --strict; echo "exit=$?"
=== 无 skill: Triton 稿 ===
FAIL: found Triton @triton.jit --use NineToothed premake/application instead
FAIL: missing function: application
FAIL: kernel must use premake (ntops) or arrangement+make (examples)
FAIL: missing ninetoothed import/usage
FAIL: missing # noqa: F841 on output assignment (ntops convention)
exit=1
=== 有 skill: forge 生成稿 ===
OK: preflight passed
exit=0
(base) root@autodl-container-6764489861-420726ac:~/work/skill# python scripts/forge_diagnose.py --text "No module named pytest"
python scripts/forge_diagnose.py --text "FAIL: found Triton @triton.jit"
python scripts/forge_diagnose.py --text "can't open file '/root/scripts/forge.py'"
WARN: no fix card matched; read skills/ntops-forge/fix_cards.md
=== Fix Cards ===
FC-001: 改用 premake/application, 禁止 Triton

详情: /root/work/skill/skills/ntops-forge/fix_cards.md
=== Fix Cards ===
FC-004: cd /root/work/skill 后再跑 forge

详情: /root/work/skill/skills/ntops-forge/fix_cards.md
(base) root@autodl-container-6764489861-420726ac:~/work/skill#

```

图9 fix_cards 自动诊断

图9 Triton→FC-001; 路径错误→FC-004

创新点 C6: jsonl 全链路审计

每次 forge run 写入 docs/forge_runs.jsonl, 五阶段 ok/elapsed 可复查。

```

详情: /root/work/skill/skills/ntops-forge/fix_cards.md
(base) root@autodl-container-6764489861-420726ac: /work/skill# python scripts/forge.py gate --ntops-root /root/work/ntops >/dev/null 2>&1
tail -5 docs/forge_runs.json | python -m json.tool 2>/dev/null | tail -3 docs/forge_runs.json
{"spec_id": "forge-silu", "op": "silu", "started_at": "2026-06-08T17:07:42", "stages": [{"stage": "plan", "ok": true, "error": ""}, {"stage": "codegen", "ok": true, "error": ""}, {"stage": "guard", "ok": true, "error": ""}, {"stage": "prove", "ok": true, "error": ""}, {"stage": "ship", "ok": true, "error": ""}], "ok": true, "kernel_path": "/tmp/silu_forge_kernel.py", "elapsed_seconds": 6.967365264892578}
{"spec_id": "forge-add", "op": "add", "started_at": "2026-06-08T17:07:49", "stages": [{"stage": "plan", "ok": true, "error": ""}, {"stage": "codegen", "ok": true, "error": ""}, {"stage": "guard", "ok": true, "error": ""}, {"stage": "prove", "ok": true, "error": ""}, {"stage": "ship", "ok": true, "error": ""}], "ok": true, "kernel_path": "/tmp/add_forge_kernel.py", "elapsed_seconds": 6.947627544403076}
{"spec_id": "forge-gelu", "op": "gelu", "started_at": "2026-06-08T17:07:56", "stages": [{"stage": "plan", "ok": true, "error": ""}, {"stage": "codegen", "ok": true, "error": ""}, {"stage": "guard", "ok": true, "error": ""}, {"stage": "prove", "ok": true, "error": ""}, {"stage": "ship", "ok": true, "error": ""}], "ok": true, "kernel_path": "/tmp/gelu_forge_kernel.py", "elapsed_seconds": 6.921516180039492}
(base) root@autodl-container-6764489861-420726ac: /work/skill#

```

图10 jsonl 审计日志

图10 silu/add/gelu 三算子 jsonl 五阶段 ok:true

创新点 C7: 自然语言生成 spec + 仓库结构

一句话描述算子即可生成 forge spec YAML, taxonomy 自动分类。

```

Wrote /tmp/silu_torch.py
OK: preflight passed
OK: preflight passed
OK: application() matches reference
-----
8 passed in 3.54s
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_kernel.py --kernel
OK: silu registered
$ /root/miniconda3/bin/python /root/work/skill/scripts/compare_ref.py /tmp/silu_kernel.py --ref /root/work/ntops/src/ntops/kernels/silu.py
$ /root/miniconda3/bin/python -m pytest -q tests/test_silu.py
OK: pytest passed
OK: verify task finished
OK: recorded treatment/silu -> /root/work/skill/docs/ah_runs.csv
WARN: /root/work/ntops/src/ntops/kernels/silu.py already exists; use --force to overwrite
INFO: scaffolding to temp: /tmp/silu_kernel.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_kernel.py --name silu --pattern unary --style ntops --out /tmp/silu_kernel.py --formula output = input / (1 + ntl.exp(-ntl.cast(input, n
1: float32)))
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_torch.py --name silu --pattern unary --out /tmp/silu_torch.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_kernel.py --kernel
$ /root/miniconda3/bin/python /root/work/skill/scripts/verify_task.py --name silu --ntops-root /root/work/ntops --kernel /tmp/silu_kernel.py --pytest --pytest-file tests/test_silu.py --compare-ref /ro
ot/work/ntops/src/ntops/kernels/silu.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task silu --preflight-pass --pytest-pass --steps 2 --elapsed 90

== Next steps (Agent/human) ==
1) Edit application() in /tmp/silu_kernel.py
   Formula hints: skills/ntops-copilot/formulas.md
   Reference: ntops/src/ntops/kernels/silu.py
2) Register: python scripts/register_op.py --name silu --ntops-root /root/work/ntops
3) Verify: python scripts/verify_task.py --name silu --ntops-root /root/work/ntops --pytest
4) Test: cd /root/work/ntops && pytest -q tests/test_silu.py
5) PR branch: 2026-spring-hongwei-2026-TI-1-X
6) PR title: [2026春季][TI-1-X] hongwei-2026

== Optional: run pytest now ==
cd /root/work/ntops && pytest -q tests/test_silu.py
(base) root@autodl-container-6764489861-420728ac:/work/skill# python scripts/forge_spec.py "relu unary max zero" --out /tmp/custom_relu.yaml
cat /tmp/custom_relu.yaml
python scripts/forge.py list
Wrote /tmp/custom_relu.yaml [relu/elementwise_unary]
id: forge-relu-custom
op: relu
family: elementwise_unary
pattern: unary
spec: |
  Auto-generated from: relu unary max zero
  formula: "output = max(0.0, input)"
  reference: src/ntops/kernels/relu.py
  pytest: tests/test_relu.py
  contest_id: TI-1-X
  github_id: hongwei-2026
acceptance:
  preflight_strict: true
  compare_ref: true
  pytest: true
op, family, pattern, spec, file
add, elementwise_binary, binary, skills/ntops-forge/specs/add.yaml
gelu, elementwise_unary, unary, skills/ntops-forge/specs/gelu.yaml
silu, elementwise_unary, unary, skills/ntops-forge/specs/silu.yaml
(base) root@autodl-container-6764489861-420728ac:/work/skill#

```

图11 NL→spec + forge list

图11 relu unary max zero → custom_relu.yaml

```

Reference: ntops/src/ntops/kernels/silu.py
2) Register: python scripts/register_op.py --name silu --ntops-root /root/work/ntops
3) Verify: python scripts/verify_task.py --name silu --ntops-root /root/work/ntops --pytest
4) Test: cd /root/work/ntops && pytest -q tests/test_silu.py
5) PR branch: 2026-spring-hongwei-2026-TI-1-X
6) PR title: 2026-spring-hongwei-2026-TI-1-X hongwei-2026

-- Optional: run pytest now --
cd /root/work/ntops && pytest -q tests/test_silu.py
(base) root@autodl-container-6764489861-420726ac: /work/skill# python scripts/forge_spec.py "relu unary max zero" --out /tmp/custom_relu.yaml
cat /tmp/custom_relu.yaml
python scripts/forge.py list
Wrote /tmp/custom_relu.yaml [relu/elementwise_unary]
id: forge-relu-custom
op: relu
family: elementwise_unary
pattern: unary
spec: |
  Auto-generated from: relu unary max zero
  formula: output = max(0.0, input)
  reference: src/ntops/kernels/relu.py
  pytest: tests/test_relu.py
  contest: id: TI-1-X
  github id: hongwei-2026
  acceptance:
    preflight: strict: true
    compare: ref: true
  pytest: true
op family pattern spec_file
add elementwise_unary binary skills/ntops-forge/specs/add.yaml
gelu elementwise_unary unary skills/ntops-forge/specs/gelu.yaml
silu elementwise_unary unary skills/ntops-forge/specs/silu.yaml
(base) root@autodl-container-6764489861-420726ac: /work/skill# find skills/scripts -maxdepth 2 -type f | head -25
skills/ntops-copilot/meta.json
skills/ntops-copilot/examples.md
skills/ntops-copilot/formulas.md
skills/ntops-copilot/reference.md
skills/ntops-copilot/Skill.md
skills/ntops-forge/meta.json
skills/ntops-forge/fix_cards.md
skills/ntops-forge/Skill.md
skills/ntops-forge/taxonomy.md
scripts/_upload_seeta.py
scripts/compare_ref.py
scripts/doctor.py
scripts/eval_ab.py
scripts/forge.py
scripts/forge_diagnose.py
scripts/forge_spec.py
scripts/list_tasks.py
scripts/md_to_pdf.py
scripts/pack_submission.py
scripts/preflight.py
scripts/record_run.py
scripts/register_op.py
scripts/run_kernel.py
scripts/scaffold_kernel.py
scripts/scaffold_torch.py

```

图12 仓库结构与 demo 日志

图12 skills/scripts 目录 + forge list 三算子




图13 批量演示日志可复现

图13 demo-logs 全套日志 + A/B 报告 + copilot finish

六、适用任务范围与不适用范围

适用：ntops elementwise 一元/二元算子；2026-spring PR 规范；GPU + conda + editable ntops

不适用：Triton 风格；norm/attention 复杂算子（PLAN 阶段停止）；无 CUDA；全量 pytest tests/

七、安装与使用方式

```
source /root/miniconda3/bin/activate base pip install pytest && pip install -e /root/work/ntops cd /root/work/skill python scripts/doctor.py python scripts/forge.py gate --ntops-root /root/work/ntops
```

Cursor 安装：.cursor/skills/ntops-forge/（主）+ ntops-copilot/（辅）

八、自测任务、运行记录与 correctness 结果

8.1 自测任务集

类型	任务	预期
公开任务	silu / add / gelu	各 8 passed
模拟任务	forge spec + 任务卡	GUARD+PROVE 通过
规范任务	PR 分支/标题	SHIP 自动打印

8.2 GPU 实测（RTX 4080 · 2026-06-08）

算子	GUARD	pytest	耗时
silu	matches reference	8 passed	6.8s
add	matches reference	8 passed	7.0s
gelu	matches reference	8 passed	6.9s

```

=== GATE SUMMARY ===
GATE OK: all operators passed
(base) root@autodl-container-6764489861-420726ac:~/work/skill# python scripts/forge.py run silu --ntops-root /root/work/ntops 2>&1 | tee docs/demo-logs/02-forge-run-silu.log
WARN: /root/work/ntops/src/ntops/kernels/silu.py exists; using /tmp (pass --force to overwrite)

=== [PLAN] ===
op=silu family=elementwise unary pattern=unary
pytest=tests/test_silu.py reference=src/ntops/kernels/silu.py
OK: plan ready

=== [CODEGEN] ===
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_kernel.py --name silu --pattern unary --style ntops --out /tmp/silu_forge_kernel.py --formula output = input / (1 + ntl.exp(-ntl.cast(input, ntl.float32)))
Wrote /tmp/silu_forge_kernel.py [ntops/unary] +formula
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_torch.py --name silu --pattern unary --out /tmp/silu_forge_torch.py
Wrote /tmp/silu_forge_torch.py
OK: codegen finished

=== [GUARD] ===
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_forge_kernel.py --kernel --strict
OK: preflight passed
$ /root/miniconda3/bin/python /root/work/skill/scripts/compare_ref.py /tmp/silu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/silu.py
OK: application() matches reference
OK: guard passed

=== [PROVE] ===
$ /root/miniconda3/bin/python -m pytest -q tests/test_silu.py
.....
8 passed in 3.54s
[100%]
OK: prove passed

=== [SHIP] ===
PR branch: 2026-spring-hongwei-2026-T1-1-1
PR title: [2026春季][T1-1-1] hongwei-2026
Kernel: /tmp/silu_forge_kernel.py
HONOR/REFERENCE: update before ntops upstream PR
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task silu --mode treatment --preflight-pass --pytest-pass --steps 1 --elapsed 60
OK: recorded treatment/silu -> /root/work/skill/docs/ab_runs.csv
OK: ship pack ready

=== FORGE OK (silu) in 6.8s ===
Audit log: /root/work/skill/docs/forge_runs.jsonl
(base) root@autodl-container-6764489861-420726ac:~/work/skill#

```

图14 silu 流水线 SHIP 阶段

图14 silu 完整流水线含 pytest 8 passed 与 SHIP 记录

九、A/B 对比：有 Skill vs 无 Skill

指标	Baseline (无 skill)	Treatment (有 skill)	提升
preflight 通过率	0%	100%	+100%
pytest 通过率	未跑通	100%	质变
平均步骤	6	1	-5
人工介入	4 次	0 次	-4
平均耗时	~1200s	~6s/算子	-99.5%

```

{"spec_id": "forge-gelu", "op": "gelu", "started_at": "2026-06-08T17:07:56", "stages": [{"stage": "plan", "ok": true, "k": true, "error": ""}, {"stage": "prove", "ok": true, "error": ""}, {"stage": "ship", "ok": true, "error": ""}], "ok": true, "error": ""}
038452)
(base) root@autodl-container-6764489861-420726ac:~/work/skill# cat docs/ab_runs.csv
echo "___"
cat docs/AB_Report.md
mode,task,preflight_pass,pytest_pass,steps,intervention_count,elapsed_seconds,recorded_at
baseline,silu,false,not_run,6.4,1200,2026-06-08 17:00
treatment,silu,true,true,1.0,6,2026-06-08 17:00
treatment,add,true,true,1.0,6,2026-06-08 17:00
treatment,gelu,true,true,1.0,6,2026-06-08 17:00
treatment,silu,true,true,1.0,60,2026-06-08 17:02
treatment,add,true,true,1.0,60,2026-06-08 17:02
treatment,gelu,true,true,1.0,60,2026-06-08 17:02
treatment,silu,true,true,1.0,60,2026-06-08 17:03
treatment,silu,true,true,1.0,60,2026-06-08 17:07
treatment,add,true,true,1.0,60,2026-06-08 17:07
treatment,gelu,true,true,1.0,60,2026-06-08 17:08

___
# A/B Evaluation Report

## Data Summary

- Total baseline runs: 1
- Total treatment runs: 3

## Metrics

| Metric | Baseline | Treatment | Delta (Treatment - Baseline) |
|---|---|---|---|
| preflight pass rate | 0.0% | 100.0% | 100.0% |
| pytest pass rate | N/A | 100.0% | N/A |
| avg steps | 6.00 | 1.00 | -5.00 |
| avg interventions | 4.00 | 0.00 | -4.00 |
| avg elapsed seconds | 1200.00 | 6.00 | -1194.00 |

## Conclusion

- Quality: Treatment 在 CPU 环境 pytest 通过率 100.0%; Baseline 无 skill 时 preflight 0.0%、pytest 未跑通。
- Efficiency: Treatment 平均步骤 1.0 vs Baseline 6.0 (-5.00) 。
- Human effort: Treatment 人工介入 0.0 次 vs Baseline 4.0 次 (-4.00) 。
(base) root@autodl-container-6764489861-420726ac:~/work/skill#

```

图15 A/B 评估报告

图15 ab_runs.csv + AB_Report.md 完整对比

轻量路径: ntops-copilot

```
## Data Summary
- Total baseline runs: 1
- Total treatment runs: 3

## Metrics
Metric | Baseline | Treatment | Delta (Treatment - Baseline) |
-----|-----|-----|-----|
preflight pass rate | 0.0% | 100.0% | 100.0% |
pytest pass rate | N/A | 100.0% | N/A |
avg steps | 6.00 | 1.00 | -5.00 |
avg interventions | 4.00 | 0.00 | -4.00 |
avg elapsed seconds | 1200.00 | 6.00 | -1194.00 |

## Conclusion
- Quality: Treatment 在 GPU 环境 pytest 通过率 100.0%, Baseline 无 skill 时 preflight 0.0%, pytest 未跑通。
- Efficiency: Treatment 平均步骤 1.0 vs Baseline 6.0 (-5.00)。
- Human effort: Treatment 人工介入 0.0 次 vs Baseline 4.0 次 (-4.00)。
(base) root@ntops:~/container-0f04d92861-20726ac7/work/skill# python scripts/run_task.py --task silu --ntops-root /root/work/ntops --finish 2&1 | tee docs/demo-logs/03-copilot-finish.log
Wrote /tmp/silu_kernel.py [ntops/unary] +formula
Wrote /tmp/silu_torch.py
OK: preflight passed
OK: preflight passed
OK: application() matches reference
-----
$ passed in 3.54s
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_kernel.py --kernel
OK: silu registered
$ /root/miniconda3/bin/python /root/work/skill/scripts/compare_ref.py /tmp/silu_kernel.py --ref /root/work/ntops/src/ntops/kernels/silu.py
$ /root/miniconda3/bin/python -m pytest -q tests/test_silu.py
OK: pytest passed
OK: verify task finished
OK: recorded treatment/silu -> /root/work/skill/docs/ab_runs.csv
WARN: root/work/ntops/src/ntops/kernels/silu.py already exists; use --force to overwrite
INFO: scaffolding to temp: /tmp/silu_kernel.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_kernel.py --name silu --pattern unary --style ntops --out /tmp/silu_kernel.py --formula output = input / (1 + ntl.exp(-ntl.cast(input, n
tl.float32)))
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_torch.py --name silu --pattern unary --out /tmp/silu_torch.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_kernel.py --kernel
$ /root/miniconda3/bin/python /root/work/skill/scripts/verify_task.py --name silu --ntops-root /root/work/ntops --kernel /tmp/silu_kernel.py --pytest --pytest-file tests/test_silu.py --compare-ref /ro
ot/work/ntops/src/ntops/kernels/silu.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task silu --preflight-pass --pytest-pass --steps 2 --elapsed 90

== Next steps (Agent/human) ==
1) Edit application() in: /tmp/silu_kernel.py
   Formula hints: skill/ntops-copilot/formulas.md
   Reference: ntops/src/ntops/kernels/silu.py
2) Register: python scripts/register_op.py --name silu --ntops-root /root/work/ntops
3) Verify: python scripts/verify_task.py --name silu --ntops-root /root/work/ntops --pytest
4) Test: cd /root/work/ntops && pytest -q tests/test_silu.py
5) PR branch: 2026-spring-hongwei-2026-T1-1-X
6) PR title: [2026春季][T1-1-X] hongwei-2026

== Optional: run pytest now ==
cd /root/work/ntops && pytest -q tests/test_silu.py
```

图16 copilot 一键完工

图16 run_task.py --finish 亦可完成 silu 全链路（与 forge 工厂形成双路径）

十、失败诊断案例与修复过程

案例	现象	修复	状态
FC-001	Triton @triton.jit	改用 premake/application	已验证
FC-004	脚本路径错误	cd /root/work/skill	已写入 fix_cards
FC-012	No module named pytest	pip install pytest	已解决
gelu 特例	default_application	compare_ref 多函数名	已验证

十一、安全、依赖、授权与引用披露

- ☐ 无密钥、无隐藏答案、无联网强依赖
- ☐ 依赖: Python 3.10+、torch、ninetoothed、ntops (editable)、pytest
- ☐ HONOR_CODE.md: 本人独立编写声明（仓库根目录）
- ☐ REFERENCE.md: 引用 ninetoothed-examples（Apache-2.0）与官方文档

十二、Proposal 与附件说明

材料	路径
Proposal	docs/Proposal.md
自测计划	docs/SelfTestPlan.md
截图说明	docs/DemoShowcase.md
PR 模板	docs/PR_TEMPLATE.md
A/B 数据	docs/ab_runs.csv
附件 zip	submission-initial-20260608.zip

提交项	链接
Github	https://github.com/hongwei-2026/qiyuanbisa
Commit	https://github.com/hongwei-2026/qiyuanbisa/commit/8a7be7e

十三、后续可维护计划

1. 决赛前扩展 norm/attention spec (只读 reference 模式)
2. 对接组委会隐藏任务集, 优化 SKILL 触发词
3. 最终报告补充 benchmark 与性能回退分析

选手签名: 于鸿伟

日期: 2026 年 6 月 8 日