

于鸿伟_九齿skill创新挑战_中期报告

赛事：2026 春季启元人工智能大赛 · 九齿 .skill 创新挑战

报告类型：

摘要

本报告汇报 ntops-forge (v1.0) 与 ntops-copilot (v0.5) 双 Skill 套件的初赛进展。项目在 RTX 4080 GPU 环境完成 silu / add / gelu 三算子 `forge gate` 一键验收, pytest 8/8 通过; A/B 首轮显示 Treatment 相对 Baseline 步骤减少 5 步、人工介入减少 4 次。

一、.skill 名称、赛题与小组信息

项目 | 内容

主 Skill | n

提交载体以后续赛题组通知为准; 初赛以独立 skill 仓库 + commit + zip 提交, 不要求 PR 合入。

二、.skill 目标、设计原则与包结构

2.1 目标

解决 Agent 开发 ntops
九齿算子时三类失败: 写错范式 (Triton)、流程断裂 (漏注册/漏测)、无法自检 (错误推到 CI)。

2.2 设计原则

1. 可执行优先: 规范落到脚本, 不只写文档

2. 五段闭环

2.3 包结构

ntops-forge 五段流水线



输入: forge spec YAML

输出: forge_runs.jsonl

图1 五段流水线架构

图1 ntops-forge 五段流水线架构

三、核心工作流说明

阶段 | 动作 | 脚本

PLAN | 读 sp

```
(base) root@autodl-container-6764489861-420726ac:~/work/skill# source /root/miniconda3/bin/activate base
cd /root/work/skill
mkdir -p docs/screenshots docs/demo-logs
(base) root@autodl-container-6764489861-420726ac:~/work/skill# nvidia-smi -L
python scripts/doctor.py | tee docs/demo-logs/00-doctor.log
GPU 0: NVIDIA GeForce RTX 4080 (UUID: GPU-d859f103-f602-9b9a-2491-74c92c28cc9b)
ntops-copilot doctor

-----
OK python executable found
OK ninetoothed importable
OK torch importable
OK pytest importable
OK CUDA available: NVIDIA GeForce RTX 4080
OK ntops installed
OK nvidia-smi: GPU 0: NVIDIA GeForce RTX 4080 (UUID: GPU-d859f103-f602-9b9a-2491-74c92c28cc9b)
OK git available
-----

doctor finished
(base) root@autodl-container-6764489861-420726ac:~/work/skill#
```

图2 环境自检 doctor

图2 GPU 环境自检: ninetoothed / torch / pytest / ntops / CUDA 全部 OK

```
OK: prove passed

=== [SHIP] ===
PR branch: 2026-spring-hongwei-2026-T1-1-1
PR title: [2026春季][T1-1-1] hongwei-2026
Kernel: /tmp/gelu_forge_kernel.py
HONOR/REFERENCE: update before ntops upstream PR
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task gelu --mode treatment --preflight-pass --pytest-pass --steps 1 --elapsed 60
OK: recorded treatment/gelu -> /root/work/skill/docs/ab_runs.csv
OK: ship pack ready

=== FORGE OK (gelu) in 6.8s ===
Audit log: /root/work/skill/docs/forge_runs.json

=== GATE SUMMARY ===
OK silu
OK add
OK gelu
GATE OK: all operators passed
WARN: /root/work/ntops/src/ntops/kernels/silu.py exists; using /tmp (pass --force to overwrite)

=== [PLAN] ===
op=silu family=elementwise_unary pattern=unary
pytest-tests/test_silu.py reference=src/ntops/kernels/silu.py
OK: plan ready

=== [CODEGEN] ===
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_kernel.py --name silu --pattern unary --style ntops --out /tmp/silu_forge_kernel.py --formula output = input / (1 + ntl.exp(-ntl.cast(input, ntl.float32)))
Wrote /tmp/silu_forge_kernel.py [ntops/unary] +formula

$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_torch.py --name silu --pattern unary --out /tmp/silu_forge_torch.py
Wrote /tmp/silu_forge_torch.py

OK: codegen finished

=== [GUARD] ===
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_forge_kernel.py --kernel --strict
OK: preflight passed

$ /root/miniconda3/bin/python /root/work/skill/scripts/compare_ref.py /tmp/silu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/silu.py
OK: application() matches reference

OK: guard passed

=== [PROVE] ===
$ /root/miniconda3/bin/python -m pytest -q tests/test_silu.py
.....
8 passed in 3.56s
[100%]

OK: prove passed

=== [SHIP] ===
PR branch: 2026-spring-hongwei-2026-T1-1-1
PR title: [2026春季][T1-1-1] hongwei-2026
Kernel: /tmp/silu_forge_kernel.py
HONOR/REFERENCE: update before ntops upstream PR
```

图3 单算子五段流水线 silu

图3 `forge run silu` 完整输出: PLAN → SHIP, 约 6.8s

四、适用任务范围与不适用范围

4.1 适用范围

* ntops elementwise 一元/二元算子 (silu、add、gelu、relu、mul 等)

* 大赛 2

4.2 不适用范围

* Triton '@triton.jit' 风格 (会被 preflight 拒绝)

* norm /

五、安装与使用方式

5.1 安装

克隆仓库

git clone ht

5.2 Cursor / Agent 安装 Skill

.cursor/skills/ntops-forge/

.cursor/skil

5.3 推荐使用方式

python scripts/doctor.py

python scrip

```
OK: application() matches reference
OK: guard passed

=== [PROVE] ===
$ /root/miniconda3/bin/python -m pytest -q tests/test_gelu.py
.s.s.s.s.s.s.s.s
8 passed, 8 skipped in 3.52s
OK: prove passed

=== [SHIP] ===
PR branch: 2026-spring-hongwei-2026-T1-1-1
PR title: [2026春季][T1-1-1] hongwei-2026
Kernel: /tmp/gelu_forge_kernel.py
HONOR/REFERENCE: update before ntops upstream PR
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task gelu --mode treatment --preflight-pass --pytest-pass --steps 1 --elapsed 60
OK: recorded treatment/gelu -> /root/work/skill/docs/ab_runs.csv

OK: ship pack ready

=== FORGE OK (gelu) in 6.9s ===
Audit log: /root/work/skill/docs/forge_runs.jsonl

=== GATE SUMMARY ===
OK silu
OK add
OK gelu
GATE OK: all operators passed
(base) root@autodl-container-6764489861-420726ac:~/work/skill# grep -E "PLAN|GUARD|PROVE|matches reference|passed|GATE" docs/demo-logs/01-forge-gate.log
=== FORGE GATE: silu, add, gelu ===
=== [PLAN] ===
=== [GUARD] ===
OK: preflight passed
OK: application() matches reference
OK: guard passed
=== [PROVE] ===
8 passed in 3.54s
OK: prove passed
=== [PLAN] ===
=== [GUARD] ===
OK: preflight passed
OK: application() matches reference
OK: guard passed
=== [PROVE] ===
8 passed in 3.57s
OK: prove passed
=== [PLAN] ===
=== [GUARD] ===
OK: preflight passed
OK: application() matches reference
OK: guard passed
=== [PROVE] ===
8 passed, 8 skipped in 3.52s
OK: prove passed
=== GATE SUMMARY ===
GATE OK: all operators passed
(base) root@autodl-container-6764489861-420726ac:~/work/skill#
```

图4 一键 gate 三算子验收

图4 `forge gate`: silu / add / gelu 全部 GATE OK

六、自测任务与运行记录

6.1 自测任务集

类型 | 任务 | pytest 文件

公开任务 | s

6.2 运行记录（GPU ▪ RTX 4080 ▪ 2026-06-08）

算子 | GUARD | pytest | 耗时

silu | match

```
OK: guard passed
== [PROVE] ==
$ /root/miniconda3/bin/python -m pytest -q tests/test_silu.py
.....
$ passed in 3.54s
OK: prove passed
== [SHIP] ==
PR branch: 2026-spring-hongwei-2026-T1-1-1
PR title: [2026春季][T1-1-1] hongwei-2026
Kernel: /tmp/silu_forge_kernel.py
HONOR/REFERENCE: update before ntops upstream PR
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task silu --mode treatment --preflight-pass --pytest-pass --steps 1 --elapsed 60
OK: recorded treatment/silu -> /root/work/skill/docs/ab_runs.csv
OK: ship pack ready
== FORGE OK (silu) in 6.8s ==
Audit log: /root/work/skill/docs/forge_runs.jsonl
(base) root@autodl-container-6764489861-420726ac:~/work/skill# cat skills/ntops-forge/specs/silu.yaml
echo
head -30 /tmp/silu_forge_kernel.py
id: forge-silu
op: silu
family: elementwise_unary
pattern: unary
spec: |
    silu(x) = x * sigmoid(x)
    formula: output = input / (1 + ntl.exp(-ntl.cast(input, ntl.float32)))
reference: src/ntops/kernels/silu.py
pytest: tests/test_silu.py
contest_id: T1-1-1
github_id: hongwei-2026
acceptance:
  preflight_strict: true
  compare_ref: true
  pytest: true
"""NineToothed kernel: silu (ntops/unary scaffold)."""
import funtools
import ninetoothed.language as ntl
from ninetoothed import Tensor
from ntops.kernels.element_wise import arrangement
def application(input, output):
    output = input / (1 + ntl.exp(-ntl.cast(input, ntl.float32))) # noqa: F841
def premake(ndim, dtype=None, block_size=None):
    arrangement_ = funtools.partial(arrangement, block_size=block_size)
    tensors = (Tensor(ndim, dtype=dtype), Tensor(ndim, dtype=dtype))
    return arrangement_, application, tensors
(base) root@autodl-container-6764489861-420726ac:~/work/skill#
```

图5 规格驱动公式注入

图5 spec `formula` 自动写入生成内核 `application()`

```
tensors = (Tensor(ndim, dtype=dtype), Tensor(ndim, dtype=dtype))
return arrangement_, application, tensors
(base) root@autodl-container-6764489861-420726ac:~/work/skill# python scripts/compare_ref.py /tmp/silu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/silu.py
python scripts/compare_ref.py /tmp/gelu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/gelu.py 2>/dev/null || \
python scripts/forge.py run gelu --ntops-root /root/work/ntops >/dev/null 2>&1 && \
python scripts/compare_ref.py /tmp/gelu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/gelu.py
OK: application() matches reference
OK: application() matches reference
OK: application() matches reference
(base) root@autodl-container-6764489861-420726ac:~/work/skill#
```

图6 语义对照 compare_ref

图6 silu / gelu 生成稿与官方 reference 一致

```
详情: /root/work/skill/skills/ntops-forge/fix_cards.md
(base) root@autodl-container-6764489861-420726ac:~/work/skill# python scripts/forge.py gate --ntops-root /root/work/ntops >/dev/null 2>&1
tail -5 docs/forge_runs.jsonl | python -m json.tool 2>/dev/null | tail -3 docs/forge_runs.jsonl
{"spec_id": "forge-silu", "op": "silu", "started_at": "2026-06-08T17:07:40", "stages": [{"stage": "plan", "ok": true, "error": ""}, {"stage": "codegen", "ok": true, "error": ""}, {"stage": "guard", "ok": true, "error": ""}, {"stage": "prove", "ok": true, "error": ""}, {"stage": "ship", "ok": true, "error": ""}], "ok": true, "kernel_path": "/tmp/silu_forge_kernel.py", "elapsed_seconds": 6.967365264892578}
{"spec_id": "forge-add", "op": "add", "started_at": "2026-06-08T17:07:49", "stages": [{"stage": "plan", "ok": true, "error": ""}, {"stage": "codegen", "ok": true, "error": ""}, {"stage": "guard", "ok": true, "error": ""}, {"stage": "prove", "ok": true, "error": ""}, {"stage": "ship", "ok": true, "error": ""}], "ok": true, "kernel_path": "/tmp/add_forge_kernel.py", "elapsed_seconds": 6.947627544403076}
{"spec_id": "forge-gelu", "op": "gelu", "started_at": "2026-06-08T17:07:56", "stages": [{"stage": "plan", "ok": true, "error": ""}, {"stage": "codegen", "ok": true, "error": ""}, {"stage": "guard", "ok": true, "error": ""}, {"stage": "prove", "ok": true, "error": ""}, {"stage": "ship", "ok": true, "error": ""}], "ok": true, "kernel_path": "/tmp/gelu_forge_kernel.py", "elapsed_seconds": 6.921516180038452}
(base) root@autodl-container-6764489861-420726ac:~/work/skill#
```

图7 jsonl 全链路审计

图7 三算子 jsonl 五阶段 ok:true, 可追溯

七、自测结果与 A/B 对比（有 skill vs 无 skill）

7.1 结构护栏对比

```

(base) root@autodl-container-6764489861-420726ac:~/work/skill# python scripts/compare_ref.py /tmp/silu_forge_kernel.py --ref /root/work/n
python scripts/compare_ref.py /tmp/gelu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/gelu.py 2>/dev/null || \
python scripts/forge.py run gelu --ntops-root /root/work/ntops >/dev/null 2>&1 && \
python scripts/compare_ref.py /tmp/gelu_forge_kernel.py --ref /root/work/ntops/src/ntops/kernels/gelu.py
OK: application() matches reference
OK: application() matches reference
OK: application() matches reference
(base) root@autodl-container-6764489861-420726ac:~/work/skill# cat > /tmp/baseline_triton.py << 'EOF'
import triton
import triton.language as tl

@triton.jit
def bad_kernel(x_ptr, y_ptr, n, BLOCK: tl.constexpr):
    pass
EOF

echo "=== 无 skill: Triton 稿 ==="
python scripts/preflight.py /tmp/baseline_triton.py --kernel --strict; echo "exit=$?"

echo "=== 有 skill: forge 生成稿 ==="
python scripts/preflight.py /tmp/silu_forge_kernel.py --kernel --strict; echo "exit=$?"
=== 无 skill: Triton 稿 ===
FAIL: found Triton @triton.jit —use NineToothed premake/application instead
FAIL: missing function: application
FAIL: kernel must use premake (ntops) or arrangement+make (examples)
FAIL: missing ninetoothed import/usage
FAIL: missing # noqa: F841 on output assignment (ntops convention)
exit=1
=== 有 skill: forge 生成稿 ===
OK: preflight passed
exit=0
(base) root@autodl-container-6764489861-420726ac:~/work/skill#

```

图8 Triton 被拒 vs forge 通过

图8 无 skill: Triton 稿 5 项 FAIL; 有 skill: forge 稿 preflight OK

7.2 A/B 量化结果

指标 | Baseline (无 skill) | Treatment (有 skill) | 差值

preflight 通


```

{"spec_id": "forge-gelu", "op": "gelu", "started_at": "2026-06-08T17:07:56", "stages": [{"stage": "plan", "ok": true, "k": true, "error": ""}, {"stage": "prove", "ok": true, "error": ""}, {"stage": "ship", "ok": true, "error": ""}], "ok": true, "error": ""}
038452}
(base) root@autodl-container-6764489861-420726ac:~/work/skill# cat docs/ab_runs.csv
echo "___"
cat docs/AB_Report.md
mode,task,preflight_pass,pytest_pass,steps,intervention_count,elapsed_seconds,recorded_at
baseline,silu,false,not_run,6,4,1200,2026-06-08 17:00
treatment,silu,true,true,1,0,6,2026-06-08 17:00
treatment,add,true,true,1,0,6,2026-06-08 17:00
treatment,gelu,true,true,1,0,6,2026-06-08 17:00
treatment,silu,true,true,1,0,60,2026-06-08 17:02
treatment,add,true,true,1,0,60,2026-06-08 17:02
treatment,gelu,true,true,1,0,60,2026-06-08 17:02
treatment,silu,true,true,1,0,60,2026-06-08 17:03
treatment,silu,true,true,1,0,60,2026-06-08 17:07
treatment,add,true,true,1,0,60,2026-06-08 17:07
treatment,gelu,true,true,1,0,60,2026-06-08 17:08
___
# A/B Evaluation Report

## Data Summary

- Total baseline runs: 1
- Total treatment runs: 3

## Metrics

| Metric | Baseline | Treatment | Delta (Treatment - Baseline) |
|---|---|---|---|
| preflight pass rate | 0.0% | 100.0% | 100.0% |
| pytest pass rate | N/A | 100.0% | N/A |
| avg steps | 6.00 | 1.00 | -5.00 |
| avg interventions | 4.00 | 0.00 | -4.00 |
| avg elapsed seconds | 1200.00 | 6.00 | -1194.00 |

## Conclusion

- Quality: Treatment 在 GPU 环境 pytest 通过率 100.0%; Baseline 无 skill 时 preflight 0.0%、pytest 未跑通。
- Efficiency: Treatment 平均步骤 1.0 vs Baseline 6.0 (-5.00)。
- Human effort: Treatment 人工介入 0.0 次 vs Baseline 4.0 次 (-4.00)。
(base) root@autodl-container-6764489861-420726ac:~/work/skill#

```

图9 A/B 评估报告

图9 ab_runs.csv 与 AB_Report.md 汇总

7.3 轻量路径对比

```
## Data Summary
- Total baseline runs: 1
- Total treatment runs: 3

## Metrics
| Metric | Baseline | Treatment | Delta (Treatment - Baseline) |
|---|---|---|---|
| preflight pass rate | 0.0% | 100.0% | 100.0% |
| pytest pass rate | N/A | 100.0% | N/A |
| avg steps | 6.00 | 1.00 | -5.00 |
| avg interventions | 4.00 | 0.00 | -4.00 |
| avg elapsed seconds | 1200.00 | 6.00 | -1194.00 |

## Conclusion
- Quality: Treatment 在 GPU 环境 pytest 通过率 100.0%; Baseline 无 skill 时 preflight 0.0%, pytest 未跑通。
- Efficiency: Treatment 平均步骤 1.0 vs Baseline 6.0 (-5.00)。
- Human effort: Treatment 人工介入 0.0 次 vs Baseline 4.0 次 (-4.00)。
(base) root@autodl-container-6764489861-420726ac:~/work/skill# python scripts/run_task.py --task silu --ntops-root /root/work/ntops --finish 2&1 | tee docs/demo-logs/03-copilot-finish.log
Wrote /tmp/silu_kernel.py [ntops/unary] *formula
Wrote /tmp/silu_torch.py
OK: preflight passed
OK: preflight passed
OK: application() matches reference
.....
$ passed in 3.54s
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_kernel.py --kernel
OK: 'silu' registered
$ /root/miniconda3/bin/python /root/work/skill/scripts/compare_ref.py /tmp/silu_kernel.py --ref /root/work/ntops/src/ntops/kernels/silu.py
$ /root/miniconda3/bin/python -m pytest -q tests/test_silu.py
$ pytest passed
OK: verify task finished
OK: recorded treatment/silu -> /root/work/skill/docs/ab_runs.csv
WARN: /root/work/ntops/src/ntops/kernels/silu.py already exists: use --force to overwrite
INFO: scaffolding to temp: /tmp/silu_kernel.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_kernel.py --name silu --pattern unary --style ntops --out /tmp/silu_kernel.py --formula output = input / (1 + ntl.exp(-ntl.cast(input, n
tl.float32)))
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_torch.py --name silu --pattern unary --out /tmp/silu_torch.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_kernel.py --kernel
$ /root/miniconda3/bin/python /root/work/skill/scripts/verify_task.py --name silu --ntops-root /root/work/ntops --kernel /tmp/silu_kernel.py --pytest --pytest-file tests/test_silu.py --compare-ref /ro
ot/work/ntops/src/ntops/kernels/silu.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task silu --preflight-pass --pytest-pass --steps 2 --elapsed 90

== Next steps (Agent/human) ==
1) Edit application() in: /tmp/silu_kernel.py
   Formula hints: skills/ntops-copilot/formulas.md
   Reference: ntops/src/ntops/kernels/silu.py
2) Register: python scripts/register_op.py --name silu --ntops-root /root/work/ntops
3) Verify: python scripts/verify_task.py --name silu --ntops-root /root/work/ntops --pytest
4) Test: cd /root/work/ntops && pytest -q tests/test_silu.py
5) PR branch: 2026-spring-hongwei-2026-T1-1-X
6) PR title: [2026春季][T1-1-X] hongwei-2026

== Optional: run pytest now ==
cd /root/work/ntops && pytest -q tests/test_silu.py
```

[100%]

图10 copilot 一键完工

图10 `run\_task.py --finish` 亦可完成 silu 全链路

八、失败诊断案例与修复过程

案例 | 现象 | 修复

FC-001 | Tri

```

import triton.language as tl

@triton.jit
def bad_kernel(x_ptr, y_ptr, n, BLOCK: tl.constexpr):
    pass
EOF

echo "=== 无 skill: Triton 稿 ==="
python scripts/preflight.py /tmp/baseline_triton.py --kernel --strict; echo "exit=$?"

echo "=== 有 skill: forge 生成稿 ==="
python scripts/preflight.py /tmp/silu_forge_kernel.py --kernel --strict; echo "exit=$?"
=== 无 skill: Triton 稿 ===
FAIL: found Triton @triton.jit --use NineToothed premake/application instead
FAIL: missing function: application
FAIL: kernel must use premake (ntops) or arrangement+make (examples)
FAIL: missing ninetoothed import/usage
FAIL: missing # noqa: F841 on output assignment (ntops convention)
exit=1
=== 有 skill: forge 生成稿 ===
OK: preflight passed
exit=0
(base) root@autodl-container-6764489861-420726ac:~/work/skill# python scripts/forge_diagnose.py --text "No module named pytest"
python scripts/forge_diagnose.py --text "FAIL: found Triton @triton.jit"
python scripts/forge_diagnose.py --text "can't open file '/root/scripts/forge.py'"
WARN: no fix card matched; read skills/ntops-forge/fix_cards.md
=== Fix Cards ===
FC-001: 改用 premake/application, 禁止 Triton

详情: /root/work/skill/skills/ntops-forge/fix_cards.md
=== Fix Cards ===
FC-004: cd /root/work/skill 后再跑 forge

详情: /root/work/skill/skills/ntops-forge/fix_cards.md
(base) root@autodl-container-6764489861-420726ac:~/work/skill#

```

图11 失败自动诊断 fix_cards

图11 forge_diagnose 自动匹配 FC-001 / FC-004

```

Wrote /tmp/silu_torch.py
OK: preflight passed
OK: preflight passed
OK: application() matches reference
.....
8 passed in 3.54s
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_kernel.py --kernel
OK: silu registered
$ /root/miniconda3/bin/python /root/work/skill/scripts/compare_ref.py /tmp/silu_kernel.py --ref /root/work/ntops/src/ntops/kernels/silu.py
INFO: scaffolding to temp: /tmp/silu_kernel.py
$ /root/miniconda3/bin/python -m pytest -q tests/test_silu.py
OK: pytest passed
OK: verify task finished
OK: recorded treatment/silu -> /root/work/skill/docs/ab_runs.csv
WARN: /root/work/ntops/src/ntops/kernels/silu.py already exists; use --force to overwrite
INFO: scaffolding to temp: /tmp/silu_kernel.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_kernel.py --name silu --pattern unary --style ntops --out /tmp/silu_kernel.py --formula output = input / (1 + ntl.exp(-ntl.cast(input, n
tl.float32)))
$ /root/miniconda3/bin/python /root/work/skill/scripts/scaffold_torch.py --name silu --pattern unary --out /tmp/silu_torch.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/preflight.py /tmp/silu_kernel.py --kernel
$ /root/miniconda3/bin/python /root/work/skill/scripts/verify_task.py --name silu --ntops-root /root/work/ntops --kernel /tmp/silu_kernel.py --pytest --pytest-file tests/test_silu.py --compare-ref /ro
ot/work/ntops/src/ntops/kernels/silu.py
$ /root/miniconda3/bin/python /root/work/skill/scripts/record_run.py --task silu --preflight-pass --pytest-pass --steps 2 --elapsed 90

=== Next steps (Agent/human) ===
1) Edit application() in: /tmp/silu_kernel.py
   Formula hints: skills/ntops-copilot/formulas.md
   Reference: ntops/src/ntops/kernels/silu.py
2) Register: python scripts/register_op.py --name silu --ntops-root /root/work/ntops
3) Verify: python scripts/verify_task.py --name silu --ntops-root /root/work/ntops --pytest
4) Test: cd /root/work/ntops && pytest -q tests/test_silu.py
5) PR branch: 2026-spring-hongwei-2026-T1-1-X
6) PR title: [2026春季][T1-1-X] hongwei-2026

=== Optional: run pytest now ===
cd /root/work/ntops && pytest -q tests/test_silu.py
(base) root@autodl-container-6764489861-420726ac:~/work/skill# python scripts/forge_spec.py "relu unary max zero" --out /tmp/custom_relu.yaml
cat /tmp/custom_relu.yaml
python scripts/forge.py list
Wrote /tmp/custom_relu.yaml [relu/elementwise_unary]
id: forge-relu-custom
op: relu
family: elementwise_unary
pattern: unary
spec: |
  Auto-generated from: relu unary max zero
  formula: "output = max(0.0, input)"
  reference: src/ntops/kernels/relu.py
  pytest: tests/test_relu.py
  contest_id: T1-1-X
  github_id: hongwei-2026
  acceptance:
    preflight_strict: true
    compare_ref: true
    pytest: true
  op:
    family: pattern_spec_file
  add:
    elementwise_binary: binary skills/ntops-forge/specs/add.yaml
  gelu:
    elementwise_unary: unary skills/ntops-forge/specs/gelu.yaml
  silu:
    elementwise_unary: unary skills/ntops-forge/specs/silu.yaml
(base) root@autodl-container-6764489861-420726ac:~/work/skill#

```

图12 自然语言生成 spec

图12 `forge\_spec.py "relu unary max zero"` 生成 YAML spec

九、安全、依赖、授权与引用披露

9.1 安全与依赖

* 无密钥：仓库不含 token / 密码

* 无联网

9.2 HONOR_CODE.md 与 REFERENCE.md

* HONOR_CODE.md：本人独立编写声明，见仓库根目录

* REFERENCE

9.3 诚信

已阅读大赛诚信守则；内核模式参考公开发布示例，非抄袭其他选手作品。

十、Proposal 与附件说明

材料 | 路径

Proposal | d

提交项 | 链接

Github | htt

十一、后续可维护计划

1. 决赛前：扩展 norm/attention spec（只读 reference 模式）

2. 对接隐

选手签名：于鸿伟

日期：2026