

CMPT 280

Topic 5: Trees

Mark G. Eramian

University of Saskatchewan

Based on notes by G. Cheston and J. P. Tremblay

Timing Analysis for Recursive Algorithms

- If we define

$T_p^R(j)$ = the time for the j -th recursive call of method p

- Then the total time used by method p is:

$$T_p = \sum_{j=1}^k T_p^R(j)$$

where k is the number of recursive calls.

- If T_p^R has the same order for all calls, it can be factored out of the sum:

$$T_p = \sum_{j=1}^k T_p^R(j) = T_p^R \cdot \sum_{j=1}^k 1 = T_p^R \cdot k$$

Practice

- Compute the worst-case time complexity of the traversal methods we added to `LinkedSimpleTree280<I>` in Lecture 08.
 - Exercise 1: Print the nodes with a pre-order traversal.
 - Exercise 2: In-order traversal.
 - Exercise 3: Post-order traversal.
 - Exercise 4: Count the number of nodes (with post-order).
 - Exercise 5: Count the height of the tree (with post-order).
 - Exercise 6: Print the nodes in level-order.
- All except one of them are recursive...

Timing Analysis for Recursive Algorithms

Keys to timing analysis of recursive algorithms:

- What is $T_p^R(j)$ for algorithm p ?
- Does it vary with j ?
- How many calls are done?