



Aalto University
School of Science
and Technology

Structured output prediction for multilabel classification

Hongyu Su

Helsinki Institute for Information Technology HIIT
Department of Computer Science, Aalto University

December 3, 2015

An update-to-date version of this slide is available from [my GitHub](#).

<http://github.com/hongyusu>

More about me


Take a look at my homepage and [my technical blog](#).

<http://www.hongyusu.com>

<http://www.hongyusu.com/pages.html>

About me

- ▶ Postdoc in Helsinki Institute for Information Technology and Aalto University since 2015.5.
- ▶ Research: build advance machine learning models to solve large scale data analysis problem (research project).
- ▶ Equivalent to: continuously learning, thinking, implementing, reporting.



Educations



- ▶ Bachelor in Computer Science and Engineering, Xidian University, 2007
- ▶ Master in Bioinformatics, University of Helsinki, 2010
- ▶ Phd in Information and Computer Science, Aalto University, 2015

'Everything comes with a price. Some things just cost more than others.'
-Brom, *The Child thief*

Awards

- ▶ Chinese government awards for outstanding Phd candidate



A big fan of modern information technologies

- ▶ <http://sentimentx.herokuapp.com>
- ▶ <http://tripassistant.herokuapp.com>
- ▶ Know new technologies very well, e.g., deep learning, big data, Kafka, Spark, IoT.
- ▶ Maintain a technical blog at www.hongyusu.com on technology innovations.
- ▶ Double blade: new are not always good, e.g., I like old-fashion mechanical keyboard.



A big fan of sports

- ▶ I enjoy competitions and aggressive sport for example basketball.



- ▶ Now I try to discover unknown part of myself
 - ▶ Downhill snowboarding.
 - ▶ Bouldering (license)
 - ▶ Paragliding
 - ▶ Open water diving (license)
- ▶ A lot of gyms.

A cat person

- ▶ Pabulo




- ▶ Miu



- ▶ Cats are independent and make my life not very technical.

A hiker

I like to discover new places.



A photographer with a Flickr account

I like to memorize great moments.



A bottle collector

I like to taste new things.



Multilabel classification

- ▶ An important research field in machine learning.
- ▶ **Input:** $x \in \mathcal{X}$ lives in some input space \mathcal{X} .
- ▶ **Output:** $y = (y_1, \dots, y_j, \dots, y_l) \in \mathcal{Y}$ is a vector of ℓ variables.
- ▶ y : *multilabel*, y_j : *microlabel*.
- ▶ Output space \mathcal{Y} is composed by a tensor product of ℓ sets

$$\mathcal{Y} = \mathcal{Y}_1 \times \cdots \times \mathcal{Y}_\ell, \mathcal{Y}_i = \{+1, -1\}.$$

- ▶ For example, in document classification, a document x_0 could be tagged with “news” “movie” “art” but not “sports” “politics” “finance”.

$$y_0 = (+1, +1, -1, -1, -1, +1, -1).$$

news movie sports politics finance science art

- ▶ **Goal:** find a mapping function $f \in \mathcal{H}$ that predicts the best values of an output y given an input x , $f : \mathcal{X} \rightarrow \mathcal{Y}$.

Concerns

- ▶ Exponential Search space!

$$\mathcal{Y} = \mathcal{Y}_1 \times \cdots \times \mathcal{Y}_\ell, \mathcal{Y}_i = \{+1, -1\} \quad |\mathcal{Y}| = 2^\ell.$$

- ▶ Dependency of microlabels!

- ▶ If a document is tagged with “movie”, then it is more likely to be in the category of “art” than “science”.

$$\mathbf{y} = (\underbrace{?}_{\text{news}}, \underbrace{?}_{\text{movie}}, \underbrace{?}_{\text{sports}}, \underbrace{?}_{\text{politics}}, \underbrace{?}_{\text{finance}}, \underbrace{?}_{\text{science}}, \underbrace{?}_{\text{art}}).$$

Motivated by applications

- ▶ Document classification, an article can be assigned to multiple categories.

$x_0 =$



$$y = (+1, +1, -1, -1, -1, -1, -1)$$

news economics sports politics movie science art

Motivated by applications (cont.)

- ▶ Image annotation, an image can associate with multiple tags.

$\mathbf{x}_0 =$



$$\mathbf{y} = (+1, +1, -1, -1, -1, +1, +1)$$

boat sea sun beach people ice land

Motivated by applications (cont.)

- ▶ Drug discovery, a drug can be effective for multiple symptoms.

$x_0 =$




$$\mathbf{y} = (+1, +1, +1, +1, -1, -1, +1)$$

heart stroke blood fever digest liver swelling

Motivated by applications (cont.)

- ▶ Protein function, a protein have multiple function in biological system.

$\mathbf{x}_0 =$




$$\mathbf{y} = (\underbrace{+1}_{\alpha\text{-channel}} , \underbrace{+1}_{\beta\text{-barrel}} , \underbrace{+1}_{\text{holins}} , \underbrace{-1}_{\text{vesicle fusion pores}} , \underbrace{-1}_{\text{Phosphotransfer-driven Group}})$$

Motivated by applications (cont.)

- Social network, information can spread through multiple users.

$x_0 =$



$$y = (+1, \underbrace{-1}_{\text{Alice}}, \underbrace{+1}_{\text{David}}, \underbrace{-1}_{\text{Mark}}, \underbrace{+1}_{\text{Alex}}, \underbrace{-1}_{\text{Zoe}}, \underbrace{-1}_{\text{Frank}})$$


Flat classification approach

- ▶ The scheme is proposed in [Tsoumakas et al., 2010]
- ▶ The output variable y is assumed to be a flat vector.
- ▶ Problem transformation
 - ▶ Model the problem as a collection of single-label classification problems and solve each problem independently.
 - ▶ E.g., ML-KNN [Zhang and Zhou, 2007], CC [Read et al., 2011], IBLR [Cheng and Hüllermeier, 2009].
- ▶ Algorithm adaptation
 - ▶ Adapt single-label classification models to multilabel classification problems.
 - ▶ E.g., CORRLOG [Bian et al., 2012], MTL [Argyriou et al., 2008], ADABOOST.MH [Schapire and Singer, 1999, Esuli et al., 2008].
- ▶ These approaches do not model the dependency structure of microlabels.

Output correlation structure

- ▶ Protein function, a protein have multiple function in biological system.

$x_0 =$



$G =$


- 1: Channels/Pores
- 2: Electrochemical Potential-driven Transporters
 - 2.A: Porters (uniporters, symporters, antiporters)
 - 2.B: Nonribosomally synthesized porters
 - 2.C: Ion-gradient-driven energizers
 - 2.D: Transcompartment Lipid Carrier
 - 2.D.1: The PIP/PS Counter Transporter (P/P-CT) Family
- 3: Primary Active Transporters
- 4: Group Translocators
- 5: Transmembrane Electron Carriers
- 6: Accessory Factors Involved in Transport
- 9: Incompletely Characterized Transport Systems

$$y = (\underbrace{+1}_{\alpha\text{-channel}} , \underbrace{+1}_{\beta\text{-barrel}} , \underbrace{+1}_{\text{holins}} , \underbrace{-1}_{\text{vesicle fusion pores}} , \underbrace{-1}_{\text{Phosphotransfer-driven Group}})$$


Output correlation structure (cont.)

- Social network, information can spread through multiple users.

$x_0 =$



$G =$



$$y = (+1, -1, +1, -1, +1, -1, -1)$$

Ted Alice David Mark Alex Zoe Frank

Structured output prediction approach

- ▶ The scheme is proposed in [Su, 2015].
- ▶ Models the dependency by an *output graph* defined on microlabels.
- ▶ Hierarchical classification
 - ▶ The output graph is a rooted tree defining different levels of granularities.
 - ▶ E.g., SSVM
[Tsochantaridis et al., 2004, Tsochantaridis et al., 2005].
- ▶ Graph labeling
 - ▶ The output graph has a more general form (e.g., a tree, a chain).
 - ▶ E.g., CRF [Lafferty et al., 2001, Taskar et al., 2002], M³N
[Taskar et al., 2004], MMCRF [Rousu et al., 2007, Su et al., 2010],
SPIN [Su et al., 2014].
- ▶ These approaches assume the output graph is known *a priori*.
- ▶ More general, there is no pre-defined output graph!

My contributions

- ▶ SOP models developed for observed output graph.
 - ▶ Extend MMCRF to general output graph structures [Su et al., 2010].
 - ▶ SPIN on DAG for network influence prediction [Su et al., 2014].
 - ▶ SOP model for transporter protein classification [Su et al., 2015].
- ▶ SOP models developed for unknown output graph.
 - ▶ MVE to combine multiple structured output predictors by ensemble [Su and Rousu, 2011].
 - ▶ AMM and MAM to aggregate the inference results from multiple structured output predictors [Su and Rousu, 2013, Su and Rousu, 2015].
 - ▶ RTA to perform joint learning and inference over a collection of random spanning tree predictors [Marchand et al., 2014].
 - ▶ Joint learning and inference with sparse structure selection [Cousins et al., 2015a, Cousins et al., 2015b].
- ▶ Dissertation **Multilabel classification through structured output learning** [Su, 2015].
- ▶ Codes are available from <http://github.com/hongyusu>.

The rest of the talk

- ▶ Preliminaries
- ▶ Structured output prediction
 - ▶ Undirected graph
 - ▶ DAG
 - ▶ Special pattern
 - ▶ Unknown output graph
- ▶ Experimental evaluations
- ▶ Conclusions and future work

Preliminaries

- ▶ Training examples come in pairs $(\mathbf{x}, \mathbf{y}) \in \mathcal{X} \times \mathcal{Y}$.
- ▶ \mathcal{X} is an arbitrary input space.
- ▶ \mathcal{Y} is an output space of a collection of ℓ -dimensional *multilabels*.

$$\mathbf{y} = (y_1, \dots, y_\ell) \in \mathcal{Y}.$$

- ▶ y_i is a *microlabel* and $y_i \in \{1, \dots, r_i\}$, $r_i \in \mathbb{Z}$.
- ▶ For example, multilabel binary classification $y_i \in \{-1, +1\}$.
- ▶ We are given a set of m training examples $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i=1}^m$.
- ▶ Each example (\mathbf{x}, \mathbf{y}) is mapped into a joint feature space $\phi(\mathbf{x}, \mathbf{y})$.
- ▶ \mathbf{w} is the weight vector operates in the joint feature space.
- ▶ Define a linear score function $F(\mathbf{w}, \mathbf{x}, \mathbf{y}) = \langle \mathbf{w}, \phi(\mathbf{x}, \mathbf{y}) \rangle$.
- ▶ \mathbf{w} ensures that example \mathbf{x}_i with correct multilabel \mathbf{y}_i achieves higher score than with any other incorrect multilabel $\mathbf{y}' \in \mathcal{Y}$.

Prediction


- ▶ The prediction $y_w(x)$ of an input x is the multilabel y that maximizes the score function

$$y_w(x) = \operatorname{argmax}_{y \in \mathcal{Y}} \langle w, \phi(x, y) \rangle. \quad (1)$$

- ▶ Search space is exponential in size, $|\mathcal{Y}| = 2^\ell$.
- ▶ (1) is called *inference* problem which is \mathcal{NP} -hard for most output feature maps.
- ▶ Often, we want a feature map in which the inference can be solved with a polynomial algorithm, e.g., dynamic programming.

Input/output feature maps

- ▶ We assume that the joint feature map ϕ is a potential function on a Markov network (undirected graph) $G = (E, V)$.
- ▶ A vertex $v_i \in V$ corresponds to a microlabel y_i , an edge $(v_i, v_j) \in E$ corresponds to the pairwise correlation of the microlabel y_i and y_j .
- ▶ G models potential pairwise correlations and is given *a priori*.




- ▶ $\varphi(\mathbf{x}) \in \mathbb{R}^d$ is the input feature map, e.g., bag-of-words of a document.
- ▶ $\psi(\mathbf{y}) \in \mathbb{R}^{4|E|}$ is the output feature map which maps the multilabel \mathbf{y} into a collection of edges and labels

$$\varphi(\mathbf{y}) = (u_e)_{e \in E}, u_e \in \{-1, +1\}^2.$$

An example of $\psi(\mathbf{y})$

- ▶ Markov network (undirected graph) $G = (E, V)$



- ▶ Multilabel \mathbf{y}

$$\mathbf{y} = (y_1, y_2, y_3, y_4) = (+1, -1, +1, +1)$$

- ▶ Output feature map $\psi(\mathbf{y})$


$$\psi(\mathbf{y}) = (\underbrace{0, 0, 0}_{\text{---}}, \underbrace{0, 1, 0}_{\text{--+}}, \underbrace{0, 0, 1}_{\text{+-}}, \underbrace{1, ++, 0}_{\text{++}}, \underbrace{0, 0, 0}_{\text{---}}, \underbrace{0, 1, 0}_{\text{--+}}, \underbrace{0, 0, 1}_{\text{+-}}, \underbrace{0, ++, 0}_{\text{++}}, \underbrace{0, 0, 0}_{\text{---}}, \underbrace{0, 0, 0}_{\text{--+}}, \underbrace{0, 0, 1}_{\text{+-}}, \underbrace{1, ++, 0}_{\text{++}})$$

(v_1, v_3) (v_1, v_2) (v_3, v_4)

Joint feature map $\phi(\mathbf{x}, \mathbf{y})$

- ▶ The joint feature is the Kronecker product of $\varphi(\mathbf{x})$ and $\psi(\mathbf{y})$

$$\phi(\mathbf{x}, \mathbf{y}) = (\phi_e(\mathbf{x}, \mathbf{y}))_{e \in E} = (\varphi(\mathbf{x}) \otimes \psi_e(\mathbf{y}_e))_{e \in E}.$$




- ▶ The score function can be factorized by the output graph G

$$F(\mathbf{w}, \mathbf{x}, \mathbf{y}) = \langle \mathbf{w}, \phi(\mathbf{x}, \mathbf{y}) \rangle = \sum_{e \in E} \langle \mathbf{w}_e, \phi_e(\mathbf{x}, \mathbf{y}_e) \rangle.$$

Optimization problem

- Max-margin learning for \mathbf{w}

$$\gamma(\mathbf{w}, \mathbf{x}_i) = F(\mathbf{w}, \mathbf{x}_i, \mathbf{y}_i) - \max_{\mathbf{y} \in \mathcal{Y}/\mathbf{y}_i} F(\mathbf{w}, \mathbf{x}_i, \mathbf{y})$$



- The model is max-margin conditional random field MMCRF [Rousu et al., 2007, Su et al., 2010].
- The primal optimization problem is defined as

$$\min_{\mathbf{w}, \xi_k} \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_{k=1}^m \xi_k \quad (2)$$

$$\text{s.t. } \langle \mathbf{w}, \phi(\mathbf{x}_k, \mathbf{y}_k) \rangle - \langle \mathbf{w}, \phi(\mathbf{x}_k, \mathbf{y}) \rangle \geq \ell(\mathbf{y}_k, \mathbf{y}) - \xi_k, \\ \xi_k \geq 0, \forall \mathbf{y} \in \mathcal{Y}, k \in \{1, \dots, m\}.$$

- $\ell(\mathbf{y}, \mathbf{y}_k)$ scales the margin according to the multilabel \mathbf{y} .

Marginal-dual optimization

- ▶ (2) is difficult as the number of the constraints is $m \times |\mathcal{Y}|$.
- ▶ The dual optimization problem is defined as

$$\begin{aligned} \max_{\alpha \geq 0} \quad & \alpha^\top \ell - \frac{1}{2} \alpha^\top K \alpha \\ \text{s.t.} \quad & \sum_{y \in \mathcal{Y}} \alpha(k, y) \leq C, \forall k \in \{1, \dots, m\}. \end{aligned} \tag{3}$$

- ▶ (3) is also challenging due to the exponential number of dual variables.
- ▶ We use edge marginals to replace the dual variables [Taskar et al., 2004]

$$\mu(k, e, u_e) = \sum_y \mathbf{1}_{\{\psi_e(y)=u_e\}} \alpha(k, y).$$

- ▶ The margin-dual optimization problem is

$$\max_{\mu \in \mathcal{M}} \mu^\top \ell - \frac{1}{2} \mu^\top K \mu. \tag{4}$$

- ▶ The number of marginal-dual variables is $m \times 4|E|$.

Conditional gradient descent

- ▶ (4) is optimized by conditional gradient decent.
- ▶ In each iteration it optimizes μ_k that corresponds to a single example while keeps others ($\mu_j, j \neq k$) fixed

$$\max_{\mu_k \in \mathcal{M}} \quad \mu_k^\top \ell_k - \frac{1}{2} \sum_j \mu_k^\top K \mu_j, \quad \forall k.$$

- ▶ Current gradient of μ_k is given by $g_i = \ell_i - \sum_j K \mu_j$.
- ▶ Compute the maximal feasible solution μ_k^* as an update direction


$$\mu_k^* = \operatorname{argmax}_{\mu_k \in \mathcal{M}} \mu_k^\top g_k = \operatorname{argmax}_{\mu_k \in \mathcal{M}} \sum_e \mu(k, e)^\top g(k, e). \quad (5)$$

- ▶ What is actually going on here?
- ▶ (5) is an instantiation of MAP problem

Output graph	Inference problem	Inference algorithm
Tree	Polynomial	DP [Rousu et al., 2007]
Graph	\mathcal{NP} -hard	LBP [Su et al., 2010]

- ▶ Perform the update via exact line search $\mu_k \leftarrow \mu_k + \tau(\mu_k^* - \mu_k)$.

What is happening?



Exact line search

- ▶ Line search gives the optimal feasible solution as a stationary point (τ)

$$\begin{aligned} \max_{\tau} \quad & g(\mu_k + \tau \Delta \mu_k) \\ \text{s.t.} \quad & 0 \leq \tau \leq 1. \end{aligned} \tag{6}$$

- ▶ $\tau = 0$ corresponds to no update.
- ▶ Feasible maximum update is achieved at $\tau = 1$.
- ▶ The cost of computing (6) is significantly smaller than the cost of computing (5).

Duality gap

- We use duality gap to measure the progress of the optimization.
- Primal and marginal-dual objective functions

$$f(\mathbf{w}) = \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_{k=1}^m (\ell_k - \langle \mathbf{w}, \Delta\phi(\mathbf{x}_k, \mathbf{y}_k) \rangle)$$

$$g(\mu) = \sum_{k=1}^m \mu_k \ell_k - \frac{1}{2} \sum_{k=1}^m \sum_{j=1}^m \mu_k K^{\Delta\phi}(\mathbf{x}_k, \mathbf{y}_k; \mathbf{x}_j, \mathbf{y}_j) \mu_j$$

- $\max_{\mu} g(\mu) \leq \min_{\mathbf{w}} f(\mathbf{w})$, gap is minimized at optimal.
- Duality gap at μ^t

$$\begin{aligned} f(\mathbf{w}^t) - g(\mu^t) &= C \left(\ell - K^{\Delta\phi} \mu^t \right) - \mu^t \left(\ell - K^{\Delta\phi} \mu^t \right) \\ &= C^\top \nabla g(\mu^t) - \mu^{t\top} \nabla g(\mu^t) \end{aligned}$$

1. Estimate the marginal-dual objective by linear approximation $\nabla g(\mu^t)$.
2. Marginal-dual objective value at μ^t is computed by $\mu^{t\top} \nabla g(\mu^t)$.
3. Primal objective value is estimate by $C^\top \nabla g(\mu^t)$.

Short summary

- ▶ We have seen so far.


Output graph	Inference problem	Inference algorithm
Tree	Polynomial	DP [Rousu et al., 2007]
Graph	\mathcal{NP} -hard	LBP [Su et al., 2010]

- ▶ What if the solution y corresponds to some special structure?

Pattern and Exponential reduction

Transporter protein classification [Su et al., 2015]

- ▶ 12456 protein, $x_i, \forall i \in \{1, \dots, 12456\}$.
- ▶ 3145 transporter function classes, $\mathbf{y} = (y_1, \dots, y_{3145})$.
- ▶ A hierarchical structured G defined on 3145 classes.




- ▶ **Task:** predict y_0 given x_0 .
- ▶ It seems: $|\mathcal{Y}| = 2^{3145}$, DP on G .
- ▶ **Pattern:**
 - ▶ a valid annotation is a path from root to leave.
 - ▶ exponential reduction of search space $|\mathcal{Y}| = 2^{3145} \rightarrow |\mathcal{Y}| \approx 2000$.

Pattern and Exponential reduction

Transporter protein classification [Su et al., 2015]

- ▶ 12456 protein, $x_i, \forall i \in \{1, \dots, 12456\}$.
- ▶ 3145 transporter function classes, $\mathbf{y} = (y_1, \dots, y_{3145})$.
- ▶ A hierarchical structured G defined on 3145 classes.




- ▶ **Task:** predict y_0 given x_0 .
- ▶ It seems: $|\mathcal{Y}| = 2^{3145}$, DP on G .
- ▶ **Pattern:**
 - ▶ a valid annotation is a path from root to leave.
 - ▶ exponential reduction of search space $|\mathcal{Y}| = 2^{3145} \rightarrow |\mathcal{Y}| \approx 2000$.

Pattern and Exponential reduction

Transporter protein classification [Su et al., 2015]

- ▶ 12456 protein, $x_i, \forall i \in \{1, \dots, 12456\}$.
- ▶ 3145 transporter function classes, $\mathbf{y} = (y_1, \dots, y_{3145})$.
- ▶ A hierarchical structured G defined on 3145 classes.




- ▶ **Task:** predict y_0 given x_0 .
- ▶ It seems: $|\mathcal{Y}| = 2^{3145}$, DP on G .
- ▶ **Pattern:**
 - ▶ a valid annotation is a path from root to leave.
 - ▶ exponential reduction of search space $|\mathcal{Y}| = 2^{3145} \rightarrow |\mathcal{Y}| \approx 2000$.

Pattern and Exponential reduction

Transporter protein classification [Su et al., 2015]

- ▶ 12456 protein, $x_i, \forall i \in \{1, \dots, 12456\}$.
- ▶ 3145 transporter function classes, $\mathbf{y} = (y_1, \dots, y_{3145})$.
- ▶ A hierarchical structured G defined on 3145 classes.




- ▶ **Task:** predict y_0 given x_0 .
- ▶ It seems: $|\mathcal{Y}| = 2^{3145}$, DP on G .
- ▶ **Pattern:**
 - ▶ a valid annotation is a path from root to leave.
 - ▶ exponential reduction of search space $|\mathcal{Y}| = 2^{3145} \rightarrow |\mathcal{Y}| \approx 2000$.

Pattern and Exponential reduction

Transporter protein classification [Su et al., 2015]

- ▶ 12456 protein, $x_i, \forall i \in \{1, \dots, 12456\}$.
- ▶ 3145 transporter function classes, $\mathbf{y} = (y_1, \dots, y_{3145})$.
- ▶ A hierarchical structured G defined on 3145 classes.




- ▶ **Task:** predict y_0 given x_0 .
- ▶ It seems: $|\mathcal{Y}| = 2^{3145}$, DP on G .
- ▶ **Pattern:**
 - ▶ a valid annotation is a path from root to leave.
 - ▶ exponential reduction of search space $|\mathcal{Y}| = 2^{3145} \rightarrow |\mathcal{Y}| \approx 2000$.

Pattern and Exponential reduction

Transporter protein classification [Su et al., 2015]

- ▶ 12456 protein, $x_i, \forall i \in \{1, \dots, 12456\}$.
- ▶ 3145 transporter function classes, $\mathbf{y} = (y_1, \dots, y_{3145})$.
- ▶ A hierarchical structured G defined on 3145 classes.




- ▶ **Task:** predict y_0 given x_0 .
- ▶ It seems: $|\mathcal{Y}| = 2^{3145}$, DP on G .
- ▶ **Pattern:**
 - ▶ a valid annotation is a path from root to leave.
 - ▶ exponential reduction of search space $|\mathcal{Y}| = 2^{3145} \rightarrow |\mathcal{Y}| \approx 2000$.

Pattern and Exponential reduction

Transporter protein classification [Su et al., 2015]

- ▶ 12456 protein, $x_i, \forall i \in \{1, \dots, 12456\}$.
- ▶ 3145 transporter function classes, $\mathbf{y} = (y_1, \dots, y_{3145})$.
- ▶ A hierarchical structured G defined on 3145 classes.



- ▶ **Task:** predict y_0 given x_0 .
- ▶ It seems: $|\mathcal{Y}| = 2^{3145}$, DP on G .
- ▶ **Pattern:**
 - ▶ a valid annotation is a path from root to leave.
 - ▶ exponential reduction of search space $|\mathcal{Y}| = 2^{3145} \rightarrow |\mathcal{Y}| \approx 2000$.

Actual model

- The primal optimization problem is defined as

$$\begin{aligned} \min_{\mathbf{w}, \xi_k} \quad & \frac{1}{2} \|\mathbf{w}\|^2 + C \sum_{k=1}^m \xi_k \\ \text{s.t.} \quad & \langle \mathbf{w}, \phi(\mathbf{x}_k, \mathbf{y}_k) \rangle - \langle \mathbf{w}, \phi(\mathbf{x}_k, \mathbf{y}) \rangle \geq \ell(\mathbf{y}_k, \mathbf{y}) - \xi_k, \\ & \xi_k \geq 0, \forall \mathbf{y} \in \mathcal{Y}, k \in \{1, \dots, m\}. \end{aligned}$$

- In stead of CGD, we do gradient descent for all examples in each iteration.
- Multi-view data: 30 set of features, $\{\phi(\mathbf{x}_i)_k\}_{k=1}^{30}$.
- Multiple kernel learning (MKL): ALIGN, ALIGNF.
- Experiments:

	0/1 (full annotation)					
	Linear			Gaussian		
	SVM	MMR	SOP	SVM	MMR	SOP
UNIF	53.3	12.0	66.8	23.2	68.1	69.7
ALIGN	54.8	12.4	63.3	16.0	71.9	74.2
ALIGNF	60.5	17.5	64.3	32.9	68.4	71.2

Table : Prediction performance with kernels from MKL.

Short summary

- ▶ We have seen so far.


Output graph	Inference problem	Inference algorithm
Tree Graph	Polynomial \mathcal{NP} -hard	DP [Rousu et al., 2007] LBP [Su et al., 2010]
→Pattern	Linear?	Reduction [Su et al., 2015]

- ▶ What if the output graph is DAG ?

Output graph is DAG

Predicting network response [Su et al., 2014]


A Twitter (follower-ship) network consists of five users.



Output graph is DAG

Predicting network response [Su et al., 2014]


Alice tweets after World Cup final.



Output graph is DAG

Predicting network response [Su et al., 2014]


Bob saw the tweet and retweets from Alice.



Output graph is DAG

Predicting network response [Su et al., 2014]


Jacob retweets from Bob.



Output graph is DAG

Predicting network response [Su et al., 2014]


Ben retweets from Jacob.



Output graph is DAG


Predicting network response [Su et al., 2014]

David is not a fan.



Network response problem

- ▶ Definition:
 - ▶ Given: a network $G = (E, V)$, and an action x performed on G .
 - ▶ Task: predict the subnetwork that responses to the action.
 - ▶ Which nodes $v \in V$ perform the action?
 $V_x = \{Alice, Bob, Jacob, Ben\}$
 - ▶ Which directed edges $e \in E_x$ relay the action from one node to its neighbors? $E_x = \{a, c, d\}$




- ▶ Applications: Information propagation, idea formation, disease spreads, adoption of new technologies.

Direct output graph

- ▶ Model is defined on directed network.
 - ▶ Any undirected network can be seen as special case by replacing undirected edges with two directed ones.




- ▶ Notation of edge labels:



- ▶ *Input feature*: Encode x as $\varphi(x)$ (e.g. bag-of-word of a tweet).
- ▶ *Output feature*: Encode G_y as $\psi(y)$ (e.g. a set of edges and their labels)

$$\psi(y) = \left(\underbrace{1, 0, 0}_{++}, \underbrace{1, 0, 0}_{++}, \underbrace{0, 1, 0}_{+-}, \dots \right)$$

The equation shows the encoding of the output feature G_y as a vector. The vector is represented as a sequence of triplets: $(1, 0, 0), (1, 0, 0), (0, 1, 0), \dots$. These triplets are grouped under labels a , b , and c at the bottom, corresponding to the labels 'pp', 'pn', and 'nn' respectively from the previous diagram.



Structure output prediction model

- ▶ Compatibility score for (\mathbf{x}, \mathbf{y}) : $F(\mathbf{x}, \mathbf{y}, \mathbf{w}) = \langle \mathbf{w}, \phi(\mathbf{x}, \mathbf{y}) \rangle$
 - ▶ \mathbf{w} is the feature weight to be learned.
 - ▶ $\phi(\mathbf{x}, \mathbf{y}) = \varphi(\mathbf{x}) \otimes \psi(\mathbf{y})$ is joint feature map.
 - ▶ Intuition: given an action \mathbf{x} , the score of correct response graph (\mathbf{x}, \mathbf{y}) should be higher than any incorrect response graph $(\mathbf{x}, \mathbf{y}')$

$$F(\mathbf{x}, \mathbf{y}, \mathbf{w}) > F(\mathbf{x}, \mathbf{y}', \mathbf{w}), \quad \forall \mathbf{y}' \in \mathcal{H}(G).$$

- ▶ \mathbf{w} is learned by solving structured output learning problem

$$\begin{aligned} \min_{\mathbf{w}, \xi} \quad & \frac{1}{2} \|\mathbf{w}\|_2^2 + C \sum_{i=1}^m \xi_i \\ \text{s.t.} \quad & F(\mathbf{x}_i, \mathbf{y}_i; \mathbf{w}) > \max_{G'_{\mathbf{x}_i} \in \mathcal{H}(G)} (F(\mathbf{x}_i, \mathbf{y}'_i,) \\ & + \ell_G(\mathbf{y}_i, \mathbf{y}'_i)) - \xi_i, \xi_i \geq 0, \forall i \in \{1, \dots, m\}, \end{aligned}$$

Inference problem

- ▶ To solve the optimization, we have to solve similar inference problem appeared both in training and in prediction.
- ▶ In prediction phase:
 - ▶ Given the feature weight \mathbf{w} and the complex network G .
 - ▶ To find out a DAG $H^* = (V_H, E_H)$ that gives the maximal compatibility score for a given action \mathbf{x}

$$H^*(\mathbf{x}) = \underset{H \in \mathcal{H}(G)}{\operatorname{argmax}} \sum_{e \in E_H} s_{y_e}(e, \mathbf{x}, \mathbf{w}). \quad (7)$$


Lemma

Finding the graph that maximizes Eq. (7) is an NP-hard problem.


Proof.

Reduction from MAX-CUT problem. □

What is happening?



What is happening?



Approximate inference via SDP relaxation

- ▶ We formulate the inference problem as *integer quadratic program* (IQP).
 - ▶ Introduce for each node $u \in V$ a binary variable $x_u \in \{-1, +1\}$.
 - ▶ Introduce a special variable $x_0 \in \{-1, +1\}$ to distinguish activated node.

$$\begin{aligned} \max \quad & \frac{1}{4} \sum_{(u,v) \in E} [s_{pn}(u,v)(1 + x_0x_u - x_0x_v - x_ux_v) \\ & + s_{nn}(u,v)(1 - x_0x_u - x_0x_v + x_ux_v) \\ & + s_{pp}(u,v)(1 + x_0x_u + x_0x_v + x_ux_v)] \\ \text{s.t.} \quad & x_0, x_u, x_v \in \{-1, +1\}, \text{ for all } u, v \in V, \end{aligned}$$

- ▶ IQP is relaxed into *quadratic program* (QP) and solved by *semidefinite programming relaxation* (SDP).
- ▶ Optimization guarantee $E[Z] \geq (\alpha - \epsilon)Z_R$ with $\alpha > 0.796$, Z is objective achieved by SDP, Z_R is objective of IQP.

SPIN for context-sensitive prediction

- ▶ We assume action $\varphi(x)$ is known (e.g. bag-of-word of a tweet).
- ▶ Task is to predict the response network given the action.
- ▶ *Predicted Subgraph Coverage* (PSC) is the relative size of correctly predicted subgraph in terms of node labels.
- ▶ The result is shown in the following table.

Dataset	Node Accuracy			Node F_1 Score			Edge Acc		PSC		
	SVM	MMCRF	SPIN	SVM	MMCRF	SPIN	SVM	SPIN	SVM	MMCRF	SPIN
memeS	73.4	68.0	72.2	39.0	39.8	47.1	62.7	45.6	23.4	25.3	33.6
memeM	82.1	79.0	81.5	29.1	30.1	38.0	61.1	68.8	18.6	18.8	28.3
memeL	89.9	88.3	89.8	26.7	27.1	35.0	45.5	80.0	17.7	18.9	27.6
M700	91.9	94.1	92.1	13.8	7.3	14.2	26.3	93.0	29.4	23.9	34.4
M1k	94.1	95.8	94.2	10.9	3.5	9.3	26.6	94.7	33.7	16.6	35.2
M2k	96.8	97.6	96.7	6.2	1.4	3.4	25.3	97.6	34.6	9.6	14.7
L700	89.7	92.4	89.7	16.2	9.4	17.3	26.5	90.4	9.5	6.7	12.5
L1k	92.4	94.4	91.5	12.4	6.4	13.9	26.4	92.3	6.1	4.4	8.4
L2k	92.5	94.5	91.9	12.3	5.4	12.7	26.5	93.2	6.0	2.9	7.2
Geom.	85.5	86.4	86.6	19.8	12.6	20.3	32.6	79.7	18.9	14.2	21.7

SPIN for context-free prediction

- ▶ We assume action is unknown during prediction phase.
- ▶ Task is to predict directed edges (network skeleton) from a cascade of actions.
- ▶ The measure of success is *Precision@K*, where we ask for top-*K* percent edge predictions and compute the precision.
- ▶ The result is shown in the following table.

Dataset	Model	T (10^3 s)	Precision @ K					
			10%	20%	30%	40%	50%	60%
memeS	SPIN	5.50	82.9	81.0	76.0	74.0	74.0	70.0
	ICM-EM	0.01	60.3	63.5	65.1	62.0	62.0	61.5
	NETRATE	5.83	76.2	73.8	70.4	68.7	68.7	66.8
memeM	SPIN	5.52	82.7	72.1	70.5	69.2	69.2	67.9
	ICM-EM	0.02	56.3	55.3	56.8	57.4	57.4	56.3
	NETRATE	13.93	61.2	64.6	62.9	62.5	62.5	62.4
memeL	SPIN	4.75	82.2	73.6	69.1	66.7	66.7	65.9
	ICM-EM	0.01	52.1	55.7	54.2	56.5	56.5	56.7
	NETRATE	12.63	56.5	57.8	60.0	59.3	59.3	59.4

Short summary

- ▶ We have seen so far.

Output graph	Inference problem	Inference algorithm
Tree	Polynomial	DP [Rousu et al., 2007]
Graph	\mathcal{NP} -hard	LBP [Su et al., 2010]
Pattern	Linear?	Reduction [Su et al., 2015]
→ DAG	\mathcal{NP} -hard	SDP [Su et al., 2014]

- ▶ What if the output graph is not observed?

Research question

- ▶ The output graph G is hidden in many applications.
 - ▶ E.g., possible tags for a surveillance photo: “building”, “road”, “pedestrian”, and “vehicle”.
- ▶ Structured output learning when the output graph is not observed.
- ▶ In particular:
 - ▶ Dependency via a complete set of pairwise correlations.
 - ▶ Structured output learning with a complete graph.
 - ▶ Solve the \mathcal{NP} -hard inference problem via a polynomial time approximation algorithm.
- ▶ In general, a structured prediction model which performs max-margin learning on a random collection of spanning trees sampled from the output graph.

Complete graph as output graph

- ▶ We assume that the joint feature map ϕ is a potential function on a Markov network (undirected graph) $G = (E, V)$.
- ▶ G : complete graph with $|V| = \ell$ nodes and $|E| = \frac{\ell(\ell-1)}{2}$ undirected edges.
- ▶ G models all pairwise correlations.
- ▶ $\varphi(\mathbf{x})$ is the input feature map, e.g., bag-of-words feature of an example \mathbf{x} .
- ▶ $\psi(\mathbf{y})$ is the output feature map which is a collection of edges and labels

$$\varphi(\mathbf{y}) = (u_e)_{e \in E}, u_e \in \{-1, +1\}^2.$$

- ▶ The joint feature is the Kronecker product of $\varphi(\mathbf{x})$ and $\psi(\mathbf{y})$

$$\phi(\mathbf{x}, \mathbf{y}) = (\phi_e(\mathbf{x}, \mathbf{y}))_{e \in E} = (\varphi(\mathbf{x}) \otimes \psi_e(\mathbf{y}_e))_{e \in E}.$$

- ▶ The score function can be factorized by the complete graph G

$$F(\mathbf{w}, \mathbf{x}, \mathbf{y}) = \langle \mathbf{w}, \phi(\mathbf{x}, \mathbf{y}) \rangle = \sum_{e \in E} \langle \mathbf{w}_e, \phi_e(\mathbf{x}, \mathbf{y}_e) \rangle.$$

Inference in terms of all spanning trees

- ▶ Solving the following inference problem on a complete graph is \mathcal{NP} -hard

$$\mathbf{y}_w(\mathbf{x}) = \operatorname{argmax}_{\mathbf{y} \in \mathcal{Y}} F(\mathbf{w}, \mathbf{x}, \mathbf{y}) = \operatorname{argmax}_{\mathbf{y} \in \mathcal{Y}} \sum_{e \in E} \langle \mathbf{w}_e, \phi_e(\mathbf{x}, \mathbf{y}_e) \rangle.$$

$$\phi_G(\mathbf{x}, \mathbf{y}) = \{\phi_{G,e}(\mathbf{x}, \mathbf{y}_e)\}_{e \in G}, \mathbf{w}_G = \{\mathbf{w}_{G,e}\}_{e \in G}, \|\phi_G(\mathbf{x}, \mathbf{y})\| = \|\mathbf{w}_G\| = 1$$

- ▶ For a complete graph, there are $\ell^{\ell-2}$ unique spanning trees.
- ▶ $\phi_T(\mathbf{x}, \mathbf{y}) = \{\phi_e(\mathbf{x}, \mathbf{y})\}_{e \in T}$ is the projection of $\phi_G(\mathbf{x}, \mathbf{y})$ on $T \in S(G)$.
- ▶ $\mathbf{w}_T = \{\mathbf{w}_{G,e}\}_{e \in T}$ is the projection of \mathbf{w}_G on $T \in S(G)$.
- ▶ We can write $F(\mathbf{w}, \mathbf{x}, \mathbf{y})$ as a conic combination of all spanning trees

$$F(\mathbf{w}, \mathbf{x}, \mathbf{y}) = \mathbf{E}_{T \in U(G)} a_T \langle \mathbf{w}_T, \phi_T(\mathbf{x}, \mathbf{y}) \rangle$$
$$\mathbf{E}_{T \in U(G)} a_T^2 = 1, \quad \mathbf{E}_{T \in U(G)} a_T < 1.$$

- ▶ $U(G)$ is the uniform distribution over $\ell^{\ell-2}$ spanning trees.
- ▶ The number of spanning trees is exponentially dependent on the number of nodes ℓ .

A sample of n spanning trees

- ▶ Instead of using all spanning trees, we can just use n spanning trees

$$F_T(\mathbf{w}, \mathbf{x}, \mathbf{y}) = \frac{1}{n} \sum_{i=1}^n a_{T_i} \langle \mathbf{w}_{T_i}, \phi_{T_i}(\mathbf{x}, \mathbf{y}) \rangle$$

$$\frac{1}{n} \sum_{i=1}^n a_{T_i}^2 = 1, \quad \frac{1}{n} \sum_{i=1}^n a_{T_i} < 1.$$

- ▶ When

$$n \geq \frac{\ell^2}{\epsilon^2} \left(\frac{1}{16} + \frac{1}{2} \ln \frac{8\sqrt{n}}{\delta} \right),$$

we have $|F_T(\mathbf{w}, \mathbf{x}, \mathbf{y}) - F(\mathbf{w}, \mathbf{x}, \mathbf{y})| \leq \epsilon$, with high probability.

- ▶ A sample of $n \in \Theta(\ell^2/\epsilon^2)$ random spanning tree is sufficient to estimate the score function.
- ▶ Margin achieved by $F(\mathbf{w}, \mathbf{x}, \mathbf{y})$ is also preserved by the sample of n random spanning trees $F_T(\mathbf{w}, \mathbf{x}, \mathbf{y})$ [Marchand et al., 2014].

Random spanning tree approximation RTA

- The optimization problem of RTA is defined as [Marchand et al., 2014]

$$\begin{aligned} \min_{\mathbf{w}_{T_i}, \xi_i} \quad & \frac{1}{2} \sum_{i=1}^n \|\mathbf{w}_{T_i}\|^2 + C \sum_{k=1}^m \xi_k \\ \text{s.t.} \quad & \frac{1}{\sqrt{n}} \sum_{i=1}^n \langle \mathbf{w}_{T_i}, \phi_{T_t}(\mathbf{x}_k, \mathbf{y}_k) \rangle - \max_{\mathbf{y} \neq \mathbf{y}_k} \frac{1}{\sqrt{n}} \sum_{i=1}^n \langle \mathbf{w}_{T_i}, \phi_{T_i}(\mathbf{x}_k, \mathbf{y}) \rangle \geq 1 - \xi_k, \\ & \xi_k \geq 0, \forall k \in \{1, \dots, m\}. \end{aligned}$$

- The marginal-dual form is given by

$$\begin{aligned} \max_{\mu \in \mathcal{M}} \quad & \sum_{i=1}^n \left(\mu_{T_i} \ell_{T_i} - \frac{1}{2} \mu_{T_i} K_{T_i}^{\Delta \phi} \mu_{T_i} \right) \\ \text{s.t.} \quad & \sum_{u_e} \mu_{T_i, e}(u_e) \leq C. \end{aligned}$$

- Inside the summation, there is a structure output model with parameter μ_{T_i} defined on a spanning tree T_i .
- The problem is how to jointly optimize structured output models defined on n spanning trees.

Inference problem for a collection of trees

- ▶ The inference problem of RTA is defined as finding the multilabel $\mathbf{y}_{\mathcal{T}}(\mathbf{x})$ that maximizes the sum of scores over a collection of trees

$$\mathbf{y}_{\mathcal{T}}(\mathbf{x}) = \operatorname{argmax}_{\mathbf{y} \in \mathcal{Y}} F_{\mathcal{T}}(\mathbf{x}, \mathbf{y}; \mathbf{w}_{\mathcal{T}}) = \operatorname{argmax}_{\mathbf{y} \in \mathcal{Y}} \sum_{t=1}^n \langle \mathbf{w}_{T_t}, \phi_{T_t}(\mathbf{x}, \mathbf{y}) \rangle.$$

- ▶ The inference problem on each individual spanning tree can be solved efficiently in $\Theta(\ell)$ by *dynamic programming*

$$\mathbf{y}_{T_t}(\mathbf{x}) = \operatorname{argmax}_{\mathbf{y} \in \mathcal{Y}} F_{T_t}(\mathbf{x}, \mathbf{y}; \mathbf{w}_{T_t}) = \operatorname{argmax}_{\mathbf{y} \in \mathcal{Y}} \langle \mathbf{w}_{T_t}, \phi_{T_t}(\mathbf{x}, \mathbf{y}) \rangle.$$

- ▶ There is no guarantee that there exists a tree $T_t \in \mathcal{T}$ in which the maximizer of F_{T_t} is the maximizer of $F_{\mathcal{T}}$.

Fast inference for a collection of trees

- ▶ For each tree T_t , instead of computing the best multilabel \mathbf{y}_{T_t} , we compute K -best multilabels in $\Theta(K\ell)$ time

$$\mathcal{Y}_{T_t, K} = \{\mathbf{y}_{T_t, 1}, \dots, \mathbf{y}_{T_t, K}\}.$$


- ▶ Performing the same computation on all trees gives a candidate list of $n \times K$ multilabels (K best list) in $\Theta(nK\ell)$ time

$$\mathcal{Y}_{T, K} = \mathcal{Y}_{T_1, K} \cup \dots \cup \mathcal{Y}_{T_n, K}.$$

- ▶ We prove that with high probability the global best multilabel will exist in K best list.
- ▶ We have developed a condition to verify the global best multilabel from K best list in linear time $\Theta(nK)$.

RTA inference algorithm

- ▶ 10 datasets, $|\mathcal{T}| = \{5, 10, 40\}$, $K = \{2, 4, 8, 16, 32, 40, 60\}$.
- ▶ Y-axis is the percentage of examples with exact inference.
- ▶ X-axis is the value of K as the percentage of the number of microlabels.
- ▶ $K = 100\%|Y|$ corresponds to a complexity of $\Theta(nl^2)$.



RTA on multilabel benchmark datasets

- ▶ Prediction performance on multilabel benchmark datasets.
- ▶ Measurement of success is microlabel accuracy and multilabel accuracy.
- ▶ The result is shown in the following table.

DATASET	MICROLABEL LOSS (%)					0/1 LOSS (%)				
	SVM	MTL	MMCRF	MAM	RTA	SVM	MTL	MMCRF	MAM	RTA
EMOTIONS	22.4	20.2	20.1	19.5	18.8	77.8	74.5	71.3	69.6	66.3
YEAST	20.0	20.7	21.7	20.1	19.8	85.9	88.7	93.0	86.0	77.7
SCENE	9.8	11.6	18.4	17.0	8.8	47.2	55.2	72.2	94.6	30.2
ENRON	6.4	6.5	6.2	5.0	5.3	99.6	99.6	92.7	87.9	87.7
CAL500	13.7	13.8	13.7	13.7	13.8	100.0	100.0	100.0	100.0	100.0
FINGERPRINT	10.3	17.3	10.5	10.5	10.7	99.0	100.0	99.6	99.6	96.7
NCI60	15.3	16.0	14.6	14.3	14.9	56.9	53.0	63.1	60.0	52.9
MEDICAL	2.6	2.6	2.1	2.1	2.1	91.8	91.8	63.8	63.1	58.8
CIRCLE10	4.7	6.3	2.6	2.5	0.6	28.9	33.2	20.3	17.7	4.0
CIRCLE50	5.7	6.2	1.5	2.1	3.8	69.8	72.3	38.8	46.2	52.8

Short summary

- ▶ We have seen so far.

Output graph	Inference problem	Inference algorithm
Tree	Polynomial	DP [Rousu et al., 2007]
Graph	\mathcal{NP} -hard	LBP [Su et al., 2010]
Pattern	Linear?	Reduction [Su et al., 2015]
DAG	\mathcal{NP} -hard	SDP [Su et al., 2014]
→unknown	\mathcal{NP} -hard	MVE AMM MAM [Su and Rousu, 2015] RTA [Marchand et al., 2014]


Conclusions

- ▶ Structured output learning is family of methods for multilabel classification.
- ▶ The output graph is often assumed to be known *a priori*.
 - ▶ MMCRF assumes tree or general undirected graph as output graph.
 - ▶ SPIN assumes DAG as output graph.
 - ▶ Possible for exponential reduction of the search space.
- ▶ In addition, we focus on the problems where the output graph is unobserved.
 - ▶ MVE AMM MAM aggregates the inference results from base models.
 - ▶ RTA is a unified learning and inference framework.
 - ▶ Model all pairwise correlations with a complete graph.
 - ▶ Under margin assumption, the properties of a complete graph can be achieved by a collection of its spanning trees.
- ▶ All developed models are tested with real-world applications or benchmark datasets.
- ▶ Codes are available from <http://hongyusu.github.io>.

Ongoing work

Optimization for RTA with Juho Rousu


- ▶ From K-best inference algorithm
- ▶ To a Newton method: a conic combination of multiple update directions



Ongoing work

Optimization for RTA with Juho Rousu

- ▶ From K-best inference algorithm
- ▶ To a Newton method: a conic combination of multiple update directions



Ongoing work

L_1 norm RTA with John Shawe-Taylor, Mario Marchand

- ▶ From conic combination of a collection of random spanning trees

$$F(\mathbf{w}, \mathbf{x}, \mathbf{y}) = \mathbf{E}_{T \in U(G)} a_T \langle \mathbf{w}_T, \phi_T(\mathbf{x}, \mathbf{y}) \rangle \quad \mathbf{E}_{T \in U(G)} a_T^2 = 1, \quad \mathbf{E}_{T \in U(G)} a_T < 1.$$

- ▶ To convex combination of a collection of random spanning trees

$$F(\mathbf{w}, \mathbf{x}, \mathbf{y}) = \mathbf{E}_{T \in U(G)} a_T \langle \mathbf{w}_T, \phi_T(\mathbf{x}, \mathbf{y}) \rangle \quad \mathbf{E}_{T \in U(G)} a_T = 1, \quad \mathbf{E}_{T \in U(G)} a_T < 1.$$

- ▶ Optimization problem (tree selection!)

$$\min_{\mathbf{w}_{T_i}, \xi_i} \quad \frac{1}{2} \left(\sum_{i=1}^n \|\mathbf{w}_{T_i}\| \right)^2 + C \sum_{k=1}^m \xi_k$$

$$\text{s.t.} \quad \frac{1}{n} \sum_{i=1}^n \langle \mathbf{w}_{T_i}, \phi_{T_t}(\mathbf{x}_k, \mathbf{y}_k) \rangle - \max_{\mathbf{y} \neq \mathbf{y}_k} \frac{1}{n} \sum_{i=1}^n \langle \mathbf{w}_{T_i}, \phi_{T_i}(\mathbf{x}_k, \mathbf{y}) \rangle \geq 1 - \xi_k,$$

$$\xi_k \geq 0, \forall k \in \{1, \dots, m\}.$$

Bibliography

-  Argyriou, A., Evgeniou, T., and Pontil, M. (2008).
Convex multi-task feature learning.
Machine Learning, 73(3):243–272.
-  Bian, W., Xie, B., and Tao, D. (2012).
Corrlog: Correlated logistic models for joint prediction of multiple labels.
Journal of Machine Learning Research - Proceedings Track, pages 109–117.
-  Cheng, W. and Hüllermeier, E. (2009).
Combining instance-based learning and logistic regression for multilabel classification.
Machine Learning, 76(2-3):211–225.

Bibliography (cont.)



Cousins, S., Shawe-Taylor, J., Marchand, M., Rousu, J., and Su, H. (2015a).

Large margin learning for prediction over unknown graph structures - a multiple kernel learning approach.

Large-Scale Kernel Learning Workshop of ICML 2015.



Cousins, S., Shawe-Taylor, J., Marchand, M., Rousu, J., and Su, H. (2015b).

Multiple kernel learning for prediction on unknown graph structures.

Optimization for machine learning Workshop of NIPS 2015.



Esuli, A., Fagni, T., and Sebastiani, F. (2008).

Boosting multi-label hierarchical text categorization.

Information Retrieval, 11(4):287–313.

Bibliography (cont.)



Lafferty, J. D., McCallum, A., and Pereira, F. C. N. (2001).

Conditional random fields: Probabilistic models for segmenting and labeling sequence data.

In *Proceedings of the 8th International Conference on Machine Learning (ICML 2001)*, pages 282–289. Morgan Kaufmann Publishers Inc.



Marchand, M., Su, H., Morvant, E., Rousu, J., and Shawe-Taylor, J. (2014).

Multilabel structured output learning with random spanning trees of max-margin markov networks.

In *Advances in Neural Information Processing System NIPS2014*, page to appear.



Read, J., Pfahringer, B., Holmes, G., and Frank, E. (2011).

Classifier chains for multi-label classification.

Machine Learning, 85(3):333–359.

Bibliography (cont.)

-  Rousu, J., Saunders, C., Szedmak, S., and Shawe-Taylor, J. (2007). Efficient algorithms for max-margin structured classification. *Predicting Structured Data*, pages 105–129.
-  Schapire, R. and Singer, Y. (1999). Improved boosting algorithms using confidence-rated predictions. *Machine Learning*, 37(3):297–336.
-  Su, H. (2015). *Multilabel Classification through Structured Output Learning - Methods and Applications*. PhD thesis, Department of Information and Computer Science, Aalto University.

Bibliography (cont.)



Su, H., Gionis, A., and Rousu, J. (2014).

Structured prediction of network response.

In *Proceedings, 31th International Conference on Machine Learning ICML2014*, volume 32 of *Journal of Machine Learning Research WCP*, pages 442–450.



Su, H., Heinonen, M., and Rousu, J. (2010).

Structured output prediction of anti-cancer drug activity.

In *Proceedings, 5th IAPR International Conference on Pattern Recognition in Bioinformatics (PRIB2010)*, volume 6282 of *Lecture Note in Computer Science*, pages 38–49.



Su, H. and Rousu, J. (2011).

Multi-task drug bioactivity classification with graph labeling ensembles.

In *Proceedings, 6th IAPR International Conference on Pattern Recognition in Bioinformatics (PRIB2011)*, volume 7035 of *Lecture Note in Computer Science*, pages 157–167.

Bibliography (cont.)

-  Su, H. and Rousu, J. (2013).
 Multilabel classification through random graph ensembles.
 In *Proceedings, 5th Asian Conference on Machine Learning (ACML2013)*, volume 29 of *Journal of Machine Learning Research WCP*, pages 404–418.
-  Su, H. and Rousu, J. (2015).
 Multilabel classification through random graph ensembles.
 Machine Learning, 99(2):231–256.
-  Su, H., Valentini, G., Szedmark, S., and Rousu, J. (2015).
 Transporter protein classification through structured prediction and multiple kernel learning.
 Machine learning in computational biology and machine learning in system biology workshop of NIPS 2015.

Bibliography (cont.)



Taskar, B., Abbeel, P., and Koller, D. (2002).

Discriminative probabilistic models for relational data.

In *Proceedings of the Eighteenth Conference on Uncertainty in Artificial Intelligence (UAI 2002)*, pages 485–492, San Francisco, CA, USA. Morgan Kaufmann Publishers Inc.



Taskar, B., Guestrin, C., and Koller, D. (2004).

Max-margin markov networks.

In Thrun, S., Saul, L., and Schölkopf, B., editors, *Advances in Neural Information Processing Systems 16*, pages 25–32. MIT Press.



Tsochantaridis, I., Hofmann, T., Joachims, T., and Altun, Y. (2004).

Support vector machine learning for interdependent and structured output spaces.

In *Proceedings of the 21th International Conference on Machine Learning (ICML 2004)*, pages 823–830. ACM.

Bibliography (cont.)

-  Tsochantaridis, I., Joachims, T., Hofmann, T., and Altun, Y. (2005).
 Large margin methods for structured and interdependent output variables.
Journal of Machine Learning Research, 6:1453–1484.
-  Tsoumakas, G., Katakis, I., and Vlahavas, I. (2010).
 Mining multi-label data.
 In Maimon, O. and Rokach, L., editors, *Data Mining and Knowledge Discovery Handbook*, pages 667–685. Springer US.
-  Zhang, M. and Zhou, Z. (2007).
 MI-knn: A lazy learning approach to multi-label learning.
Pattern Recognition, 40:2007.