[Paper Title]

Anonymous Author(s)
Affiliation
Address
email

Abstract

1 Introduction

Contributions.

- TODO: contribution 1.
- TODO: contribution 2.
- TODO: contribution 3.

2 Related Work

Memory-based Robotic Manipulation Models. History-dependent manipulation has motivated a rapidly growing family of memory designs for VLA policies, but the design space remains fragmented. The most direct treatment is to feed history in as additional context: ContextVLA [22] concatenates a sliding window of past visual tokens to the transformer input, while BC-RNN [29] rolls history through a recurrent state. Both extremes scale poorly — the former pays linear attention cost in horizon length, the latter compresses without selection. Recent state-space policies, including RoboMamba [28] and MITL [47], replace the RNN with Mamba-style updates [18], preserving constant-memory recurrence while extending the effective context window.

A second line of work inserts an explicit *memory bank* between the encoder and the policy and reads from it on demand. Hamlet [24] and MemoryVLA [33] cache past visual features together with auxiliary signals such as task instructions or cognitive summaries, and retrieve the relevant entries at each step; SAM2Act [17] attaches a similar memory module to a video segmentation backbone so that object identity and action heatmaps remain stable across long horizons. MEM [49] pushes this further by organizing embodied features at multiple temporal resolutions, while BPP [50] recasts long-context imitation learning as the problem of selecting a small set of behaviorally relevant key history frames. HistRISE [9] takes the structured-state view to its extreme, tracking object-centric 3D points as a non-differentiable symbolic memory.

A third, increasingly popular direction offloads memory entirely to a large vision-language model. UniVLA [5] simply prepends past actions to the prompt, while MemER [36], Gemini-Robotics-1.5 [38], and the steerable $\pi_{0.7}$ generalist [48] rely on a VLM to produce language-based subgoals or natural-language plans that condition a downstream policy. This keeps the policy itself short-context, but introduces costly modular inference and breaks end-to-end optimization. Taken together, these works establish that memory is essential, yet they differ in backbone, in what is stored, and in how memory is integrated, making head-to-head comparison difficult — the gap our controlled study targets, by training a family of memory-augmented VLAs on the same backbone and evaluating diverse representations and integration mechanisms in a unified setting.

Submitted to 40th Conference on Neural Information Processing Systems (NeurIPS 2026). Do not distribute.

Efficient Video Representation for Robotic Manipulation. Episodic robot videos are heavily redundant: adjacent frames differ only in a few interaction-relevant pixels, and most patches encode static background or the robot's own body. General video understanding addresses this with token-level pruning and resampling — TimeChat-Online [44] shows that roughly 80% of visual tokens are naturally redundant in streaming video, and VideoLLM-online [10] streams video into a language model under an incremental token budget. In manipulation the constraint is tighter still: a policy must run at control rate while keeping many seconds of history within a fixed token window. Robotic methods therefore aggregate frames at the encoder side — ContextVLA [22] amortizes multi-frame context into a compact history bundle, Hamlet [24] turns a vanilla VLA into a history-aware policy by switching its inputs at inference time, and long-context diffusion policies [39] supervise past-token prediction so that the compressed history retains causally relevant information. A complementary thread asks *which* frames matter: BPP [50] explicitly selects key history frames for imitation learning, and SAM2Act [17] reuses a video segmentation foundation model to anchor object identity across long horizons. We build on these observations by combining TokenDropped keyframe patches with a MotionEncoder summary, decoupling sparse visual evidence from high-frequency motion structure and giving every memory variant the same fixed-size video representation budget.

3 Method

3.1 Preliminaries and Problem Setup

3.2 Model Architecture

Our policy is a memory-augmented vision-language-action (VLA) model built on top of the $\pi_{0.5}$ backbone. We initialize from the pre-trained backbone and fine-tune its experts end-to-end in Stage 2 (Sec. **??**). The only components kept frozen throughout both stages are the SigLIP2 visual encoder and, after Stage 1, the MotionEncoder f_θ. We inject the per-episode memory sequence assembled in Sec. 3.3 as additional context tokens.

$\pi_{0.5}$ backbone. At history timestep t, the policy receives language tokens $\boldsymbol{\ell} = \mathrm{Tok}_{\mathrm{text}}(l) \in \mathbb{R}^{N_\ell \times d}$ and multi-view image tokens $\mathbf{o}_t = \mathrm{Tok}_{\mathrm{img}}(I_t) \in \mathbb{R}^{N_o \times d}$ extracted by a frozen SigLIP2 encoder. $\pi_{0.5}$ follows the π_0 multi-expert design and is composed of (i) a *VLM expert* E_{vlm} that fuses language and vision and (ii) an *action expert* E_{act} that predicts an action chunk conditioned on the VLM features and a denoising timestep τ. Both experts are L-layer transformers connected by a *blockwise causal attention* operator

$$\mathbf{y} \;=\; \mathrm{BlockAttn}(\mathbf{x}_1, \mathbf{x}_2, \ldots, \mathbf{x}_G), \tag{1}$$

in which attention is bidirectional within each block $\mathbf{x}_i$ and causal across blocks (block i may attend blocks $1{:}i$ but not future blocks). The action expert is conditioned on τ via AdaLN-Zero modulation: with action latent $\mathbf{s}_t^k$ at layer k,

$$\tilde{\mathbf{s}}_t^k = \mathbf{s}_t^{k-1} + g_\tau \odot \mathrm{BlockAttn}^k\big(\mathrm{Norm}^k_{\mathrm{vlm}}(\mathbf{u}_t^{k-1}),\, \mathrm{Norm}^k_{\mathrm{act}}(\mathbf{s}_t^{k-1}, \tau)\big), \quad \mathbf{s}_t^k = \tilde{\mathbf{s}}_t^k + \tilde{g}_\tau \odot \mathrm{MLP}^k_{\mathrm{act}}\big(\mathrm{Norm}^k_{\mathrm{act}}(\tilde{\mathbf{s}}_t^k, \tau)\big), \tag{2}$$

where $g_\tau, \tilde{g}_\tau$ are gates conditioned on τ. Unlike the original $\pi_{0.5}$, which uses the VLM expert to also generate low-level language commands, we keep the VLM as a pure feature extractor; this leaves a clean interface at which memory can be injected.

Memory token block. To enable history-dependent reasoning, we augment the policy with an explicit memory state $\mathbf{M}_t$:

$$a_t \;\sim\; \pi(\cdot \mid l,\, \mathbf{o}_t,\, \mathbf{M}_t)\,, \tag{3}$$

where $\mathbf{M}_t$ is the length-B projection of the causal prefix $\mathcal{M}_t$ (Eq. 15), containing only observations and motion windows that have fully elapsed before step t. For fair comparison across designs, we allocate a fixed memory token budget B for all memory-based models: each representation produces at most B tokens; if fewer are available, the sequence is zero-padded. Thus all memory variants share the same interface

$$\mathbf{M}_t \;\in\; \mathbb{R}^{B \times d}. \tag{4}$$

We expose the memory sequence $\mathcal{M}$ produced in Sec. 3.3 to the backbone as this token block. The two-token-kind structure of $\mathcal{M}$ — TokenDropped keyframe patches and MotionEncoder motion tokens — is opaque to the backbone: from the policy's perspective $\mathbf{M}_t$ is just a length-B sequence of d-dimensional vectors carrying time tags.

Figure 1: TODO: method overview figure. Left: offline memory pipeline (CLIP keyframe detection $\rightarrow$ TokenDrop $\rightarrow$ MotionEncoder motion tokens) producing $\mathbf{M}_t$. Right: the three injection sites in the $\pi_{0.5}$ backbone — Memory-as-Context into the VLM input, Memory-as-Modulator into AdaLN of the action expert, and Memory-as-Expert as a dedicated third expert.

Three integration mechanisms. We systematically study three places at which $\mathbf{M}_t$ can enter the backbone, trading parameter count, attention budget, and isolation of the pretrained VLM features against each other.

(1) Memory-as-Context (MaC). The simplest variant: concatenate $\mathbf{M}_t$ with the standard inputs of the VLM expert,

$$\mathbf{u}_t^0 \;=\; [\,\mathbf{M}_t;\, \mathbf{o}_t;\, \boldsymbol{\ell}\,], \qquad \mathbf{u}_t \;=\; E_{\mathrm{vlm}}(\mathbf{u}_t^0). \tag{5}$$

MaC introduces *no* new parameters and reuses the existing blockwise causal attention (1); its cost is that memory tokens compete with raw observation tokens for the same attention budget inside E_{vlm}, and any noise in $\mathbf{M}_t$ propagates through every downstream feature.

(2) Memory-as-Modulator (MaM). Instead of feeding memory through the VLM, we use it to *modulate* the action expert. At each layer k, the action latent $\tilde{\mathbf{s}}_t^k$ first cross-attends $\mathbf{M}_t$, and the result is mapped to per-feature scale/shift parameters via a zero-initialized MLP that is then composed with AdaLN:

$$\mathbf{r}_t^k = \mathrm{Attn}_{\mathrm{mod}}^k\big(Q{=}\tilde{\mathbf{s}}_t^k,\; K{=}\mathbf{M}_t,\; V{=}\mathbf{M}_t\big), \tag{6}$$

$$(\gamma_t^k, \beta_t^k) = \mathrm{MLP}_{\mathrm{mod}}^k(\mathbf{r}_t^k), \tag{7}$$

$$\widehat{\mathbf{s}}_t^k = \gamma_t^k \odot \mathrm{Norm}_{\mathrm{mod}}^k(\tilde{\mathbf{s}}_t^k) + \beta_t^k, \tag{8}$$

$$\mathbf{s}_t^k = \widehat{\mathbf{s}}_t^k + \tilde{g}_\tau \odot \mathrm{MLP}_{\mathrm{act}}^k\big(\mathrm{Norm}_{\mathrm{act}}^k(\widehat{\mathbf{s}}_t^k, \tau)\big). \tag{9}$$

$\mathrm{MLP}_{\mathrm{mod}}^k$ is initialized so that $(\gamma_t^k, \beta_t^k){=}(1, 0)$ at the start of fine-tuning, making the modulation an exact identity at step zero and protecting the pretrained $\pi_{0.5}$ behavior. MaM adds a moderate number of parameters ($\sim$80M, see Sec. 3.5) and, importantly, leaves the VLM expert untouched.

(3) Memory-as-Expert (MaE). We allocate a dedicated third expert E_{mem} that processes $\mathbf{M}_t$ through its own L layers of self-attention plus MLP:

$$\tilde{\mathbf{v}}_t^k = \mathbf{v}_t^{k-1} + \mathrm{BlockAttn}^k\big(\mathrm{Norm}_{\mathrm{mem}}^k(\mathbf{v}_t^{k-1})\big), \quad \mathbf{v}_t^k = \tilde{\mathbf{v}}_t^k + \mathrm{MLP}_{\mathrm{mem}}^k\big(\mathrm{Norm}_{\mathrm{mem}}^k(\tilde{\mathbf{v}}_t^k)\big), \tag{10}$$

with $\mathbf{v}_t^0 = \mathbf{M}_t$. The action expert's update (2) is then extended to attend *both* VLM and memory features as additional context blocks:

$$\tilde{\mathbf{s}}_t^k = \mathbf{s}_t^{k-1} + g_\tau \odot \mathrm{BlockAttn}^k\big(\mathrm{Norm}_{\mathrm{mem}}^k(\mathbf{v}_t^{k-1}),\, \mathrm{Norm}_{\mathrm{vlm}}^k(\mathbf{u}_t^{k-1}),\, \mathrm{Norm}_{\mathrm{act}}^k(\mathbf{s}_t^{k-1}, \tau)\big). \tag{11}$$

The blockwise causal mask is configured asymmetrically: the VLM expert and memory expert each use self-attention only and *do not* attend each other; the action expert is the sole consumer that attends both. This asymmetry preserves the pretrained $\pi_{0.5}$ representations exactly while allocating a separate transformer's worth of capacity ($\sim$190M parameters) to memory processing.

3.3 Memory Token Generation and Training

As the robot executes, the memory $\mathcal{M}_\tau$ grows online from the history of observations accumulated prior to policy step τ. It is a sparse, time-aligned sequence of two complementary token kinds: (i)

keyframe tokens, which anchor the scene at semantic transitions, and (ii) *motion tokens*, fixed-stride summaries of short-range visual change produced by a learned MotionEncoder. Both kinds are encoded strictly from already-elapsed frames: keyframe tokens are committed as soon as a keyframe is detected, and a motion token m_t over window $[t,\ t{+}\Delta]$ becomes available only after step $t{+}\Delta$ has passed (Eq. 15). All encoding is performed by frozen perception backbones independently of the VLA; no gradient flows back into these encoders during VLA training.

Keyframe detection. Let $\{I_t\}_{t\geq 0} \subset \mathbb{R}^{3\times H\times W}$ denote the sequence of RGB frames observed during execution. Keyframes mark moments of meaningful scene change (object pickup, contact events, viewpoint shifts). Each frame is scored by the smoothed discrete derivative of a frozen CLIP encoder Φ_{CLIP}:

$$d_t \;=\; \big\|\Phi_{\text{CLIP}}(I_t) - \Phi_{\text{CLIP}}(I_{t-1})\big\|_2, \qquad \tilde{d}_t \;=\; (k_{\text{rbf}} * d)_t, \tag{12}$$

where k_{rbf} is a small RBF kernel that suppresses frame-rate jitter. Keyframes are local maxima of $\tilde{d}_t$ exceeding a threshold τ, with the first frame $t = 0$ always retained as an anchor. The detector is purely deterministic preprocessing and has no learnable parameters; τ is a single hyperparameter chosen so that the average inter-keyframe gap is $\sim$32 frames.

Keyframe TokenDrop. Storing the full S-token grid for every keyframe is wasteful: most of the image (background, robot base, table) repeats across keyframes. For every keyframe k_i with $i > 0$ we retain only the patches that actually changed relative to its *previous* keyframe k_{i-1}. Concretely, on the 16×16 patch grid we mark a patch as *significant* if its mean per-pixel absolute difference between I_{k_i} and $I_{k_{i-1}}$ exceeds δ, and we keep the union of all significant patches together with the patches lying inside their axis-aligned bounding rectangle (the latter preserves spatial contiguity for downstream attention). The first keyframe k_0 is always kept in full (S tokens); each subsequent keyframe contributes $|\mathcal{P}_i| \leq S$ tokens. TokenDrop is also parameter-free.

Motion tokens. Let $\Phi_{\text{SigLIP}} : \mathbb{R}^{3\times H\times W} \to \mathbb{R}^{S\times E}$ ($S = 256$ patches, $E = 1152$) be the frozen SigLIP tokenizer, and let $x_t = \Phi_{\text{SigLIP}}(I_t) \in \mathbb{R}^{S\times E}$; $\{s_t\}$ denotes the proprioceptive state sequence. Independently of keyframe placement, we tile the video with non-overlapping windows of fixed stride Δ (we use $\Delta = 8$). For each window $[t,\ t{+}\Delta]$ a trainable *MotionEncoder* f_θ compresses the visual change into M latent tokens $m_t \in \mathbb{R}^{M\times D_m}$:

$$m_t \;=\; f_\theta(\,x_t,\ x_{t+\Delta},\ \Delta s_t\,), \qquad \Delta s_t = s_{t+\Delta} - s_t. \tag{13}$$

Internally, f_θ (i) computes the patchwise visual delta $\Delta x \;=\; x_{t+\Delta} - x_t \;\in\; \mathbb{R}^{S\times E}$, (ii) spatially average-pools Δx to a single global delta token in $\mathbb{R}^{1\times E}$ and projects it to the encoder width H, (iii) projects Δs_t to H and adds it to the pooled delta token (this is the only place proprioception enters the memory pipeline), (iv) appends M learned read-out queries at the tail, and (v) runs a small causal transformer (RMSNorm, 1D-RoPE causal self-attention, SwiGLU FFN) so that each query attends to the fused delta token before it. The last M positions are projected to motion dimension D_m and constitute m_t. Since m_t requires both endpoints of window $[t,\ t{+}\Delta]$, it becomes causally available only at step $t{+}\Delta$.

Memory sequence assembly. The final memory for an episode is the time-ordered concatenation

$$\mathcal{M} \;=\; \big[\, x^{\text{full}}_{k_0},\ m_0,\ m_\Delta,\ \ldots,\ x^{\text{TD}}_{k_i},\ \ldots\,\big], \tag{14}$$

where each entry carries its source timestamp as a positional tag. At policy step τ, the policy receives the causally valid prefix

$$\mathcal{M}_\tau \;=\; \big\{\, x_{k_j} : k_j \leq \tau \,\big\} \;\cup\; \big\{\, m_t : t + \Delta \leq \tau \,\big\}, \tag{15}$$

i.e. keyframe tokens whose frame index is at most τ, and motion tokens whose entire window $[t,\ t{+}\Delta]$ has elapsed by τ. The sequence $\mathcal{M}_\tau$ grows monotonically: at each new step the pipeline appends newly completed tokens without recomputing earlier ones. Keyframe selection and TokenDrop are training-free; the only learnable parameters in the memory pipeline are those of the MotionEncoder f_θ, which is pre-trained in Stage 1 of Sec. 3.4 and then frozen. The trained f_θ, together with the parameter-free keyframe and TokenDrop modules, is what ultimately writes into $\mathcal{M}$.

3.4 Training Objective

The full system has two distinct loss surfaces, optimized in two stages: a latent future-prediction loss $\mathcal{L}_{\text{pred}}$ that trains the MotionEncoder f_θ of Sec. 3.3, and a flow-matching loss $\mathcal{L}_{\text{FM}}$ that trains the VLA backbone together with the integration module.

Latent future-prediction loss for f_θ. We train f_θ jointly with an auxiliary *MotionDiT* decoder g_ϕ: a conditional-diffusion decoder that regresses the SigLIP tokens of the future frame from the current tokens and the motion code. Given $(x_t, x_{t+\Delta})$, we sample a diffusion-style timestep $k \sim \mathcal{U}\{1, \ldots, K\}$ and ask g_ϕ to predict the (token-normalized) future tokens from the current tokens, the motion code, and k:

$$\hat{x}^{(k)}_{t+\Delta} \;=\; g_\phi(\, x_t,\; m_t,\; k\,), \qquad m_t = f_\theta(x_t, x_{t+\Delta}, \Delta s_t), \tag{16}$$

$$\mathcal{L}_{\text{pred}} \;=\; \mathbb{E}_{t,\,k}\Big[\, \big\|\hat{x}^{(k)}_{t+\Delta} \;-\; \text{TokenNorm}(x_{t+\Delta})\big\|_2^2 \,\Big]. \tag{17}$$

TokenNorm is a per-feature standardization applied to the target SigLIP tokens to stabilize the regression target. g_ϕ is a small DiT with AdaLN-zero timestep modulation and a tied gated input/output projection initialized to zero, so at $k=0$ the decoder acts as a normalized identity copy of x_t and only learns residual corrections driven by m_t. This zero-initialized residual head is the sole reason the loss is stable when f_θ is randomly initialized: gradients flow through g_ϕ into f_θ only via the correction term, forcing m_t to encode exactly the information needed to bridge $x_t \to x_{t+\Delta}$. Crucially, g_ϕ exists only during pre-training: at deployment the robot has already executed both endpoints of every motion window, so memory tokens are produced by a single forward pass through Φ_{SigLIP} and f_θ; no decoding is performed and g_ϕ is discarded.

Flow-matching action loss. Following $\pi_{0.5}$, the policy predicts an H-step action chunk $\mathbf{A}_t = [a_t, a_{t+1}, \ldots, a_{t+H-1}] \in \mathbb{R}^{H\times D}$ via conditional flow matching. Given a ground-truth chunk $\mathbf{A}_t^{\text{data}} \sim p_{\text{data}}$, Gaussian noise $\mathbf{A}_t^{\text{noise}} \sim \mathcal{N}(\mathbf{0}, \mathbf{I})$, and a denoising timestep $\tau \sim \mathcal{U}(0,1)$, we form the linear interpolant

$$\mathbf{A}_t^{\tau} \;=\; (1-\tau)\,\mathbf{A}_t^{\text{data}} \;+\; \tau\,\mathbf{A}_t^{\text{noise}}, \tag{18}$$

whose constant time-derivative is $\frac{d}{d\tau}\mathbf{A}_t^{\tau} = \mathbf{A}_t^{\text{noise}} - \mathbf{A}_t^{\text{data}}$. The action expert parameterizes a conditional velocity field $\mathbf{v}_\theta(\mathbf{A}_t^{\tau}, \tau, \mathbf{h}_t)$, where the context features $\mathbf{h}_t$ are the layer-L outputs of the integrated backbone — so $\mathbf{h}_t$ depends on the chosen integration mechanism: in MaC the memory enters $\mathbf{h}_t$ through the VLM expert (5); in MaM through the per-layer modulation (6–9); in MaE through the cross-expert attention (11). The training objective is

$$\mathcal{L}_{\text{FM}} \;=\; \mathbb{E}_{t,\,\tau,\,\mathbf{A}_t^{\text{data}},\,\mathbf{A}_t^{\text{noise}}}\Big[\, \big\|\mathbf{v}_\theta\big(\mathbf{A}_t^{\tau}, \tau, \mathbf{h}_t\big) \;-\; \big(\mathbf{A}_t^{\text{noise}} - \mathbf{A}_t^{\text{data}}\big)\big\|_2^2 \,\Big]. \tag{19}$$

At inference the action chunk is generated by integrating $\mathbf{v}_\theta$ from $\tau = 1$ (pure noise) to $\tau = 0$ (data) through a small number of Euler steps.

Two-stage training. The two losses are optimized sequentially, not jointly, because the memory pipeline encodes a task-agnostic visual-dynamics prior whereas the integration module is task-specific.

Stage 1: Memory-pipeline pre-training. On unlabeled robot videos we jointly train the MotionEncoder f_θ and the auxiliary MotionDiT decoder g_ϕ to minimize $\mathcal{L}_{\text{pred}}$. The SigLIP and CLIP backbones, the keyframe detector, and the TokenDrop module are training-free throughout. After Stage 1, g_ϕ is discarded and f_θ is frozen.

Stage 2: VLA fine-tuning. For every demonstration episode we *pre-compute and cache* the full memory sequence $\mathcal{M}$ using the frozen pipeline of Stage 1. At each training step t we extract the causally valid prefix $\mathcal{M}_t$ (Eq. 15) from the cached sequence and project it to $\mathbf{M}_t \in \mathbb{R}^{B\times d}$; no future motion tokens (i.e. windows with $t' + \Delta > t$) are visible to the policy. SigLIP2 visual tokens are likewise pre-computed and cached, following the $\pi_{0.5}$ recipe. Trainable parameters in Stage 2 are exactly: (i) the VLM expert, (ii) the action expert, and (iii) the integration module — which contributes 0 new parameters for MaC (Eq. 5), ~ 80M for MaM (Eqs. 6–9), or ~ 190M for MaE (Eqs. 10–11). The single optimization objective is $\mathcal{L}_{\text{FM}}$. No proprioceptive state enters the backbone in Stage 2 (proprioception only participates in Sec. 3.3 when forming motion tokens).

This decoupling is what makes the same memory pipeline reusable across all three integration variants and across downstream tasks: Stage 1 is run once; Stage 2 is repeated for each (task, integration) configuration.

3.5 Implementation Details

Memory pipeline. SigLIP2 provides $S = 256$ patch tokens of width $E = 1152$ per 256×256 frame. CLIP keyframe detection uses an RBF smoother of width 3 frames and a threshold τ tuned so that the average inter-keyframe gap is ~ 32 frames. TokenDrop operates on the 16×16 patch grid; a patch is marked significant when its mean per-pixel absolute RGB difference w.r.t. the previous keyframe exceeds $\delta = 10^{-2}$, after which we add the patches inside the axis-aligned bounding rectangle of the significant set. The first keyframe is always retained in full at S tokens. The MotionEncoder uses an 8-frame window at stride $\Delta = 16$, $M = 1$ readout query, an encoder-width $H = 1024$, and a 4-layer causal transformer (RMSNorm, 1D-RoPE, SwiGLU). MotionDiT g_ϕ is a 6-layer DiT with AdaLN-zero modulation and a tied gated input/output projection initialized to zero. All memory-pipeline parameters total ~ 60M; SigLIP2 and CLIP are frozen.

Memory budget and compression. We cap the keyframe-token memory at $B = 2000$ tokens of width $d = 1024$; the MotionEncoder contributes up to 125 motion tokens separately, giving a combined budget of $2000 + 125$, padding with zeros when shorter. Compared with the naive flattened representation of $T \cdot S$ patch tokens per episode, this is a $\sim 250\times$ reduction at $T \approx 2000$, while preserving both the long-range keyframe anchors (the first keyframe contributes a full $S = 256$ tokens) and short-range dynamics ($M = 1$ motion token per $\Delta = 16$-frame window).

Backbone and training schedule. The base $\pi_{0.5}$ policy processes 576 context tokens (512 visual + 64 language) and contains 3.2B parameters. Stage 2 fine-tuning uses AdamW ($\beta_1 = 0.9$, $\beta_2 = 0.95$, weight decay 0), constant learning rate 5×10^{-5} with 5% warmup, gradient-norm clip 1.0, EMA 0.999, action horizon $H = 20$, and 80k steps. Effective batch size is 64 for MaC and MaM and 8 for MaE (the larger memory expert is the bottleneck). All runs use $4\times$NVIDIA A40 GPUs with FSDP, $\sim$3–4 days per configuration. Stage 1 uses the same optimizer with a shorter 40k-step schedule on a separate unlabeled video corpus. The SigLIP2 ViT is frozen and its outputs are cached on disk to amortize cost across configurations.

4 Experiments

4.1 Experimental Setup

4.2 Main Results

Baselines. We compare our method against five reference configurations and an extra backbone study, all instantiated under the *Memory-as-Modulation* (MaM) integration mechanism so that differences are attributable to memory *content* rather than *injection*:

- **MME-VLA Clip-Keyframe** retains every 16×16 token of the selected keyframes (§3.3) without compression, giving an upper-bound configuration of $\sim 8000+$ tokens.
- **MME-VLA Clip-Keyframe + TokenDrop** adds the temporal-saliency token-dropping policy on top, compressing the memory to a fixed budget of 2000 tokens.
- **MME-VLA Clip-Keyframe + TokenDrop + Motion (Ours)** further appends 125 motion tokens that summarise short-range dynamics, yielding a total budget of $2000 + 125$.
- **MME-VLA Even Frame Sampling** is the naive frame-sampling baseline (§3.3, FrameSamp): uniformly spaced frames with pooled tokens, swept over budgets $\{1024, 512, 256, 128, 64\}$ to characterise how purely temporal subsampling degrades with shrinking memory.
- **MME-VLA Even TokenDropping** is the naive token-dropping baseline that ignores temporal-saliency scoring, swept over the same five budgets to isolate the value of the importance-weighted selection used by our method.
- **Other backbones (OpenVLA, Qwen2.5-VL)** swap the $\pi_{0.5}$ backbone for two alternative VLA backbones with the same memory pipeline, probing how transferable the proposed memory design is across model families.

Table 1: Main results on RoboMME. We compare our *Clip-Keyframe* + *TokenDrop* + *Motion* memory against keyframe-only / token-drop variants and the FrameSamp / TokenDrop budget sweeps, all under the *Memory-as-Modulation* integration mechanism. Success Rate is reported in %; *ongoing* denotes runs whose evaluation has not yet finished.

Method	Integration	Memory Budget	Success Rate (%)
MME-VLA Clip-Keyframe + TokenDrop + Motion (Ours)	Modulation	2000+125	*ongoing*
MME-VLA Clip-Keyframe	Modulation	8000+	*ongoing*
MME-VLA Clip-Keyframe + TokenDrop	Modulation	2000	*ongoing*
MME-VLA Even Frame Sampling	Modulation	1024	45.87
	Modulation	512	44.51
	Modulation	256	42.90
	Modulation	128	36.54
	Modulation	64	30.42
MME-VLA Even TokenDropping	Modulation	1024	40.17
	Modulation	512	38.02
	Modulation	256	36.36
	Modulation	128	32.76
	Modulation	64	18.11
Other backbones (OpenVLA, Qwen2.5-VL)	—	—	*ongoing*

4.3 Ablation Studies

4.4 Analysis

5 Conclusion

References

References follow the acknowledgments in the camera-ready paper. Use unnumbered first-level heading for the references. Any choice of citation style is acceptable as long as you are consistent. It is permissible to reduce the font size to `small` (9 point) when listing the references. Note that the Reference section does not count towards the page limit.

[1] Alexander, J.A. & Mozer, M.C. (1995) Template-based algorithms for connectionist rule extraction. In G. Tesauro, D.S. Touretzky and T.K. Leen (eds.), *Advances in Neural Information Processing Systems 7*, pp. 609–616. Cambridge, MA: MIT Press.

[2] Bower, J.M. & Beeman, D. (1995) *The Book of GENESIS: Exploring Realistic Neural Models with the GEneral NEural SImulation System.* New York: TELOS/Springer–Verlag.

[3] Hasselmo, M.E., Schnell, E. & Barkai, E. (1995) Dynamics of learning and recall at excitatory recurrent synapses and cholinergic modulation in rat hippocampal region CA3. *Journal of Neuroscience* **15**(7):5249-5262.

[48] Physical Intelligence. (2026) $\pi_{0.7}$: a Steerable Generalist Robotic Foundation Model with Emergent Capabilities.

[49] Physical Intelligence. (2026) MEM: Multi-Scale Embodied Memory for Vision Language Action Models.

[50] Sobol Mark, N. et al. (2026) BPP: Long-Context Robot Imitation Learning by Focusing on Key History Frames.

A Technical appendices and supplementary material

Technical appendices with additional results, figures, graphs, and proofs may be submitted with the paper submission before the full submission deadline (see above). You can upload a ZIP file for videos or code, but do not upload a separate PDF file for the appendix. There is no page limit for the technical appendices.

Note: Think of the appendix as “optional reading” for reviewers. The paper must be able to stand alone without the appendix; for example, adding critical experiments that support the main claims to an appendix is inappropriate.