


BDD

RAPPORT TP3 /TACHES

KIROUANE NERMINE ISIL B GROUPE 1



THIS TP IS ABOUT USER AND THEIR PRIVILEGES

TP N°3 : Data Control Language (DCL)

Introduction

DCL commands are used to manage database security by **controlling user access and permissions**. It allows the administrator to define **access privileges** (droits d'accès) : The right to access data, determining who can view, modify, or delete data within the database system.

The two main commands are **GRANT** and **REVOKE**.

Types of DCL commands

- **GRANT** : It gives a user specific permissions to perform actions on database objects (like

1/Exécutez le script fourni TP3_script.sql, puis affichez le nom de la base de données actuellement active.

```
mysql> tee C:/Users/HP/OneDrive/Documents/BDD/spool5.txt
Logging to file 'C:/Users/HP/OneDrive/Documents/BDD/spool5.txt'
mysql> source C:/Users/HP/Downloads/TP3_script.sql
Query OK, 1 row affected (0.21 sec)
```

command : source called and after it is where the file do existe

```
mysql> show databases;
+-----+
| Database |
+-----+
| cinema   |
| execution_db |
| information_schema |
| mysql    |
| performance_schema |
| uni2     |
| university_db |
| usthb_cs_bd |
| usthb_info_db |
+-----+
```

```
mysql> SELECT DATABASE();
+-----+
| DATABASE() |
+-----+
| cinema     |
+-----+
1 row in set (0.00 sec)
```

the selected database is cinema

2. Affichez la liste de toutes les tables, puis affichez le contenu (toutes les lignes) de chaque table.

```
mysql> use cinema;
Database changed
mysql> show tables;
+-----+
| Tables_in_cinema |
+-----+
| film              |
| plays            |
| produces          |
| screening         |
| seen              |
+-----+
```

i used the active database and used the command show tables to show all the tables in the db

```
mysql> select * from film;
```

Title	DURATION	NATIONALITY	DIRECTOR
Body Guard	120	US	Mark Gordo
ET	165	US	Spielberg
High Crimes	115	US	Carl Franc
Il Faut Sauver Le soldat Ryan	162	US	Spielberg
Indiana Jones	170	US	Spielberg
Le Dernier Chateau	132	US	Rod Lurie
Le Destin De Will Hunting	120	US	Gus Van Sa
Le Negociateur	140	US	David Aube
Le Pacificateur	135	US	Ashley Jud
Le Parrain	168	US	Francis Fo
Les Incorruptibles	160	US	Rickley Mo
Men	140	US	Rickley Mo
Nous Etions Soldat	139	US	Randall Wa
Perfect World	150	US	Clint East
Spy Games	127	US	Tony Scott
Top Gun	127	US	Tony Scott

```
16 rows in set (0.00 sec)
```

```
mysql> select * from plays;
```

ACTOR	TITLE
Kevin Costner	Body Guard
Aaron Smith	ET
Amanda Peet	ET
Aaron Smith	Il Faut Sauver Le soldat Ryan
Amanda Peet	Il Faut Sauver Le soldat Ryan

to show all the lines we use the command:

SELECT * FROM table-name;

this select all the lines in table

3. Créez un nouvel utilisateur "TP3user1" ayant le mot de passe "TP31".

```
mysql> CREATE USER 'TP3user1'@'localhost' IDENTIFIED BY 'TP31'
;
Query OK, 0 rows affected (0.01 sec)
```

i created using the command

```
-- Syntax 2 :
CREATE USER "username"@"host" IDENTIFIED BY "password";
```

so i choose the one the restrict access

4. Affichez l'utilisateur connecté.

```
mysql> SELECT USER FROM mysql.user ;
r ;
+-----+
| USER |
+-----+
| dounia |
| TP3user1 |
| mysql.infoschema |
| mysql.session |
| mysql.sys |
| root |
+-----+
6 rows in set (0.00 sec)
```

i used the command

Display list of all users in the server

```
SELECT USER FROM mysql.user ;
```

this to display the users in the server

5. Accorder tous les privilèges à l'utilisateur "TP3user1" et connectez vous à cet utilisateur.

```
mysql> grant all privileges on cinema.* TO 'TP3user1'@'localhost';
Query OK, 0 rows affected (0.01 sec)


mysql>
```

i used this command

Example 3 : Granting ALL privileges on all tables inside USTHB_DB

```
GRANT ALL PRIVILEGES ON USTHB_DB.* TO "sara";
```

that give all privileges to the user created



i am connected to TP3user1

6. Exécutez l'instruction `SELECT * FROM FILM` pour afficher le contenu de la table FILM. En cas d'échec, expliquez, corrigez et re-exécutez de nouveau.

1 • `SELECT * FROM FILM;`

Result Grid

	Title	DURATION	NATIC
▶	Body Guard	120	US
	ET	165	US
	High Crimes	115	US
	Il Faut Sauver Le soldat Ryan	162	US
	Indiana Jones	170	US

FILM 1 x Apply R

Output

Action Output

	Time	Action
✓	1 09:40:26	SELECT * FROM FILM LIMIT 0, 1000

it worked successfully and return 16rows because the user is created
because i give privileges to this user so he can access the film table of the cinema

7. Supprimez tous les privilèges accordés à l'utilisateur "TP3user1".

```
mysql> GRANT ALL PRIVILEGES ON cinema.* TO 'TP3user1'@'localhost';
Query OK, 0 rows affected (0.01 sec)

mysql>
```

8. Supprimez l'utilisateur "TP3user1".

```
mysql> DROP user 'TP3user1'@'localhost';
Query OK, 0 rows affected (0.01 sec)

mysql> D
```

Tâche 2 :

1. Créez un nouvel utilisateur "TP3user2" ayant le mot de passe "TP32".

```
mysql> CREATE USER 'TP3user2' identified by 'TP32';  
Query OK, 0 rows affected (0.02 sec)  
  
mysql> |
```

i created this time the user without restricting

2. Accordez le privilège SELECT sur la table SCREENING à l'utilisateur "TP3user2".

```
mysql> grant select  
-> on cinema.screening  
-> to 'TP3user2';  
Query OK, 0 rows affected (0.01 sec)  
  
mysql> |
```


i gave the privileges the thetable screening to the user2 of TP3

3. Accordez le privilège INSERT sur la table SEEN à l'utilisateur "TP3user2".

```
mysql> grant INSERT  
-> ON cinema.seen  
-> TO 'TP3user2';  
Query OK, 0 rows affected (0.01 sec)  
  
mysql> |
```

i gave one privilege to the user in the table seen so the user can insert in the table

4. Connectez l'utilisateur "TP3user2".



connected to the user2

in the workbench sql

5. Testez tous les privilèges accordés à l'utilisateur "TP3user2".

```
mysql> show tables;
+-----+
| Tables_in_cinema |
+-----+
| film              |
| plays             |
| produces          |
| screening         |
| seen              |
+-----+
5 rows in set (0.00 sec)

mysql> describe seen;
+-----+-----+-----+-----+-----+-----+
| Field | Type          | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| ACTOR | varchar(50)   | NO   | PRI | NULL    |       |
| TITLE | varchar(50)   | NO   | PRI | NULL    |       |
+-----+-----+-----+-----+-----+-----+
```

i will try to insert into seen

09:59:09	INSERT into seen VALUES('TOM CRUS' , 'DOGMAN')	Error Code: 1216. Cannot add or update a child row: a ...	0.016
----------	--	---	-------

i got en error saying that foreign key fails constraint so

```
mysql> select * from plays;
+-----+-----+
| ACTOR          | TITLE                |
+-----+-----+
| Kevin Costner  | Body Guard           |
| Aaron Smith    | ET                   |
| Amanda Peet    | ET                   |
| Aaron Smith    | Il Faut Sauver Le soldat Ryan |
| Amanda Peet    | Il Faut Sauver Le soldat Ryan |
+-----+-----+
```

i searched at real things i can insert

finally worked

1 • `INSERT INTO seen VALUES ('Nicole Kidman', 'Men');`

Automatic console disabled. Use the manual button to manually get the current caret position or toggle automatic console.

Context Help Snippets

Output

Action Output

		Time	Action	Message
✖	1	09:59:09	INSERT into seen VALUES('TOM CRUS', 'DOGMAN')	Error Code: 1216. Cannot add or update a child row
✖	2	10:00:58	INSERT INTO SEEN (ACTOR, TITLE) VALUES ('Tom...	Error Code: 1216. Cannot add or update a child row
✖	3	10:08:00	INSERT into seen VALUES('Kevin Costner', 'Body Gu...	Error Code: 1062. Duplicate entry 'Kevin Costner-Bo
✖	4	10:10:31	INSERT INTO seen VALUES ('Tom Cruise', 'Top Gun')	Error Code: 1062. Duplicate entry 'Tom Cruise-Top C
✔	5	10:12:09	INSERT INTO seen VALUES ('Nicole Kidman', 'Men')	1 row(s) affected

the error was that i created none existence actor and film then inserted something that exist while it primary key

2. Duplicate entry 'Tom Cruise-Top Gun' for key 'seen.PRIMARY' (

then i created a row that do not existe and it worked mean that the user can insert into seen ill try to delete to see if it will work or not

6. Supprimez tous les privilèges accordés à l'utilisateur "TP3user2".

```
mysql> revoke insert
      -> on cinema.seen
      -> from 'TP3user2';
Query OK, 0 rows affected (0.01 sec)

mysql> |
```

it got removed

```
mysql> revoke select
      -> on cinema.screening
      -> from 'TP3user2';
Query OK, 0 rows affected (0.01 sec)

mysql> |
```

```
mysql> show grants for 'TP3user2';
+-----+
| Grants for TP3user2@% |
+-----+
| GRANT USAGE ON *.* TO `TP3user2`@`%` |
+-----+
1 row in set (0.00 sec)
```

7. Supprimez l'utilisateur "TP3user2".


```
mysql> drop user 'TP3user2';
Query OK, 0 rows affected (0.01 sec)

mysql> |
```

Tâche 3 :


1. Créez un nouvel utilisateur "TP3user3" ayant le mot de passe "TP33".

```
mysql> create user 'TP3user3' identified by 'TP33';  
Query OK, 0 rows affected (0.02 sec)  
  
mysql> |
```



2. Accordez à l'utilisateur "TP3user3" tous les privilèges (à l'exception de CREATE et DROP) sur la base de données Cinema.

```
mysql> grant all privileges on cinema.* to 'TP3user3';  
Query OK, 0 rows affected (0.00 sec)  
  
mysql> revoke create , drop on cinema.*  
      -> from 'TP3user3';  
ERROR 1141 (42000): There is no such grant defined for user 'T  
P3user3' on host '%'  
mysql> revoke create,DROP  
      -> ON cinema.*  
      -> FROM 'TP3user3';  
Query OK, 0 rows affected (0.00 sec)  
  
mysql> |
```



i gave all privileges then removed creat and drop

3. Testez tous les privilèges accordés à l'utilisateur "TP3user3".

```


-----+
GRANT USAGE ON *.* TO `TP3user3`@`%`

|

GRANT SELECT, INSERT, UPDATE, DELETE, REFERENCES, INDEX, ALTER,
CREATE TEMPORARY TABLES, LOCK TABLES, EXECUTE, CREATE VIEW,
SHOW VIEW, CREATE ROUTINE, ALTER ROUTINE, EVENT, TRIGGER ON
cinema`.* TO `TP3user3`@`%` |
-----+

```

many privileges ill try to test some



connected

```
SELECT * FROM film;
```

Grid	Filter Rows:	Edit:	Export/Imp
title	DURATION	NATIONALITY	DIRECTOR
Body Guard	120	US	Mark Gordon
ET	165	US	Spielberg
Seven Years in Tibet	115	US	Carl Frandkin
Faut Sauver Le soldat Ryan	162	US	Spielberg
Indiana Jones	170	US	Spielberg
Dernier Chateau	132	US	Rod Lurie
Destin De Will Hunting	120	US	Gus Van Sant

2 •

```
SELECT * FROM produces;
```

Result Grid	Filter Rows:
PRODUCER	TITLE
Roger Taylor	Indiana Jones
Adam Moore	Men
Clint Eastwood	Perfect World
Alex May	Top Gun
NULL	NULL

3 •

```
SELECT * FROM screening;
```

Result Grid	Filter Rows:	Edit:	Export/Imp
TITLE	ROOM	START_TIME	VERSION
Body Guard	Alpha	21:00:00	VO
ET	Ibn Zeidoun	11:00:00	VO
Indiana Jones	Alpha	13:00:00	VF
Le Pacificateur	Beta	23:00:00	VF
Les Incorruptibles	Ibn Zeidoun	13:00:00	VO

screening 3 x

Output


```

4 • UPDATE FILM
5 SET NATIONALITY = 'ALGER'
6 WHERE TITLE = 'BODY GUARD';
7

```

Output



Action Output

		Time	Action	Message
✓	3	10:38:56	SELECT * FROM film LIMIT 0, 1000	16 row(s) returned
✓	4	10:39:40	SELECT * FROM produces LIMIT 0, 1000	4 row(s) returned
✓	5	10:39:59	SELECT * FROM screening LIMIT 0, 1000	8 row(s) returned
✓	6	10:40:32	UPDATE FILM SET NATIONALITY = 'ALGER' WHERE T...	1 row(s) affected Row

Title	DURATION	NATIONAL
CTOR		
Body Guard	120	ALGER
Gordon		
ET	165	US
lberg		

```
6 WHERE TITLE = BODY GUARD ;
```

```
7 • DELETE FROM FILM WHERE TITLE = 'Perfect World';
```

put

Action Output

	Time	Action	Message
4	10:39:40	SELECT * FROM produces LIMIT 0, 1000	4 row(s) returned
5	10:39:59	SELECT * FROM screening LIMIT 0, 1000	8 row(s) returned
6	10:40:32	UPDATE FILM SET NATIONALITY = 'ALGER' WHERE T...	1 row(s) affected R
7	10:41:22	DELETE FROM FILM WHERE TITLE = 'Perfect World'	1 row(s) affected

```
8 • CREATE TABLE UPUP( id INT PRIMARY KEY UNIQUE , name VARCHAR(20))
```

Le Destin De Will

Context Help

Output

Action Output

	Time	Action	Message
5	10:39:59	SELECT * FROM screening LIMIT 0, 1000	8 row(s) returned
6	10:40:32	UPDATE FILM SET NATIONALITY = 'ALGER' WHERE T...	1 row(s) affected Rows matched: 1 Changed: 1 Warnings: 0
7	10:41:22	DELETE FROM FILM WHERE TITLE = 'Perfect World'	1 row(s) affected
8	10:41:43	CREATE TABLE UPUP(id INT PRIMARY KEY UNIQUE , ...	Error Code: 1142. CREATE command denied to user 'TP3u...

denied here i couldnt create is send error

<code>DROP TABLE FILM;</code>			Context Help Sni
ion Output			
	Time	Action	Message
6	10:40:32	UPDATE FILM SET NATIONALITY = 'ALGER' WHERE T...	1 row(s) affected Rows matched: 1 Changed: 1 Warnings: 0
7	10:41:22	DELETE FROM FILM WHERE TITLE = 'Perfect World'	1 row(s) affected
8	10:41:43	CREATE TABLE UPUP(id INT PRIMARY KEY UNIQUE , ...	Error Code: 1142. CREATE command denied to user 'TP3u...
9	10:42:19	DROP TABLE FILM	Error Code: 1142. DROP command denied to user 'TP3user...

command denied also for dropping

• `ALTER TABLE FILM rename CATS;`

out		
Action Output		
	Time	Action
7	10:41:22	DELETE FROM FILM WHERE TITLE = 'Perfect World'
8	10:41:43	CREATE TABLE UPUP(id INT PRIMARY KEY UNIQUE , name VARCHAR(20))
9	10:42:19	DROP TABLE FILM
10	10:43:03	ALTER TABLE FILM rename CATS

even alter table is denied even tho i didnt revoke that access

so the user3 can only do what he have access to or privileges to

4. Supprimez tous les privilèges accordés à l'utilisateur "TP3user3" sur la table SEEN.

```
16 rows in set (0.00 sec)

mysql> revoke all privileges on cinema.* FROM TP3user3;
Query OK, 0 rows affected (0.01 sec)

mysql> show grants for 'TP3user3';
+-----+
| Grants for TP3user3@% |
+-----+
| GRANT USAGE ON *.* TO `TP3user3`@`%` |
+-----+
1 row in set (0.00 sec)
```

5. Supprimez l'utilisateur "TP3user3".

```
1 row in set (0.00 sec)

mysql> drop user 'TP3user3';
Query OK, 0 rows affected (0.01 sec)

mysql> |
```

```
+-----+
1 row in set (0.00 sec)

mysql> select user from mysql.user;
+-----+
| user |
+-----+
| dounia |
| mysql.infoschema |
| mysql.session |
| mysql.sys |
| root |
+-----+
5 rows in set (0.00 sec)
```