



# Chapter 2: Intro to Relational Model

**Database System Concepts, 7<sup>th</sup> Ed.**

©Silberschatz, Korth and Sudarshan

See [www.db-book.com](http://www.db-book.com) for conditions on re-use



# Outline

- Structure of Relational Databases
- Database Schema
- Keys
- Schema Diagrams
- Relational Query Languages
- The Relational Algebra



# Example of a *Instructor* Relation

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
10101	Srinivasan	Comp. Sci.	65000
12121	Wu	Finance	90000
15151	Mozart	Music	40000
22222	Einstein	Physics	95000
32343	El Said	History	60000
33456	Gold	Physics	87000
45565	Katz	Comp. Sci.	75000
58583	Califieri	History	62000
76543	Singh	Finance	80000
76766	Crick	Biology	72000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000

attributes  
(or columns)

tuples  
(or rows)

نکته: توی پایگاه داده رابطه و جدول را هم ارز می گیرند

نکته: توی رابطه بیشتر تعریف مهمه

به ستون های جدول **attributes** می گن

هر سطر جدول اطلاعات یک استاد را نگهداری میکنه

نکته: هر سطر را می توان **tuples** در نظر گرفت

نکته: در مدل رابطه ای اصطلاح رابطه برای اشاره به جدول استفاده میشود و اصطلاح تاپل برای

اشاره به یک سطر و همین طور اصطلاح ویژگی برای اشاره به یک ستون



# Relation Schema and Instance

- $A_1, A_2, \dots, A_n$  are *attributes*
- $R = (A_1, A_2, \dots, A_n)$  is a *relation schema*

Example:

*instructor* = (*ID*, *name*, *dept\_name*, *salary*)

- A relation instance  $r$  defined over schema  $R$  is denoted by  $r(R)$ .
- The current values a relation are specified by a table
- An element  $t$  of relation  $r$  is called a *tuple* and is represented by a *row* in a table

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
10101	Srinivasan	Comp. Sci.	65000
12121	Wu	Finance	90000
15151	Mozart	Music	40000
22222	Einstein	Physics	95000
32343	El Said	History	60000
33456	Gold	Physics	87000
45565	Katz	Comp. Sci.	75000
58583	Califieri	History	62000
76543	Singh	Finance	80000
76766	Crick	Biology	72000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000

attributes  
(or columns)

tuples  
(or rows)



# Attributes

- The set of allowed values for each attribute is called the **domain** of the attribute
- Attribute values are (normally) required to be **atomic**; that is, indivisible
- The special value ***null*** is a member of every domain. Indicated that the value is “unknown”

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
10101	Srinivasan	Comp. Sci.	65000
12121	Wu	Finance	90000
15151	Mozart	Music	40000
22222	Einstein	Physics	95000
32343	El Said	History	
33456	Gold	Physics	87000
45565	Katz	Comp. Sci.	75000
58583	Califieri	History	62000
76543	Singh		80000
76766	Crick	Biology	72000
83821	Brandt	Comp. Sci.	92000
98345	Kim	Elec. Eng.	80000

attributes  
(or columns)

tuples  
(or rows)



# Relations are Unordered

- Order of tuples is irrelevant (tuples may be stored in an arbitrary order)
- Example: *instructor* relation with unordered tuples

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
22222	Einstein	Physics	95000
12121	Wu	Finance	90000
32343	El Said	History	60000
45565	Katz	Comp. Sci.	75000
98345	Kim	Elec. Eng.	80000
76766	Crick	Biology	72000
10101	Srinivasan	Comp. Sci.	65000
58583	Califieri	History	62000
83821	Brandt	Comp. Sci.	92000
15151	Mozart	Music	40000
33456	Gold	Physics	87000
76543	Singh	Finance	80000



# Database Schema

- Database schema -- is the logical structure of the database.
- Database instance -- is a snapshot of the data in the database at a given instant in time.
- Example:
  - schema: *instructor (ID, name, dept\_name, salary)*
  - Instance:

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
22222	Einstein	Physics	95000
12121	Wu	Finance	90000
32343	El Said	History	60000
45565	Katz	Comp. Sci.	75000
98345	Kim	Elec. Eng.	80000
76766	Crick	Biology	72000
10101	Srinivasan	Comp. Sci.	65000
58583	Califieri	History	62000
83821	Brandt	Comp. Sci.	92000
15151	Mozart	Music	40000
33456	Gold	Physics	87000
76543	Singh	Finance	80000





# Keys

- Let  $K \subseteq R$
- $K$  is a **superkey** of  $R$  if values for  $K$  are sufficient to identify a unique tuple of each possible relation  $r(R)$
- That is, if  $t1$  and  $t2$  are in  $r$  and  $t1 \neq t2$ , then  $t1.K \neq t2.K$ .
  - Example:  $\{ID\}$  and  $\{ID, name\}$  are both superkeys of *instructor*.
- Superkey  $K$  is a **candidate key** if  $K$  is minimal  
Example:  $\{ID\}$  is a candidate key for *Instructor*
- One of the candidate keys is selected to be the **primary key**.
  - Which one?
- It is customary to list the primary key attributes of a relation schema before the other attributes. Primary key attributes are also underlined.
- **Foreign key** constraint: Value in one relation must appear in another
  - Example: *dept\_name* in *instructor* is a foreign key from *instructor* referencing *department*
  - Note that in a foreign-key constraint, the referenced attribute(s) must be the primary key of the referenced relation.


----

نکته: برای کلید تکرار بودن نباید وجود داشته باشد مثلا شماره دانشجویی یک کلید است چون فقط منحصر به یک فرد است

نکته: یک چیزی می تونه کلید باشه اگر ما رو منحصر بکنه به یک سطر پس کلید را نمی تونیم ستون در نظر بگیریم



# Schema Diagram for University Database





# Relational Algebra

- A procedural language consisting of a set of operations that take one or two relations as input and produce a new relation as their result.
- Six basic operators
  - select:  $\sigma$
  - project:  $\Pi$
  - union:  $\cup$
  - set difference:  $-$
  - Cartesian product:  $\times$
  - rename:  $\rho$



# Select Operation

- The **select** operation selects tuples that satisfy a given predicate.
- Notation:  $\sigma_p(r)$
- $p$  is called the **selection predicate**
- Example: select those tuples of the *instructor* relation where the instructor is in the “Physics” department.

- Query

$\sigma_{dept\_name="Physics"}(instructor)$

- Result

به این زرده می گن Query

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
22222	Einstein	Physics	95000
33456	Gold	Physics	87000

<i>ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>
22222	Einstein	Physics	95000
12121	Wu	Finance	90000
32343	El Said	History	60000
45565	Katz	Comp. Sci.	75000
98345	Kim	Elec. Eng.	80000
76766	Crick	Biology	72000
10101	Srinivasan	Comp. Sci.	65000
58583	Califieri	History	62000
83821	Brandt	Comp. Sci.	92000
15151	Mozart	Music	40000
33456	Gold	Physics	87000
76543	Singh	Finance	80000



# Select Operation (Cont.)

- We allow comparisons using

$=, \neq, >, \geq, <, \leq$

in the selection predicate.

- We can combine several predicates into a larger predicate by using the connectives:

$\wedge$  (**and**),  $\vee$  (**or**),  $\neg$  (**not**)

- Example: Find the instructors in Physics with a salary greater \$90,000, we write:

$\sigma_{dept\_name="Physics" \wedge salary > 90,000} (instructor)$

- The select predicate may include comparisons between two attributes.

- Example, find all departments whose name is the same as their building name:
- $\sigma_{dept\_name=building} (department)$



# Project Operation

- A unary operation that returns its argument relation, with certain attributes left out.
- Notation:

$$\Pi_{A_1, A_2, A_3 \dots A_k}(r)$$

where  $A_1, A_2, \dots, A_k$  are attribute names and  $r$  is a relation name.

- The result is defined as the relation of  $k$  columns obtained by erasing the columns that are not listed
- Duplicate rows removed from result, since relations are sets



# Project Operation Example

- Example: eliminate the *dept\_name* attribute of *instructor*
- Query:

$\Pi_{ID, name, salary} (instructor)$

- Result:

<i>ID</i>	<i>name</i>	<i>salary</i>
10101	Srinivasan	65000
12121	Wu	90000
15151	Mozart	40000
22222	Einstein	95000
32343	El Said	60000
33456	Gold	87000
45565	Katz	75000
58583	Califieri	62000
76543	Singh	80000
76766	Crick	72000
83821	Brandt	92000
98345	Kim	80000





# Composition of Relational Operations

- The result of a relational-algebra operation is relation and therefore of relational-algebra operations can be composed together into a **relational-algebra expression**.
- Consider the query -- Find the names of all instructors in the Physics department.

اول سلکت ینی از داخلی ترین پرانتز شروع میکنیم

$$\Pi_{name}(\sigma_{dept\_name = "Physics"}(instructor))$$

- Instead of giving the name of a relation as the argument of the projection operation, we give an expression that evaluates to a relation.



# Cartesian-Product Operation

- The Cartesian-product operation (denoted by  $\times$ ) allows us to combine information from any two relations.
- Example: the Cartesian product of the relations *instructor* and *teaches* is written as:

*instructor*  $\times$  *teaches*

- We construct a tuple of the result out of each possible pair of tuples: one from the *instructor* relation and one from the *teaches* relation (see next slide)
- Since the instructor *ID* appears in both relations we distinguish between these attribute by attaching to the attribute the name of the relation from which the attribute originally came.

- *instructor.ID*

- *teaches.ID*



# The *instructor X teaches* table

<i>instructor.ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>	<i>teaches.ID</i>	<i>course_id</i>	<i>sec_id</i>	<i>semester</i>	<i>year</i>
10101	Srinivasan	Comp. Sci.	65000	10101	CS-101	1	Fall	2017
10101	Srinivasan	Comp. Sci.	65000	10101	CS-315	1	Spring	2018
10101	Srinivasan	Comp. Sci.	65000	10101	CS-347	1	Fall	2017
10101	Srinivasan	Comp. Sci.	65000	12121	FIN-201	1	Spring	2018
10101	Srinivasan	Comp. Sci.	65000	15151	MU-199	1	Spring	2018
10101	Srinivasan	Comp. Sci.	65000	22222	PHY-101	1	Fall	2017
...	...	...	...	...	...	...	...	...
...	...	...	...	...	...	...	...	...
12121	Wu	Finance	90000	10101	CS-101	1	Fall	2017
12121	Wu	Finance	90000	10101	CS-315	1	Spring	2018
12121	Wu	Finance	90000	10101	CS-347	1	Fall	2017
12121	Wu	Finance	90000	12121	FIN-201	1	Spring	2018
12121	Wu	Finance	90000	15151	MU-199	1	Spring	2018
12121	Wu	Finance	90000	22222	PHY-101	1	Fall	2017
...	...	...	...	...	...	...	...	...
...	...	...	...	...	...	...	...	...
15151	Mozart	Music	40000	10101	CS-101	1	Fall	2017
15151	Mozart	Music	40000	10101	CS-315	1	Spring	2018
15151	Mozart	Music	40000	10101	CS-347	1	Fall	2017
15151	Mozart	Music	40000	12121	FIN-201	1	Spring	2018
15151	Mozart	Music	40000	15151	MU-199	1	Spring	2018
15151	Mozart	Music	40000	22222	PHY-101	1	Fall	2017
...	...	...	...	...	...	...	...	...
...	...	...	...	...	...	...	...	...
22222	Einstein	Physics	95000	10101	CS-101	1	Fall	2017
22222	Einstein	Physics	95000	10101	CS-315	1	Spring	2018
22222	Einstein	Physics	95000	10101	CS-347	1	Fall	2017
22222	Einstein	Physics	95000	12121	FIN-201	1	Spring	2018
22222	Einstein	Physics	95000	15151	MU-199	1	Spring	2018
22222	Einstein	Physics	95000	22222	PHY-101	1	Fall	2017
...	...	...	...	...	...	...	...	...
...	...	...	...	...	...	...	...	...



# Join Operation

- The Cartesian-Product

*instructor X teaches*

associates every tuple of *instructor* with every tuple of *teaches*.

- Most of the resulting rows have information about instructors who did NOT teach a particular course.
- To get only those tuples of “*instructor X teaches*” that pertain to instructors and the courses that they taught, we write:

$\sigma_{instructor.id = teaches.id} (instructor \times teaches)$

- We get only those tuples of “*instructor X teaches*” that pertain to instructors and the courses that they taught.
- The result of this expression, shown in the next slide



# Join Operation (Cont.)

- The table corresponding to:

$$\sigma_{instructor.id = teaches.id}(instructor \times teaches)$$

<i>instructor.ID</i>	<i>name</i>	<i>dept_name</i>	<i>salary</i>	<i>teaches.ID</i>	<i>course_id</i>	<i>sec_id</i>	<i>semester</i>	<i>year</i>
10101	Srinivasan	Comp. Sci.	65000	10101	CS-101	1	Fall	2017
10101	Srinivasan	Comp. Sci.	65000	10101	CS-315	1	Spring	2018
10101	Srinivasan	Comp. Sci.	65000	10101	CS-347	1	Fall	2017
12121	Wu	Finance	90000	12121	FIN-201	1	Spring	2018
15151	Mozart	Music	40000	15151	MU-199	1	Spring	2018
22222	Einstein	Physics	95000	22222	PHY-101	1	Fall	2017
32343	El Said	History	60000	32343	HIS-351	1	Spring	2018
45565	Katz	Comp. Sci.	75000	45565	CS-101	1	Spring	2018
45565	Katz	Comp. Sci.	75000	45565	CS-319	1	Spring	2018
76766	Crick	Biology	72000	76766	BIO-101	1	Summer	2017
76766	Crick	Biology	72000	76766	BIO-301	1	Summer	2018
83821	Brandt	Comp. Sci.	92000	83821	CS-190	1	Spring	2017
83821	Brandt	Comp. Sci.	92000	83821	CS-190	2	Spring	2017
83821	Brandt	Comp. Sci.	92000	83821	CS-319	2	Spring	2018
98345	Kim	Elec. Eng.	80000	98345	EE-181	1	Spring	2017



# Join Operation (Cont.)

- The **join** operation allows us to combine a select operation and a Cartesian-Product operation into a single operation.
- Consider relations  $r (R)$  and  $s (S)$
- Let “theta” be a predicate on attributes in the schema  $R \cup S$ . The join operation  $r \bowtie_{\theta} s$  is defined as follows:

$$r \bowtie_{\theta} s = \sigma_{\theta} (r \times s)$$

- Thus

$$\sigma_{\text{instructor.id} = \text{teaches.id}} (\text{instructor} \times \text{teaches})$$

- Can equivalently be written as

$$\text{instructor} \bowtie_{\text{Instructor.id} = \text{teaches.id}} \text{teaches.}$$

نکته: دوتا موجودیت هم نام نباید توی پایگاه داده داشته باشیم



# Union Operation

- The union operation allows us to combine two relations
- Notation:  $r \cup s$
- For  $r \cup s$  to be valid.
  1.  $r, s$  must have the **same arity** (same number of attributes)
  2. The attribute domains must be **compatible** (example: 2<sup>nd</sup> column of  $r$  deals with the same type of values as does the 2<sup>nd</sup> column of  $s$ )
- Example: to find all courses taught in the Fall 2017 semester, or in the Spring 2018 semester, or in both

$\Pi_{course\_id} (\sigma_{semester="Fall" \wedge year=2017}(section)) \cup$

$\Pi_{course\_id} (\sigma_{semester="Spring" \wedge year=2018}(section))$

-----

شبیه اجتماع است

اینجا دوتا قید داریم: ینی یه سری محدودیت هایی قرار میدیم چرا؟ چون دیتاهاش میخواد بشینه کنار هم پس باید یه ساختار مشخصی داشته باشه (ینی ظاهر دیتاها واسمون مهم نیست ولی ساختارشون واسمون مهمه) ینی ما نمیتونیم رابطه با 4 ستون رو با رابطه ای با 5 ستون با هم ترکیب کنیم پس قیدی که داریم این است که:

- 1- از لحاظ تعداد با هم بخونن ینی تعداد ستون هاشون یکی باشه
- 2- دامنه اطلاعاتشون مثل هم باشه ینی یکی عدد نباشه و یکی دیگه رشته مثلا میتونیم یه رابطه ای داشته باشیم در مورد استاد و یه رابطه ای در مورد دانشجو و در اخر اینا رو با هم ترکیب کنیم پس مهم نیست اسم رابطه ها فرق داره ینی کلا اسم هاشون هم فرق داشته باشه باز موردی نیست فقط باید اون دوتا شرطو داشته باشه





# Union Operation (Cont.)

- Result of: زرد: تعداد ستون هاش یه دونه است

$\Pi_{course\_id} (\sigma_{semester="Fall" \wedge year=2017}(section)) \cup$

$\Pi_{course\_id} (\sigma_{semester="Spring" \wedge year=2018}(section))$

سبز: تعداد ستون هاش یه دونه است

<i>course_id</i>
CS-101
CS-315
CS-319
CS-347
FIN-201
HIS-351
MU-199
PHY-101

---

توی این مثال تعداد ستون ها و دامنه ها یکیه پس می تونیم ترکیب رو انجام بدیم ولی مثلا اگر یکی رو داشتیم name و یکی دیگه رو داشتیم id در این حالت جنساشون با هم فرق می کرد ینی دامنه یکی میشد رشته و دامنه یکی دیگه میشد عدد پس نمی تونستیم اجتماع بگیریم



# Set-Intersection Operation

- The set-intersection operation allows us to find tuples that are in both the input relations.
- Notation:  $r \cap s$
- Assume:
  - $r, s$  have the same arity
  - attributes of  $r$  and  $s$  are compatible ینی ویژگی  $r, s$  بهم بخورن
- Example: Find the set of all courses taught in both the Fall 2017 and the Spring 2018 semesters.

$$\Pi_{course\_id} (\sigma_{semester="Fall" \wedge year=2017}(section)) \cap \Pi_{course\_id} (\sigma_{semester="Spring" \wedge year=2018}(section))$$

- Result

<i>course_id</i>
CS-101



# Set Difference Operation

- The set-difference operation allows us to find tuples that are in one relation but are not in another.
- Notation  $r - s$
- Set differences must be taken between **compatible** relations.
  - $r$  and  $s$  must have the **same** arity
  - attribute domains of  $r$  and  $s$  must be compatible
- Example: to find all courses taught in the Fall 2017 semester, but not in the Spring 2018 semester

$$\Pi_{course\_id} (\sigma_{semester="Fall" \wedge year=2017}(section)) - \Pi_{course\_id} (\sigma_{semester="Spring" \wedge year=2018}(section))$$

<i>course_id</i>
CS-347
PHY-101



# The Assignment Operation

- It is convenient at times to write a relational-algebra expression by assigning parts of it to temporary relation variables.
- The assignment operation is denoted by  $\leftarrow$  and works like assignment in a programming language.
- Example: Find all instructor in the “Physics” and Music department.

$Physics \leftarrow \sigma_{dept\_name=“Physics”}(instructor)$

$Music \leftarrow \sigma_{dept\_name=“Music”}(instructor)$

$Physics \cup Music$

- With the assignment operation, a query can be written as a sequential program consisting of a series of assignments followed by an expression whose value is displayed as the result of the query.

---

ینی ما بیایم به رابطه ها یه متغیر بدیم مثلا کل رابطه اولی رو بریزیم توی متغیر فیزیک و از اینجا به بعد با این متغیر کار کنیم ولی این متغیر هم باز رابطه حساب میشود



# The Rename Operation

- The results of relational-algebra expressions do not have a name that we can use to refer to them. The rename operator,  $\rho$ , is provided for that purpose
- The expression:

$$\rho_x(E)$$

returns the result of expression  $E$  under the name  $x$

- Another form of the rename operation:

$$\rho_{x(A1,A2, \dots, A_n)}(E)$$

- Example: “Find the ID and name of those instructors who earn more than the instructor whose ID is 12121”

$$\Pi_{I.ID, I.name} ((\sigma_{I.salary > w.salary}(\rho_I(instructor) \times \sigma_{w.ID=12121}(\rho_w(instructor)))))$$

---  
(Px(E ینی خروجی E رو بریز توی x که این x برمیگرده به رابطه ما ینی اسم رابطه رو الان گذاشته x





# Equivalent Queries

- There is more than one way to write a query in relational algebra.
- Example\): Find the instructors in Physics with a salary greater \$90,000  
Query 1

$\sigma_{dept\_name="Physics" \wedge salary > 90,000} (instructor)$

- Query 2

$\sigma_{dept\_name="Physics"} (\sigma_{salary > 90,000} (instructor))$

- The two queries are not identical; they are, however, equivalent -- they give the same result on any database.



# Equivalent Queries

- Example 2: Find information about courses taught by instructors in the Physics department

- Query 1

$\sigma_{dept\_name="Physics"}(instructor \bowtie_{instructor.ID = teaches.ID} teaches)$

- Query 2

$(\sigma_{dept\_name="Physics"}(instructor)) \bowtie_{instructor.ID = teaches.ID} teaches$

پیچیدگی جویین کلا بالاست



## End of Chapter 2