

Technical Manual: Wifi Hotspot Interface

- 1. To access the Wifi hotspot interface, follow these steps:
 - a. Press the **NEXT** button to slide over the tabs until you reach the "About" tab.



b. Press the **SELECT** button to enter the About tab.





c. Press **SELECT** again to switch between the inner tabs within the About tab.



- 2. In the second inner tab of the About tab (tab number 2), you will find the Wifi hotspot interface.
- 3. To open the temporary network, ensure you are in the second inner tab of the About tab, and press the **NEXT** button.





4. Once the **NEXT** button is pressed, a loading spinner will appear (top of the screen between the time and the version), and the text "Press HOME to exit" will change to "Activating wifi, please wait."



- 5. After a few seconds, the screen will display the following network data required for connecting to the wifi interface:
 - SSID (Network name)
 - Password
 - URL to open
 - Time remaining for the network to remain active
 - Number of connections to the network





6 . After you are connected to the network, the URL to open is: http://10.7.13.1:6080 (it will appear also in the screen)

This URL will open the intersection manager UI (user and password needed)

- 7. The network will remain active for 30 minutes. If you need to extend the lease for an additional 30 minutes, press the **NEXT** button again.
- 8. After the initial 30 minutes, the network will be automatically closed and no longer available for connection.
- 9. If no one connects to the network within 10 minutes, the network will also be automatically closed.
- 10. It is not necessary to close the network manually after usage. You can exit the About tab or navigate to other sections while the network remains active until it reaches the timeout.

Please note that this manual assumes prior familiarity with the device's user interface and navigation controls. If you encounter any issues or require further assistance, please contact technical support.