




Edge-centric functional network representations of human cerebral cortex reveal overlapping system-level architecture

Joshua Faskowitz ^{1,2}, Farnaz Zamani Esfahlani¹, Youngheun Jo¹, Olaf Sporns ^{1,2,3,4} and Richard F. Betzel ^{1,2,3,4} ✉




Department of
Biomedical Informatics


Neuroinformatics Journal Club Discussion

Led by Aaron S. Kemp, MBA – PhD Candidate, UAMS



08/05/22




- Define network *nodes* (spatial coordinates or regions of interest)
- Identify a timeseries associated with each node
- Estimate the *edge strengths*, or connections between the nodes
 - For example, correlate each timeseries with every other timeseries
 - If the data (and method for estimating edges) permits the estimation of causality, the edges may be uni-directional, resulting in an asymmetric network matrix




Farahani, Farzad V. (2019). "Application of Graph Theory for Identifying Connectivity Patterns in Human Brain Networks: A Systematic Review". *Frontiers in neuroscience* (1662-4548), 13 .



A IDENTIFICATION OF INTRINSIC CONNECTIVITY NETWORKS (ICNs)



B DYNAMIC FUNCTIONAL NETWORK CONNECTIVITY (dFNC) ESTIMATION AND CLUSTERING



Calhoun, Vince D., et al. The chronnectome: time-varying connectivity networks as the next frontier in fMRI data discovery. *Neuron* 84.2 (2014): 262-274.

An 'edgy' new look


Lucina Q. Uddin

- In traditional graph theoretic analyses of brain networks, functional connectivity (FC) between brain regions—measured as correlation or coherence—is interpreted as an indicator of inter-regional communication³.
- Strong node FC is observed between two brain regions if they exhibit a high level of instantaneous co-fluctuation in their signals and reflects temporally correlated activity between brain regions.
- Faskowitz and colleagues⁴ introduced a new metric they call edge FC (eFC) to capture a different aspect of inter-regional communication: the dynamics of edges themselves.
- If two sets of edges or connections co-fluctuate in concert, they exhibit strong eFC in this new framework.
- The added benefits of tracking eFC across the brain are that it permits analysis of how communication patterns evolve over time and can reveal whether similar patterns of communication are occurring across different parts of the brain simultaneously.

An 'edgy' new look

Lucina Q. Uddin





- There were **three main goals** of the work aiming to introduce eFC to the network neuroscience community:
 - Develop a framework for analyzing eFC using three large, publicly available neuroimaging datasets, the **Human Connectome Project**, **Midnight Scan Club** and **Healthy Brain Network**, to establish feasibility and evaluate the stability of the metric.
 - Partition **eFC networks** to explore **community** structures derived from this novel metric.
 - Assess how eFC can be **modulated** during brain states characterized by changes in **sensory input** during passive viewing of movies.





Are two nodes conversing?
Node functional connectivity



Are conversations similar?
Edge functional connectivity



a




Are two nodes “conversing”?
Node Functional Connectivity




Are “conversations” similar?
Edge Functional Connectivity




b





c



d




e









Overview





- Network neuroscience has relied on a **node-centric network model** in which cells, populations and regions are linked to one another via anatomical or functional connections. This model cannot account for interactions of edges with one another.
- This study introduces an **edge-centric network model** that generates constructs '**edge time series**' and '**edge functional connectivity**' (eFC).
- Using network analysis, this study shows that, at rest, eFC is **consistent** across datasets and **reproducible** within the same individual over multiple scan sessions.
- Clustering eFC yields **communities of edges** that naturally divide the brain into overlapping clusters, with regions in **sensorimotor** and **attentional** networks exhibiting the **greatest levels of overlap**.
- Demonstrate that eFC is systematically **modulated** by variation in **sensory input**. In future work, the edge-centric approach could be useful for identifying novel biomarkers of disease, characterizing individual variation and mapping the architecture of highly resolved neural circuits.






Stability of eFC across datasets



















a**b****c****d****e****f**

Entropy, movie minus rest

**h**

Key Results (selected quotes from article)

- “Here we presented a network model of human cerebral cortex that focused on edge–edge interactions.
- The network formed by these interactions—a construct we referred to as eFC—was similar across datasets and more similar within individuals than between them.
- When clustered, eFC provided a natural estimate of pervasively overlapping community structure.
- We found that the amount of overlap varied across the cortex but peaked in sensorimotor and attention networks.
- We found that brain regions associated with sensorimotor and attention networks participated in disproportionately many communities compared to other brain systems, but that, relative to one another, those same regions participated in similar sets of communities.
- Lastly, we showed that eFC and community overlap varied systematically during passive viewing of movies.”

Conclusions (quotes from article)

- “In this study, we developed a novel **edge-centric representation** of functional neuroimaging data that operates directly on observed time series.
- Our method for estimating connection weights between edges can be viewed as a **temporal ‘unwrapping’ of the familiar Pearson correlation**—the measure frequently used to estimate the magnitude of nFC between pairs of brain regions.
- Whereas the Pearson correlation coefficient calculates the time-averaged co-fluctuation magnitude for node pairs, we simply omit the averaging step, yielding **‘edge time series’**, which represent the **co-fluctuation magnitude** between two nodes at every instant in time.
- This simple step enables us to track fluctuations in edge weight across time and, critically, allow for **dyadic relationships between edges**, creating an edge-centric representation of nervous system architecture.
- If we interpret edge time series as a temporal unwrapping of nFC, which is thought to reflect the aggregate effect of communication processes between neural elements, then edge times series track, with high temporal resolution, the communication patterns between distributed neural elements.”

Future Directions

- eFC might be useful in applications of machine learning and classification of neuroimaging data
- Essentially, eFC time series offer a moment-to-moment assessment of how strongly two nodes (brain regions) co-fluctuate with one another, providing an estimate of **time-varying nFC without the requirement that we specify a window.**
- This overcomes one of the main limitations of sliding window estimates of time-varying nFC, namely that the use of a window leads to a 'blurring' of events across time

a

