Work Instruction - Operations

IMPOSING OR WITHDRAWING TSR



Work description: This OCC Work Instruction details the steps required for the imposition and withdrawal of temporary speed restriction.		
Scope: This Work Instruction is written specification.	ically for OCC operating staff of Honolulu Rail Tr	ansit.
References: N/A		
PPE and precautions	Competencies or qualifications	Licenses or permits required
Track maintenance PPE when accessing lineside	OCC Supervisor, Train Controller, Engineering & Fault Controller, Customer Service Supervisor, Train Operator, Hand signalman, Station Operator	Hand Signalman, Train Driver
Tools and equipment required		
Nil		

Imposing Temporary Speed Restriction

Impact to Train Service Train service will be affected as the journey time will be lengthened by the speed restriction and the distance applied.

There may be some delay to the train service when staff is erecting the Speed Restriction Boards for manually driven trains or Maintenance of Way Vehicles.

OCC Supervisor

- if the imposition is necessary due to technical reasons, obtain the starting and ending locations, the restricted speed value of the temporary speed restriction of each of the affected section(s) of the track from the Engineering & Fault Controller
- if the imposition is necessary due to operational reasons, assess the operational circumstances with the Train Controller to determine the most appropriate values for the speed restriction, the starting and ending locations of the temporary speed restriction section of the track
- instruct the Train Controller to make the necessary arrangements for implementing temporary speed restrictions
- instruct Information Controller to inform the Customer Service Supervisors/Station Operators of the affected stations
- where required, instruct Information Controller to make public announcement to the affected trains and stations

Train Controller

- if the imposition is necessary due to operational reasons, assess the operational circumstances (train service and performance KPI) and inform the OCC Supervisor of the assessment accordingly
- assist OCC Supervisor in determining the starting and ending locations of the speed restriction section of the track

Upon authorized to impose TSR, do the below steps if a MANUAL driven train is running on mainline:

- arrange with Engineering and Fault Controller to deploy maintenance staff to erect Speed Restrictions Boards on the affected section(s) of track along the mainline using Standing Train Protection
- Speed Restriction Boards for each TSR section comprise of:
 - Speed Restriction Warning Board must be erected at the Headwall of the station in advance of the speed restriction. This board provides warnings to train drivers of the upcoming speed restriction section in which the train speed must be reduced before entering the speed restriction section.
 - Speed Restriction Starting Board
 - o Speed Restriction Termination Board



Note

Staff are to use standing train protection to install Speed Restriction Starting Boards and Termination Boards. Trains are to be stopped in the area for the installation of Speed Restriction Warning Boards

Approved By:	☐ Director, Operations and Maintenance	☐ Department Manager	☐ Manager, HSE (Operations and Maintenance)
Signature:			
Date:			

Document Code	YYY.YYY. Imposing or Withdrawing TSR.00	Effective Date:	
File Name	HNL-09408.00.00-1-Imposing or Withdrawing TSR	Rev No. 00	Page 1 of 3

IMPOSING OR WITHDRAWING TSR



	Followed by below steps for AUTO trains on the mainline:	
	 issue the ATS TSR commands specifying the required starting location, the ending location and the restricted speed value on each affected section of track on the ATS workstation (fill in the TSR Form) inform all onboard Train Operators (if any) regarding details of the imposed temporary speed restriction for each of the affected section(s) report to OCC Supervisor on the section(s) for which the temporary speed restriction has been imposed monitor the speed of the first two trains passing through the temporary speed restriction section of the track 	
Engineering & Fault Controller	 if the imposition is necessary due to technical reasons, obtain from the relevant maintenance engineer specific details (starting location, ending location, restricted speed values to be imposed) of the temporary speed restriction on each required section of the track and provide to OCC Supervisor along with the time and duration of the imposition upon being requested by the Train Controller, arrange maintenance staff to erect Speed Restrictions Boards for each affected section of the track along the mainline inform Train Controller upon the completion of placing all the Speed Restriction Boards at the required positions along the mainline by the maintenance staff 	
Train Operator (driving trains manually on mainline)	 monitor the speed of the train at each of the temporary speed restriction section operate the train speed not exceeding the speed restriction when entering the temporary speed restriction section of the track, where the Speed Restriction Starting Board is located, until the train has passed the Speed Restriction Termination Board 	
Customer Service Supervisor	 upon being requested by the Train Controller on the setup of temporary speed restriction, appoint Station Operator qualified as Hand signalman and position them at the Headwall brief the Hand signalman on his/her role before the temporary speed restriction is in effect 	
Hand Signalman	 give a STOP hand signal to (manually driven) trains approaching the station give a "Proceed with Caution" hand signal upon being authorized by the Train Controller 	

Withdrawing Temporary Speed Restriction

Impact to Train Service There will be some delay to train service when staff is withdrawing the Speed Restriction Boards for manually driven trains

OCC Supervisor

- if the imposition is necessary due to technical reasons, obtain confirmation from the Engineering & Fault Controller that the temporary speed restriction can be withdrawn
- instruct the Train Controller to make the necessary arrangements for the withdrawal of temporary speed restrictions
- instruct Information Controller to inform the Customer Service Supervisors/Station Operators of the affected
- where required, instruct Information Controller to make public announcement to the affected trains and stations

Train Controller

Upon authorized to withdraw TSR, do the below steps if a MANUAL driven train is running on mainline:

- arrange with the Customer Service Supervisor at/near the station in advance of the start of the speed restriction to deploy a Hand signalman at the Headwall to prevent any train from entering into the speed restriction section when the maintenance staff is withdrawing the Speed Restriction Boards
- arrange with Engineering and Fault Controller to deploy maintenance staff to withdraw Speed Restrictions Boards on the affected section(s) of track along the mainline
- provide safe paths for the maintenance staff to reach the required locations and back to the station(s)
- once all the Speed Restriction Boards are withdrawn as confirmed by the Engineering and Fault Controller, authorize the Customer Service Supervisor to withdraw the Hand signalman from the Headwall

Document Code	YYY.YYY. Imposing or Withdrawing TSR.00	Effective Date:	
File Name	HNL-09408.00.00-1-Imposing or Withdrawing TSR	Rev No. 00	Page 2 of 3

IMPOSING OR WITHDRAWING TSR



Followed by the below steps for AUTO trains running on the mainline:	
	arrange a Train Operator to use the first available train as sweep train to carry out LINE CLEARANCE to make sure the affected section(s) of the track is clear for the resumption of normal service
	obtain confirmation from the Train Operator that the track is clear
	 issue the ATS TSR withdrawal commands specifying the required starting location, ending location and the normal speed value for each affected section of track on the ATS workstation
	• inform the all onboard Train Operators regarding the withdrawal of temporary speed restriction for each of the affected section(s)
	• report to OCC Supervisor on the section(s) for which the temporary speed restriction has been withdrawn
	• monitor the speed of the first two trains passing through the section of the track that has the temporary speed restriction withdrawn
Engineering & Fault Controller	note the withdrawal of temporary speed restriction on the affected section(s)
Customer Service Supervisor	• upon being requested by the Train Controller on the withdrawal of temporary speed restriction, appoint Station Operator qualified as Hand signalman and position them at the Headwall
	brief the Hand signalman on his/her role before the temporary speed restriction is withdrawn
	upon being requested by the Train Controller to withdraw the Hand signalman, withdraw the Hand signalman from the Headwall
Hand Signalman	give a STOP hand signal to (manually driven) trains approaching the station
	give a "Proceed with Caution" hand signal upon being authorized by the Train Controller