Page Matrix — Technical Reference

Engineering-oriented reference for the **dashboard** ("Is this site agent-ready?"): how it scans pages, how it scores them, how it rolls them up, and the site checks. Since Phase 3 the dashboard uses **the same check engine as the panel** — the old 5-pillar model (`site-score.ts` : Crawlability, Structured, Answerability, Authority, Retrievability) is gone. The checks themselves (IDs, thresholds, credit) are documented once, in `PAGE-CHECKS-TECHNICAL.md` .

Source of truth:

- `src/hooks/useSitePages.ts` — page enumeration, scanning, the score cache, site-check inputs
- `src/lib/checks/` — the engine (see `PAGE-CHECKS-TECHNICAL.md`)
- `src/lib/checks/adapters.ts` — `PageScoreSummary` , `CATEGORY_META`
- `src/lib/site-aggregate.ts` — site roll-up and "Pages to fix first"
- `src/components/{SiteSummary,CategoryCards,SiteChecks,WorstPages,AllPagesView,PageScoreRow}.tsx` — Overview UI
- `src/hooks/useSiteType.ts` — the Site type setting
- `src/types/dashboard.ts` — `PageMatrixRow` , `MatrixFilter`

Scoring model

Each page is scored by `runPageChecks` with a context from `buildPageContext` — the same function the panel uses — and summarised by `summarisePageReport` into a `PageScoreSummary` :

Field	Meaning
`score`	0–100, or `null` when the gate blocks the page or nothing could be scored
`label`	`critical` / `warning` / `good` from `labelForPct` (80 / 60), or `null`
`blocked` , `gateReason`	the gate (P1): Sitecore Robots Meta Tag field, or a rendered noindex / nosnippet / max-snippet:0
`categories`	earned and max points for `reach` , `read` , `understand` , `trust` (max 0 when nothing in that category was scored)

Pools: Essential checks share 80 points, Recommended 20, Bonus adds up to 5, capped at 100. N/A and not-checked results are left out of the pools. Full detail in `PAGE-CHECKS-TECHNICAL.md` .

Rating bands — `labelForPct`, `src/lib/score-thresholds.ts`

Label	Range	Shown as
`good`	≥ 80	Agent-ready (Healthy in the current UI)
`warning`	60–79	Almost there (Needs work)
`critical`	< 60	Not ready (Critical)

The same `READY_PCT` (80) and `ALMOST_PCT` (60) drive the panel's `ScoreRing`, every `ScorePill` and the site roll-up.

Scanning a page (`scanOne`, `useSitePages.ts`)

- **Enumeration:** authoring GraphQL walks the site's Home item 5 levels deep; items with `__Renderings` or `__Final Renderings` are pages. For each it reads `template { name }`, `__Updated`, and the fields the checks read, by the shared names in `SCORING_FIELD_NAMES` (`pageTitle`, `MetaDescription` — overridable with `NEXT_PUBLIC_FIELD_TITLE` / `NEXT_PUBLIC_FIELD_META_DESCRIPTION` — and `robotsMetaTag`). `pageFieldsFromValues` normalises them into `row.fields`, exactly as the panel does. The OG description is also read, only as the llms.txt summary fallback.
- **Scan:** `/api/preview-fetch` for the live HTML, then `/api/ai-check` with `ParsedHtml.mainText` (on `ANTHROPIC_MODEL_BULK`, cached by content hash in localStorage, shared with the panel, and on the server). PageSpeed doesn't run in the dashboard, so P7 is "not checked" and left out of the score.
- **Concurrency:** 5 pages at a time; all unscanned rows scan in the background after enumeration.

Score cache

Summaries are cached in localStorage under `aiDiscovery:scores:v4:<siteId>`, keyed by page URL and reused while the page's `__Updated` is unchanged. **v4** is the unified engine (the shape changed from `SiteScoreResult` to `PageScoreSummary`), so v3 scores from the pillar model are never shown. **Refresh** clears the cache and re-fetches the site-check inputs.

Site roll-up (`site-aggregate.ts`)

- **Overall score:** mean of the page scores. Unscanned and **blocked** pages are left out; blocked pages are counted separately ("N Blocked" in the summary).
- **Category cards:** for each category, the mean of `earned ÷ max` over pages where that category was scored. A page "fails" a category below 40%. The "What's included" list comes from the check registry, so it always matches what's scored.

- **Pages to fix first:** scored pages sorted by score, lowest first. Blocked pages show "Blocked (noindex)" and sort with the unscanned ones.
- **Per-page breakdown:** expanding a row shows the four categories as `earned/max` pills (rounded).

Site checks card

Once per site, the hook fetches `/api/robots-check` and the home page (`/api/preview-fetch` on `<domain>/`), not awaited by enumeration. The page then runs `runSiteChecks` with:

- the home page HTML (null when it couldn't be fetched → S7 is "Couldn't check", N/A),
- robots.txt,
- the organisation for the snippet (`getOrganizationInfo` , `NEXT_PUBLIC_ORG_*` with the site's name and domain as fallbacks) and the configured organisation as the expected value (`getConfiguredOrganization`),
- the site type.

Site checks get **their own site score** (same pool maths) and never feed page scores. Phase 3 has **S2** `reach.robots-ai-rules` (the old 6-crawler robots.txt signal, moved as is) and **S7** `understand.org-schema` (home page Organization JSON-LD, graded with the four agreed rules). Phase 6 adds the rest and moves them to an Agent access tab.

Site type (Content site / Commerce / App or API) is a select in the card, stored per site in localStorage (`aiDiscovery:siteType:v1:<siteId>`). It decides which Bonus protocol checks apply (S11 App/API, S12 Commerce), which arrive in Phase 6, so it has no visible effect yet.

What changed from the pillar model

Old pillar signal	Now
Crawlability: AI crawler permissions	S2 `reach.robots-ai-rules` (site check)
Crawlability: canonical	P2 `reach.canonical` (Essential)
Crawlability: robots meta	P1 gate — blocks the score instead of costing 4 points
Structured: FAQPage / Article / BreadcrumbList	P10 `understand.json-ld` — now validates required properties, reads `@graph` and `@type` arrays, expects FAQPage from real Q&A pairs instead of question H2s
Structured: Organization (home page)	S7 `understand.org-schema` (site check)
Answerability: headings	P8 `understand.headings`
Answerability: question H2s	P13 `understand.question-headings`
Answerability: reading grade + paragraph length	P14 `understand.readability`
Authority: AI uniqueness	P16 `trust.uniqueness`
Authority: content depth	P19 `trust.depth`
Authority: freshness	P18 `trust.freshness` (adds JSON-LD `dateModified`; reads Sitecore's compact date format)
Authority: descriptive anchors	P20 `trust.anchor-text` (prefix rule narrowed, SPIKE-FINDINGS §2)
Retrievability: title + description	P9 `understand.title-meta` (Sitecore field first; title band now 50–60)
Retrievability: OG tags	P11 `understand.metadata` (adds `html lang`, `og:type`)
Retrievability: landmarks	P4 `read.landmarks`
Retrievability: image alt	P15 `understand.image-alt` (N/A without images)

New in the dashboard because it now shares the panel's checks: P11's lang and og:type, P12 FAQ answer quality, P17 author (article templates), P21 follow-up gaps (Bonus). The unused `MatrixView.tsx` table (replaced earlier by `AllPagesView`) was removed with the pillar types.

Demo mode (`?demo=1`)

`makeTestSitePages()` (`src/lib/rule-engine/test-fixture.ts`) builds 12 rows by running the **real engine** on variants of the panel's demo page, so the numbers are consistent: 3 critical, 3 warning, 5 good and 1 blocked (noindex). The row "Blog: content strategy" is the panel's demo page unchanged, so it shows the same score as the panel demo (89). `makeTestSiteContext()` gives the Site checks card a BrandX-style home page with no JSON-LD (S7: 0, warning, snippet) and a robots.txt that blocks GPTBot (S2: half credit).

Key files

Aspect	File
Enumeration, scanning, score cache, site-check inputs	`src/hooks/useSitePages.ts`
Check engine, registry, scoring	`src/lib/checks/`
Summary shape and category labels	`src/lib/checks/adapters.ts`
Site roll-up and worst pages	`src/lib/site-aggregate.ts`
Overview UI	`src/components/SiteSummary.tsx` , `CategoryCards.tsx` , `SiteChecks.tsx` , `WorstPages.tsx` , `AllPagesView.tsx` , `PageScoreRow.tsx`
Site type setting	`src/hooks/useSiteType.ts`
Dashboard types	`src/types/dashboard.ts`
Demo data	`src/lib/rule-engine/test-fixture.ts`