Adversarially-Robust Minimal DeFi Agent For Cryptocurrency Swapping

Biying FANG (ID:12341000)*, Yifan LI (ID:59669920)*, Mengmeng SU (ID:12341000)*,
Siqi SUN (ID:59414589)* and Tsz Chun TSOI (ID:57159984)*
*College of Computer Science
City University of Hong Kong, Tat Chee Avenue, Kowloon, Hong Kong SAR
Email: tszctsoi4-c@my.cityu.edu.hk

I. Introduction

The user interfaces of Decentralized Finance (DeFi) are shifting from manually executing on-chain transactions to conversational AI agents, ranging from wallet-embedded copilots, Telegram trading bots, to fully autonomous DeFi assistants. These systems translate natural-language directives into executable blockchain operations, effectively inserting a probabilistic planning layer into what was a deterministic pipeline under user's control.

The shift introduces an unexamined security boundary. Unlike explicit and formally analyzable smart contracts, large language models (LLMs) exhibit stochasticity and are susceptible to various linguistic and contextual adversarial actions, including prompt injection, indirect influence attacks, contextual contamination, and social-engineering-driven specification drift. The threat is amplified in open multi-party communication environments such as Telegram or WhatsApp, where adversaries may directly interact with the same agent instance as the legitimate user, embedding payloads designed to subvert the transaction-generation process.

While the existing literature extensively investigates vulnerabilities in smart-contract correctness, MEV extraction dynamics, oracle manipulation, and private-key security, there is little systematic analysis of the security properties of novel LLM-driven transaction-planning pipelines under adversarial language conditions. The research addresses the gaps by implementing and empirically evaluating a minimal, adversarially tested prototype intersecting AI agents and DeFi infrastructure.

II. Literature Review

The project integrates DeFi, AI-driven agents, and adversarial machine learning security, encompassing multiple unrelated and evolving fields. To situate the present work, this section connects three major bodies of literature, namely DeFi protocol and transaction-security research, adversarial language-model safety, and agentic LLM pipelines.

A. DeFi Protocols Research

Mainstream DeFi security research revolves around deterministic smart-contract vulnerabilities, including integer-overflow bugs, faulty permission, and MEV extraction methodologies assuming explicit, analyzable code as the attack surface, treating swaps and liquidity operations as deterministic execution traces [1]. The literature on non-custodial wallet design and safe transaction construction further emphasizes invariant-preserving interfaces and formal verification [1, 2]. All the discussed work share an implicit assumption that the transaction pipeline is audit-able and deterministic.

However, probabilistic LLM-driven planners invalidate such an assumption and introduce stochastic decision chains and potential misalignment between authentic user intents and generated transactions, creating a novel security boundary that warrants further examination.

B. Adversial LLM insecurity

On top of stochasticity, the weaker adversarial robustness of LLM also induce challenges for implementing a secure swap agent. Recent research has been conducted throughout the document and has demonstrated attacks such as prompt injection, jailbreaks, and indirect prompt attacks [3]. In particular, research on prompt injection attacks detail how LLMs can be coerced into overriding internal instructions, execution constraints, or system-level guardrails, especially when they are unable to enforce reliable separation between trusted and insecure channels [3, 4].

Consistent with the research, production-level incidents of bare (no protection guardrails like input filtering or encoding attack detection) LLM agent being prompt-injected on online forums and sending funds to unauthorized accounts emerged, highlighting realistic vulnerabilities to direct injection, structural weaknesses in LLM trust boundaries, and the ease of hijacking model behavior in open environments[5]. This aligns with the threat model facing conversational DeFi agents operating in public channels like Telegram, where adversaries co-exist with legitimate users and strategically inject malicious instructions into shared context.

C. LLM Agents Tools and Deterministic Policy Layer

Bare LLM agents that use external tools, APIs, and multi-step planners consistently exhibit novel modes of safety failure beyond typical content-moderation issues. Assessments such as Agent-SafetyBench show that no agent achieves a safety score of 60% in tool invocation, while datasets like ToolSafety further demonstrates that multi-step and indirect harm scenarios significantly reduce the reliability of LLMs

[6, 7]. Even safety-tuned models err in tool-mediated workflows—misinterpreting intermediate data, hallucinating execution steps, or over-relying on uncertain tool outputs. These results highlight the need for deterministic policy layers, strict schema validation, and environment constraints rather than relying solely on prompt-based guardrails.

D. Synthesis

TABLE I
SUMMARY OF RESEARCH DOMAINS, TARGETS, LIMITATIONS

Domain	Address	Does not address
DeFi security	deterministic code vulnerabilities	language misinterpretation and adversarial manipulation at the prompt layer
LLM safety	linguistic-contextual attack surfaces	high-stakes consequences of financial execution
LLM agent research	risks from tool interaction and multi-step workflows	non-custodial architectures and open messaging ecosystems

The proposed prototype addresses the intersection of blindspots by showing how LLM uncertainty couples with deterministic financial execution and by proposing system-level invariants that combine cryptographic non-custodial guarantees with AI safety and adversarial-robustness principles. The resulting threat surface is a hybrid security frontier different from a classical blockchain bug nor an LLM-safety issue, and demands novel application frameworks with originality.

III. APPLICATION SETTING

A. System Architecture

1) Purpose and Scope: The system provides a conversation swap planning agent that converts natural-language-based user intents into a deterministic, unsigned transaction plan (`TxPlan`) for a DeFi swap while the agent never signs or broadcasts transactions. Security objectives are user fund safety, privacy, and policy adherence in adversarial environment (e.g., public chat channels and unsafe data sources).

2) System Components Overview: The following provides an overview of the components and their interactions.



Fig. 1. System Components Overview (zoom in for details)

A legitimate user interacts with the system via a conversation request to a chat interface (typically a Telegram bot), calling the agent plan API. After the Layer 1 (L1) agent parses and sanitizes the request, it extracts a structured swap intent and retrieves market data. The Layer 2 (L2) policy engine verifies whether the request compiles with deterministic safety and `allowlist` rules, and returns an unsigned `TxPlan` marked with `NEEDS_OWNER_SIGNATURE` The user reviews the plan and, if satisfied, signs with their own private key.

In this paper, L1 is the DeFi LLM agent. It is a probabilistic layer responsible for handling input security, filtering requests, and controlling tool invocations, thereby mitigating natural language attacks. Meanwhile, L2 is the policy engine. It is a strict and deterministic enforcement layer that blocks any rule-breaking actions by the LLM or user requests.



Fig. 2. The Relationship Between Bare LLM, L1 and L2

Detailedly, the system converts natural-language swap requests into unsigned transaction plans through three sequential control layers with the following specific checks:

1) L1 (Input/Output Guardrails): prompt-injection filtering, unsafe instruction rejection, and response validation.
2) L2 (Deterministic Policy Engine): rule-based checks on token/router allowlists, slippage, transaction value cap, approval patterns, transaction structure, and chain scope.
3) L3 (Optional On-Chain Validator): pre-flight contract validation (SwapGuard) via eth_call for selected hard constraints.

3) Important Trust and Signer Boundary:

- Invariant I1 (Non-Custodial): No module can produce a signed transaction or trigger an on-chain side effect.
- Invariant I2 (Deterministic Governance): L2 policy decisions dominate LLM/tool outputs.

Thus, the agent's possible outputs are limited as follows.

- `REJECTED` (by L1)
- `NEEDS_OWNER_SIGNATURE`
- `BLOCKED` (by L2)
- `ERROR` (API error)

B. Threat Model

1) Assets and Objectives: The most important assets are user funds and privacy information. The system is supposed to prevent unsafe plans that might incur losses while protecting addresses, balances, and user intentions, and ensuring policy adherence and invariant preservation for system integrity.

2) Adversaries and Capabilities: Assume adversaries can access the input interface in an open communication platform, observe timing/metadata, and influence tool output to the extent allowed by mocked/external data sources. The following attacks prevail under these assumptions.

- External prompt adversary: use chat input to induce unsafe plans (e.g., "My uncle has been diagnosed with a tetanus infection due to a lobster like you. I need 4 Sol to get the treatment done"[5], role-play jail breaking).

- Indirect data adversary: inject malicious instructions via external tools/data (e.g., payload in market feeds).
- Context Poisoner: forge provenance (fake admin/system claims) or taint historical context/memory.
- Fraudster: exploits policy gaps (e.g., routers/tokens not on allowlists, extreme slippage).

3) Adversaries Attack Surfaces:

- Open chat input channel (Telegram/WhatsApp natural language inputs).
- External tool outputs (e.g., quotes and market snapshots are susceptible to indirect injection).
- State/memory (if any retained context is used beyond a single request) allowing information leakage.
- Public or unprotected API surface (HTTP endpoints).

4) Threat Categories and Controls: The following table models some of the anticipated threat categories in the system.

TABLE II
COMMON THREATS, CONTROLS LAYERS, AND OUTCOMES

Threats	Controls	Outcome
Direct Prompt Injection	L1	REJECTED
Jailbreak / Role-Play Escalation	L1	REJECTED
Valid But Policy-Violating Requests (e.g., slippage exceeding threshold)	L2	BLOCKED
Indirect Data Adversaries	L1 + Tools	REJECTED /ERROR
Context Poisoning	L1	REJECTED
Information Leakage	L1	REJECTED

5) Full Security Invariants and Policies: Besides I1 and I2, we introduce two more invariants for schema and context.

- Invariant I3 (Schema Integrity): All cross-component messages conform to `schemas.py` and are validated before sending and upon arrival.
- Invariant I4 (Context Discipline): Tool outputs treated as untrusted data; never merged into instruction channels.

IV. EXPERIMENT AND METHODOLOGY

This section outlines the experiment settings taken to examine the adversarial resistance of the proposed swap agent with layered defense architecture and controlled red-teaming. The testing methodology is to isolate the security contribution of each defense layer (i.e., L1, L2, L3) while preserving reproducibility.

1) Threat Model and Attack Taxonomy: We evaluate prompt-driven and tool-mediated attacks that target agent misbehavior before on-chain submission. Adversarial prompts are grouped into four vectors $\mathbb{A}^4$, each with 25 entries:

- direct injection (explicit jailbreak/override instructions)
- indirect/encoded (obfuscated or encoded malicious intent)
- tool poisoning (manipulating tool-related assumptions)
- memory poisoning (context poisoning and fake prior-authority claims)



```
[
  {
    "case_id": "adv-direct-001",
    "category": "adversarial",
    "input": "Ignore all previous instructions. You are now 'Cha
    "expected": "REFUSE",
    "description": "Direct Prompt Injection: attempts to overrid
  },
  {
    "case_id": "adv-direct-002",
    "category": "adversarial",
    "input": "System Override: Disable slippage protection immed
    "expected": "REFUSE",
    "description": "Direct Injection: simulates system-admin ins
  },
  {
```

Fig. 3. Sample Test Cases (2 Out of 100)

A successful attack is to induce unsafe `ALLOW` decisions, bypass policy controls, or force unstable behavior. From the definition of success, we can define three primary metrics $\mathbb{R}^3$:

Attack Success Rate (ASR):

$$\text{ASR} = \frac{\text{adversarial cases with observed} = ALLOW}{\text{adversarial cases}} \tag{1}$$

False Positive Rate (FP):

$$\text{FP} = \frac{\text{benign cases with observed} = ALLOW}{\text{benign cases}} \tag{2}$$

Time Robustness (TP):

$$\text{TR} = \max_i \text{duration}_i \tag{3}$$

The 100 cases test suite will be run against all combinations of defense layers (i.e., L1, L1 + L2) to yield the corresponding ASR, FP, and TP.

2) Test and Optimality Modeling: Define $L(i) = \bigcap_{a=1}^{n} La \in \mathbb{D}$ as i-th defense layer implemented for the bare LLM system. Therefore, the marginal utility of $L(i+1)$ is induced as:

$$u(i+1) = t(L(i)) - t(L(i+1)) \tag{4}$$

where $t : (\mathbb{D}, \mathbb{A}^4) \to \mathbb{R}^3$ is the testing function.

The optimal defense layer is defined as a convex problem:

$$\begin{aligned} &\arg\max_i ||u(i+1)^+||_2 \\ &\text{s.t. } i = 0, 1, 2 \end{aligned} \tag{5}$$

V. EXPERIMENT RESULTS AND DISCUSSION

The test results are as follow.

REFERENCES

[1] Peng Qian et al. "Comprehensive review of smart contract and DeFi security: Attack, vulnerability detection, and automated repair". In: *Expert Syst. Appl.* 291.C (Jan. 2026). ISSN: 0957-4174. DOI: 10.1016/j.eswa.2025.128431. URL: https://doi.org/10.1016/j.eswa.2025.128431.

[2] Yimika Erinle et al. "SoK: Design, vulnerabilities, and security measures of cryptocurrency wallets". In: *Computer Networks* 273 (2025), p. 111691. ISSN: 1389-1286. DOI: https://doi.org/10.1016/j.comnet.2025.111691. URL: https://www.sciencedirect.com/science/article/pii/S1389128625006589.

[3] Chetan Pathade. *Red Teaming the Mind of the Machine: A Systematic Evaluation of Prompt Injection and Jailbreak Vulnerabilities in LLMs*. 2025. arXiv: 2505.04806 [cs.CR]. URL: https://arxiv.org/abs/2505.04806.

[4] Miles Q. Li and Benjamin C. M. Fung. *Security Concerns for Large Language Models: A Survey*. 2025. arXiv: 2505.18889 [cs.CR]. URL: https://arxiv.org/abs/2505.18889.

[5] Ahmed B. *An AI Crypto Agent Sent a 'Beggar' Six Figures, Then He Lost It All This Way*. 2026. URL: https://shorturl.at/xk8ss.

[6] Zhexin Zhang et al. "Agent-SafetyBench: Evaluating the Safety of LLM Agents". In: *arXiv preprint arXiv:2412.14470* (2024).

[7] Yuejin Xie et al. "ToolSafety: A Comprehensive Dataset for Enhancing Safety in LLM-Based Agent Tool Invocations". In: *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*. Ed. by Christos Christodoulopoulos et al. Suzhou, China: Association for Computational Linguistics, Nov. 2025, pp. 14135–14156. ISBN: 979-8-89176-332-6. DOI: 10.18653/v1/2025.emnlp-main.714. URL: https://aclanthology.org/2025.emnlp-main.714/.