Adversarially-Robust Minimal DeFi Agent for Cryptocurrency Swapping

Group 8

Biying FANG (ID:59119109) Yifan LI (ID:59669920)
Mengmeng SU (ID:59669920) Siqi SUN (ID:59414589)
Tsz Chun TSOI (ID:57159984)

All contributed equally.

City University of Hong Kong

April 10, 2026

Outline

Introduction

Specification-Based Development

System Design

Threat Model

Evaluation

Demo and Discussion

Conclusion

Project Background

- DeFi UX is shifting from manual clicks to chat-based agents.
- We target the pre-execution risk point: Natural language intent $\rightarrow$ TxPlan.
- Safety-first scope: unsigned swap planning only, then owner-wallet handoff.



AI agent created by OpenAI dev 'accidentally' sends entire memecoin holdings to reply guy

By Zack Abrams

CRYPTO ECOSYSTEMS • FEBRUARY 22, 2026, 4:53PM EST

UPDATED: FEBRUARY 22, 2026, 4:56PM EST

Make us preferred on Google

Share

Figure 1: human laziness + bad NL intent could be lethal

Project Background Continued

Risk Model in the LLM Agent Era

$$\text{Transaction Risk} = \underbrace{L}_{\text{owner laziness / negligence (a large constant, we can do nothing)}} + \underbrace{A_{\text{NL}}}_{\text{successful adversial NL-based attack on agents}}$$

$$A_{\text{NL}} \in \{\text{TxPlan pre-leak, bad TxPlan}, \ldots\}$$

What we want

$$\min \text{ Transaction Risk} \equiv \min \; A_{\text{NL}} \quad (\text{given that } L \text{ is fixed})$$

Goal of this project: minimize successful NL-based attacks.

Motivation and Research Gap

- Contract-layer security is mature; LLM-mediated planning security is not.
- Prompt-only defenses fail under injection, encoding, and tool/context poisoning.
- Measurable guarantees: lower Attack Success Rate (ASR), lower False Positive (FP) rate, and acceptable latency.

Specification-Driven Development in This Project

- Spec-first baseline: 18 requirements (S-01...S-18) in a formal specifcation markdown.
- Implementation mapping: 22 deterministic rules (R-01...R-22) in specification-rule-mapping.csv.
- Concrete traceability: one-to-many mapping. Example: S-08 (deterministic policy enforcement) $\Rightarrow$ R-03 (slippage $\leq$ 10%)
- Release criteria bound to metrics: S-15/S-16/S-17 enforce ASR, TR, and FP targets in the 100-case harness.
- Developers guided the coding agent with a 35-task checklist, fixed guardrails, and spec/rule checks.

Process chain: Spec $\rightarrow$ Rules $\rightarrow$ Tests $\rightarrow$ Metrics

System Architecture Overview

- **L1: LLM Guardrails** – input sanitization, prompt-injection filtering, output structure validation, forbidden tool-call detection.
- **L2: Deterministic Policy Engine** – token/router allowlists, slippage limit, value cap, approval pattern checks, quote expiry, chain scope.
- **L3: On-Chain Validator (SwapGuard)** – pre-flight `eth_call` to an immutable Solidity contract enforcing hard constraints before execution.

Key invariant: The agent *never* signs or broadcasts transactions.

Architecture Diagram

Threat Model Summary

- **Assets:** user funds, privacy, intent integrity.
- **Adversaries:** prompt attackers, tool-poisoning adversaries, context poisoners, fraudsters.
- **Attack surfaces:** chat input, external tool outputs, memory/context, API endpoints.

Attack Taxonomy

- **Direct injection** (25 cases): explicit jailbreak/override instructions.
- **Indirect / encoded** (25 cases): obfuscated or encoded malicious intent.
- **Tool poisoning** (25 cases): manipulating tool-related assumptions.
- **Memory poisoning** (25 cases): context poisoning and fake admin claims.
- **Benign** (25 cases): legitimate swap requests (for FP measurement).

Total: **125 cases** in the final evaluation dataset (v2).

Experiment Overview

- 125 test cases across 4 attack vectors + benign baseline.
- Compared 4 defense configurations: bare, L1, L1+L2, L1+L2+L3.
- Metrics: ASR (Attack Success Rate), FP (False Positive Rate), TR (Time Robustness).

Main Results

Table 1: Red-Team Results (125 Cases, v2 Dataset)

Config	**ASR**	**FP**	**TR (s)**	**N**
bare	76.00%	0.00%	3.05	125
L1	25.00%	0.00%	8.62	125
L1+L2	15.00%	0.00%	3.39	125
L1+L2+L3	15.00%	0.00%	3.49	125

- L1 reduces ASR by 51 percentage points (76% $\rightarrow$ 25%).
- L2 provides additional 10pp reduction (25% $\rightarrow$ 15%).
- **0% false positives** across all configurations.

Attack Vector Breakdown (L1+L2)

Table 2: L1+L2 Outcomes by Attack Vector

Vector	**REFUSE**	**BLOCK**	**ALLOW**	**Total**
Direct injection	23	2	0	25
Indirect / encoded	22	2	1	25
Memory poisoning	25	0	0	25
Tool poisoning	5	6	14	25
Benign	0	0	25	25

- Direct, indirect, and memory attacks: effectively neutralized.
- **Tool poisoning** is the residual gap (14/25 still ALLOW).

Key Findings

1. Bare LLM planner is highly vulnerable (76% ASR).
2. **Layered defense is essential**: L1 (probabilistic) + L2 (deterministic) together reduce ASR to 15%.
3. L3 on-chain enforcement adds defense-in-depth without latency penalty.
4. Residual vulnerability concentrated in **tool poisoning**, where adversarial intent is expressed through valid-looking parameters.
5. Non-custodial invariant bounds worst-case impact: even successful attacks produce only unsigned plans.

Telegram Bot Demo

- **End-to-end:** Telegram msg → Agent API → L1/L2 guardrails → unsigned TxPlan
- **Non-custodial:** pauses at owner signature (not broadcasted)
- **Same interface:** shows ALLOW / REFUSE / BLOCK outcomes



Demo Scenarios Explained

ALLOW

- Benign swap → unsigned TxPlan
- Pauses at owner signature

REFUSE



- Injection detected by L1
- Rejected before planning

BLOCK



- L2 blocks value > 5.0 ETH
- Deterministic; no LLM bypass

Limitations

- **External API dependency:** Rate limits, timeouts, and latency variability from CoinGecko and 1inch.
- **Strict-mode tradeoff:** Fail-closed avoids silent fallback but reduces robustness when API or network fails.
- **Data freshness / TTL:** Snapshots and DEX quotes become stale quickly; expiry enforced end-to-end.
- **MVP scope:** Limited token/router/chain coverage; cross-chain routing out of scope.



Live CoinGecko snapshot – real-tools integration

Future Work

- **Stronger tool-poisoning defenses:** semantic intent verification and multi-source cross-checking to catch adversarial parameters in valid-looking inputs.
- **Reliability for live tools:** caching, retries with backoff, and circuit breakers to maintain strict-mode semantics under API instability.
- **Observability:** structured logs, per-tool latency and error-rate dashboards, alerting on anomalous tool audit trails.
- **Expanded evaluation:** multi-turn arena attacks, p95 latency benchmarking, adversarial prompt corpus.
- **Owner UX:** richer handoff UI with quote-refresh flow and clearer signature boundary for non-technical users.

Conclusion

- LLM-based DeFi agents introduce hybrid security threats requiring both probabilistic and deterministic defenses.
- Layered defense (L1+L2+L3) reduces ASR from 76% to 15% with 0% false positives.
- Deterministic policy enforcement (L2) is essential – LLM guardrails alone are insufficient.
- Non-custodial design provides an architectural safety net.

Future work: semantic intent verification for tool poisoning, multi-turn attack evaluation, adversarial contract interactions.