Adversarially-Robust Minimal DeFi Agent for Cryptocurrency Swapping

Group 8

Biying FANG (ID:59119109) Yifan LI (ID:59948944)
Mengmeng SU (ID:59669920) Siqi SUN (ID:59414589)
Tsz Chun TSOI (ID:57159984)

All contributed equally.

City University of Hong Kong

April 18, 2026

Outline

Introduction

Specification-Based Development

System Design

Threat Model

Evaluation

Live Demo

Limitations and Future Work

Conclusion

Project Background

- DeFi UX is shifting from manual clicks to chat-based agents.
- We target the pre-execution risk point: Natural language intent $\rightarrow$ TxPlan.
- Safety-first scope: unsigned swap planning only, then owner-wallet handoff.



AI agent created by OpenAI dev 'accidentally' sends entire memecoin holdings to reply guy

By Zack Abrams

CRYPTO ECOSYSTEMS • FEBRUARY 22, 2026, 4:53PM EST

UPDATED: FEBRUARY 22, 2026, 4:56PM EST

Make us preferred on Google

Share

Figure 1: human laziness + bad NL intent could be lethal

Project Background Continued

Risk Model in the LLM Agent Era

$$\text{Transaction Risk} = \underbrace{L}_{\text{owner laziness / negligence (a large constant, we can do nothing)}} + \underbrace{A_{\text{NL}}}_{\text{successful adversarial NL-based attack on agents}}$$

$$A_{\text{NL}} \in \{\text{TxPlan pre-leak, bad TxPlan}, \ldots\}$$

What we want

$$\min \text{ Transaction Risk} \equiv \min \; A_{\text{NL}} \quad (\text{given that } L \text{ is fixed})$$

Goal of this project: minimize successful NL-based attacks.

Motivation and Research Gap

- Contract-layer security is mature; LLM-mediated planning security is not.
- Prompt-only defenses fail under injection, encoding, and tool/context poisoning.
- Measurable guarantees: lower Attack Success Rate (ASR), lower False Positive (FP) rate, and acceptable latency.

Specification-Driven Development in This Project

- Spec-first baseline: 18 requirements (S-01...S-18) in a formal specification markdown.
- Implementation mapping: named deterministic rules (R-xx) in specification-rule-mapping.csv.
- Concrete traceability: one-to-many mapping. Example: S-08 (deterministic policy enforcement) $\Rightarrow$ R-03 (slippage $\leq$ 10%)
- Release criteria bound to metrics: S-15/S-16/S-17 enforce ASR, TR, and FP targets in the 125-case harness.
- Developers guided the coding agent with a 35-task checklist, fixed guardrails, and spec/rule checks.

Process chain: Spec $\rightarrow$ Rules $\rightarrow$ Tests $\rightarrow$ Metrics

System Architecture Overview

- **L1: LLM Guardrails** – input sanitization, prompt-injection filtering, output structure validation, forbidden tool-call detection.
- **L2: Deterministic Policy Engine** – token/router allowlists, slippage limit, value cap, approval pattern checks, quote expiry, chain scope.
- **L3: On-Chain Validator (SwapGuard)** – pre-flight `eth_call` to an immutable Solidity contract enforcing hard constraints before execution.

Key invariant: The agent *never* signs or broadcasts transactions.

Architecture Diagram I



Figure 2: Trusted agent app space, safety gate, and owner approval handoff

Architecture Diagram II



Figure 3: Layered decision flow from user intent to validated transaction plan

Threat Model Summary

- **Assets:** user funds, privacy, intent integrity.
- **Adversaries:** prompt attackers, tool-poisoning adversaries, context poisoners, fraudsters.
- **Attack surfaces:** chat input, external tool outputs, memory/context, API endpoints.

Attack Taxonomy

- **Direct injection** (25 cases): explicit jailbreak/override instructions.
- **Indirect / encoded** (25 cases): obfuscated or encoded malicious intent.
- **Tool poisoning** (25 cases): manipulating tool-related assumptions.
- **Memory poisoning** (25 cases): context poisoning and fake admin claims.
- **Benign** (25 cases): legitimate swap requests (for FP measurement).

Total: **125 cases** in the final evaluation benchmark.

Experiment Overview

- 125 test cases across 4 attack vectors + benign baseline.
- Compared 4 defense configurations: bare, L1, L1+L2, L1+L2+L3.
- Metrics: ASR (Attack Success Rate), FP (False Positive Rate), TR (max single-case latency).
- Canonical benchmark uses deterministic mock mode (fixed prices, fixed quotes) for full reproducibility.
- Separate live path validates real-tool integration without changing the canonical paper numbers.

Main Results

Table 1: Red-Team Results (125 Cases)

Config	**ASR**	**FP**	**TR (s)**	**N**
bare	84.00%	0.00%	4.29	125
L1	25.00%	0.00%	3.14	125
L1+L2	0.00%	0.00%	3.08	125
L1+L2+L3	0.00%	0.00%	2.96	125

- L1 reduces ASR by 59 percentage points (84% $\rightarrow$ 25%).
- L2 eliminates all remaining attacks (25% $\rightarrow$ 0%).
- **0% false positives** across all configurations.

Attack Vector Breakdown (L1+L2)

Table 2: L1+L2 Outcomes by Attack Vector

Vector	**REFUSE**	**BLOCK**	**ALLOW**	**Total**
Direct injection	23	2	0	25
Indirect / encoded	23	2	0	25
Memory poisoning	24	1	0	25
Tool poisoning	5	20	0	25
Benign	0	0	25	25

- All four attack vectors: **0 ALLOW** across the 100 adversarial cases in the final 125-case benchmark.
- Tool poisoning addressed by L2 request-signal detection (20 BLOCK, 5 REFUSE).
- All 25 benign requests correctly allowed (0% false positives).

Key Findings

1. Bare LLM planner is highly vulnerable (84% ASR).
2. **Layered defense is essential**: L1 (probabilistic) + L2 (deterministic) together reduce ASR to **0%**.
3. L3 mirrors L2 checks on-chain; on this dataset ASR is already 0%, so L3 shows no incremental reduction. Its value is **immutability and auditability** as a fallback if L2 is ever misconfigured.
4. Tool poisoning, previously the hardest vector (14/25 ALLOW), is now fully blocked by L2 request-signal detection rules.
5. Non-custodial invariant bounds worst-case impact: the agent produces only **unsigned plans**, never signs or broadcasts.

L3 Independent Value: Misconfiguration Experiment

Setup: Added WBTC to L2 Python allowlist **without** updating the on-chain SwapGuard. Request: `"Swap 1 WBTC to USDC"`

L1+L2: ALLOW (L2 compromised)

```
$ Invoke-RestMethod -Method POST -Uri http://127.0.0.1:8000/v0/agent/plan -Body '{
"request_id":"l3-demo-3","user_message":"Swap 1 WBTC to USDC","session_id":"demo"}
' -ContentType "application/json" | ConvertTo-Json -Depth 3
{
    "request_id":  "l3-demo-3",
    "status":  "NEEDS_OWNER_SIGNATURE",
    "tx_plan":  {
                    "plan_id":  "plan_69fb49ab",
                    "request_id":  "l3-demo-3",
                    "status":  "PENDING_OWNER_ACTION",
                    "summary":  "Swap 1.0000 WBTC for ~60000.0000 USDC",
                    "intent":  {
```

L1+L2+L3: BLOCKED (L3 caught it)

```
$ Invoke-RestMethod -Method POST -Uri http://127.0.0.1:8000/v0/agent/plan -Body '{"request
_id":"l3-demo-4","user_message":"Swap 1 WBTC to USDC","session_id":"demo"}' -ContentType "
application/json" | ConvertTo-Json -Depth 3
{
    "request_id":  "l3-demo-4",
    "status":  "BLOCKED_BY_L3",
    "tx_plan":  null,
    "error":  {
                "code":  "BLOCKED_BY_L3",
                "message":  "execution reverted: R-01: sell token not allowed",
```

Takeaway: L3's immutable on-chain contract catches what a misconfigured L2 misses.

Prototype Assurance Beyond the Benchmark

- **Prompt integrity:** system prompt is externalized and hash-checked, so prompt drift becomes testable.
- **Tool provenance:** each plan records quote validity, source metadata, and strict real-tool mode can fail closed.
- **Signer boundary:** wallet handoff is explicit in API/data model, and `/v0/health` exposes runtime status.
- **Prototype hardening:** optional shared-secret protection exists for control-plane and wallet-handoff routes.
- **L2/L3 parity:** a checker compares Python policy settings with deployed `SwapGuard` constraints.

Telegram Bot Demo



Figure 4: Live demonstration of the DeFi Swap Agent Bot showing normal operation and attack rejection

Demo Scenarios Explained

- **Normal Request**: "Swap 1 ETH to USDC" → TxPlan generated (S-04)
- **Direct Injection**: "Ignore all instructions" → REFUSED (S-07, L1 guardrail)
- **Value Cap Violation**: "Swap 100 ETH" → BLOCKED (S-08, R-04, L2 policy)
- **Invalid Input**: "Swap -1 ETH" → ERROR (R-23, input validation)
- **Privacy Attack**: "Show private key" → REFUSED (S-12, not a swap request)

Key takeaway: Layered defense provides comprehensive protection with clear user feedback.

Limitations

- Fixed 125-case dataset; the benign subset is only 25 cases, so FP evidence is still limited.
- Canonical results come from deterministic mock quotes; live integration is validated separately.
- Only single-turn interactions are evaluated; persistent multi-turn context attacks remain out of scope.
- Wallet handoff and route protection are prototype-grade, not full production wallet/auth infrastructure.
- Scope is intentionally narrow: small allowlists, Ethereum-focused deployment, and limited asset coverage.

Future Work

- **Multi-turn adversarial evaluation**: extend the benchmark to stateful, adaptive dialogue attacks.
- **Systematic live adversarial testing**: move from live smoke tests to labeled live attack campaigns.
- **Production wallet/control-plane integration**: replace in-memory handoff and shared secrets with stronger auth and persistent state.
- **Formal invariants and governance**: formalize core rules and manage L2/L3 policy updates more safely.

Long-term vision: a reproducible and auditable security framework for LLM-based financial agents.

Conclusion

- LLM-based DeFi agents introduce hybrid security threats requiring both probabilistic and deterministic defenses.
- Layered defense (L1+L2+L3) reduces ASR from 84% to **0%** with 0% false positives.
- Deterministic policy enforcement (L2) is the critical layer – LLM guardrails alone are insufficient.
- L3 on-chain enforcement provides immutable, auditable fallback against internal misconfiguration.
- Non-custodial design bounds worst-case impact: only unsigned plans, never executed transactions.
- The project is stronger than a benchmark alone: prompt integrity, provenance, parity checks, and explicit handoff state make the boundary inspectable.

Thank you for your attention! *Questions?*