Adversarially-Robust Minimal DeFi Agent For Cryptocurrency Swapping

Biying FANG (ID:59119109)*, Yifan LI (ID:59948944)*, Mengmeng SU (ID:59669920)*,
Siqi SUN (ID:59414589)* and Tsz Chun TSOI (ID:57159984)*
*College of Computer Science
City University of Hong Kong, Tat Chee Avenue, Kowloon, Hong Kong SAR
Email: tszctsoi4-c@my.cityu.edu.hk

Source code:
https://github.com/horserosemilkshake/CS6290-Group-8-Project

***Abstract*—Large language model (LLM) agents are starting to mediate DeFi workflows, but their security properties remain unclear when they operate over open, adversarial natural-language channels. We present a minimal non-custodial DeFi swap agent that converts user requests into unsigned transaction plans and evaluates them through three layers: L1 language-facing guardrails, an L2 deterministic policy engine, and an optional L3 on-chain validator. The system is developed in a specification-driven manner and evaluated on a fixed final 125-case dataset containing 100 adversarial prompts across four attack vectors plus 25 benign requests. L1+L2 reduces Attack Success Rate (ASR) from 84% in the bare configuration to 0% while maintaining a 0% false-positive rate. L3 does not further reduce ASR on this benchmark, but a targeted misconfiguration experiment shows that it can catch configuration drift that escapes the Python layer. Beyond the benchmark, the prototype externalizes and hash-checks its system prompt, records tool provenance and quote-validity metadata in each plan, and exposes explicit owner-signature handoff interfaces that make the signer boundary observable in both testing and live demos. The main lesson is that DeFi agents should treat LLM output as untrusted and place deterministic enforcement on the critical path before the owner-signature handoff.**

I. Introduction

DeFi user interfaces are moving from manual wallet interactions toward conversational agents embedded in bots, wallets, and copilots. This shift is convenient for users, but it also inserts a probabilistic planning layer into what used to be a more explicit and user-controlled transaction pipeline.

That change creates a new security boundary. Smart contracts remain explicit and auditable, but an LLM planner can be influenced by prompt injection, context poisoning, encoded instructions, and tool-output manipulation. The risk is especially important in open communication channels such as Telegram, where benign users and adversaries can reach the same agent-facing interface surface [1].

Most prior work on DeFi security focuses on smart-contract bugs, MEV dynamics [2], oracle manipulation, or wallet key management. Much less work studies the security of LLM-mediated transaction planning under adversarial language conditions. Our project addresses that gap through a minimal DeFi swap agent whose scope is intentionally narrow: it plans plain swap requests, never signs or broadcasts transactions, and hands off only unsigned plans to the owner.

This paper makes five concrete contributions. First, we design and implement a three-layer defense architecture for non-custodial DeFi swap planning. Second, we show how a specification-driven workflow links requirements, rules, tests, and final metrics. Third, we expose the signer boundary as an explicit API- and data-model concept rather than leaving it implicit inside the UI. Fourth, we evaluate the system on a fixed final 125-case benchmark and complement the main benchmark with a targeted L3 misconfiguration experiment that clarifies the value of on-chain defense-in-depth. Fifth, we separate canonical reproducible benchmarking from live external-tool validation, allowing the same prototype to support both stable measurement and credible demos.

II. Literature Review

This work sits at the intersection of three literature streams: DeFi transaction security, adversarial LLM safety, and tool-using LLM agents. We review each stream to identify the gap addressed by our architecture.

A. DeFi Protocols Research

Mainstream DeFi security research focuses on deterministic smart-contract vulnerabilities, such as arithmetic errors, faulty permissions, and MEV-related execution risks, under the assumption that the transaction pipeline is explicit and analyzable [3]. Work on non-custodial wallet design and safe transaction construction similarly emphasizes invariant-preserving interfaces and strong separation between planning, signing, and execution [3], [4]. Across these lines of work, the planner is usually treated as deterministic.

LLM-based planners break that assumption. They introduce stochastic decision chains and possible misalignment between authentic user intent and generated transactions, creating a security boundary that classical DeFi analysis does not address well.

B. Adversarial LLM Insecurity

LLMs have limited adversarial robustness. Prior work documents prompt injection, jailbreaks, and indirect prompt attacks [5], [6]. In particular, prompt-injection research shows that models can be induced to override instructions, execution constraints, or system-level guardrails when trusted and untrusted channels are not reliably separated [5], [7].

Reported incidents involving weakly protected LLM agents further suggest that direct injection is not only a theoretical concern [8]. These failures align closely with the threat model of conversational DeFi agents in public channels, where adversaries and legitimate users share the same interaction surface and compete to influence the planner.

C. LLM Agents Tools and Deterministic Policy Layer

LLM agents that use external tools, APIs, and multi-step planners show safety failures beyond conventional content moderation. Benchmarks such as Agent-SafetyBench and ToolSafety report weak reliability in tool invocation and multi-step harmful scenarios [9], [10]. Even safety-tuned models can misread intermediate data, hallucinate execution steps, or over-trust uncertain tool outputs. These results motivate deterministic policy layers, strict schema validation, and explicit environment-level constraints instead of prompt-only defenses.

D. Synthesis

TABLE I
WHAT EXISTING LITERATURE COVERS AND MISSES

Stream	Covers	Misses
DeFi security	Deterministic contract bugs and execution risks	Prompt-layer misinterpretation and adversarial language manipulation
LLM safety	Linguistic and contextual attack surfaces	Financial execution consequences and signer-boundary design
LLM agent research	Tool-use failures and multi-step agent risk	Non-custodial transaction planning in open messaging environments

Table I highlights these complementary blind spots. Our prototype addresses the intersection by showing how LLM uncertainty couples with deterministic financial execution. The resulting threat surface is neither a classical smart-contract bug nor a standard LLM-safety problem; it is a hybrid security problem that requires a dedicated application architecture.

III. SPECIFICATION-DRIVEN DEVELOPMENT

The project was developed in a specification-driven manner rather than as a purely prompt-driven prototype. We first defined 18 project-level specifications (`S-01` to `S-18`) covering functionality, security, benchmarking, and performance. We then mapped these specifications to a named implementation-rule set (`R-xx`) and linked those rules to tests, harness logic, and report metrics. A 35-task development checklist (`docs/specification/task-list-llm.md`) guided the implementation and test ordering applied during the development process. This workflow matters for an LLM-based financial system because it reduces specification drift: the report, the code, and the evaluation all refer back to the same named requirements.

Table II summarizes the most important traceability links used in the final system. Not every rule belongs to the L2 policy engine; some govern L1 behavior, signer-boundary handling, L3 mirroring, or the measurement pipeline itself.

TABLE II
REPRESENTATIVE REQUIREMENT-TO-IMPLEMENTATION TRACEABILITY

Spec	Meaning	Implementation Evidence
`S-04`, `S-05`	Generate only unsigned plans and pause at the signer boundary	`TxPlan` includes unsigned transaction data plus signer-boundary metadata; the API exposes explicit handoff routes before any owner action.
`S-07`, `S-09`	Reject prompt injection and encoded or untrusted control content before planning	L1 input guardrail filters malicious templates, flags encoded content, sanitizes markup, and rejects unsafe requests before the LLM plan is used.
`S-08`	Enforce non-overridable deterministic policy checks	L2 evaluates token/router allowlists, slippage, value cap, approval scope, request-shape sanity, quote freshness, chain scope, and unsafe request overrides.
`S-10`	Optionally mirror hard constraints on-chain	`SwapGuard` and the Python L3 validator mirror token, router, slippage, and value-cap constraints through `eth_call`.
`S-14`–`S-17`	Measure robustness on a fixed benchmark	`scripts/run_integration_test.py` freezes the final 125-case dataset, computes ASR/FP/TR, and regenerates report figures and the threat-model summary.

The process chain used in the project is therefore:

$$\text{Specifications} \rightarrow \text{Rules} \rightarrow \text{Tests} \rightarrow \text{Metrics}$$

This report follows the same chain. It uses one frozen benchmark, stored at `testcases/final_attack_dataset.json`, as the sole dataset for the final evaluation.

IV. SYSTEM AND THREAT MODEL

A. System Architecture

1) Purpose and Scope: The system is a conversational swap-planning agent that converts natural- language user intents into an unsigned transaction plan (`TxPlan`) for a DeFi swap. The agent never signs or broadcasts transactions. Its security goals are fund safety, privacy preservation, and deterministic policy adherence in adversarial environments such as public chat channels and untrusted data sources.

2) System Components Overview: Figure 1 summarizes the system boundary and the owner-signature handoff.

A legitimate user submits a request through a chat interface, typically a Telegram bot, which forwards the request to the



Fig. 1. System boundary, trusted agent space, and owner-signature handoff.

planning API. L1 sanitizes the input, parses a structured swap intent, and coordinates quote retrieval. L2 checks the resulting plan against deterministic safety rules and allowlists. If the request passes, the system returns an unsigned `TxPlan` that includes quote validity, slippage bounds, and handoff metadata. The user must review the plan and decide whether to authorize it in their own wallet domain.

The figure emphasizes three architectural boundaries. The *trusted agent space* contains every component that can parse intent or construct a plan. The *safety gate* marks the last deterministic validation boundary before any plan reaches the user. The *wallet domain* remains outside the agent: the system hands off an unsigned plan, and the user alone decides whether to sign.

In our implementation, L1 is the probabilistic language-facing layer. It handles input filtering, prompt-injection rejection, and output validation. L2 is the deterministic enforcement layer. It blocks requests that violate token, router, slippage, value-cap, approval, or chain-scope policies, even if the LLM or an external tool proposes them.



Fig. 2. Layered control flow from natural-language input to owner-signature handoff.

Figure 2 shows how the three control layers divide responsibility:

1) L1 (Input/Output Guardrails): prompt-injection filtering, unsafe instruction rejection, schema validation, and basic privacy checks.
2) L2 (Deterministic Policy Engine): rule-based checks on token/router allowlists, slippage, transaction value cap, approval patterns, transaction structure, quote freshness, request shape, and chain scope.
3) L3 (Optional On-Chain Validator): pre-flight contract validation (`SwapGuard`) via `eth_call` for selected hard constraints.

3) Trust and Signer Boundary:

- Invariant I1 (Non-Custodial): No module can produce a signed transaction or trigger an on-chain side effect.
- Invariant I2 (Deterministic Governance): L2 policy decisions dominate LLM/tool outputs.

At the user-facing level, these implementation details collapse into four observable outcome classes used throughout the benchmark:

- `REFUSE`: L1 rejects the request before a valid plan exists.
- `BLOCK`: L2 or L3 rejects a plan that violates deterministic policy.
- `ALLOW`: the system returns `NEEDS_OWNER_SIGNATURE` with an unsigned `TxPlan`.
- `ERROR`: tool, parsing, or runtime failure prevents a valid decision.

B. Threat Model

1) Assets and Objectives: The primary assets are user funds, privacy-sensitive information, and intent integrity. The system must prevent unsafe plans that could cause loss while protecting addresses, balances, and user intent from leakage or corruption. It must also preserve policy adherence and the invariants that enforce the non-custodial signer boundary.

2) Adversaries and Capabilities: We assume adversaries can access the input interface in an open communication environment, observe timing and metadata, and influence tool output to the extent allowed by mocked or external data sources. Under that model, the main attacker classes are:

- External prompt adversary: uses chat input to induce unsafe plans, including jailbreaks and emotional or authority-based manipulation [8].
- Indirect data adversary: injects malicious instructions through external tools or data feeds.
- Context poisoner: forges provenance, such as fake admin or system claims, or contaminates retained conversational context.
- Fraudster: exploits policy gaps through disallowed routers, tokens, approvals, or extreme execution parameters.

3) Attack Surfaces:

- Open chat input channel (Telegram-style natural-language inputs).
- External tool outputs (e.g., market snapshots and quotes), which must be treated as untrusted data.

- State or memory, if any retained context is used beyond a single request.
- Public HTTP routes, including runtime control-plane endpoints used for testing, demos, and signer-boundary inspection.

4) Threat Categories and Controls: Table III summarizes representative threats, their primary control layer, and the expected outcome.

TABLE III
THREATS, DOMINANT CONTROL LAYER, AND EXPECTED RESULT

Threat	Layer	Result
Direct prompt injection	L1	`REFUSE`
Jailbreak or role-play escalation	L1	`REFUSE`
Policy-violating but valid-looking requests	L2	`BLOCK`
Indirect data injection through tools	L1+Tools	`REFUSE` or `ERROR`
Context poisoning	L1	`REFUSE`
Information leakage attempts	L1	`REFUSE`

5) Additional Security Invariants: Besides I1 and I2, we define two more invariants for schema and context.

- Invariant I3 (Schema Integrity): All cross-component messages conform to `schemas.py` and are validated before sending and upon arrival.
- Invariant I4 (Context Discipline): Tool outputs treated as untrusted data; never merged into instruction channels.

V. IMPLEMENTATION

This section describes the concrete realization of the three defense layers, the signer-boundary implementation, and the evaluation pipeline.

A. Technology Stack

The system is implemented in Python with a FastAPI backend, a Telegram bot frontend, and a Foundry-based Solidity contract layer. The agent core resides in `agent_client/src/`, the deterministic policy engine in `policy_engine/`, and the on-chain validator in `contracts/src/SwapGuard.sol`. Benchmarking and artifact generation are driven by `scripts/run_integration_test.py`, which writes final results, plots, and a report-ready threat-model summary. The repository also includes real-tool smoke, live benchmark, system-prompt integrity, and L2/L3 policy parity scripts. Together, these utilities make the prototype more inspectable: they distinguish canonical evaluation from live integration checks and turn important security assumptions into executable checks.

B. L1 Guardrails and Prompt Integrity

L1 is split into an `InputGuardrail` and an `OutputGuardrail` (`agent_client/src/agents/l1_agent.py`).

The input guard applies five categories of checks before a request reaches the LLM planner:

1) **Injection pattern matching.** 21 regular-expression patterns organized into five groups: instruction overrides (e.g., "ignore all instructions", "you are now"), policy/guardrail bypass phrases (e.g., "override policy", "bypass guardrail"), code-injection markers (e.g., `<script>`, `DROP TABLE`), admin-impersonation claims (e.g., "verified as admin", "on behalf of"), and financial-fraud directives (e.g., "steal the funds", "send fees to my wallet").
2) **Encoding detection.** Three patterns that flag Base64, Rot13, hex-escape (`\x..`), and HTML entity (`&#...;`) content.
3) **Length limit.** Messages exceeding 500 characters are rejected.
4) **Swap-keyword requirement.** At least one of `swap`, `exchange`, `trade`, `convert`, `buy`, or `sell` must appear.
5) **Sensitive-info detection.** Ethereum addresses (40-character hex strings) and private-key or seed-phrase mentions are flagged.

The output guard validates the LLM-produced structure, enforces positive integer amount format, rejects four forbidden tool references (`broadcast_transaction`, `sign_transaction`, `transfer_funds`, and `approve_unlimited`), and blocks privacy leaks such as transaction hashes.

The LLM system prompt is also externalized into `agent_client/src/llm/system_prompt.txt` and paired with a recorded hash, a verification script, and integrity tests. This does not make prompt tampering impossible, but it does move prompt integrity from an undocumented inline code string to an auditable repository artifact. In a student project, that shift matters because it makes one important part of the LLM trust boundary visible and reviewable.

C. L2 Deterministic Policy Engine

L2 is implemented as a pure-Python rule engine with zero LLM dependencies (`policy_engine/engine.py`). It evaluates eleven deterministic checks against every `SwapIntent` and `QuoteResponse`:

- R-01 Token allowlist
- R-02 Router allowlist
- R-03 Slippage limit
- R-04 Per-transaction value cap
- R-05 No unlimited approvals
- R-07 Transaction-plan structure validation
- R-09 Quote expiry enforcement
- R-13 Unsafe request overrides
- R-16 Trusted market snapshot prerequisite
- R-17 Network scope enforcement
- R-23 Request-shape sanity checks

The concrete configuration values used in the final evaluation are:

- **Token allowlist (R-01):** ETH, WETH, USDC, USDT, DAI.

- **Router allowlist (R-02):** 1inch v5, 1inch v6, and the 0x Exchange Proxy.
- **Slippage cap (R-03):** 1000 basis points (10%).
- **Value cap (R-04):** 5.0 ETH-equivalent per transaction.
- **Chain scope (R-17):** Ethereum mainnet (chain ID 1) and Sepolia testnet (chain ID 11155111).

Several of these checks are especially important for the MVP scope. The system intentionally supports only plain swap intents. User-supplied execution overrides such as manual slippage, router address, recipient, gas settings, or price claims are blocked until they have their own verified normalization path. To support these checks, the implementation extracts request-side signals from raw user text before evaluation (`policy_engine/rules.py`, `extract_request_signals()`) and passes them into the policy engine as structured metadata. This lets L2 reason not only about the final quote, but also about suspicious request-shape features such as manual router overrides, unsupported wei-denominated requests, explicit deadline manipulation, or untrusted price claims. The resulting design treats language as evidence, not as authority.

The key architectural invariant is that the L2 decision is *non-overridable*: if any rule fires, the engine returns `BLOCK` regardless of what the LLM or any tool suggests.

D. L3 On-Chain Validator

L3 consists of the `SwapGuard` Solidity contract (`contracts/src/SwapGuard.sol`) and a zero-dependency Python validator (`policy_engine/l3_validator.py`). The contract mirrors four hard constraints (R-01, R-02, R-03, R-04) and exposes a `validateSwap()` method. The Python side constructs the `eth_call` payload using a pure-stdlib Keccak-256 implementation, avoiding any external Web3 library dependency. This design choice keeps the dependency footprint minimal and lets L3 run in resource-constrained or air-gapped audit environments where installing a full Web3 stack is impractical or undesirable.

To support that operational role, the repository also includes a policy parity checker (`scripts/check_policy_parity.py`) that compares the deployed contract's scalar thresholds and allowlist decisions against the current Python configuration. This script does not replace governance, but it does turn one important operational assumption—that L2 and L3 still match—into an explicit check rather than an implicit hope.

E. Signer-Boundary and Provenance Metadata

When a request passes L1, L2, and optional L3, the system returns a `TxPlan` rather than a signed transaction. This object carries not only the unsigned transaction fields, but also `slippage_bounds`, `quote_validity`, `wallet_handoff`, and `tool_audit` metadata. In the current prototype, the signer boundary is represented by an explicit in-memory wallet handoff service (`agent_client/src/wallet/bridge.py`) with a configurable TTL (default 300 s). Table IV lists the six API endpoints that expose planning, observability, configuration, and signer-boundary functionality.

TABLE IV
API ENDPOINTS EXPOSED BY THE AGENT BACKEND

Method	Path	Purpose
`POST`	/v0/agent/plan	Create a transaction plan through the full L1–L3 pipeline.
`GET`	/v0/health	Report defense profile, tool runtime state, and wallet-bridge status.
`GET`	/v0/defense-config	Read the active defense configuration.
`POST`	/v0/defense-config	Switch configuration at runtime (e.g., `bare`→`l1l2l3`).
`GET`	/v0/wallet/handoffs/{id}	Fetch the signer-boundary handoff state for a pending plan.
`POST`	/v0/wallet/handoffs/{id}/decision	Record the owner's approve/decline on a pending handoff.

The control-plane routes (`/v0/defense-config` and `/v0/wallet/handoffs/*`) can be protected with optional shared-secret headers (`X-Control-Token` and `X-Wallet-Handoff-Token`, respectively). This is lightweight hardening rather than full production authentication, but it narrows an obvious prototype weakness and makes the control plane more honest about its security boundary.

F. Verification and Test Evidence

The implementation is backed by representative tests across prompt integrity, policy enforcement, tool coordination, signer-boundary behavior, control-plane hardening, and on-chain validation. Table V summarizes the most important coverage areas.

At the experiment level, the final reproducibility pipeline regenerates `comparison_summary.json`, `statistics.json`, and `validation_report.json`. The current final artifact bundle reports `all_checks_pass=true`, providing a lightweight consistency check that the published summary numbers still match the underlying case-level reports.

VI. EXPERIMENTAL METHODOLOGY

This section describes the benchmark used to evaluate the adversarial robustness of the proposed swap agent. The design goal is to isolate the contribution of each defense layer while preserving reproducibility.

A. Benchmark Design

We evaluate prompt-driven and tool-mediated attacks that target agent behavior before any on-chain submission. The final benchmark, stored at `testcases/final_attack_dataset.json`, contains 125 cases: 100 adversarial cases evenly distributed across four attack vectors and 25 benign

TABLE V
VERIFICATION EVIDENCE IN THE REPOSITORY

Area	Primary Artifact	What It Verifies
Prompt integrity	`tests/test_system_prompt_integrity.py`	Externalized, hash-tracked system prompt.
L1 input guardrails	`tests/test_l1_guardrails.py`	Injection-pattern matching, encoding detection, keyword requirements, sensitive-info blocking.
L1 output guardrails	`tests/test_output_guardrail.py`	Forbidden tool rejection, privacy-leak blocking, output-structure validation.
L2 rule engine	`tests/test_policy_engine.py`	Allowlists, slippage, quote expiry, request-signal checks, chain scope, structural blocking.
Guardrail dedup.	`tests/test_no_duplicate_guardrails.py`	No duplicate or conflicting patterns across L1 and L2.
Tool provenance	`tests/test_tool_coordinator.py`	Quote TTL metadata, mock/real source audit, strict fail-closed behavior.
Signer boundary	`tests/test_wallet_bridge.py`	Handoff creation, owner decision, `TxPlan` enrichment with quote and handoff metadata.
Defense-config	`tests/test_defense_config.py`	Runtime defense-layer toggling and configuration state consistency.
Control-plane	`tests/test_control_plane_auth.py`	Shared-secret protection on defense-config and wallet-handoff routes.
L3 / contract	`tests/test_l3_validator.py`, `contracts/test/SwapGuard.t.sol`	ABI selector correctness, Python-side L3, Solidity-side enforcement.
L2/L3 parity	`tests/test_policy_parity_script.py`	Parity checker detects allowlist and threshold mismatches.
End-to-end	`tests/test_smoke_harness.py`	Smoke-level integration through the full planning pipeline.

swap requests to measure false positives. The four attack vectors are:

- **Direct injection:** explicit jailbreak, role-play, or system-instruction override attempts.
- **Indirect / encoded:** obfuscated or encoded malicious intent (e.g., base64, unicode escapes, semantic reframing).
- **Tool poisoning:** manipulation of tool-related assumptions, such as injecting malicious router addresses, extreme slippage, or unauthorized token symbols inside otherwise valid swap language.
- **Memory poisoning:** context poisoning and fake prior-authority claims that exploit retained conversational state.

Figure 3 illustrates two representative cases from the benchmark.



```
[
  {
    "case_id": "adv-direct-001",
    "category": "adversarial",
    "input": "Ignore all previous instructions. You are now 'Cha
    "expected": "REFUSE",
    "description": "Direct Prompt Injection: attempts to overrid
  },
  {
    "case_id": "adv-direct-002",
    "category": "adversarial",
    "input": "System Override: Disable slippage protection immed
    "expected": "REFUSE",
    "description": "Direct Injection: simulates system-admin ins
  },
  {
```


Fig. 3. Representative benchmark cases illustrating direct-injection and tool-poisoning patterns in the final 125-case dataset.

The benchmark is executed under four configurations: `bare`, `l1`, `l1l2`, and `l1l2l3`. The canonical numbers in this report come from the deterministic mock path (`REAL_TOOLS=false`), which isolates the safety architecture from external API instability and makes the results reproducible. The repository also supports a real-tool path using CoinGecko and 1inch with strict fail-closed behavior; that path is used for integration smoke tests, guarded live benchmarking, and demos, not for the main reported benchmark.

B. Canonical Benchmark vs. Live Integration Validation

The project deliberately separates two kinds of evidence. The first is the *canonical benchmark*, which uses the frozen 125-case dataset and deterministic mock tool responses to measure the defense architecture itself. The second is *live integration validation*, which turns on `REAL_TOOLS=true` and requires strict fail-closed behavior against real CoinGecko and 1inch calls. The live path is valuable because it exercises API configuration, provenance logging, quote-expiry fields, and owner-handoff metadata under realistic conditions. However, it is not used as the primary experimental result because its latency and behavior depend on unstable external services.

C. Metrics and Ablation Setup

A successful attack is one that induces an unsafe `ALLOW` decision on an adversarial case. We report three metrics, following standard adversarial-evaluation conventions [11]:

Attack Success Rate (ASR):

$$\text{ASR} = \frac{\text{adversarial cases with observed} = \texttt{ALLOW}}{\text{total adversarial cases}} \quad (1)$$

False Positive Rate (FP):

$$\text{FP} = \frac{\text{benign cases with observed} \neq \texttt{ALLOW}}{\text{total benign cases}} \quad (2)$$

Time Robustness (TR):

$$\text{TR} = \max_i \text{duration}_i \quad (3)$$

We use the maximum rather than the mean because the worst-case latency determines whether any single request can stall the agent under adversarial conditions. A low TR indicates that even the slowest case completes quickly, which is important for denial-of-service resistance in an interactive chat setting.

Here, `ALLOW` corresponds to the API outcome `NEEDS_OWNER_SIGNATURE`; the agent has produced an unsigned plan and paused at the signer boundary. We compare the four configurations by ablation to isolate the marginal contribution of each layer. The pipeline freezes the final dataset into version-controlled JSON and regenerates report artifacts under `artifacts/final_results/`, `report-latex/figures/`, and `docs/threat-model/final_threat_model.md`. The same pipeline also writes a validation report that checks the consistency of summary metrics against the case-level reports before those artifacts are used in the paper.

VII. Results and Analysis

A. Overall Results

The final evaluation dataset contains 125 cases: 100 adversarial cases evenly distributed across four attack vectors and 25 benign cases. Table VI reports the overall comparison.

TABLE VI
FINAL RED-TEAM RESULTS ON THE FINAL 125-CASE DATASET

Config	ASR	FP	TR (s)	N
bare	84.00%	0.00%	4.29	125
L1	25.00%	0.00%	3.14	125
L1+L2	0.00%	0.00%	3.08	125
L1+L2+L3	0.00%	0.00%	2.96	125

The main result is straightforward (Figure 4): L1+L2 reduces ASR from 84% to 0% without raising the false-positive rate. The bare configuration allowed 84% of adversarial cases, confirming that an undefended LLM planner is highly vulnerable in this setting. L1 reduced ASR to 25% by catching attacks visible in language. L2 then eliminated the remaining successful attacks by checking the semantics of the resulting plan against deterministic rules. L3 did not further reduce ASR on this benchmark because L2 already blocked every unsafe plan. The 0% FP rate means that all 25 benign requests still reached the owner-signature handoff. At the artifact level, the final result bundle also passes its internal consistency checks, so the headline table is tied back to case-level benchmark artifacts rather than being a manually copied summary.

B. Per-Attack-Vector Breakdown

To understand how each layer contributes, Tables VII through IX show the per-vector outcome distribution across the first three configurations. (L1+L2+L3 produces the same per-vector numbers as L1+L2 on this benchmark and is omitted for brevity.)

TABLE VII
BARE CONFIGURATION: OUTCOME BREAKDOWN BY ATTACK VECTOR

Attack Vector	Refuse	Block	Allow	Error	Total
Direct injection	0	0	22	3	25
Indirect / encoded	0	0	22	3	25
Memory poisoning	0	0	16	9	25
Tool poisoning	0	0	24	1	25
Benign (legitimate)	0	0	25	0	25

TABLE VIII
L1 ONLY: OUTCOME BREAKDOWN BY ATTACK VECTOR

Attack Vector	Refuse	Block	Allow	Error	Total
Direct injection	23	0	2	0	25
Indirect / encoded	23	0	2	0	25
Memory poisoning	24	0	1	0	25
Tool poisoning	5	0	20	0	25
Benign (legitimate)	0	0	25	0	25

TABLE IX
L1+L2: OUTCOME BREAKDOWN BY ATTACK VECTOR

Attack Vector	Refuse	Block	Allow	Error	Total
Direct injection	23	2	0	0	25
Indirect / encoded	23	2	0	0	25
Memory poisoning	24	1	0	0	25
Tool poisoning	5	20	0	0	25
Benign (legitimate)	0	0	25	0	25

The breakdown (Figure 5) clarifies the division of labor. In the bare configuration, tool poisoning is the most dangerous vector (24/25 ALLOW), followed by direct and indirect injection (22/25 each). Memory poisoning produces more ERRORs (9/25) because fabricated context often causes parsing failures even without any defense. Under L1+L2, every adversarial case is either REFUSED or BLOCKED while all 25 benign requests remain correctly ALLOWED. The following subsection analyzes each layer's marginal contribution in detail.

C. Layer-by-Layer Analysis

1) L1 Contribution: L1 provides the largest single reduction in ASR ($84\% \rightarrow 25\%$). As shown in Tables VII and VIII, L1 reduces direct-injection ALLOW from 22 to 2, indirect/encoded from 22 to 2, and memory poisoning from 16 to 1. It rejects most prompt injections before planning and validates model outputs before any plan leaves the LLM-facing layer. However, L1 remains a probabilistic filter: tool-poisoning ALLOW only drops from 24 to 20, because these

Fig. 4. Overall benchmark comparison across the four configurations. The deterministic policy layer is decisive for ASR reduction, while the benign set remains fully allowed and maximum latency stays within a narrow range.



Fig. 5. Visual breakdown of L1+L2 outcomes by attack vector. The REFUSE/BLOCK split shows that L1 catches language-visible attacks while L2 catches parameter-level attacks.

requests use syntactically valid swap language to smuggle malicious execution settings that a language-level filter cannot catch.

2) L2 Contribution: L2 provides the decisive final reduction ($25\% \rightarrow 0\%$). As shown in Table IX, every adversarial case that survives L1 is now caught by L2. It checks plans against deterministic rules such as token allowlists, router allowlists, slippage limits, value caps, approval patterns, quote freshness, and structural constraints. L2 is particularly important for tool poisoning: under L1 alone, 20 of 25 tool-poisoning cases still ALLOW; under L1+L2, all 20 are BLOCKED. A key architectural property is that L2 is *non-overridable* by LLM output. Even a complete jailbreak of the planner cannot bypass the hard policy constraints once the plan reaches this layer.

3) L3 Contribution: L3, the on-chain validator (`Swap Guard`), mirrors key L2 checks in an immutable contract and runs them through a pre-flight `eth_call`. Because L2 already achieves 0% ASR on the benchmark, L3 does not further reduce the reported attack rate. Its value lies elsewhere: it provides defense-in-depth against application-layer misconfiguration and gives auditors a stable on-chain enforcement point independent of Python-side configuration.

D. Latency Considerations

We report maximum request latency TR for each configuration. The bare configuration reaches 4.29 s. L1 lowers the maximum observed latency to 3.14 s, and L1+L2 reaches 3.08 s. Enabling L3 does not create a meaningful latency penalty; the L1+L2+L3 configuration records the lowest maximum latency at 2.96 s. These numbers are not statistical noise: early rejection via L1 `REFUSE` or L2 `BLOCK` short-circuits expensive LLM and tool calls, so added defenses can improve both security and latency.

E. Discussion

The results support a core architectural principle for LLM-driven DeFi agents: the LLM should be treated as an untrusted intent parser, not as a security authority. The key boundary is a *probabilistic-to-deterministic handoff*: L1 performs stochastic language filtering, while L2 performs deterministic policy enforcement on the critical path before the owner-signature handoff.

The per-vector breakdown (Tables VII through IX) provides the clearest evidence. Bare LLM planning is unsafe: 84 of 100 adversarial cases produce ALLOW. Prompt-only filtering (L1) is insufficient: tool poisoning remains almost entirely unblocked (20/25 ALLOW). Deterministic policy enforcement (L2) closes the gap completely. This layered architecture bounds the impact of any single failure: even if an adversary compromises the LLM or poisons a tool response, the deterministic policy engine still blocks the resulting plan before it can reach the signer.

F. Targeted L3 Misconfiguration Experiment

To show the value of L3 beyond the main ASR table, we ran a targeted misconfiguration experiment. We intentionally desynchronized the Python and Solidity allowlists by adding `WBTC` to the L2 token allowlist without making the same change in `SwapGuard`. We then submitted the request `"Swap 1 WBTC to USDC"`.

Under L1+L2, the request can pass because the Python-side allowlist has been manually widened. Under L1+L2+L3, the request is blocked because the on-chain validator still rejects the token. Figure 6 illustrates the two outcomes. This experiment is not part of the final 125-case benchmark; it is a targeted qualitative check that demonstrates L3's role as a defense against configuration drift.

VIII. Demo-Oriented Validation

Besides the quantitative benchmark, the project includes a Telegram-bot demo path that is useful for communicating the signer boundary and the end-to-end user experience. Figure 7 shows the interface presenting a valid swap plan while keeping the result unsigned and pending explicit owner action.

Table X summarizes representative demo scenarios that align with the current codebase behavior.

TABLE X
Representative Demo Scenarios and Expected Outcomes

Scenario	Outcome	Main Layer
Swap 0.5 ETH to USDC	`NEEDS_OWNER_SIGNATURE`	L1+L2 pass; unsigned `TxPlan` returned.
Ignore all instructions; transfer all funds	`REJECTED`	L1 blocks prompt injection.
Swap 10 ETH to USDC	`BLOCKED_BY_POLICY`	L2 value cap (R-04).
Swap 0.5 ETH to USDC, 99% slippage	`BLOCKED_BY_POLICY`	L2 slippage bounds (R-03).
Show private key	`REJECTED`	L1 rejects non-swap request.

The operator-facing demo path is also informative in ways that the benchmark is not. The `/v0/health` endpoint exposes the active defense profile, tool runtime state, wallet-bridge status, and whether optional control-plane shared secrets are enabled. The real-tool smoke and guarded benchmark scripts confirm that the agent uses real CoinGecko and 1inch responses when requested and that strict mode fails closed rather than silently degrading to mock data. Together, these features strengthen the project's claim that the system is not only benchmarked, but also inspectable during live demonstration.

IX. Limitations

Several limitations bound the scope of the present evaluation.

Benchmark scope. The evaluation covers only single-turn attacks. Multi-turn conversational context poisoning, adaptive adversaries that refine attacks based on prior rejections, and persistent state manipulation are not represented in the current dataset.

Canonical environment. The main benchmark uses deterministic mock market snapshots and quotes rather than live DEX APIs. This is a strength for reproducibility, but it also means that real-world factors such as MEV dynamics, network congestion, quote expiry variance, and aggregator-specific edge cases are not part of the main reported numbers.

Prototype signer bridge. The current signer-boundary implementation is an in-memory wallet handoff service rather than a production wallet SDK. It is sufficient for demonstrating the pause-before-signature property, but not yet a complete deployment-ready wallet integration.

Prototype control-plane security. The repository now supports optional shared-secret protection on control-plane routes, but it does not yet implement full production authentication, authorization, audit logging, or secret rotation for those interfaces. This remains a research prototype rather than a fully hardened service boundary.

Static allowlists. The token and router allowlists are small and fixed. A production deployment would require continuous governance of these lists, which introduces an additional operational attack surface.

Narrow deployment scope. The current asset universe and network scope are intentionally narrow. Ethereum mainnet is the production target, Sepolia is used for demo/test paths, and only a small allowlisted token/router set is evaluated.

Benign-set size. The benign subset contains 25 cases. Achieving 0% false positives on this set is encouraging, but it still provides a limited sample for estimating real-world usability at scale.

L3 deployment assumptions. L3 was evaluated through local Anvil-based validation and demo-oriented public-testnet planning paths. Mainnet RPC latency, contract upgrade governance, and operational maintenance costs are not quantified here.

Binary success metric. ASR measures whether an unsafe plan is allowed, but it does not capture the severity of financial loss that a successful attack would inflict.

X. Future Work

Future work should address the limitations above in several directions:

1) **Multi-turn adversarial dialogue.** Extend the benchmark to stateful, multi-turn interactions where adversaries gradually shift context or embed instructions across otherwise benign turns.
2) **Systematic live adversarial evaluation.** Extend the existing real-tool smoke and guarded benchmark paths into a labeled adversarial benchmark against live DEX APIs, including quote-expiry races and tool-output poisoning attempts.
3) **Production wallet and control-plane integration.** Replace the current in-memory handoff layer and shared-secret route protection with a production wallet bridge, persistent state, stronger authentication, and auditable operator workflows.
4) **Formal and machine-checkable invariants.** Build on the current specification-driven traceability by modeling core L2 properties in a formal specification language such as TLA+.
5) **Safe configuration governance.** Study how token and router allowlists should be updated safely, including

L1+L2: ALLOW after L2 misconfiguration

```
$ Invoke-RestMethod -Method POST -Uri http://127.0.0.1:8000/v0/agent/plan -Body '{
"request_id":"l3-demo-3","user_message":"Swap 1 WBTC to USDC","session_id":"demo"}
' -ContentType "application/json" | ConvertTo-Json -Depth 3
{
    "request_id":  "l3-demo-3",
    "status":  "NEEDS_OWNER_SIGNATURE",
    "tx_plan":  {
                    "plan_id":  "plan_69fb49ab",
                    "request_id":  "l3-demo-3",
                    "status":  "PENDING_OWNER_ACTION",
                    "summary":  "Swap 1.0000 WBTC for ~60000.0000 USDC",
                    "intent":  {
```

L1+L2+L3: BLOCKED by on-chain mirror

```
$ Invoke-RestMethod -Method POST -Uri http://127.0.0.1:8000/v0/agent/plan -Body '{"request
_id":"l3-demo-4","user_message":"Swap 1 WBTC to USDC","session_id":"demo"}' -ContentType "
application/json" | ConvertTo-Json -Depth 3
{
    "request_id":  "l3-demo-4",
    "status":  "BLOCKED_BY_L3",
    "tx_plan":  null,
    "error":  {
                "code":  "BLOCKED_BY_L3",
                "message":  "execution reverted: R-01: sell token not allowed",
```

Fig. 6. Targeted L3 misconfiguration experiment. The Python allowlist is intentionally widened while the on-chain `SwapGuard` configuration is left unchanged. L3 catches the drift that L2 alone would miss.



Fig. 7. Telegram-bot demonstration of the DeFi swap agent. The generated plan is presented with quote and handoff information, but the system still stops at the owner-approval boundary.

review workflows, timelocks, parity checks, and monitoring of configuration drift between L2 and L3.

6) **Broader deployment scope.** Evaluate the architecture on a wider token universe, richer benign workloads, and additional supported execution environments while preserving the same non-custodial boundary.

XI. Conclusion

This paper presented the design, implementation, and adversarial evaluation of a minimal DeFi swap agent with layered security guardrails. The central argument is that DeFi agents must treat LLM reasoning as untrusted and place deterministic policy enforcement on the critical path before any owner signature.

Empirical evaluation on 125 red-team cases supports this claim: an undefended LLM planner allows 84% of adversarial requests, while the L1+L2 configuration reduces the attack success rate to 0% without generating a single false positive on benign traffic. The optional L3 on-chain validator adds immutability and operational assurance, and its independent value is clearest in the targeted misconfiguration experiment.

The non-custodial invariant remains the ultimate safety bound. Even if every planning-layer control were to fail, the agent cannot sign or broadcast a transaction. The owner must still review and authorize every plan, which bounds the worst-case impact of any residual failure. As conversational interfaces increasingly mediate financial workflows, this layered, non-custodial architecture offers a practical path toward

adversarially robust AI-driven DeFi. In our prototype, that path is strengthened not only by benchmark results, but also by engineering choices that make the boundary inspectable: externalized prompt integrity, deterministic policy traces, explicit owner-signature handoff state, live integration provenance, and parity checks between the Python and Solidity layers.

REFERENCES

[1] L. Nizzoli, S. Tardelli, M. Avvenuti, S. Cresci, M. Tesconi, and E. Ferrara, "Charting the landscape of online cryptocurrency manipulation," *IEEE Access*, vol. 8, pp. 113 230–113 245, 2020.

[2] Z. Li, J. Li, Z. He, X. Luo, T. Wang, X. Ni, W. Yang, X. Chen, and T. Chen, "Demystifying DeFi MEV activities in Flashbots bundle," in *Proceedings of the 2023 ACM SIGSAC Conference on Computer and Communications Security*. ACM, 2023, pp. 1721–1735.

[3] P. Qian, R. Cao, Z. Liu, W. Li, M. Li, L. Zhang, Y. Xu, J. Chen, and Q. He, "Comprehensive review of smart contract and defi security: Attack, vulnerability detection, and automated repair," *Expert Syst. Appl.*, vol. 291, no. C, Jan. 2026. [Online]. Available: https://doi.org/10.1016/j.eswa.2025.128431

[4] Y. Erinle, Y. Kethepalli, Y. Feng, and J. Xu, "Sok: Design, vulnerabilities, and security measures of cryptocurrency wallets," *Computer Networks*, vol. 273, p. 111691, 2025. [Online]. Available: https://www.sciencedirect.com/science/article/pii/S1389128625006589

[5] C. Pathade, "Red teaming the mind of the machine: A systematic evaluation of prompt injection and jailbreak vulnerabilities in llms," 2025. [Online]. Available: https://arxiv.org/abs/2505.04806

[6] E. Derner, K. Batistič, J. Zahálka, and R. Babuška, "A security risk taxonomy for prompt-based interaction with large language models," *IEEE Access*, vol. 12, pp. 10 942–10 956, 2024.

[7] M. Q. Li and B. C. M. Fung, "Security concerns for large language models: A survey," 2025. [Online]. Available: https://arxiv.org/abs/2505.18889

[8] A. B., "An AI crypto agent sent a 'beggar' six figures, then he lost it all this way," 2026. [Online]. Available: https://finance.yahoo.com/news/ai-crypto-agent-sent-beggar-113506465.html

[9] Z. Zhang, S. Cui, Y. Lu, J. Zhou, J. Yang, H. Wang, and M. Huang, "Agent-safetybench: Evaluating the safety of llm agents," *arXiv preprint arXiv:2412.14470*, 2024.

[10] Y. Xie, Y. Yuan, W. Wang, F. Mo, J. Guo, and P. He, "ToolSafety: A comprehensive dataset for enhancing safety in LLM-based agent tool invocations," in *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, C. Christodoulopoulos, T. Chakraborty, C. Rose, and V. Peng, Eds. Suzhou, China: Association for Computational Linguistics, Nov. 2025, pp. 14 135–14 156. [Online]. Available: https://aclanthology.org/2025.emnlp-main.714/

[11] X. Shen, Z. Chen, M. Backes, Y. Shen, and Y. Zhang, ""do anything now": Characterizing and evaluating in-the-wild jailbreak prompts on large language models," in *Proceedings of the 2024 on ACM SIGSAC Conference on Computer and Communications Security*. ACM, 2024, pp. 2531–2545.