



Z.C.E

شركة الزهراء
للمقاولات الهندسية
والتوريدات

EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying

Project Report: EEE

Project Details

Name: EEE

Client Name: E

Capacity: E



Z.C.E

شركة الزهراء
للمقاولات الهندسية
والتوريدات

EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying

1. Belt Conveyor

Sec01: General Data

Field	Value
Manufacturer	Winkel
Quantity	1

Sec02: Design Data

Field	Value
Width	800
Length	2000

Sec03: Gearbox Data

Field	Value
Trade Mark	SEW
Model	SA57T

Sec04: Motor Data

Field	Value
Trade Mark	SEW
Rated Power	0.37 kW
Supply Voltage	380 V, 3 Phases, 50 Hz
Insulation	Class F
Temp Rise	Class B
Ingress Protection	IP65

Sec05: Material Data

Field	Value
-------	-------



Z.C.E

شركة الزهراء
للمقاولات الهندسية
والتوريدات

EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying

Frame	Hot deep galvanized steel
Roller	Hot deep galvanized steel
Bolts & Nuts	AISI 304 (A2)
Conveyor	Rubber 10 mm (3Ply cotton/nylon)



Z.C.E

EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying

شركة الزهراء
للمقاولات الهندسية
والتوريدات

2. Gritremoval

Sec01: General Data

Field	Value
Manufacturer	Factory
Quantity	One bridge serve two channel
Function	Waste water
Installation location	Rectangle tank
Installation country	Egypt
Installation (indoor, outdoor)	outdoor
Continuous operation	yes
No. Of hours a day	24/24 h

Sec02: Design Data

Field	Value
Total tank width	600 mm
Total tank length	7500 mm
Water depth	600 mm
Length of the bridge	2000 mm
Width of bridge	1000 mm
Qty of driving wheels / bridge	2
Qty of free wheels / bridge	2
Qty of drive gearbox / bridge	1
Admissible load on bridge / tank	500 kg / m ²
Max. Allowable deflection / tank	1/500

Sec03: Walkway, Handrail, Wheel Data



Z.C.E

شركة الزهراء
للمقاولات الهندسية
والتوريدات

EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying

Field	Value
Walkway type	Grating
Handrail Type	tubular
Handrail Height	1000 mm
Wheel Diameter	300 mm
Wheel Width	90 mm
Wheel rail	square bar 40x40mm

Sec04: Scrapper Data

Field	Value
Grease scrapper Thickness	6 mm
Height of the scrapper	300 mm
Fixation of sludge scrapper	by pipe suspenders
Rubber wearing strips cross section	12x100 mm
Scum ramp thickness	6mm

Sec05: Gearmotor Data

Field	Value
Gearbox Qty	1
Gearbox Trade mark	SEW
Model	SA57/T
Electric Motor Trade Mark	SEW
Rated Power	0.37 kW
Supply Voltage	380 V, 3 Phases, 50 Hz
Insulation	Class F
Temp Rise	Class B
Ingress Protection	IP65



Z.C.E

شركة الزهراء
للمقاولات الهندسية
والتوريدات

EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying

Sec06: Scrapper Data

Field	Value
Sand Scrapper Thickness	6 mm
Height of the scrapper	300 mm
Fixation of sludge scrapper	by pipe suspenders
Rubber wearing strips cross section	12x100 mm

Sec07: Drive unit

Field	Value
Drive Unit Gearbox Qty	1
Drive Unit Trade Mark	SEW
Drive Unit Model	SA77/T
Electric Motor Trade Mark	SEW
Electric Motor Rated Power	0.18 kW
Insulation	Class F
Temp Rise	Class B
Ingress Protection	IP65

Sec08: Control panel Data

Field	Value
Local control panel	Electrostatic painting
Panel thicknesses	2 mm
Component	Schneider
Operation	Manual / Automatic timer switch

Sec09: Material Data

Field	Value
-------	-------



Z.C.E

شركة الزهراء
للمقاولات الهندسية
والتوريدات

EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying

Material of Bridge	Hot deep galvanized steel
Scum ramp	AISI 304
Grease Scraper	AISI 304
Sludge Scraper	AISI 304
Bolts and nuts	AISI 304 (A2)
Open mesh floor	GRP or Hot deep galvanized steel
Wheel	Carbon steel
Wheel Shaft	Carbon steel