

# شركة الزهراء للمقاولات الهندسية والتوريدات

# **EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying**

Project Name:

testdxf

Client Name:

te

Capacity:

te



شركة الزهراء للمقاولات الهندسية والتوريدات

**EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying** 

## 1. Test Machine



شركة الزهراء للمقاولات الهندسية والتوريدات

## **EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying**

# 2. Belt Conveyor

#### Sec01: General Data

Field	Value
Manufacturer	Winkel
Quantity	1

#### Sec02: Design Data

Field	Value
Width	1600
Length	4000

#### Sec03: Gearbox Data

Field	Value
Trade Mark	SEW
Model	SA57T

#### Sec04: Motor Data

Field	Value
Trade Mark	SEW
Rated Power	0.37 kW
Supply Voltage	380 V, 3 Phases, 50 Hz
Insulation	Class F
Temp Rise	Class B

#### **Sec05: Material Data**

Field	Value
Frame	Hot deep galvanized steel



شركة الزهراء للمقاولات الهندسية والتوريدات

### **EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying**

Roller Hot deep galvanized steel

Bolts & Nuts AISI 304 (A2)

Conveyor Rubber 10 mm (3Ply cotton/nylon)



شركة الزهراء للمقاولات الهندسية والتوريدات

**EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying** 

# 3. Wall Penstocks



شركة الزهراء للمقاولات الهندسية والتوريدات

# **EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying**

#### 4. Gritremoval

#### Sec01: General Data

Field	Value
Manufacturer	Factory
Quantity	One bridge serve two channel
Function	Waste water
Installation location	Rectangle tank
Installation country	Egypt
Installation (indoor, outdoor)	outdoor
Continuous operation	yes
No. Of hours a day	24/24 h

### Sec02: Design Data

Field	Value
Total tank width	600 mm
Total tank length	7500 mm
Water depth	600 mm
Length of the bridge	2000 mm
Width of bridge	1000 mm
Qty of driving wheels / bridge	2
Qty of free wheels / bridge	2
Qty of drive gearbox / bridge	1
Admissible load on bridge / tank	500 kg / m2
Max. Allowable deflection / tank	1/500

#### Sec03: Walkway, Handrail, Wheel Data



شركة الزهراء للمقاولات الهندسية والتوريدات

# **EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying**

Field	Value
Walkway type	Grating
Handrail Type	tubular
Handrail Height	1000 mm
Wheel Diameter	300 mm
Wheel Width	90 mm
Wheel rail	square bar 40x40mm

#### **Sec04: Scrapper Data**

Field	Value
Grease scrapper Thickness	6 mm
Height of the scrapper	300 mm
Fixation of sludge scrapper	by pipe suspenders
Rubber wearing strips cross section	12x100 mm
Scum ramp thickness	6mm

#### **Sec05: Gearmotor Data**

Field	Value
Gearbox Qty	1
Gearbox Trade mark	SEW
Model	SA57/T
Electric Motor Trade Mark	SEW
Rated Power	0.37 kW
Supply Voltage	380 V, 3 Phases, 50 Hz
Insulation	Class F
Temp Rise	Class B
Ingress Protection	IP65



شركة الزهراء للمقاولات الهندسية والتوريدات

#### **EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying**

### **Sec06: Scrapper Data**

Field	Value
Sand Scrapper Thickness	6 mm
Height of the scrapper	300 mm
Fixation of sludge scrapper	by pipe suspenders
Rubber wearing strips cross section	12x100 mm

#### Sec07: Drive unit

Field	Value
Drive Unit Gearbox Qty	1
Drive Unit Trade Mark	SEW
Drive Unit Model	SA77/T
Electric Motor Trade Mark	SEW
Electric Motor Rated Power	0.18 kW
Insulation	Class F
Temp Rise	Class B
Ingress Protection	IP65

#### Sec08: Control panel Data

Field	Value
Local control panel	Electrostatic painting
Panel thicknesses	2 mm
Component	Schneider
Operation	Manual / Automatic timer switch

#### Sec09: Material Data

Field	Value	
-------	-------	--



شركة الزهراء للمقاولات الهندسية والتوريدات

### **EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying**

Material of Bridge Hot deep galvanized steel

Scum ramp AISI 304

Grease Scraper AISI 304

Sludge Scraper AISI 304

Bolts and nuts AISI 304 (A2)

Open mesh floor GRP or Hot deep galvanized steel

Wheel Carbon steel

Wheel Shaft Carbon steel



# شركة الزهراء للمقاولات الهندسية والتوريدات

#### **EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying**

### 5. Sand Silo

#### **Sec01**:

Field	Value
Manufacturer	Factory
Quantity	1

#### Sec02:

Field	Value
Capacity	5 m3
Inlet	Pipe 150 mm PN10
Outlet	Pipe 150 mm PN10

#### **Sec03:**

Field	Value
Shell	Epoxy coated steel 37
Cone	Epoxy coated steel 37
Nozzle	Epoxy coated steel 37



شركة الزهراء للمقاولات الهندسية والتوريدات

## **EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying**

### 6. Manual Screen

#### Sec01: General Data

Field	Value
Manufacturer	Factory
Quantity	1
Operation	Manual

### Sec02: Design Data

Field	Value
Flow	0.11 m3/s
Width	970 mm
Length	9000 mm
Hand rake	No. 2
Space between bar	50 mm
Bar Type	Rectangular
Bar section	10x30 mm
Inclination	45 Deg

#### Sec03: Material Data

Field	Value
Frame	AISI 316
Rake	AISI 316
Bar screen	AISI 316

#### Sec04: Channel Data

Field	Value
Channel Width	600 mm



شركة الزهراء للمقاولات الهندسية والتوريدات

## **EIZAHRAA FOR ENGINEERING CONTRACTING AND Supplying**

Depth 1180 mm