

For best experience please consider to run **Hosam\_Mahmoud\_300327269\_Reinforcement\_Learning.py** on Spyder to see all created variables on variables explorer tab.

The screenshot displays the Spyder Python IDE interface. The main editor window on the left contains a Python script named `Hosam_Mahmoud_300327269_Reinforcement_Learning.py`. The script defines a Gym environment, a Q-learning training function, and a grid search for optimal hyperparameters. The `Variable Explorer` tab is open on the right, showing a table of variables created in the script. Two red arrows point to the `Variable Explorer` menu item in the `View` dropdown and the `Variable Explorer` tab in the bottom right pane.

Name	Type	Size	Value
Alpha_Gamma_Epsilon	list	3	[[0.1, 0.2, 0.3, 0.4, 0.5, ...], [0.1, 0.2, 0.3, 0.4, 0.5, ...], [0.1, ...]]
env	wrappers.order_enforcing.OrderEnforcing	1	OrderEnforcing object of gym.wrappers.order_enforcing module
frames	list	2843	[['frame's'-----]]

```
1 import gym
2 from IPython.display import clear_output
3 from time import sleep
4 import numpy as np
5 import random
6
7 def PrintEnvData(Env_Text):
8
9
10
11
12
13 def BrouteForce(Env):
14
15
16
17
18
19 def Q_Learning_Training_decay(Alpha, Gamma, Epsilon, Env, DecayRate):
20
21
22
23
24
25 def Q_Learning_Training(Alpha, Gamma, Epsilon, Env):
26
27
28
29
30
31 def Evaluation(Q_Table, Env):
32
33
34
35
36
37 def GridSearch(Alphas, Gammas, Epsilons, Env):
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
```

env = gym.make("Taxi-v3").env  
PrintEnvData("Taxi-v3")  
Alpha\_Gamma\_Epsilon = [[0.1,0.2,0.3,0.4,0.5,0.6,0.7,0.8,0.9],[0.1,0.2,0.3,0.4,0.5,0.6,0.7,0.8,0.9],[0.1,0.2,0.3,0.4,0.5,0.6,0.7,0.8,0.9]]  
frames = BrouteForce(env)  
print\_frames(frames)  
BrouteForce(env)  
q = Q\_Learning\_Training(0.2,0.3,0.4,env)  
q\_decay = Q\_Learning\_Training\_decay(0.3,0.3,0.4,env,0.1)  
Evaluation(q, env)  
Evaluation(q\_decay, env)  
Results = GridSearch(Alpha\_Gamma\_Epsilon[0], Alpha\_Gamma\_Epsilon[1], Alpha\_Gamma\_Epsilon[2], env)  
Optimal\_Hyperparameter = Results[max(Results)]

Console 1/A x  
[V] : [0] :  
+-----+  
(West)  
Timestep: 28  
State: 117  
Action: 3  
Reward: -1  
+-----+  
[R] : [0] :  
[ : : : :  
[ : : : :  
[ : : : :  
[V] : [0] :  
+-----+  
(South)  
Timestep: 29  
State: 217  
Action: 0  
Reward: -1  
+-----+  
[R] : [0] :  
[ : : : :  
[ : : : :  
[ : : : :  
[V] : [0] :  
+-----+  
(West)  
Timestep: 30  
State: 217  
Action: 3

Please make sure that you have installed these libraries before importing it ->

***import gym***

***from IPython.display import clear\_output***

***from time import sleep***


***import numpy as np***

***import random***

-----  
To install the missing libraries, you have to write something like this ->

**>>> pip install *numpy***

In Spyder console.



```
warnings.warn(
C:\Users\Hosam\anaconda3\lib\site-packages\sklearn\base.py:450: UserWarning: X does not have
valid feature names, but SVC was fitted with feature names
  warnings.warn(
C:\Users\Hosam\anaconda3\lib\site-packages\sklearn\base.py:450: UserWarning: X does not have
valid feature names, but SVC was fitted with feature names
  warnings.warn(


In [2]: pip install pandas
```

The screenshot shows the Spyder console window. At the top, there's a tab labeled 'Console 1/A'. The main area displays a warning message from sklearn about feature names. Below the warning, the command 'In [2]: pip install pandas' is entered. The bottom status bar shows 'IPython console', 'History', 'LSP Python: ready', 'Kite: initializing', 'conda (Python 3.9.7)', 'Line 12, Col 1', 'ASCII', 'CRLF', 'RW', and 'Mem 35%'.

or

**>>> conda install pandas**


In Anaconda prompt.



```
Select Anaconda Prompt (anaconda3)

(base) C:\Users\Hosam>conda install pandas
```

The screenshot shows the Anaconda Prompt window. The title bar says 'Select Anaconda Prompt (anaconda3)'. The main area shows the command '(base) C:\Users\Hosam>conda install pandas' entered at the prompt.



Here I have 7 functions in my code.

**def PrintEnvData(Env\_Text):** is for printing the number of actions and states of the environments.

**def BrouteForce(Env):** to try all the possible paths for one state.

**def print\_frames(frames):** to animate the paths.

**def Q\_Learning\_Training\_decay(Alpha, Gamma, Epsilon, Env, DecayRate):** Training function using a decay over episodes.

Here is the parameter tuning part, but in case of **gamma** and **epsilon** I have tried to change its values but I got an infinite loop when applying evaluation.

```

89
90     if i % 100 == 0:
91         clear_output(wait = True)
92         print(f"Episode: {i}")
93         alpha = abs(alpha - (1/(1 + (DecayRate * 100000))) * alpha)
94         # gamma = abs(gamma - (1/(1 + (DecayRate * 100000))) * gamma)
95         # epsilon = abs(epsilon - (1/(1 + (DecayRate * 100000))) * epsilon)
96
97         print('Alpha = ', alpha)
98         print('Gamma = ', gamma)
99         print('Epsilon = ', epsilon)
100
101         alpha = Alpha if alpha == 0 else alpha
102         # gamma = Gamma if gamma == 0 else gamma
103         # epsilon = Epsilon if epsilon == 0 else epsilon
104
105     print("Training finished.\n")
106     return q_table

```

**def Q\_Learning\_Training(Alpha, Gamma, Epsilon, Env):** Training function without parameter tuning.

**def Evaluation(Q\_Table, Env):** to return the performance indicator of each reinforcement model.

**def GridSearch(Alphas , Gammas, Epsilons , Env):** to apply GridSearch and optain the optimal hyperparameters.

```
193
194 #-----MAIN-----
195
196
197 env = gym.make("Taxi-v3").env
198
199 PrintEnvData("Taxi-v3")
200
201 Alpha_Gamma_Epsilon = [[0.1,0.2,0.3,0.4,0.5,0.6,0.7,0.8,0.9],[0.1,0.2,0.3,0.4,0.5,0.6,0.7,0.8,0.9],[0.1,0.2,0.3,0.4,0.5,0.6,0.7,0.8,0.9]]
202
203 frames = BrouteForce(env)
204 print_frames(frames)
205 BrouteForce(env)
206
207 q = Q_Learning_Training(0.2,0.3,0.4,env)
208 q_decay = Q_Learning_Training_decay(0.5,0.3,0.4,env,0.1)
209
210 Evaluation(q , env)
211 Evaluation(q_decay , env)
212
213 Results = GridSearch(Alpha_Gamma_Epsilon[0], Alpha_Gamma_Epsilon[1], Alpha_Gamma_Epsilon[2], env)
214 Optimal_Hyperparameter = Results[max(Results)]
```


For the MAIN part I have created environment and print its number of states and actions.

```
In [7]: runfile('E:/Reinforcement Learning/Hosam_Mahmoud_300327269_Reinforcement_Learning.py', wdir='E:/
Reinforcement Learning')
Action Space Discrete(6)
State Space Discrete(500)


In [8]:
```

After that I have created list of each parameter (alpha, gamma and epsilon), and I'll use it for grid search -> 9\*9\*9 but this took too long time, so I tried with another lists -> [0.3,0.6,0.9] which will give us a total number of combinations = 3\*3\*3

And after that I animated the paths of Brute force function.



After that I trained the two models (using decay and without using decay). And the values of alpha are changed every 100 episodes.



After Evaluation (without using decay)

```
Results after 1000 episodes:  
Average timesteps per episode: 13.284  
Average penalties per episode: 0.0  
Average reward per episode: 20.0
```

After Evaluation (using decay)

```
Results after 1000 episodes:  
Average timesteps per episode: 12.976  
Average penalties per episode: 0.0  
Average reward per episode: 20.0
```

And we found that (with using decay) is faster than the normal model.

After that I applied GridSearch on function (without using Decay)

```
182  
183 def GridSearch(Alphas , Gammas, Epsilons , Env): # to apply GridSearch and obtain the optimal hyperparameters.  
184     Dictionary = {}  
185     for Alpha in Alphas:  
186         for Gamma in Gammas:  
187             for Epsilon in Epsilons:  
188                 q = Q_Learning_Training(Alpha, Gamma , Epsilon, Env)  
189                 Metric = Evaluation(q , Env)  
190                 Dictionary[Metric] = [Alpha, Gamma , Epsilon]  
191     return Dictionary  
192
```

For experiments purposes I have choose small values for parameters so the program run faster -> 2\*2\*2

 Alpha\_Gamma\_Epsilon - List (3 elements)

Ind ▲	Type	Size	Value
0	list	2	[0.3, 0.6]
1	list	2	[0.3, 0.6]
2	list	2	[0.3, 0.6]

After applying GridSearch we will choose the maximum key and return its parameter  
And the key is equal to that equation -> **Metric = (total\_reward/(total\_penalties + total\_epochs))**.

Results - Dictionary (7 elements)

Key	Type	Size	Value
1.54762825969202	list	3	[0.3, 0.6, 0.6]
1.54499806875241	list	3	[0.3, 0.3, 0.3]
1.54095076662301	list	3	[0.3, 0.6, 0.3]
1.53586238673015	list	3	[0.6, 0.3, 0.3]
1.52963671128107	list	3	[0.6, 0.6, 0.6]
1.52230172020094	list	3	[0.6, 0.3, 0.6]
1.52021891152326	list	3	[0.6, 0.6, 0.3]

And Finally, we obtained the optimal hyperparameters.

```
Results = GridSearch(Alpha_Gamma_Epsilon[0], Alpha_Gamma_Epsilon[1], Alpha_Gamma_Epsilon[2], env)
Optimal_Hyperparameter = Results[max(Results)]
```

Optimal\_Hyperparameter - List (3 elements)

Ind	Type	Size	Value
0	float	1	0.3
1	float	1	0.6
2	float	1	0.6